



Name: Cohort/Batch: Date: Score:

SPRING SECURITY PRACTICE SHEET - 10 CONCEPTUAL Q&A

10 Q&A on filter chain, JWT, OAuth2, CSRF, and method security

TOTAL: 10 QUESTIONS

Q1 What is the Spring Security filter chain and how does it process requests? Filter Model

Q6 How does method-level security work in Spring Security? Availability

Q2 What is the difference between Authentication and Authorization? Architecture

Q7 What is an OAuth2 Resource Server and how do you configure one? Configure

Q3 How do you implement stateless JWT authentication in Spring Security? Implementation

Q8 How do you configure CORS in a Spring Security application? Configuration

Q4 What does UserDetailsService do in Spring Security? Hardening

Q9 What is CSRF and when can you safely disable it? Testing

Q5 What are hasRole(), hasAuthority(), and isAuthenticated() security expressions? CSO / IdP

Q10 How do you test Spring Security with @WithMockUser? Tuning



ANSWER KEY & EXPLANATORY SOLUTIONS

Comprehensive verified answers, best-practice configs, security controls & reference

VERIFIED SOLUTIONS

A1 Spring Security registers a chain of servlet

Mitigation

Spring Security registers a chain of servlet filters via DelegatingFilterProxy. Each filter handles a concern: SecurityContextPersistenceFilter restores session state, UsernamePasswordAuthenticationFilter processes form logins, and ExceptionTranslationFilter maps exceptions to HTTP responses.

A6 Add @EnableMethodSecurity to a config class. Annotate service

State availability

Add @EnableMethodSecurity to a config class. Annotate service methods with @PreAuthorize("hasRole('ADMIN')") or @PostAuthorize. Spring wraps the bean in a proxy that evaluates the SpEL expression before or after the method runs.

A2 Authentication verifies who the user is (username/password)

Yes

Authentication verifies who the user is (username/password, JWT, OAuth2 token). Authorization decides what they can do (can this principal access this resource?). Spring Security does auth first, then authz on the resolved principal.

A7 A Resource Server validates Bearer tokens on

Automation

A Resource Server validates Bearer tokens on incoming requests. Configure it with .oauth2ResourceServer(oauth2 -> oauth2.jwt(...)) and spring.security.oauth2.resourceserver.jwt.issuer-uri pointing to your authorization server for JWK key discovery.

A3 Disable sessions (SessionCreationPolicy.STATELESS), add a

add a

Disable sessions (SessionCreationPolicy.STATELESS), add a custom OncePerRequestFilter that parses the JWT, builds a UsernamePasswordAuthenticationToken, and stores it in SecurityContextHolder. Protect routes with .authorizeHttpRequests().

A8 Define a CorsConfigurationSource bean or use @CrossOrigin

Cross origin

Define a CorsConfigurationSource bean or use @CrossOrigin, then call .cors(cors -> cors.configurationSource(source)) in the security filter chain BEFORE other filters. Without this, Spring Security blocks CORS preflight OPTIONS requests.

A4 UserDetailsService.loadUserByUsername(username) returns as

returns as

UserDetailsService.loadUserByUsername(username) returns a UserDetails object containing the username, hashed password, and granted authorities. DaoAuthenticationProvider calls it during form-login to authenticate against a database user.

A9 CSRF forges state-changing requests using a victim's

Assessment

CSRF forges state-changing requests using a victim's authenticated session. Disable it only for stateless REST APIs that authenticate via headers (JWT, API keys) rather than cookies - browsers cannot set custom headers from attacker pages.

A5 hasRole('ADMIN') checks for ROLE_ADMIN in

Federation

hasRole('ADMIN') checks for ROLE_ADMIN in GrantedAuthorities (Spring auto-prefixes). hasAuthority('SCOPE_read') checks the exact authority. isAuthenticated() is true for any non-anonymous principal. Use them in @PreAuthorize or requestMatchers.

A10 @WithMockUser('user') populates the SecurityContext with a

exp with a

@WithMockUser('user') populates the SecurityContext with a mock principal for the duration of the test. @WithSecurityContext lets you build a fully custom context. Use MockMvc with springSecurity() configurator to apply filter chain logic.