



Name: _____ Cohort/Batch: _____ Date: _____ Score: _____

GIN PRACTICE SHEET - 10 CONCEPTUAL Q&A

10 Q&A on routing, middleware, binding, error handling, and testing

TOTAL: 10 QUESTIONS

Q1 What is Gin and what performance advantages does it have?

Architecture

Q6 How do you handle errors centrally in Gin?

Observability

Q2 How do you define route groups and apply group-scoped middleware?

Architecture

Q7 How do you serve static files and HTML templates in Gin?

Recycle

Q3 How do you write custom Gin middleware?

Configuration

Q8 How do you configure TLS in a Gin server?

Compliance

Q4 How does JSON binding and validation work in Gin?

Hardening

Q9 How do you use gin.Context.Set/Get to pass data between middleware and handlers?

Testing

Q5 How does Gin's Context (c *gin.Context) work?

SSO / IDP

Q10 How do you write tests for Gin routes?

Tuning



ANSWER KEY & EXPLANATORY SOLUTIONS

Comprehensive verified answers, best-practice configs, security controls & reference

VERIFIED SOLUTIONS

A1 Gin is a Go HTTP framework built

Mitigation

Gin is a Go HTTP framework built on `HttpRouter`, a radix-tree router that resolves routes in $O(k)$ where k is the URL depth. It has zero memory allocation per request on the hot path and benchmarks at ~50,000 req/s, significantly faster than standard `net/http` mux.

A6 Append errors with `c.Error(err)`. After all middleware, a final middleware reads

observability

Append errors with `c.Error(err)`. After all middleware, a final middleware reads `c.Errors` and formats a JSON response. Alternatively use `c.AbortWithStatusJSON(500, gin.H{"error": err.Error()})` inside a recovery middleware registered with `gin.Recovery()`.

A2 `api := r.Group('/api', authMiddleware)`. Inside, `api.GET('/users', handler)`

Security

`api := r.Group('/api', authMiddleware)`. Inside, `api.GET('/users', handler)` inherits `authMiddleware`. Nesting groups further: `admin := api.Group('/admin', adminOnly)`. This scopes middleware without repeating it on every individual route.

A7 `r.Static('/assets', './static')` serves a directory.

Automation

`r.Static('/assets', './static')` serves a directory. `r.StaticFile('/favicon.ico', './favicon.ico')` serves one file. Load templates with `r.LoadHTMLGlob('templates/**/*')` and render with `c.HTML(200, 'index.tmpl', gin.H{'title': 'Home'})`.

A3 A middleware is a `HandlerFunc`: `func MyMiddleware() gin.HandlerFunc`

Hardening

A middleware is a `HandlerFunc`: `func MyMiddleware() gin.HandlerFunc { return func(c *gin.Context) { // before; c.Next(); // after } }`. Call `c.Abort()` or `c.AbortWithStatus(401)` to stop the chain without calling `Next`.

A8 Replace `r.Run(':8080')` with `r.RunTLS(':443', 'cert.pem', 'key.pem')`

Governance

Replace `r.Run(':8080')` with `r.RunTLS(':443', 'cert.pem', 'key.pem')`. Alternatively pass a pre-configured `*tls.Config` via `r.RunListener(tls.NewListener(l, tlsConf))`. Use `autotls` or `certmagic` packages for Let's Encrypt automation.

A4 Define a struct with json and binding

Gotchas

Define a struct with json and binding tags: `Name string `json:"name" binding:"required"``. Call `c.ShouldBindJSON(&req)`. On validation failure `ShouldBindJSON` returns an error; `c.JSON(400, gin.H{"error": err.Error()})` sends the response. Gin uses `go-playground/validator`.

A9 `c.Set('userID', 42)` stores a value in the

Assessment

`c.Set('userID', 42)` stores a value in the context for the current request lifecycle. `c.Get('userID')` returns `(interface{}, bool)`. Use `c.MustGet('userID').(int)` for typed access. This is the correct way to share auth data from middleware to handlers.

A5 `c` wraps request and response. `c.Param('id')` reads

Federation

`c` wraps request and response. `c.Param('id')` reads path params, `c.Query('q')` reads query params, `c.ShouldBindJSON` reads body. `c.JSON(200, obj)` serializes and writes JSON. `c.Set('user', u)` and `c.Get('user')` pass values through the middleware chain.

A10 Create a test recorder: `w := httptest.NewRecorder()`

Optimization

Create a test recorder: `w := httptest.NewRecorder()`. Build a request: `req, _ := http.NewRequest("GET", '/users/1', nil)`. Call `router.ServeHTTP(w, req)`. Assert `w.Code` and `w.Body.String()`. No server port needed tests run fully in-process.