



Name: _____ Cohort/Batch: _____ Date: _____ Score: _____

LARAVEL PRACTICE SHEET - 10 CONCEPTUAL Q&A

10 Q&A on MVC, Eloquent, queues, service container, and testing

TOTAL: 10 QUESTIONS

Q1 What is Laravel's request lifecycle from incoming HTTP request to response? PHP Model

Q6 What is Laravel Sanctum and how does it authenticate SPA's? SPA's

Q2 How does Laravel Eloquent ORM define model relationships? Relationships

Q7 How does Laravel Blade template inheritance work? Lifecycle

Q3 How does Laravel's service container resolve dependencies? Dependencies

Q8 How do you write feature tests in Laravel? Compliance

Q4 What is Laravel Artisan and what are five common commands? Hardening

Q9 What are Laravel Policies and how do they control authorization? Testing

Q5 How does Laravel handle queued jobs? SSO / IdP

Q10 What is Laravel Livewire and how does it work? Tuning



ANSWER KEY & EXPLANATORY SOLUTIONS

Comprehensive verified answers, best-practice configs, security controls & reference

VERIFIED SOLUTIONS

A1 HTTP request enters public/index.php, bootstraps the service container

HTTP request enters public/index.php, bootstraps the service container, passes through HTTP Kernel middleware (CORS, session, auth), dispatches to the Router, which resolves the controller method and returns a Response that Laravel sends back.

A6 Sanctum issues API tokens stored in the

Observability

Sanctum issues API tokens stored in the personal_access_tokens table. For SPAs it uses cookie-based session auth with CSRF protection via the /sanctum/csrf-cookie endpoint. Token-based auth is for mobile clients. Both use the Auth::user() facade.

A2 Define a public method in the model.

Primitives

Define a public method in the model. hasMany(Order::class) returns a HasMany relation (posts for a user). belongsTo(User::class) defines the inverse. Eager-load with User::with('orders')->find(1) to avoid N+1. ManyToMany uses a pivot table via belongsToMany.

A7 @extends('layouts.app') references the parent template.

Automation

@extends('layouts.app') references the parent template. @section('content') and @endsection define overrideable regions. @yield('content') in the parent marks where child content renders. @include('partials.nav') embeds a partial. @stack/@push build asset stacks.

A3 When Laravel constructs a controller, it reads

Hardening

When Laravel constructs a controller, it reads its constructor type hints and resolves each from the container. Bind an interface: \$this->app->bind(PaymentGateway::class, StripeGateway::class). All classes are resolved recursively through the container.

A8 Subclass Tests\TestCase and use the RefreshDatabase trait

Performance

Subclass Tests\TestCase and use the RefreshDatabase trait to reset DB per test. \$response = \$this->postJson('/api/login', ['email'=>..., 'password'=>...]). Assert \$response->assertStatus(200)->assertJsonStructure(['token']). Use Sanctum::actingAs(user) for auth.

A4 php artisan make:model Order -m (model +

Gotchas

php artisan make:model Order -m (model + migration), make:controller (controller), migrate (apply migrations), queue:work (start queue worker), route:list (print all routes), tinker (REPL against the app). Custom commands extend Illuminate\Console\Command.

A9 A Policy class has methods like view(User

Assessment

A Policy class has methods like view(User \$user, Post \$post). Register in AuthServiceProvider. Call \$this->authorize('view', \$post) in a controller. Laravel resolves the policy and throws 403 on failure. Gate::allows('view', \$post) checks without throwing.

A5 Implement ShouldQueue on a Job class. Dispatch

Federation

Implement ShouldQueue on a Job class. Dispatch with SendEmail::dispatch(\$user). A queue worker (php artisan queue:work) fetches jobs from the backend (Redis, SQS, DB) and executes them. Failed jobs are stored in failed_jobs and can be retried with queue:retry all.

A10 Livewire is a full-stack component framework. A

Optimization

Livewire is a full-stack component framework. A PHP class (extends LivewireComponent) holds state and methods. The Blade template uses wire:model for two-way binding and wire:click for actions. AJAX requests sync state between browser and server on each interaction.