



Name: _____ Cohort/Batch: _____ Date: _____ Score: _____

MICRONAUT PRACTICE SHEET - 10 CONCEPTUAL Q&A

10 Q&A on AOT DI, data, reactive, GraalVM, and security

TOTAL: 10 QUESTIONS

Q1 What is Micronaut and why is its dependency injection compile-time?

Threat Model

Q6 How does Micronaut's declarative HTTP client work?

Observability

Q2 How does Micronaut's AOP work without runtime proxies?

Architecture

Q7 How does Micronaut support reactive programming?

Lifecycle

Q3 How do you define a REST controller in Micronaut?

Configuration

Q8 How does Micronaut's configuration system work?

Compliance

Q4 What is Micronaut Data and what makes it unique?

Hardening

Q9 How does Micronaut Security implement JWT authentication?

Testing

Q5 How does Micronaut simplify GraalVM native image creation?

SSO / IdP

Q10 How do you write tests in Micronaut?

Tuning



ANSWER KEY & EXPLANATORY SOLUTIONS

Comprehensive verified answers, best-practice configs, security controls & reference

VERIFIED SOLUTIONS

A1 Micronaut uses annotation processors at build

Mitigation

Micronaut uses annotation processors at build time to generate injection code. Unlike Spring's runtime reflection, there is no classpath scanning on startup. This means zero reflection overhead, instant startup, and low memory ideal for FaaS and containers.

A6 Annotate an interface with @Client('/api') and

Observability

Annotate an interface with @Client('/api') and declare methods with @Get, @Post, etc., mirroring the server-side API. Micronaut generates a compile-time implementation using Netty. Combine with @LoadBalanced for client-side load balancing.

A2 Micronaut generates bytecode for interceptor

Primitives

Micronaut generates bytecode for interceptor chains at compile time using ASM. @Around advice is woven into a generated subclass. Because no JDK dynamic proxy or CGLIB is involved, there is no class hierarchy restriction and overhead is minimal.

A7 Micronaut controllers can return Project Reactor

Automation

Micronaut controllers can return Project Reactor Publisher<T>/Mono<T>/Flux<T> or RxJava Observable/Single. The Netty event loop handles I/O non-blocking. Annotate @ExecuteOn(TaskExecutors.IO) to shift blocking calls to a worker thread.

A3 @Controller('/users') marks the class.

Hardening

@Controller('/users') marks the class. @Get('/{id}'), @Post, @Put, @Delete annotate methods. @PathVariable, @QueryValue, and @Body inject URL parts and request data. Micronaut validates @Body objects with Jakarta Bean Validation automatically.

A8 Properties from application.yml are bound at

Governance

Properties from application.yml are bound at compile time to @ConfigurationProperties POJO classes. Multiple environments (test, prod) load environment-specific files. MICRONAUT_APPLICATION_NAME env var and system properties can override file values.

A4 Micronaut Data generates repository query

Gotchas

Micronaut Data generates repository query implementations at compile time using the method name or @Query annotation, producing raw SQL/JPQL. There is no runtime proxy or reflection, making it significantly faster than Spring Data's runtime approach.

A9 Add micronaut-security-jwt. Configure

Assessment

Add micronaut-security-jwt. Configure jwt.signatures.secret in application.yml. Annotate endpoints with @Secured(SecurityRule.IS_AUTHENTICATED) or @Secured('ROLE_ADMIN'). Micronaut validates Bearer tokens on every request using the configured secret or JWKS.

A5 Micronaut generates GraalVM reflect-config.json,

Federation

Micronaut generates GraalVM reflect-config.json, resource-config.json, and proxy-config.json metadata files automatically during compilation. This eliminates most of the manual configuration required when adding native image support to other frameworks.

A10 @MicronautTest starts the application context

Optimization

@MicronautTest starts the application context for the test. Use the generated @Client interface or inject an HttpClient to call endpoints. Replace beans with @MockBean to provide mock implementations. EmbeddedServer starts a real HTTP server.