Memo No.....
Date...../...../.....

Mo Tu We Th Fri Sa Su

Đinh Kim Ngọc Ánh CNTT5
Mssv: 135008001 6

Bài 1:

```
interface Mail {
        void sendMail ();
        void log ();
}

class MailImpl implements Mail {
        @Override
        public void sendMail () {
            System.out.println ("Dang gui mail...");
        }

        @Override
        public void log () {
            System.out.println ("Dang ghi log...");
        }
}

public class Main {
        public static void main (String [] args) {
            MailImpl mail = new MailImpl ();
            mail.sendMail ();
            mail.log ();
        }
}
```

TUANVIET BOOKS

Memo No.....
Date...../...../.....

Bài 2:

```
interfaa Shape {
    String color = " Red ";
    void draw ();
}

class Rectangle implements Shape {
    @Overrid
    public void draw () {   " Daaw " + color + "Rectangle"
        System.out.println (" vẽ hcn vs màu "
                + color);
    }
}

Class Circle implements Shape {
    @Overrid
    public void draw () {
        System.out.println (" vẽ hình tròn vs màu "
                + color);
    }
}

Public class main {
    public static void main (String [] args) {
        Shape h1 = new Rectangle ();
        Shape h2 = new Circle ();
        h1.draw ();
        h2.draw ();
}
}
```

TUANVIET BOOKS

```
@Override
public void tangToc () {
        System.out.println (" Xe Dap TangToc")
}
@Override
public void dungLai () {
        System.out.println (" Xe Dap dung lai ")
}
@ Override
public double layVanToc () {
        return 20;
}
}

Class Main {
    public static void main ( String [ ] args ) {
        Xe Oto = new Xe Oto ("xang");
        MayBay = new MayBay ("Dau");
        XeDap = new XeDap ("Sic ng");
        System.out.println ("Van toc " + xeOto.
                layVanToc());
        System.out.println ("Van toc " + MayBay.
                layVanToc());
        System.out.println ("Van toc " + XeDap.
                layVanToc());
    }
}
```

```
@Override
Public void tangToc () {
        System.out.println (" Xe Oto TangToc")
}
@Override
Public void dungLai () {
        System.out.println (" Xe Oto DungLai")
}
@Override
Public double layVanToc () {
        return 100;
}
}

Public class XeDap implements PhuongTienDiChuyen {
    private HangSanXuat hangSanXuat;
    public XeDap (HangSanXuat hangSanXuat)
    {
        this.hangSanXuat = hangSanXuat;
    }
    @Override
    public String layTenHangSanXuat () {
        return hangSanXuat.getTenHangSanXuat();
    }
    @Override
    public void batDau () {
        System.out.println (" Xe dap bat dau
    }
```

Bài 3:

```
Interface PhuongTienDiChuyen {
    String layTenHangSanXuat ();
    void batDau ();
    void tangToc ();
    void dungLai ();
    double layVanToc ();
}
Class MayBay implements PhuongTienDiChuyen {
    private String loaiNhienLieu
    private HangSanXuat hangSanXuat;
    public MayBay ( String loaiNhienLieu, HangSanXuat
            hangSanXuat ) {
        this.hangSanXuat = hangSanXuat;
    }
    public void catCanh () {
        System.out.println (" May bay cat canh ")
    }
    public void haCanh () {
        System.out.println (" May bay ha canh")
    }
    @ Override
    public String layTenHangSanXuat () {
        return hangSanXuat.getTenHangSanXuat();
    }
    @ Override
    public void batDau () {
        System.out.println (" MayBay bat dau
    }
```

```
@Override
public void tangToc () {
        System.out.println (" MayBay TangToc ");
}
@Override
public void dungLai () {
        System.out.println (" MayBay dung Lai")
}
@Override
public double layVanToc () {
        return 800;
}
}
Class XeOto implements PhuongTienDiChuyen {
    private String loaiNhienLieu;
    private HangSanXuat hangSanXuat;
    public XeOto (String loaiNhienLieu; HangSanXuat hangSanXuat ) {
        this.loaiNhienLieu = loaiNhienLieu;
        this.hangSanXuat = hangSanXuat;
    }
    @Override
    public String layTenHangSanXuat () {
        return hangSanXuat.getTenHangSanXuat();
    }
    @Override
    public void batDau () {
        System.out.println (" Xe Oto bat dau")
    }
```

```
Public Class Main {
    public static void main (String [] args){
        Car [] ds = {
            new Bmw ("Den", 100),
            new Civic ("Tang", 50).
        };
        for ( Car c : ds ) {
            c.accelerate();
            System.out.println(c);
        }
    }
}
```

```
Class Civic implements Car {
    private String color;
    private double speed;
    public Civic (String color, double speed){
        this.color = color;
        this.speed = speed;
    }
    @Override
    public void accelerate () {
        speed += 15;
    }
    @Override
    public String getColor () {
        return color;
    }
    @Override
    public double getSpeed () {
        return speed;
    }
    @Override
    public String toString () {
        return "Civic color: " + color + ", speed: " + speed;
    }
}
```

Bài 4

```
Interface Car {
    void accelerate();
    String getColor();
    double getSpeed();
}
Class Bmw implements Car {
    private String color;
    private double speed;
    public Bmw (String color, double speed){
        this.color = color;
        this.speed = speed;
    }
    @Override
    public void accelerate () {
        speed += 20;
    }
    @Override
    public String getColor () {
        return color;
    }
    @Override
    public double getSpeed () {
        return speed;
    }
    @Override
    public String toString () {
        return "Bmw color: " + color + ", speed: " + speed
    }
}
```

```
}
}
```

Bài 5:

```
Interface Moveable {
    void moveUp();
    void moveDown();
    void moveLeft();
    void moveLeft();
    void moveRight();
}
Class MoveablePoint implements Moveable {
    private int x;
    private int y;
    private int xspeed;
    private int ySpeed;
    public MoveablePoint (int x, int y,
            int xSpeed, int ySpeed){
```

```
Class MoveableCircle implements Moveable {
    private int radius;
    private MoveablePoint center;
    public MoveablePoint center;
    public MoveableCircle (MoveablePoint
            center, int radius) {
        this.center = center;
        this.radius = radius;
    }
    @Override
    Public void moveUp() {
        center.moveUp();
    }
    @Override
    Public void moveUp() {
        center.moveUp;
    }
    @Override
    Public void moveDown() {
        center.moveDown();
    }
    @Override
    Public void moveLeft() {
        center.moveLeft();
    }
    @Override
    public void moveRight() {
        center.moveRight();
    }
```

```
    Public MoveablePoin (int x, int y, int xSpeed
            int ySpeed) {
        this.x = x;
        this.y = y;
        this.xSpeed = xSpeed;
        this.ySpeed = ySpeed;
    }
    @Override
    public void moveUp() {
        y += ySpeed;
    }
    @Override
    public void moveDown() {
        y -= ySpeed;
    }
    @Override
    public void moveLeft() {
        x -= xSpeed;
    }
    @Override
    public void moveRight() {
        x += xSpeed;
    @Override
    public String toString() {
        return "Point (x = " + x + "
            , y = " + y + ")";
    }
}
```

```
    @Override
    Public String toString() {
        return "Circle (center = " + center
            + ", radius = " + radius
            + ")";
    }
}
Public class Main {
    Public static void main (String[] args) {
        Moveable m1 = new MoveablePoint(0,0,
        Moveable m2 = new MoveableCircle (new
            MoveablePoint(1, 1, 2, 2), 10);
        m1.moveUp();
        m2.moveRight();
        System.out.println(m1);
        System.out.println(m2);
    }
}
```