Bài 1:

Lớp Hình học là lớp cha, 2 lớp con Hình tròn và HCN đều override phương thức tính DienTich() tích

```
Class HinhHoc {
    void tinhDienTich () {
        System.out.println (" Tính diện tích
                    hình học ");
    }
}

Class HinhTron extends HinhHoc {
    double bankinh;
    HinhTron (double bankinh ) {
        this.bankinh = bankinh;
    }
    @override
    void tinhdientich() {
        double dt = Math.PI * bankinh
                    * bankinh;
        System.out.println (" Diện tích
                    hình tròn : " + dt);
    }
}
```

```
Class HinhChuNhat extend HinhHoc {
    private double dai, rong;
        HinhChuNhat ( double dai, rong ){
            this.dai = dai;
            this.rong = rong;
    }
    @override
    void tinhDienTich () {
        double dienTich = chieudai * ch
        System.out.println (" Dt hcn: " + d
```

Đa hình là gì?

Tính đa hình có nghĩa là cùng 1 hành động nhưng ở ngữ cảnh ≠ nhau cho ra kq ≠ nhau, or cho ra kq ≠ nhau.

BTập.

Lớp cha: Animal

- Pig : ủn ỉn
- Cat
- Dog : gầu
- Bird

Lớp Cha

```
Public class Animal {
    public void makeSound() {
        System.out.println("Dong vat keu
    }
}

Public Class Pig extends Animal {
    @override
    public void makeSound() {
        System.out.println("ủn ỉn");
    }
}

Public Class Dog extends Animal {
    @overide
    public void makeSound() {
        System.out.println("gâu gâu");
    }
}

Public Class Cat extends Animal {
    @ override
    public void makeSound() {
        System.out.println("meo meo");
    }
}

Public Class Bird extends Animal {
    @override
    public void makeSound() {
        System.out.println("chíp chíp").
    }
}

Public Class Main {
    public static void main (String[] args) {
        Animal a1 = new Pig();
        Animal a2 = new Dog();
        Animal a3 = new Cat();
        Animal a4 = new Bird();

        a1.makeSound();
        a2.makeSound();
        a3.makeSound();
        a4.makeSound();
    }
}
```

BT 2. Class Xe đạp và Xe Đạp Đua ghiđè n

```
Class XeDap {
    Public void run() {
        System.out.println("Run");
    }
}

Class XeDapDua extends XeDap {
    @overrid
    Public void run() {
        System.out.println("Run");
    }
}
```

```
Public class Program {
    public static void main (String[] args)
    {
        xedap x1 = new xeDap ();
        xedap x2 = new xeDapDua();

        x1.run();
        x2.run();
    }
}
```

BT 3. Person - Employee - Manager

Lớp cha

```
Class Person {
    private String name;
    private Date Birthday;

    public void setName (String name) {
        this.name = name;
    }
    public void setBirthday (Date birthday)
    {
        this.birthday = birthday;
    }
    public String getDetails () {
        return "Name: " + name + ",
            Birthday: " + birthday;
    }
}
```

Employee

```
Class Employee extends Person {
    private double salary;
    public void setSalary (double salary) {
        this.salary = salary;
    }
    @Override
    public String getDetails () {
        return super.getDetails () + ",
            Salary " + salary;
    }
}
```

Manager

```
Class Manager extends Employee {
    private Employee assistant;
    public void setAssistant (Employee assist
    {
        this.assistant = assistant;
    }
    @Override
    public String getDetails () {
        return super.getDetails () +
            ", Assistant: " +
            (assistant != null ? assis
            getDetails () : "None")
    }
}
```

```
Public class Program {
    public static void main (String [] args)
    {
        Employee e = new Employee ();
        e.setName ("An");
        e.setSalary (1600);

        Manager m = new Manager ()
        m.setName ("Bu");
        m.setSalary (3900);
        m.setAssistant (e);
    System.out.println (m.getDetails ());
    }
}
```

~~BT4~~: Main4: ~~Bank~~

```
Public class Program {
    public static void main (String [] args)
    {
        Bank b1 = new SBI ();
        bank b2 = new ICICI ();
        bank b3 = new AXIS ();
        System.out.println ("SBI rate: "
                + b1.getRate() + "%");
System.out.println ("ICICI rate: " + b2.getRate()
                + "%");
System.out.println ("AXIS rate: " + b3.getRate() + "%");
    }
}
```

Bài tập 4 Bank

```
Class Bank {
    public double getRate () {
        return 0;
    }
}

Class SBI extends Bank {
    @override
    public double getRate () {
        return 8;
    }
}

Class ICICI extends Bank {
    @ override
    public double getRate () {
        return 7;
    }
}

Class Axis extends Bank {
    @ override
    public double getRate () {
        return 9;
    }
}
```

TUANVIET BOOKS