

Setting up and running CpHMD

Prerequisites

charmm

amber

chamber (parmed)

see also github.com/dkortzak/CpHMD

Force-fields and engines

If you are familiar with GROMACS you know the difference between engine and force-field

CHARMM and AMBER both are names for force-field as well as MD engines

Here we use the CHARMM **force-field** and AMBER **engine**

AMBER was never designed to do that, but there are workarounds:

First generate CHARMM input files and then convert them into AMBER input files with **parmed**

CHARMM CpHMD force-field files

All potential protons have to present as a (dummy) particles

For HIS just take HSP

For ASP and GLU we need a residue with (dummy) protons on both oxygens

AMBER vs GROMACS vs CHARMM

GROMACS and AMBER are similar in having tons of binaries for different tasks

pdb2gmx - tleap (only works with AMBER force-field)

grompp + mdrun - pmemd

trjconv, trjcat, rms, rmsf, ... are all collected in **cpptraj** (more details tomorrow)

CHARMM is one single binary for everything. What it does is defined in the input file.

AMBER vs GROMACS vs CHARMM

mdin vs mdp files

Overall very similar, parameter values are more cryptic in AMBER and more self-explanatory in GROMACS

Whereas grompp generates a single input file with all settings stored in the tpr file, AMBER skips this step. Topology and parameters are directly fed to the MD executable.

AMBER GPU implementation

CPU is not used at all except for i/o

Only one GPU should be used per system (it can use multiple but performance gain is bad)

If you have multiple GPUs per node you should start several systems in parallel, e.g. different pH values

Makes it very cost efficient but not on a cluster which was designed with GROMACS in mind

CpHM workflow

1. Start with a pdb file of the (pre-equilibrated) system
2. Separate components
3. Separate big files (only 100,000 atoms per file)
4. Renumber residues and atoms (always start from 1 in each file)
5. Adjust residue names
6. Remove all protons from protein
7. generate charmm coordinate and topology files for each component
8. assemble them back into one coordinate and one topology file
9. convert those to amber input files
10. Run CpHMD with AMBER engine

CpHMD workflow

1. Start with a pdb file of the (pre-equilibrated) system
2. Separate components
3. Separate big files (only 100,000 atoms per file)
4. Renumber residues and atoms (always start from 1 in each file)
5. adjust residue names
6. Remove all protons from protein

Many ways to achieve this, do whatever you prefer.

E.g. grep, sed and some python scripts, gmx editconf

Residue names to adjust

all aspartates need to be named ASP

all glutamates need to be named GLU

all histidines need to be named HSP

all waters need to be named TIP3

These are just the standard residue names, you might add your own residues if you want to mimic pH gradients or target parameters of a specific residue

Structure processing example

```
1  grep PROA system.pdb > proah.pdb
2  grep POPC system.pdb > memb.pdb
3  grep TIP3 system.pdb > bwat.pdb
4  grep CLA system.pdb > cla.pdb
5  grep SOD system.pdb > sod.pdb
6
7  sed -i '/TER /d' memb.pdb
8  sed -i '/TER /d' bwat.pdb
9  sed -i 's/OH2 TIP /OH2 TIP3/g' bwat.pdb
10 sed -i 's/H1 TIP /H1 TIP3/g' bwat.pdb
11 sed -i 's/H2 TIP /H2 TIP3/g' bwat.pdb
12 sed -i 's/ 0.00      / 0.00      TIP3 /g' bwat.pdb
13 sed -i "s/TIP3S/TIP3 /g" bwat.pdb
14 sed -i "s/SOLV/TIP3 /g" bwat.pdb
15 python noh.py|
16
17 sed -i 's/HSE/HSP/g' proa.pdb
18 sed -i 's/HSD/HSP/g' proa.pdb
19 sed -i '/H.*HSP/d' proa.pdb
20
21
22 python sepwat.py
23 python sepmemb.py
24 python sepprot.py
25 python sepions.py
```

CHARMM input files

```
1      stream toppar.str
2
3      open unit 1 read form name sod.pdb
4      read sequ pdb unit 1
5      gene IONS setup warn first none last n
6
7      open unit 1 read card name sod.pdb
8      read coor pdb unit 1 resid
9
10     IOFormat EXTENDED
11
12     open write unit 1 card name sod1.psf
13     write psf unit 1 card
14
15     open write card unit 1 name sod1.crd
16     write coor unit 1 card
17
18     stop
```

Load force-field

Load pdb

generate and save topology

CHARMM input files

```
3  set input prob.pdb
4  set outname prob_h
5  set segid PROB
6  ! read in modified top and par files
7  set TOPPAR = toppar
8  set top = @TOPPAR/top_all22_prot.rtf
9  set par = @TOPPAR/par_all22_prot.prm
10 set watstr = @TOPPAR/toppar_water_ions.str
11 set phstr = @TOPPAR/toppar_phmd_c22_foramber.str
12
13 open unit 1 read form name @top
14 read rtf card unit 1
15 close unit 1
16
17 open unit 1 read form name @par
18 read param card unit 1 flex
19 close unit 1
20
21 stream @phstr
22 stream @watstr
23
24 ! read in sequence
25 open unit 1 read form name @input
26 read sequ pdb unit 1
27
28 ! generate psf
29 generate @segid first ACE last CT3 setup
30 !generate @segid
31
```

```
! patch dummy atoms for ASP and GLU
! -----
define ANY sele bynu 1 end
set res1 = ?selresi      ! get the starting value of resid
calc reslast = ?selresi + ?nres -1

set ires @res1

prnlev -1 !turn off printing

label patch
define residue sele segid @segid .and. resid @ires show end
if ?selresn eq asp patch aspp2 @segid @ires
if ?selresn eq glu patch glup2 @segid @ires
incr ires
if ires le @reslast goto patch

autogen angles dihed

hbuild sele segi @segid .and. resn asp .and. type HD* end ! Build coordinates for dummy hydrogen in Asp
hbuild sele segi @segid .and. resn glu .and. type HE* end ! Build coordinates for dummy hydrogen in Glu

prnlev 5

! Edit Dihedrals for Glupp2 and Aspp2
!-----

define ANY sele bynu 1 end
set res1 = ?selresi      ! get the starting value of resid
calc reslast = ?selresi + ?nres -1

ic gene
ic fill
```

parmed

```
chamber -top toppar/top_all22_prot.rtf -top toppar/top_all36_na.rtf -top toppar/top_all36_lipid.rtf  
-top toppar/top_all36_carb.rtf -top toppar/top_all36_cgenff.rtf -param toppar/par_all22_prot.prm  
-param toppar/par_all36_na.prm -param toppar/par_all36_carb.prm -param  
toppar/par_all36_lipid.prm -param toppar/par_all36_cgenff.prm -str toppar/toppar_water_ions.str  
-str toppar/toppar_phmd_c22_foramber.str -psf hhv1.psf -crd hhv1.crd -box  
83.13,83.13,103.25,90,90,90
```

```
parmout hhv1.parm7 hhv1.rst7
```

```
go
```

Adjust box vectors

parmed Hydron mass repartitioning

We can redistribute some masses to H atoms and then use a 4fs time-step.

```
parm hhv1.parm7
```

```
hmassrepartition
```

```
outparm hhv1_0.parm7
```

```
quit
```

pmemd arguments

-O overwrite outputs

unlike GROMACS, AMBER will not make backups of files that already exists.

In case an output file already exists, it will either crash if -O is not set or overwrite without asking or backing up.

pmemd arguments inputs

-i MD parameter file

-p Topology

-c Start structure or restart file (may have positions only or positions and velocities)

-ref Reference for position restraints

CpHMD specific files

-phmdparm CpHMD parameters

-phmdin phmd settings

-phmdstrt state of lambda variables

pmemd arguments outputs

-r Restart file

-x trajectory

-o logfile

CpHMD specific files

-phmdout protonation states

-phmdrestrt Restart file for CpHMD

Step1 Minimization

Done without CpHMD activated

Safer to do on CPU

Step2 Equilibrations

Several stages with different position restraints

Where I come from:

1. Position restraints on everything but water
2. Position restraints on all protein atoms
3. Position restraints on all protein backbone atoms

1 and 2 can be relatively short and fixed duration

3 should be done until it is done, how long that takes will be different for different systems

Can be done at one pH and then simulations at other pH values can be started from the equilibrated system

Just recommendation what you do for your system might be different

Some AMBER parameters

```
1  Minimization input file in explicit solvent
2  &cntrl
3      ! Minimization options
4      imin=1,          ! Turn on minimization
5      maxcyc=500,      ! Maximum number of minimization cycles
6      ncyc=500,        ! 100 steepest-descent steps, better for strained systems
7
8      ! Potential energy function options
9      cut=12.0,        ! nonbonded cutoff, in angstroms
10     fswitch=10.0,    ! Force-based switching
11
12     ! Control how often information is printed to the output file
13     ntp=100,         ! Print energies every 100 steps
14     ntpr=2,          ! Write NetCDF format
15
16     ! Restraint options
17     ntr=1,           ! Positional restraints for proteins, sugars, ligands, and lipid head groups
18     nmropt=1,        ! Dihedral restraints for sugars and lipids
19
20     ! Set water atom/residue names for SETTLE recognition
21     watnam='TIP3',   ! Water residues are named WAT
22     owtm='OH2',      ! Water oxygens are named O
23 /
```

Some AMBER parameters

```
1      A NPT simulation for common production-level simulations
2      &cntrl
3          imin=0,          ! No minimization
4          irest=1,         ! This IS a restart of an old MD simulation
5          ntx=5,           ! So our inpcrd file has velocities
6
7          ! Temperature control
8          ntt=3,           ! Langevin dynamics
9          gamma_ln=1.0,    ! Friction coefficient (ps^-1)
10         temp0=310,        ! Target temperature
11
12         ! Potential energy control
13         cut=12.0,         ! nonbonded cutoff, in angstroms
14         fswitch=10.0,     ! Force-based switching
15
16         ! MD settings
17         nstlim=50000,     ! 250K steps, 500 ps total
18         dt=0.004,         ! time step (ps)
19     o
```

Some AMBER parameters

```
! Control how often information is printed
ntpr=1000,      ! Print energies every 1000 steps
ntwx=50000,     ! Print coordinates every 5000 steps to the trajectory
ntwr=10000,     ! Print a restart file every 10K steps (can be less frequent)
! ntwv=-1,      ! Uncomment to also print velocities to trajectory
! ntwf=-1,      ! Uncomment to also print forces to trajectory
ntxo=2,         ! Write NetCDF format
ioutfm=1,       ! Write NetCDF format (always do this!)

! Wrap coordinates when printing them to the same unit cell
iwrap=1,

! Constant pressure control.
barostat=2,     ! MC barostat... change to 1 for Berendsen
ntp=3,          ! 1=isotropic, 2=anisotropic, 3=semi-isotropic w/ surften
pres0=1.0,      ! Target external pressure, in bar

! Constant surface tension (needed for semi-isotropic scaling). Uncomment
! for this feature. csurften must be nonzero if ntp=3 above
csurften=3,     ! Interfaces in 1=yz plane, 2=xz plane, 3=xy plane
gamma_ten=0.0,  ! Surface tension (dyne/cm). 0 gives pure semi-iso scaling
ninterface=2,   ! Number of interfaces (2 for bilayer)
```

Position restraints

Two ways to define restraints:

```
! Restraint options
ntr=1,          ! Positional restraints for proteins, sugars, ligands, and lipid head groups
restraintmask="@CA,N,C",
restraint_wt=1.0,
```

```
Protein posres
10.0
RES 1 134
END
Membrane posres
10.0
FIND
P * * POPC
SEARCH
RES 1 10946
END
END
```


Selection syntax

Syntax	Example
<code>{residue numlist}</code>	<code>'1-10', '1,3,5', '1-3,5,7-9'</code>
<code>@{atom numlist}</code>	<code>'@12,17', '@54-85', '@12,54-85,90'</code>
<code>{residue namelist}</code>	<code>'LYS', 'ARG,ALA,GLY'</code>
<code>@{atom namelist}</code>	<code>'@CA', '@CA,C,O,N,H'</code>
<code>@%{atom type name}</code>	<code>'@%CT'</code>
<code>@/{atom_element_name}</code>	<code>'@/N'</code>
Selection for CHAIN ID's	#Select chain A <pre>::A</pre> # Select residues 1-10 of chains A, B, and C <pre>::A,B,C:1-10</pre> # Select protein backbone atoms of residues 2-20 in chains A and B <pre>::A,B:2-20@CA,C,O,N</pre>

Selection syntax

:ALA,TRP	All alanine and tryptophan residues.
:5,10@CA CA	carbon in residues 5 and 10.
:*&!@H=	All non-hydrogen atoms (equivalent to "!@H=").
@CA,C,O,N,H	All (protein) backbone atoms.
!@CA,C,O,N,H	All non-backbone atoms (=sidechains for proteins only).
:1-500@O&!(:WAT :LYS,ARG)	All backbone oxygens in residues 1-500 but not in water, lysine or arginine residues.
(:11@CD<:5.5)&:Na+	Select all residues within 5.5 Ang. of atom CD from residue 11) AND those residues must be named Na+

CpHMD settings

```
1      &phmdin
2          QMass_PHMD = 10,           ! Mass of the Lambda Particle
3          Temp_PHMD = 310,          ! Temp of the lambda particle
4          phbeta = 5,               ! Friction Coefficient (1/ps) for titration integrator
5          iphfrq = 1,               ! Frequency to update the lambda forces
6          NPrint_PHMD = 5000,       ! How often to print the lambda
7          PrLam = .true.,           ! Should lambda be printed
8          PrDeriv = .false.,        ! Do you want to print the derivatives?
9          PRNLEV = 7,               ! Sets what is printed out, (7) normal print level
10         PHTest = 0,               ! Are lambda and theta fixed, (0) = not fixed, (1) = fixed
11         MaskTitrRes(:) = 'ASP','GLU','HSP','AST','GLT','HST', ! Residues to include as titratable
12         MaskTitrResTypes = 6,     ! number of titratable residues
13         QPHMDStart = .true.,      ! Initialize velocities of titration variables with a Boltzmann distribution
14     /
```