

Government Engineering College, Thrissur

CS333– Application Software Development Lab

Documentation -

Exp 4 – Constraints and Views

Exp 7 - Creation of Views and Assertions

Date of Submission

22 September 2020

Submitted By

**Kowsik Nandagopan D**

Roll No 31

TCR18CS031

GECT CSE S5

# Experiment 4

## AIM

Creating a database to set various constraints.

## Description

Relations between the database is already created in the Experiment 1 and 2. In this experiment we will be focusing on setting constraints on tables that were created in the previous experiments.

Constraints that are available in MySQL are Use constraints like Not Null, Primary Key, Unique, Foreign Key.

Note: CHECK command is not supported in some MySQL versions

## Output / Screenshots

1. Displaying the Constraints set during Table creation

```
mysql> show tables;
+-----+
| Tables_in_ppm |
+-----+
| Consultant_Technologies |
| Consultants |
| Contacts |
| Customers |
| Designations |
| Project_Resources |
| Project_Technologies |
| Project_Transaction |
| Projects |
| Technology |
| Users |
+-----+
11 rows in set (0.00 sec)
```

```
mysql> describe Consultant_Technologies;
```

Field	Type	Null	Key	Default	Extra
ID	int(11)	NO	PRI	NULL	auto_increment
TechID	int(11)	NO	MUL	NULL	
ConsultantID	int(11)	NO	MUL	NULL	

3 rows in set (0.00 sec)

```
mysql> describe Consultants;
```

Field	Type	Null	Key	Default	Extra
ID	int(11)	NO	PRI	NULL	auto_increment
name	varchar(200)	NO		NULL	
phone	varchar(14)	NO		NULL	
email	varchar(200)	NO		NULL	
presentAddress	varchar(300)	NO		NULL	
pAddress	varchar(200)	NO		NULL	
highest_edu	varchar(100)	NO		NULL	
experience	int(11)	NO		0	
designation	int(11)	NO	MUL	NULL	

9 rows in set (0.00 sec)

```
mysql> describe Contacts;
```

Field	Type	Null	Key	Default	Extra
Conatct_Person	varchar(200)	NO		NULL	
ID	int(11)	NO	PRI	NULL	auto_increment
phone	varchar(14)	NO		NULL	
mobile	varchar(14)	NO		NULL	
Email	varchar(200)	NO		NULL	
profile_desc	varchar(300)	NO		NULL	
CustomerID	int(11)	NO	MUL	NULL	

7 rows in set (0.00 sec)

```
mysql> describe Customers;
```

Field	Type	Null	Key	Default	Extra
Name	varchar(200)	NO		NULL	
ID	int(11)	NO	PRI	NULL	auto_increment
phone	varchar(14)	NO		NULL	
email	varchar(200)	NO		NULL	
fax	varchar(14)	YES		NULL	
pAddress	int(11)	YES	MUL	NULL	

6 rows in set (0.00 sec)

```
mysql> describe Designations;
```

Field	Type	Null	Key	Default	Extra
ID	int(11)	NO	PRI	NULL	auto_increment
Grade	varchar(8)	NO		NULL	
Designation	varchar(50)	NO		NULL	

3 rows in set (0.00 sec)

```
mysql> describe Project_Resources;
```

Field	Type	Null	Key	Default	Extra
ID	int(11)	NO	PRI	NULL	auto_increment
Project_ID	int(11)	NO	MUL	NULL	
Resource_ID	int(11)	NO	MUL	NULL	
Hourly_Rate	double(12,2)	NO		0.00	
Estimate_Effort	double(12,2)	NO		0.00	
Actual_Effort	double(12,2)	NO		0.00	
Relative_Percentage_completed	double(5,2)	NO		0.00	

7 rows in set (0.00 sec)

```
mysql> describe Project_Technologies;
```

Field	Type	Null	Key	Default	Extra
ID	int(11)	NO	PRI	NULL	auto_increment
ProjectID	int(11)	NO	MUL	NULL	
TechID	int(11)	NO	MUL	NULL	

3 rows in set (0.00 sec)

```
mysql> describe Project_Transaction;
```

Field	Type	Null	Key	Default	Extra
ID	int(11)	NO	PRI	NULL	auto_increment
Resource_ID	int(11)	NO	MUL	NULL	
Entry_Date	datetime	NO		CURRENT_TIMESTAMP	
Effort_Spent	decimal(10,2)	NO		0.00	
Percentage_Completed	decimal(5,2)	NO		0.00	
ProjectID	int(11)	NO	MUL	NULL	

6 rows in set (0.01 sec)

```
mysql> describe Projects;
```

Field	Type	Null	Key	Default	Extra
ID	int(11)	NO	PRI	NULL	auto_increment
Title	varchar(200)	NO		NULL	
Description	varchar(300)	NO		NULL	
CustomerID	int(11)	NO	MUL	NULL	
PM	int(11)	NO	MUL	NULL	
status	int(11)	NO		NULL	
estimated_effort	double(10,2)	NO		0.00	
estimated_cost	double(10,2)	NO		0.00	
pCompleted	double(5,2)	NO		0.00	
Start_Date	datetime	NO		CURRENT_TIMESTAMP	
Finish_Date	datetime	NO		CURRENT_TIMESTAMP	

11 rows in set (0.00 sec)

```
mysql> describe Technology;
```

Field	Type	Null	Key	Default	Extra
ID	int(11)	NO	PRI	NULL	auto_increment
Technology	varchar(200)	NO		NULL	
Version	varchar(10)	NO		NULL	

3 rows in set (0.01 sec)

```
mysql> describe Users;
```

Field	Type	Null	Key	Default	Extra
ID	int(11)	NO	PRI	NULL	auto_increment
username	varchar(200)	NO		NULL	
password	varchar(1000)	NO		NULL	
consultant	tinyint(1)	NO		0	
user_id	int(11)	NO	UNI	NULL	
active	tinyint(1)	NO		1	

6 rows in set (0.01 sec)

## 2. Trying to Override the constraints

- Trying to insert into Projects Table with NULL and check whether it produces an error
- Also For estimated\_effort | estimated\_cost | pCompleted | Start\_Date | Finish\_Date check whether DEFAULT Constraint works

### 2.1 NOT NULL

```
mysql> INSERT INTO Projects (Title, Description, CustomerID, PM, status) VALUES ("Pide Piper", "Compression Tool", 1, 1, 1);
Query OK, 1 row affected (0.07 sec)
```

### 2.2 DEFAULT

```
mysql> INSERT INTO Projects (Title, Description, CustomerID, PM, status) VALUES ("Pide Piper", "Compression Tool", 1, 1, 1);
Query OK, 1 row affected (0.07 sec)

mysql> SELECT * FROM Projects ORDER BY ID DESC LIMIT 1;
```

ID	Title	Description	CustomerID	PM	status	estimated_effort	estimated_cost	pCompleted	Start_Date	Finish_Date
4	Pide Piper	Compression Tool	1	1	1	0.00	0.00	0.00	2020-09-22 11:52:12	2020-09-22 11:52:12

1 row in set (0.00 sec)

### 2.3 Trying to add using duplicate PRIMARY KEY

- Try to Insert row into Projects table with duplicate primary key
- Select the last entered row and use it's primary key

```
mysql> INSERT INTO Projects (ID, Title, Description, CustomerID, PM, status) VALUES (4, "Pide Piper", "Compression Tool", 1, 1, 1);
ERROR 1062 (23000): Duplicate entry '4' for key 'PRIMARY'
```

### 2.4 Non Existing FOREIGN KEY

Try to add a Project with non existing FOREIGN KEY (Non existing Project Manager)

```
mysql> INSERT INTO Projects (Title, Description, CustomerID, PM, status) VALUES (NULL, NULL, NULL, 1, 1);
ERROR 1048 (23000): Column 'Title' cannot be null
```

- This will give an error - ERROR 1452 (23000): Cannot add or update a child row: a foreign key constraint fails (`ppm`.`Projects`, CONSTRAINT `Projects\_ibfk\_2` FOREIGN KEY (`PM`) REFERENCES `Consultants` (`ID`))
- Due to PM (FOREIGN KEY to Consultants Table) does not exist

Correct:

```
mysql> INSERT INTO Projects (Title, Description, CustomerID, PM, status) VALUES (NULL, NULL, NULL, 1, 1);
ERROR 1048 (23000): Column 'Title' cannot be null
```

## 2.5 UNIQUE

Try to override UNIQUE Constraint of user id (FOREIGN KEY) in User Table

```
mysql> SELECT * FROM Users;
+-----+-----+-----+-----+
| ID | username | password | active |
+-----+-----+-----+-----+
| 1 | dkowsikpat | 1f40fc92da241694750979ee6cf582f2d5d7d28e18335de05abc54d0560e0f5302860c652bf08d560252aa5e74210546f369fbbbce8c12cfc7957b2652fe9a75 |
| 1 | 1 | 1 | 1 |
+-----+-----+-----+-----+
1 row in set (0.00 sec)

mysql> INSERT INTO Users (username, password, user_id) VALUES (
-> "pide piper",
-> "1f40fc92da241694750979ee6cf582f2d5d7d28e18335de05abc54d0560e0f5302860c652bf08d560252aa5e74210546f369fbbbce8c12cfc7957b2652fe9a75",
-> 1);
ERROR 1062 (23000): Duplicate entry '1' for key 'user_id'
```

Correct:

```
mysql> INSERT INTO Users (username, password, user_id) VALUES (
-> "pide piper",
-> "1f40fc92da241694750979ee6cf582f2d5d7d28e18335de05abc54d0560e0f5302860c652bf08d560252aa5e74210546f369fbbbce8c12cfc7957b2652fe9a75",
-> 2);
Query OK, 1 row affected (0.06 sec)
```

# Experiment 7

## AIM

Creation of Views and Assertions

## Description

Relations between the database is already created in the Experiment 1 and 2. In this experiment we will be focusing on setting different views that can be created on relations between table using the CREATE VIEW command in SQL

Note: ASSERTION command is not supported in some MySQL versions

## Output / Screenshots

1. Project Technology Table Join View - Technologies used in Project

```
mysql> CREATE VIEW Projects_Technologies AS SELECT
-> Projects.ID, Projects.Title, Technology.ID AS TID, Technology.Techno
oggy
-> FROM
T * FROM Projects, Consultants:
-> Projects JOIN Project_Technologies
-> JOIN Technology
-> ON Projects.ID = Project_Technologies.ProjectID
E VIEW Projects_Technologies AS SELECT
-> Projects.ID, Projects.Title, Technology.ID AS TID, Technology.Techno
```

```
+---+---+---+---+
| ID | Title | TID | Technology |
+---+---+---+---+
| 1 | Sirius | 1 | Django |
| 1 | Sirius | 2 | Node JS |
| 1 | Sirius | 3 | Android |
| 1 | Sirius | 4 | Tensorflow |
| 1 | Sirius | 5 | Flutter |
| 2 | Open PPM | 1 | Django |
| 2 | Open PPM | 2 | Node JS |
| 2 | Open PPM | 3 | Android |
| 2 | Open PPM | 4 | Tensorflow |
| 2 | Open PPM | 5 | Flutter |
+---+---+---+---+
10 rows in set (0.00 sec)
```



2. Project Consultants - People working in the projects, Project Customer , Displays the relative efforts spent by the consultants on particular project

```
mysql> CREATE VIEW Projects_Consultants AS SELECT
-> Projects.ID, Projects.Title, Consultants.ID AS CID, Consultants.name
-> FROM Projects JOIN Consultants
-> WHERE Projects.PM = Consultants.ID;
Query OK, 0 rows affected (0.06 sec)

mysql> CREATE VIEW Projects_Customers AS SELECT
-> Projects.ID, Projects.Title, Customers.ID AS Cust_ID, Customers.Name
-> FROM Projects JOIN Customers
-> ON Projects.CustomerID = Customers.ID;
Query OK, 0 rows affected (0.07 sec)

mysql> CREATE VIEW Projects_Efforts AS SELECT
-> Projects.ID, Projects.Title, Consultants.ID AS CID, Consultants.name, Project_Transaction.Effort_Spent
-> FROM Projects JOIN Consultants JOIN Project_Transaction
-> ON Projects.ID = Project_Transaction.ProjectID
-> AND Consultants.ID = Project_Transaction.Resource_ID;
Query OK, 0 rows affected (0.08 sec)
```

Project - Consultants

ID	Title	CID	name
1	Sirius	4	Anna Mull
2	Open PPM	4	Anna Mull
3	Pide Piper	1	Petey Cruiser
4	Pide Piper	1	Petey Cruiser
5	Pide Piper	1	Petey Cruiser
6	Pide Piper	1	Petey Cruiser
7	Pide Piper	1	Petey Cruiser

7 rows in set (0.00 sec)

Project - Customer

ID	Title	Cust_ID	Name
1	Sirius	1	Acme Corporation
2	Open PPM	2	Soylent Corp
3	Pide Piper	1	Acme Corporation
4	Pide Piper	1	Acme Corporation
5	Pide Piper	1	Acme Corporation
6	Pide Piper	1	Acme Corporation
7	Pide Piper	1	Acme Corporation

7 rows in set (0.00 sec)

## Project – Effort

ID	Title	CID	name	Effort_Spent
2	Open PPM	1	Petey Cruiser	22.00
2	Open PPM	2	Anna Sthesia	10.00
2	Open PPM	3	Paul Molive	10.00
2	Open PPM	4	Anna Mull	15.00
2	Open PPM	5	Gail Forcewind	25.20
2	Open PPM	6	Paige Turner	5.00
2	Open PPM	7	Walter Melon	2.00
2	Open PPM	8	Nick R. Bocker	25.00
1	Sirius	9	Alex Fleix	26.00

9 rows in set (0.01 sec)

## 3. Consultant Designation Details

```
mysql> CREATE VIEW Consultant_Designation AS SELECT
-> Consultants.ID, Consultants.name, Designations.ID AS Desig_ID, Designations.Designation, Designations.Grade
-> FROM
-> Consultants JOIN Designations ON Consultants.designation = Designations.ID;
Query OK, 0 rows affected (0.09 sec)
```

ID	name	Desig_ID	Designation	Grade
1	Petey Cruiser	1	CEO	1
2	Anna Sthesia	2	Accounts Manager	2
3	Paul Molive	3	Design Manager	2
4	Anna Mull	4	Project Manager	2
5	Gail Forcewind	5	Marketing Manager	2
6	Paige Turner	7	CFO	1
7	Walter Melon	8	Android Developer	3
8	Nick R. Bocker	9	Data Analyst	3
9	Alex Fleix	6	Web Developer	3

9 rows in set (0.00 sec)

P. T. O

## 4. Alternate contact Information related to each project

```
mysql> CREATE VIEW Project_Customer_Alt_Contacts AS SELECT
-> Projects.ID, Projects.Title, Customers.ID AS Cust_ID, Customers.Name, Contacts.phone
-> FROM
-> Projects JOIN Customers JOIN Contacts
->     ON Projects.CustomerID = Customers.ID
->     AND Customers.ID = Contacts.CustomerID
->     AND Customers.pAddress <> Contacts.ID;
Query OK, 0 rows affected (0.04 sec)
```

ID	Title	Cust_ID	Name	phone
1	Sirius	1	Acme Corporation	7759478389
2	Open PPM	2	Soylent Corp	3277574011
3	Pide Piper	1	Acme Corporation	7759478389
4	Pide Piper	1	Acme Corporation	7759478389
5	Pide Piper	1	Acme Corporation	7759478389
6	Pide Piper	1	Acme Corporation	7759478389
7	Pide Piper	1	Acme Corporation	7759478389

7 rows in set (0.00 sec)