

DATA.STAT.840 Statistical Methods for Text Data Analysis

Exercises for Lectures 7: Hidden Markov models

Exercise 7.1: The Forward-Backward algorithm.

Consider a HMM model with the following vocabulary of 14 words:

{a, the, over, beside, near, quick, brown, lazy, jumps, runs, walks, fox, dog, cat}

and five states ($z=1, z=2, z=3, z=4, z=5$), where the distribution of the initial state is uniform and the states have the following emission distributions:

	a	the	over	beside	near	quick	brown	lazy	jumps	runs	walks	fox	dog	cat
$\{\beta_1(w)\} =$	{ 0.6,	0.4,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0}
$\{\beta_2(w)\} =$	{ 0,	0,	0.2,	0.4,	0.4,	0,	0,	0,	0,	0,	0,	0,	0,	0}
$\{\beta_3(w)\} =$	{ 0,	0,	0,	0,	0,	0.5,	0.3,	0.2,	0,	0,	0,	0,	0,	0}
$\{\beta_4(w)\} =$	{ 0,	0,	0,	0,	0,	0,	0,	0,	0.1,	0.4,	0.5,	0,	0,	0}
$\{\beta_5(w)\} =$	{ 0,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0.3,	0.4,	0.3}

and the following transition probabilities:

		z_t					
		1	2	3	4	5	
$\{\theta_{z_t z_{t-1}}\} =$	z_{t-1}	1	{ 0,	0,	0.5,	0,	0.5,
		2	1,	0,	0,	0,	0,
		3	0,	0,	0.3,	0,	0.7,
		4	0,	1,	0,	0,	0,
		5	0,	0.5,	0,	0.5,	0,

a) Use the forward-backward algorithm to compute the probability of the sentence "the quick fox jumps over a dog".

Report your computation steps and your answer.

Exercise 7.2: The Viterbi algorithm.

Consider a HMM model with the following vocabulary of 17 words:

{a, the, I, you, can, will, call, own, take, book, round, claim, car, hotel, new, great}

and five states ($z=1, z=2, z=3, z=4, z=5$), where the distribution of the initial state is uniform and the states have the following emission distributions:

	a	the	I	you	can	will	call	own	take	book	round	claim	car	hotel	new	great
$\{\beta_1(w)\} =$	{ 0.4,	0.3,	0.2,	0.1,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0}
$\{\beta_2(w)\} =$	{ 0.3,	0.4,	0,	0.3,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0}
$\{\beta_3(w)\} =$	{ 0,	0,	0,	0,	0.1,	0.15,	0.15,	0.15,	0.15,	0.1,	0.1,	0.1,	0,	0,	0,	0}
$\{\beta_4(w)\} =$	{ 0,	0,	0,	0,	0,	0,	0,	0,	0,	0,	0.3,	0,	0,	0,	0.4,	0.3}
$\{\beta_5(w)\} =$	{ 0,	0,	0,	0.05,	0.05,	0.05,	0.1,	0,	0,	0.15,	0.1,	0.15,	0.2,	0.15,	0,	0}

and the following transition probabilities:

		z_t					
		1	2	3	4	5	
$\{\theta_{z_t z_{t-1}}\} =$	z_{t-1}	1	{ 0,	0,	0.3,	0.3,	0.4,
		2	0,	0,	0,	0.4,	0.6,
		3	0,	0.75,	0.25,	0,	0,
		4	0,	0,	0,	0,	1,
		5	0,	0,	1,	0,	0,

In this HMM model words can act in multiple roles, e.g. 'book' be used as a noun or a verb, so there could be more than one way to parse some sentences.

Use the Viterbi algorithm to compute the most likely state sequence corresponding to the observed word sequence "you claim you can book a round hotel".

Report your computation steps and your answer.

(exercises continue on the next page)

Exercise 7.3: The Baum-Welch algorithm.

Consider the HMM model of exercise 7.1. Suppose the sentence "the quick fox jumps over a dog" is the only training data. Suppose the HMM parameter values listed in exercise 7.1 are initial values to be further optimized. Perform one iteration of the Baum-Welch algorithm to optimize the parameters for the training data.

Report your computation steps and your answer.