

TrackSessions Multi-User Architecture & Technical Explanation

Script: [TrackSessions.Simulator CR1.PreReserve.2026-09-07.mod1.ps1](#)

Version: cr1 Sept 2026

Last Updated: September 17, 2026

Executive Summary

What This Script Does

The **Windows Session Tracker** is a WPF-based PowerShell application that monitors and displays real-time session activity across multiple PAWS (Privileged Access Workstations) machines. The application serves as a coordination tool to help users identify which machines are currently in use and by whom.

Core Functionality:

- **Session Tracking:** Each running instance writes a JSON file containing session metadata (machine name, user, timestamps, status)
- **Multi-Machine Monitoring:** Displays activity from all configured PAWS machines in a centralized grid view
- **Status Detection:** Automatically determines session states (Logged In, Disconnected, Logged Out)
- **Shared Storage:** All sessions write to a common UNC network path for cross-machine visibility
- **Auto-Refresh:** Grid updates automatically via dual mechanisms (timer + file watcher)

User Workflow:

1. User launches the app on their PAWS machine (e.g., MTB012VP0030366)
 2. App creates a session JSON file in the shared folder (e.g.,
`\\server\share\Session.cr1.MTB012VP0030366.DS-YMJNB.YMJNB.20260917_021246Z.json`)
 3. App displays a grid showing sessions from OTHER machines (excluding current machine)
 4. User can see who is logged into other PAWS machines and their status
 5. When user disconnects or logs out, the JSON file is marked with appropriate status
 6. When user closes the app, a `.Logout.json` file is created to signal session end
-

Shared Settings Architecture

Settings File Structure

The application uses a hierarchical JSON settings file ([TrackSessions.Settings.json](#)) that stores:

```
{
  "SchemaVersion": "1.0",
  "MiniWindow": {
    "Left": 1000.0,
```

```

    "Top": 800.0
  },
  "Layout": {
    "BottomPaneHeight": 250.0,
    "WindowLeft": 100.0,
    "WindowTop": 100.0,
    "WindowWidth": 900.0,
    "WindowHeight": 500.0
  },
  "Tracking": {
    "SharedPath": "\\server\\share\\PAWS-Sessions",
    "Machines": [
      { "ShortName": "PAWS001", "FQDN": "PAWS001.domain.local", "Comment":
"Executive PAW" },
      { "ShortName": "PAWS002", "FQDN": "PAWS002.domain.local", "Comment": "Admin
PAW" }
    ]
  },
  "StartupTrace": {
    "Enabled": true,
    "Events": []
  }
}

```

Shared JSON Files - Multi-User Coordination

Location: `\\server\\share\\PAWS-Sessions\\` (configurable via settings)

File Naming Convention:

```
Session.<version>.<machine>.<domain-user>.<display-name>.<timestamp>Z.json
```

Example:

```
Session.cr1 Sept 2026.MTB012VP0030366.DS-YMJNB.YMJNB.20260917_021246Z.json
```

File Lifecycle:

1. **Creation:** File created when app starts, contains initial session metadata
2. **Updates:** File updated every 3 minutes with fresh `LastUpdatedAtGmt` timestamp
3. **Closure:** When app closes, adds `SessionStatus: "Closed"` and `SessionClosedAtGmt`
4. **Logout Marker:** Creates companion `.Logout.json` file with final state

Access Contention & File Locking

Challenge: Multiple users writing to the same shared folder simultaneously can cause:

- File lock conflicts when reading/writing

- Race conditions during concurrent updates
- Parsing errors when reading partially-written files

Mitigation Strategies in Current Implementation:

1. **Unique File Names:** Each session gets a unique filename with timestamp, preventing overwrites

```
$jsonFileName = "Session.{0}.{1}.{2}.{3}.{4}.json" -f  
    $appVersion, $fileMachine, $fileUser, $fileDisplay, $fileStamp
```

2. **Read-Only Access from Watchers:** FileSystemWatcher only reads files; doesn't hold locks

```
Get-Content -LiteralPath $file.FullName -Raw -ErrorAction Stop | ConvertFrom-  
Json
```

3. **Error Tolerance:** Parsing failures silently skip problematic files

```
catch {  
    Add-DebugLog "    -> ERROR processing file: $($_.Exception.Message)"  
}
```

4. **Atomic Writes:** Uses `Set-Content` which performs atomic file replacement

```
$snapshot | ConvertTo-Json -Depth 5 | Set-Content -LiteralPath $JsonPath -  
Encoding UTF8
```

Remaining Contention Points:

- No explicit file locking mechanism
- Network latency can delay file visibility
- No distributed lock coordination between instances
- Settings file shared by all users (last-write-wins model)

Technical Deep Dive

1. Debouncing Mechanism

Purpose: Prevent excessive UI updates when multiple file change events fire rapidly (e.g., bulk file operations, network latency bursts).

Implementation: Stopwatch-based non-blocking debounce (Lines 2337-2349)

```
# Initialize stopwatch before window shows
$script:lastFileWatcherTime = [System.Diagnostics.Stopwatch]::StartNew()

$fileChangedAction = {
    param($source, $eventArgs)

    # Debounce: only process if at least 500ms have passed since last event
    if ($script:lastFileWatcherTime.ElapsedMilliseconds -lt 500) {
        return # Exit early, ignore this event
    }
    $script:lastFileWatcherTime.Restart() # Reset the timer

    # Process the file change (non-blocking dispatch to UI thread)
    $window.Dispatcher.BeginInvoke({
        Add-DebugLog "FileSystemWatcher detected change: $($eventArgs.Name)"
        Update-SessionGridData
    }) | Out-Null
}
```

How It Works:

1. **Stopwatch Tracks Time:** `$script:lastFileWatcherTime` measures elapsed milliseconds since last processed event
2. **Early Exit:** If less than 500ms has passed since last event, immediately return (ignore this event)
3. **Reset on Process:** When event is processed, restart the stopwatch for next cycle
4. **Non-Blocking:** Uses `Dispatcher.BeginInvoke()` instead of `Invoke()` to avoid UI thread deadlocks

Why 500ms?

- Fast enough to feel responsive (sub-second)
- Slow enough to batch rapid-fire file changes
- Prevents UI thread saturation from network folder events

Previous Crash Cause (Fixed):

```
# ❌ OLD CODE - Caused crashes:
Start-Sleep -Milliseconds 200 # Blocked background thread
$window.Dispatcher.Invoke({ # Blocked waiting for UI thread (deadlock
    Update-SessionGridData
})

# ✅ NEW CODE - Non-blocking:
if ($script:lastFileWatcherTime.ElapsedMilliseconds -lt 500) { return }
$script:lastFileWatcherTime.Restart()
$window.Dispatcher.BeginInvoke({ Update-SessionGridData }) | Out-Null
```

2. Deduplication Logic

Purpose: When multiple JSON files exist for the same machine+user combination (e.g., multiple logins across different sessions), display only the MOST RECENT entry.

Implementation: Hash table keyed by machine+user (Lines 578-606)

```
# Deduplicate: keep only the most recent entry per machine + user combination
$deduped = @{}

foreach ($row in $rows) {
    # Create unique key: "MACHINE|DOMAIN\USER"
    $key = "{0}|{1}" -f $row.MachineName.ToUpperInvariant(),
    $row.UserId.ToUpperInvariant()

    if (-not $deduped.ContainsKey($key)) {
        # First entry for this machine+user combo
        $deduped[$key] = $row
        Add-DebugLog "Added to final list: $key | Status: $($row.RowStatus)"
    }
    else {
        # Duplicate found - compare timestamps
        $existing = $deduped[$key]
        try {
            $existingTime = [datetime]::Parse($existing.LastActivity,
                [System.Globalization.CultureInfo]::InvariantCulture,
                [System.Globalization.DateTimeStyles]::AssumeUniversal)
            $currentTime = [datetime]::Parse($row.LastActivity,
                [System.Globalization.CultureInfo]::InvariantCulture,
                [System.Globalization.DateTimeStyles]::AssumeUniversal)

            if ($currentTime -gt $existingTime) {
                # Current entry is newer - replace existing
                Add-DebugLog "Updating $key from Status: $($existing.RowStatus) to
                $($row.RowStatus) (newer timestamp)"
                $deduped[$key] = $row
            }
            else {
                # Existing entry is newer - keep it
                Add-DebugLog "Skipped duplicate $key - keeping existing Status:
                $($existing.RowStatus)"
            }
        }
        catch {
            # Timestamp parse failed - keep existing entry
            Add-DebugLog "Failed to parse timestamps for $key, keeping existing"
        }
    }
}

Add-DebugLog "Deduplication complete: $($rows.Count) rows ->
$($deduped.Values.Count) final entries"
return @($deduped.Values)
```

Key Design Decisions:

1. **Case-Insensitive Keys:** `ToUpperInvariant()` ensures "MTB012VP0030366" and "mtb012vp0030366" are treated as same machine
2. **Composite Key:** `MachineName|UserId` allows same user on different machines (different entries) but deduplicates same user on same machine (one entry)
3. **Timestamp Comparison:** Uses ISO 8601 timestamps (`LastActivity`) to determine recency
 - Format: `2026-09-17T02:12:46Z`
 - Culture-invariant parsing for reliability
4. **Safe Fallback:** If timestamp parsing fails, keeps existing entry (conservative approach)

Example Scenario:

Input Files:

- Session.cr1.PAWS001.DS-ALICE.Alice.20260917_100000Z.json (LastActivity: 10:00 AM)
- Session.cr1.PAWS001.DS-ALICE.Alice.20260917_110000Z.json (LastActivity: 11:00 AM)
- Session.cr1.PAWS002.DS-ALICE.Alice.20260917_103000Z.json (LastActivity: 10:30 AM)

After Deduplication:

- PAWS001|DS\ALICE → 11:00 AM entry (newer timestamp wins)
- PAWS002|DS\ALICE → 10:30 AM entry (only entry for this machine)

Grid Display: 2 rows (one per machine)

3. Dual Auto-Refresh Architecture

Design Philosophy: Redundant coverage ensures grid stays current via multiple mechanisms.

Mechanism 1: Timer-Based Refresh (Every 60 Seconds)

```
$gridRefreshTimer = New-Object System.Windows.Threading.DispatcherTimer
$gridRefreshTimer.Interval = [TimeSpan]::FromSeconds(60)
$gridRefreshTimer.Add_Tick({
    try {
        Add-DebugLog "Grid refresh timer fired - updating grid data"
        Update-SessionGridData
    }
    catch {
        Add-DebugLog "ERROR in grid refresh timer: $_"
    }
})
$gridRefreshTimer.Start()
```

Benefits:

-  Independent of file changes (catches status transitions)
-  Detects "Disconnected" status (sessions inactive > 3 minutes)
-  Works even when user's own session isn't being updated
-  Simple, predictable behavior

Mechanism 2: FileSystemWatcher (Event-Driven)

```
$watcher = New-Object System.IO.FileSystemWatcher
$watcher.Path = $script:effectiveOutputFolder
$watcher.Filter = "*.json"
$watcher.NotifyFilter = [System.IO.NotifyFilters]::LastWrite -bor
[System.IO.NotifyFilters]::FileName

$watcher.Add_Changed($fileChangedAction) # Existing file modified
$watcher.Add_Created($fileChangedAction) # New file created
$watcher.Add_Deleted($fileChangedAction) # File deleted (logout)
$watcher.EnableRaisingEvents = $true
```

Benefits:

-  Immediate detection of new sessions (< 1 second response)
-  Catches rapid status changes between timer intervals
-  No polling overhead (event-driven)
-  Monitors Created, Changed, Deleted events

Combined Advantage:

Timeline Example:

```
00:00 - User A logs in → FileSystemWatcher triggers → Grid updates immediately
00:45 - User B logs in → FileSystemWatcher triggers → Grid updates immediately
01:00 - Timer fires → Grid updates (catches any missed events)
02:00 - Timer fires → Grid updates (detects User A disconnected at 03:01)
02:15 - User C logs out → FileSystemWatcher triggers → Grid updates immediately
```

4. Status Detection Algorithm**Three Status States:**

1. **Logged In** (Green) - Session active, recent timestamp
2. **Disconnected** (Blue) - Session inactive > 3 minutes, no logout marker
3. **Logged Out** (Red) - Session explicitly closed

Implementation: (Lines 609-640)

```

function Get-SessionStatusFromSnapshot {
    param(
        [Parameter(Mandatory = $true)]$SnapshotObject,
        [Parameter(Mandatory = $true)][string]$SourceFilePath
    )

    $fileName = [System.IO.Path]::GetFileName($SourceFilePath)

    # Safe property access - returns $null if property doesn't exist
    $sessionStatus = $SnapshotObject | Select-Object -ExpandProperty SessionStatus
    -ErrorAction SilentlyContinue
    $closeEvent = $SnapshotObject | Select-Object -ExpandProperty
    SessionCloseEvent -ErrorAction SilentlyContinue
    $closedAt = $SnapshotObject | Select-Object -ExpandProperty SessionClosedAtGmt
    -ErrorAction SilentlyContinue

    # Priority 1: Check if logged out (filename, status, or close timestamps)
    if ($fileName -like '*.Logout.json' -or
        $sessionStatus -eq 'Closed' -or
        -not [string]::IsNullOrEmpty($closedAt) -or
        -not [string]::IsNullOrEmpty($closeEvent)) {
        return 'Logged Out'
    }

    # Priority 2: Check LastUpdatedAtGmt from JSON content
    $lastUpdateRaw = $SnapshotObject | Select-Object -ExpandProperty
    LastUpdatedAtGmt -ErrorAction SilentlyContinue
    if (-not [string]::IsNullOrEmpty($lastUpdateRaw)) {
        try {
            $lastUpdate = [datetime]::Parse($lastUpdateRaw,
                [System.Globalization.CultureInfo]::InvariantCulture,
                [System.Globalization.DateTimeStyles]::AssumeUniversal)
            $age = [DateTime]::UtcNow - $lastUpdate.ToUniversalTime()


            # If timestamp is older than 3 minutes, consider disconnected
            if ($age.TotalMinutes -ge 3) {
                return 'Disconnected'
            }
        }
        catch {
            # Timestamp parse failed - assume logged in
        }
    }

    # Default: Assume logged in (recent or active session)
    return 'Logged In'
}

```

Decision Tree:

Check Filename & JSON Properties



Critical Fix Applied:

```

# ❌ OLD CODE - Caused crashes when property doesn't exist:
$sessionStatus = [string]$SnapshotObject.SessionStatus # Throws error if property
missing

# ✅ NEW CODE - Safe property access:
$sessionStatus = $SnapshotObject | Select-Object -ExpandProperty SessionStatus -
ErrorAction SilentlyContinue
# Returns $null if property doesn't exist, no error thrown

```

Why Properties Might Not Exist:

- New session files only have `CreatedAtGmt`, `LastUpdatedAtGmt`, basic metadata
- `SessionStatus`, `SessionCloseEvent`, `SessionClosedAtGmt` added only on closure
- Logout files add additional properties (`LogoutFileCreatedAtGmt`, etc.)

Performance Characteristics

Current Performance Profile

Startup Time:

- Cold start: ~2-3 seconds (load WPF, read settings, enumerate initial files)
- Settings load: < 50ms (JSON parse + validation)
- Initial grid population: 200-500ms for 30-50 JSON files

Runtime Performance:

- Grid refresh (manual): 300-600ms per refresh (depends on file count)
- Timer refresh (60s auto): Same as manual, runs in background
- FileSystemWatcher event: < 100ms dispatch to UI thread (debounced)

- Memory footprint: ~80-120 MB (WPF + PowerShell host + grid data)

Network Considerations:

- File enumeration: Network latency dependent (UNC paths)
- Single file read: 20-80ms per file (network round-trip)
- Shared folder with 50 files: ~1-2 seconds to enumerate + read all

Scaling Limits

Current Design Constraints:

Factor	Limit	Impact When Exceeded
JSON Files	~100-200 files	Grid refresh slows to 1-2 seconds
Tracked Machines	~20 machines	Settings UI becomes unwieldy
Concurrent Users	~10-15 users	Network folder contention increases
FileSystemWatcher Events	~50 events/sec	Debouncing prevents most, but possible queue buildup
Grid Rows Displayed	~50 rows	WPF DataGrid performance degrades

Bottlenecks:

1. **File I/O:** Network UNC path reads are primary bottleneck

- Each **Get-Content** call requires network round-trip
- No caching of previously-read files
- Re-reads all files on every refresh

2. **JSON Parsing:** **ConvertFrom-Json** on every file every refresh

- CPU-bound operation
- No parsed-object caching
- Repeated parsing of unchanged files

3. **Grid Refresh:** Full ItemsSource replacement

```
$gridSessionFiles.ItemsSource = $null  
$gridSessionFiles.ItemsSource = $combinedRows
```

- Forces full grid re-render
- No incremental updates
- WPF rebinds all visual elements

4. **No Threading:** All file I/O on UI thread via Dispatcher

- Blocks UI during long folder reads
- No parallel file reading

Issues & Root Causes

1. Filtering Errors (Machine 366 Not Showing)

Symptom: Files for machine MTB012VP0030366 failed to appear in grid despite existing in folder.

Root Cause: Property access errors on incomplete JSON objects

```
# Error logged:  
The property 'SessionStatus' cannot be found on this object. Verify that the  
property exists.
```

Explanation:

- Newly created session files don't have `SessionStatus` property (added only on close)
- Direct property access `$obj.SessionStatus` throws error when property missing
- Error caused entire file to be skipped via catch block
- Machine 366 files were all "active session" files (no `SessionStatus` yet) → all skipped

Fix Applied:

```
# Before: Direct access (throws error if missing)  
$sessionStatus = [string]$SnapshotObject.SessionStatus  
  
# After: Safe access (returns $null if missing)  
$sessionStatus = $SnapshotObject | Select-Object -ExpandProperty SessionStatus -  
ErrorAction SilentlyContinue
```

Lines Changed: 616-628

2. Application Lock-Up / Crash After 3-4 Minutes

Symptom: App became unresponsive and crashed after running for a few minutes.

Root Causes:

Cause 2A: Blocking Sleep in FileSystemWatcher Event Handler

```
# ❌ BLOCKING CODE (caused deadlock):  
$fileChangedAction = {  
    Start-Sleep -Milliseconds 200 # BLOCKS background thread  
    $window.Dispatcher.Invoke({ # Then WAITS for UI thread  
        Update-SessionGridData  
    })  
}
```

Problem:

- **Start-Sleep** blocks the FileSystemWatcher background thread
- Multiple events queue up while thread is sleeping
- Thread pool exhaustion as threads block waiting to sleep
- UI thread blocked waiting for FileSystemWatcher thread via **Invoke()**
- **Classic deadlock scenario**

Fix:

```
# ✅ NON-BLOCKING CODE:
$fileChangedAction = {
    if ($script:lastFileWatcherTime.ElapsedMilliseconds -lt 500) { return }
    $script:lastFileWatcherTime.Restart()
    $window.Dispatcher.BeginInvoke({ # Async dispatch, no wait
        Update-SessionGridData
    }) | Out-Null
}
```

Cause 2B: Blocking Dispatcher.Invoke() Call

```
# ❌ BLOCKING:
$window.Dispatcher.Invoke({ ... }) # Waits for UI thread to finish

# ✅ NON-BLOCKING:
$window.Dispatcher.BeginInvoke({ ... }) | Out-Null # Returns immediately
```

Invoke vs BeginInvoke:

- **Invoke()**: Synchronous, blocks caller until UI thread executes code
- **BeginInvoke()**: Asynchronous, queues work and returns immediately

Why Invoke Caused Crashes:

1. FileSystemWatcher event fires on background thread
2. Event handler calls **Invoke()** → blocks background thread waiting for UI thread
3. If UI thread is busy (e.g., processing another event, rendering grid) → background thread waits
4. Multiple events fire → multiple background threads block → thread pool exhaustion
5. Eventually no threads available → app hangs → Windows kills process

Cause 2C: No Error Handling in Event Handlers

```
# ❌ OLD: Unhandled exceptions crash timer/watcher
$timer.Add_Tick({
    Update-SessionGridData # If this throws, timer dies
})

# ✅ NEW: Error handling prevents crashes
```

```
$timer.Add_Tick({
    try {
        Update-SessionGridData
    }
    catch {
        Add-DebugLog "ERROR in timer: $_"
    }
})
```

Lines Changed: 2337-2414 (FileSystemWatcher setup), 2353-2365 (grid refresh timer)

3. Grid Not Showing Current Machine Exclusion

Symptom: Current machine (e.g., NCT001MA4573619) sometimes appeared in grid showing "own" session.

Root Cause: Machine name comparison logic case sensitivity

Fixed By: Consistent `ToUpperInvariant()` usage

```
$excludeToken = $ExcludeMachineName.Trim().ToUpperInvariant()
$machineToken = $machineValue.Trim().ToUpperInvariant()

if ($machineToken -eq $excludeToken) {
    continue # Skip current machine
}
```

Lines Changed: 497-533

Suggestions for Improvement

High Priority: Performance & Scalability

1. File Read Caching

Problem: Re-reads all JSON files on every refresh (expensive network I/O)

Solution: Cache file content keyed by path + LastWriteTime

```
$script:fileCache = @{}

function Get-CachedJsonContent {
    param([string]$Path)

    $fileInfo = Get-Item -LiteralPath $Path
    $cacheKey = "{0}|{1}" -f $Path, $fileInfo.LastWriteTimeUtc.Ticks

    if ($script:fileCache.ContainsKey($cacheKey)) {
        return $script:fileCache[$cacheKey] # Cache hit
    }
}
```

```

    }

    # Cache miss - read and parse
    $content = Get-Content -LiteralPath $Path -Raw | ConvertFrom-Json
    $script:fileCache[$cacheKey] = $content

    # Limit cache size (keep last 100 entries)
    if ($script:fileCache.Count -gt 100) {
        $oldestKeys = $script:fileCache.Keys | Select-Object -First 50
        foreach ($key in $oldestKeys) {
            $script:fileCache.Remove($key)
        }
    }

    return $content
}

```

Expected Improvement: 50-70% reduction in refresh time for unchanged files

2. Parallel File Reading

Problem: Sequential file reads (network latency adds up)

Solution: Use runspace or workflow parallel to read files concurrently

```

$files = Get-ChildItem -LiteralPath $FolderPath -Filter '*.json'

# Read files in parallel (up to 10 at once)
$results = $files | ForEach-Object -Parallel {
    try {
        Get-Content -LiteralPath $_.FullName -Raw | ConvertFrom-Json
    }
    catch {
        $null # Return null for failed reads
    }
} -ThrottleLimit 10

```

Expected Improvement: 3-5x faster for 30+ files (network latency bound)

Note: Requires PowerShell 7+ for `ForEach-Object -Parallel`. Alternative: use runspace for PowerShell 5.1.

3. Incremental Grid Updates

Problem: Full ItemsSource replacement causes entire grid re-render

Solution: Use ObservableCollection and modify existing items

```

# Initialize once at startup
$script:gridCollection = New-Object

```

```

System.Collections.ObjectModel.ObservableCollection[Object]
$gridSessionFiles.ItemsSource = $script:gridCollection

# On refresh, update collection incrementally
function Update-SessionGridIncremental {
    param($NewRows)

    # Remove entries no longer present
    for ($i = $script:gridCollection.Count - 1; $i -ge 0; $i--) {
        $existing = $script:gridCollection[$i]
        $found = $NewRows | Where-Object {
            $_.MachineName -eq $existing.MachineName -and $_.UserId -eq
            $existing.UserId
        }
        if (-not $found) {
            $script:gridCollection.RemoveAt($i)
        }
    }

    # Add or update entries
    foreach ($row in $NewRows) {
        $existing = $script:gridCollection | Where-Object {
            $_.MachineName -eq $row.MachineName -and $_.UserId -eq $row.UserId
        }
        if ($existing) {
            # Update existing row properties
            $existing.LastActivity = $row.LastActivity
            $existing.RowStatus = $row.RowStatus
        }
        else {
            # Add new row
            $script:gridCollection.Add($row)
        }
    }
}

```

Expected Improvement: 30-50% reduction in UI update time, smoother animations

4. Background Thread for File Enumeration

Problem: File I/O blocks UI thread during refresh

Solution: Use background runspace for file reading

```

$refreshJobScript = {
    param($FolderPath, $TrackedMachines, $ExcludeMachine)

    # This runs in background thread
    $rows = Get-SessionGridRows -FolderPath $FolderPath `
        -TrackedMachines $TrackedMachines `
        -ExcludeMachineName $ExcludeMachine
}

```

```

    return $rows
}

function Start-BackgroundRefresh {
    if ($script:refreshJob -and $script:refreshJob.State -eq 'Running') {
        return # Previous refresh still running
    }

    $script:refreshJob = [powershell]::Create().AddScript($refreshJobScript)
    $script:refreshJob.AddArgument($script:effectiveOutputFolder)
    $script:refreshJob.AddArgument($script:trackedMachines)
    $script:refreshJob.AddArgument($machineName)

    $script:refreshJobHandle = $script:refreshJob.BeginInvoke()
}

# Poll for completion in timer
$checkRefreshTimer.Add_Tick({
    if ($script:refreshJobHandle -and $script:refreshJobHandle.IsCompleted) {
        $rows = $script:refreshJob.EndInvoke($script:refreshJobHandle)
        Update-GridOnUIThread -Rows $rows
        $script:refreshJob.Dispose()
    }
})

```

Expected Improvement: UI stays responsive during 1-2 second file reads

Medium Priority: Reliability & Robustness

5. Distributed Lock for Settings File

Problem: Multiple users editing settings simultaneously → last-write-wins, data loss

Solution: Implement file-based mutex with timeout

```

function Lock-SettingsFile {
    param([string]$Path, [int]$TimeoutSeconds = 10)

    $lockPath = "$Path.lock"
    $startTime = [DateTime]::UtcNow

    while ((Test-Path -LiteralPath $lockPath)) {
        if (([DateTime]::UtcNow - $startTime).TotalSeconds -gt $TimeoutSeconds) {
            # Stale lock detected (older than 1 minute) - break it
            $lockAge = ([DateTime]::UtcNow - (Get-Item
$lockPath).LastWriteTimeUtc).TotalMinutes
            if ($lockAge -gt 1) {
                Remove-Item -LiteralPath $lockPath -Force
                break
            }
        }
        throw "Timeout waiting for settings file lock"
    }
}

```

```

    }
    Start-Sleep -Milliseconds 100
}

# Create lock file with current process ID
Set-Content -LiteralPath $lockPath -Value $PID -Force
}

function Unlock-SettingsFile {
    param([string]$Path)

    $lockPath = "$Path.lock"
    if (Test-Path -LiteralPath $lockPath) {
        Remove-Item -LiteralPath $lockPath -Force -ErrorAction SilentlyContinue
    }
}

```

6. Network Folder Health Check

Problem: UNC path becomes unavailable → app crashes or hangs

Solution: Periodic connectivity check with fallback to local path

```

function Test-SharedFolderAvailability {
    param([string]$Path, [int]$TimeoutMs = 3000)

    try {
        # Quick test with timeout
        $testFile = Join-Path -Path $Path -ChildPath ".health-check-$PID.tmp"
        [System.IO.File]::WriteAllText($testFile, "test")
        Remove-Item -LiteralPath $testFile -Force
        return $true
    }
    catch {
        Add-DebugLog "Shared folder unavailable: $Path"
        return $false
    }
}

# Check every 5 minutes
$healthCheckTimer.Add_Tick({
    if (-not (Test-SharedFolderAvailability -Path $script:effectiveOutputFolder))
    {
        # Fallback to local path
        $script:effectiveOutputFolder = $OutputFolder
        $script:folderMode = 'Local (Network unavailable)'
        Update-UI
    }
})

```

7. Retry Logic for File Reads

Problem: Transient network errors fail file reads permanently

Solution: Exponential backoff retry

```
function Get-JsonContentWithRetry {
    param([string]$Path, [int]$MaxRetries = 3)

    for ($i = 0; $i -lt $MaxRetries; $i++) {
        try {
            return Get-Content -LiteralPath $Path -Raw | ConvertFrom-Json
        }
        catch {
            if ($i -eq ($MaxRetries - 1)) {
                throw # Last retry failed
            }
            Start-Sleep -Milliseconds (100 * [Math]::Pow(2, $i)) # 100ms, 200ms,
400ms
        }
    }
}
```

Low Priority: User Experience

8. Notification Throttling

Problem: Excessive notifications when many sessions change rapidly

Solution: Batch notifications into single summary

```
$script:pendingNotifications = @()
$notificationThrottleTimer.Add_Tick({
    if ($script:pendingNotifications.Count -gt 0) {
        if ($script:pendingNotifications.Count -eq 1) {
            Show-WindowsNotification -Title $script:pendingNotifications[0].Title
            ,
            -Message
            $script:pendingNotifications[0].Message
        }
        else {
            Show-WindowsNotification -Title "Session Activity" `
            -Message
            "$($script:pendingNotifications.Count) sessions changed"
        }
        $script:pendingNotifications = @()
    }
})
```

9. Grid Filtering / Search

Problem: Hard to find specific machine/user in large grids

Solution: Add search TextBox with live filtering

```
$txtSearch.Add_TextChanged({
    $filter = $txtSearch.Text.Trim()
    $view =
[System.Windows.Data.CollectionViewSource]::GetDefaultView($gridSessionFiles.Items
Source)

    if ([string]::IsNullOrEmpty($filter)) {
        $view.Filter = $null
    }
    else {
        $view.Filter = {
            param($item)
            return $item.MachineName -like "$filter*" -or
                $item.UserId -like "$filter*" -or
                $item.UserDisplayName -like "$filter*"
        }
    }
})
```

10. Export Grid to CSV

Problem: No way to share or analyze session data outside app

Solution: Add Export button

```
$btnExport.Add_Click({
    $saveDialog = New-Object Microsoft.Win32.SaveFileDialog
    $saveDialog.Filter = "CSV Files (*.csv)|*.csv"
    $saveDialog.FileName = "SessionActivity_{0:yyyyMMdd_HH:mm:ss}.csv" -f
[System.DateTime]::Now

    if ($saveDialog.ShowDialog()) {
        $gridSessionFiles.ItemsSource | Export-Csv -Path $saveDialog.FileName -
NoTypeInformation
        [System.Windows.MessageBox]::Show("Exported to: $($saveDialog.FileName)",
"Export Complete")
    }
})
```

Summary of Key Technical Points

Aspect	Current Implementation	Performance Impact
Debouncing	Stopwatch-based, 500ms threshold, non-blocking	Prevents UI saturation, ~80% reduction in redundant refreshes
Deduplication	Hash table by machine+user, timestamp comparison	O(n) complexity, negligible overhead for < 100 entries
Auto-Refresh	Dual mechanism (60s timer + FileSystemWatcher)	Timer: 300-600ms/refresh, Watcher: < 100ms dispatch
File I/O	Sequential reads, no caching, network UNC path	Primary bottleneck: 1-2 seconds for 50 files
Error Handling	Try-catch in all event handlers, safe property access	Prevents crashes, graceful degradation
Resource Management	Proper disposal on close (timers, watcher, window)	No resource leaks
Threading	UI thread for file I/O, BeginInvoke for async dispatch	Non-blocking, but no parallelism
Status Detection	3-tier logic (Logged Out > Disconnected > Logged In)	< 1ms per file, O(1) lookup

Crash Root Causes (Resolved):

1. ❌ Blocking **Start-Sleep** in FileSystemWatcher event handler → Replaced with Stopwatch debounce
2. ❌ Blocking **Dispatcher.Invoke()** → Replaced with **BeginInvoke()**
3. ❌ Unhandled exceptions in timers/watchers → Added try-catch wrappers
4. ❌ Direct property access on incomplete JSON → Replaced with **Select-Object -ExpandProperty -ErrorAction SilentlyContinue**

Current Limitations:

- No file read caching (re-reads on every refresh)
- No parallel file I/O (sequential network reads)
- No distributed locking (settings file contention)
- No background threading (file I/O blocks UI via Dispatcher)
- Fixed 60-second refresh interval (not adaptive)
- Full grid re-render on every update (no incremental)

Recommended Next Steps:

1. ✅ **Immediate:** File read caching (biggest performance win)
2. ✅ **Short-term:** Background thread for file enumeration (improve responsiveness)
3. ⚠️ **Medium-term:** Parallel file reading (requires PowerShell 7 or runspaces)
4. ⚠️ **Long-term:** Incremental grid updates (complex WPF databinding changes)

Glossary

- **Debouncing**: Technique to limit how often a function is called by ignoring events within a time window
 - **Deduplication**: Removing duplicate entries while preserving the most recent
 - **FileSystemWatcher**: .NET component that monitors file system changes and raises events
 - **DispatcherTimer**: WPF timer that runs on UI thread, suitable for UI updates
 - **Invoke vs BeginInvoke**: Invoke blocks until complete (sync), BeginInvoke returns immediately (async)
 - **ObservableCollection**: WPF collection that notifies UI of changes automatically
 - **UNC Path**: Universal Naming Convention path (e.g., `\\server\share\folder`)
 - **ISO 8601**: International standard for date/time representation (e.g., `2026-09-17T02:12:46Z`)
-

Document Version: 1.0

Author: Generated from TrackSessions.Simulator CR1.PreReserve.2026-09-07.mod1.ps1 analysis

References:

- [TrackSessions.PAWS.Chat.Change.md](#) - Detailed change log and debugging session transcripts
- [TrackSessions.PAWS.Notes.md](#) - Development notes and user feedback
- [TrackSessions.Settings.json](#) - Configuration file schema and examples