


# CONVOLUTIONAL NEURAL NETWORKS

**Informationsverarbeitung II:  
Informationsextraktion mit Neuronalen  
Netzwerken**  
Eduard Saller



# Overview

---

- History
- CNN Topology Overview
- Example with step by step introduction of important terms
- CNNs for NLP
- Discussion

# History


---



- Yann LeCun

New York University

Facebook Artificial Intelligence Research




- Yoshua Bengio

Université de Montréal

- In 1995, **Yann LeCun** and **Yoshua Bengio** introduced the concept of convolutional neural networks.


# CNN Topology



# Recap: Non-Linearity?

---


- A neural network is only non-linear if you squash the output signal from the nodes with a non-linear activation function.  
  
=> arbitrary function approximator
- Interpreting the squashed output signal could very well be interpreted as the strength of this signal (biologically speaking)



# Toy Example

---

A two-dimensional  
array of pixels



**X** or **O**





# Toy Example

---



## Harder to solve problem

---







**X**

translation

scaling

rotation

weight




**O**




# How to compare?

---




?



# Compare smaller areas

---



## Term: Filter

---


1	-1	-1
-1	1	-1
-1	-1	1

1	-1	1
-1	1	-1
1	-1	1

-1	-1	1
-1	1	-1
1	-1	-1

# Term: Filter

---



# Term: Convolution

---

1 <sub>x1</sub>	1 <sub>x0</sub>	1 <sub>x1</sub>	0	0
0 <sub>x0</sub>	1 <sub>x1</sub>	1 <sub>x0</sub>	1	0
0 <sub>x1</sub>	0 <sub>x0</sub>	1 <sub>x1</sub>	1	1
0	0	1	1	0
0	1	1	0	0

Image

4		

Convolved  
Feature

Used filters to create a **filter layer** based on the input

- Yellow area: counts all ones that are part of ist diagonal
- Green area: input features

---

1	-1	-1
-1	1	-1
-1	-1	1

1	1	1
1	1	1
1	1	1

$$\frac{1+1+1+1+1+1+1+1+1}{9} = 1$$

[illegible]A 10x10 grid with a light gray background and darker gray grid lines. A red square is drawn in the top-left corner, spanning the first two columns and the first two rows. Inside the red square, in the top-right corner, is a white square containing the black number '1'. Two diagonal lines, one brown and one black, run from the top-left towards the bottom-right, passing through the grid.

-1	-1	-1	-1	-1	-1	-1	-1	-1
-1	1	-1	-1	-1	-1	-1	1	-1
-1	-1	1	-1	-1	-1	1	-1	-1
-1	-1	-1	1	-1	1	-1	-1	-1
-1	-1	-1	1	-1	1	-1	-1	-1
-1	-1	1	-1	-1	-1	1	-1	-1
-1	1	-1	-1	-1	-1	-1	1	-1
-1	-1	-1	-1	-1	-1	-1	-1	-1



1	-1	-1
-1	1	-1
-1	-1	1

=

0.77	-0.11	0.11	0.33	0.55	-0.11	0.33
-0.11	1.00	-0.11	0.33	-0.11	0.11	-0.11
0.11	-0.11	1.00	-0.33	0.11	-0.11	0.55
0.33	0.33	-0.33	0.55	-0.33	0.33	0.33
0.55	-0.11	0.11	-0.33	1.00	-0.11	0.11
-0.11	0.11	-0.11	0.33	-0.11	1.00	-0.11
0.33	-0.11	0.55	0.33	0.11	-0.11	0.77

-1	-1	-1	-1	-1	-1	-1	-1	-1
-1	1	-1	-1	-1	-1	-1	1	-1
-1	-1	1	-1	-1	-1	1	-1	-1
-1	-1	-1	1	-1	1	-1	-1	-1
-1	-1	-1	1	-1	1	-1	-1	-1
-1	-1	1	-1	-1	-1	1	-1	-1
-1	1	-1	-1	-1	-1	-1	1	-1
-1	-1	-1	-1	-1	-1	-1	-1	-1



1	-1	1
-1	1	-1
1	-1	1

=

0.33	-0.55	0.11	-0.11	0.11	-0.55	0.33
-0.55	0.55	-0.55	0.33	-0.55	0.55	-0.55
0.11	-0.55	0.55	-0.77	0.55	-0.55	0.11
-0.11	0.33	-0.77	1.00	-0.77	0.33	-0.11
0.11	-0.55	0.55	-0.77	0.55	-0.55	0.11
-0.55	0.55	-0.55	0.33	-0.55	0.55	-0.55
0.33	-0.55	0.11	-0.11	0.11	-0.55	0.33

-1	-1	-1	-1	-1	-1	-1	-1	-1
-1	1	-1	-1	-1	-1	-1	1	-1
-1	-1	1	-1	-1	-1	1	-1	-1
-1	-1	-1	1	-1	1	-1	-1	-1
-1	-1	-1	1	-1	1	-1	-1	-1
-1	-1	1	-1	-1	-1	1	-1	-1
-1	1	-1	-1	-1	-1	-1	1	-1
-1	-1	-1	-1	-1	-1	-1	-1	-1




-1	-1	1
-1	1	-1
1	-1	-1

=

0.33	-0.11	0.55	0.33	0.11	-0.11	0.77
-0.11	0.11	-0.11	0.33	-0.11	1.00	-0.11
0.55	-0.11	0.11	-0.33	1.00	-0.11	0.11
0.33	0.33	-0.33	0.55	-0.33	0.33	0.33
0.11	-0.11	1.00	-0.33	0.11	-0.11	0.55
-0.11	1.00	-0.11	0.33	-0.11	0.11	-0.11
0.77	-0.11	0.11	0.33	0.55	-0.11	0.33


# Recap: CNN Topology





# Term: Pooling Layers

---



<http://cs231n.github.io/convolutional-networks/#pool>

0.77	-0.11	0.11	0.33	0.55	-0.11	0.33
-0.11	1.00	-0.11	0.33	-0.11	0.11	-0.11
0.11	-0.11	1.00	-0.33	0.11	-0.11	0.55
0.33	0.33	-0.33	0.55	-0.33	0.33	0.33
0.55	-0.11	0.11	-0.33	1.00	-0.11	0.11
-0.11	0.11	-0.11	0.33	-0.11	1.00	-0.11
0.33	-0.11	0.55	0.33	0.11	-0.11	0.77



1.00	0.33	0.55	0.33
0.33	1.00	0.33	0.55
0.55	0.33	1.00	0.11
0.33	0.55	0.11	0.77

0.33	-0.55	0.11	-0.11	0.11	-0.55	0.33
-0.55	0.55	-0.55	0.33	-0.55	0.55	-0.55
0.11	-0.55	0.55	-0.77	0.55	-0.55	0.11
-0.11	0.33	-0.77	1.00	-0.77	0.33	-0.11
0.11	-0.55	0.55	-0.77	0.55	-0.55	0.11
-0.55	0.55	-0.55	0.33	-0.55	0.55	-0.55
0.33	-0.55	0.11	-0.11	0.11	-0.55	0.33



0.55	0.33	0.55	0.33
0.33	1.00	0.55	0.11
0.55	0.55	0.55	0.11
0.33	0.11	0.11	0.33


0.33	-0.11	0.55	0.33	0.11	-0.11	0.77
-0.11	0.11	-0.11	0.33	-0.11	1.00	-0.11
0.55	-0.11	0.11	-0.33	1.00	-0.11	0.11
0.33	0.33	-0.33	0.55	-0.33	0.33	0.33
0.11	-0.11	1.00	-0.33	0.11	-0.11	0.55
-0.11	1.00	-0.11	0.33	-0.11	0.11	-0.11
0.77	-0.11	0.11	0.33	0.55	-0.11	0.33



0.33	0.55	1.00	0.77
0.55	0.55	1.00	0.33
1.00	1.00	0.11	0.55
0.77	0.33	0.55	0.33


# Stacking

---




# Stacking

---




# Term: fully-connected layer

- takes an input volume and outputs an N dimensional vector




# Toy example: fully-connected layer

---




fully-connected layer => Voting on an answer

---



# Term: Strides

---




<http://cs231n.github.io/convolutional-networks/>




# Term: Strides

---





without strides



with strides

# Term: Padding


---



A Convolutional Neural Network for Modelling Sentences (2014)

# Term: Padding

---



# NLP: What area would be good fits

---

classifications tasks, such as:

- ▮ Sentiment Analysis
- ▮ Spam Detection
- ▮ Topic Categorization

# NLP: What area would be bad fits

---


Convolutions and pooling operations lose information about the local order of words

- PoS Tagging

- Entity Extraction

=> sequence tagging is a harder to fit into a pure CNN architecture

# NLP



# References

---

- [1] Kim, Y. (2014). Convolutional Neural Networks for Sentence Classification. Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing (EMNLP 2014), 1746-1751.
- [2] Kalchbrenner, N., Grefenstette, E., & Blunsom, P. (2014). A Convolutional Neural Network for Modelling Sentences. Acl, 655-665.
- [3] Santos, C. N. dos, & Gatti, M. (2014). Deep Convolutional Neural Networks for Sentiment Analysis of Short Texts. In COLING-2014 (pp. 69-78).
- [4] Johnson, R., & Zhang, T. (2015). Effective Use of Word Order for Text Categorization with Convolutional Neural Networks. To Appear : NAACL-2015, (2011).
- [5] Johnson, R., & Zhang, T. (2015). Semi-supervised Convolutional Neural Networks for Text Categorization via Region Embedding.
- [6] Wang, P., Xu, J., Xu, B., Liu, C., Zhang, H., Wang, F., & Hao, H. (2015). Semantic Clustering and Convolutional Neural Network for Short Text Categorization. Proceedings ACL 2015, 352-357.
- [7] Zhang, Y., & Wallace, B. (2015). A Sensitivity Analysis of (and Practitioners' Guide to) Convolutional Neural Networks for Sentence Classification,
- [8] Nguyen, T. H., & Grishman, R. (2015). Relation Extraction: Perspective from Convolutional Neural Networks. Workshop on Vector Modeling for NLP, 39-48.
- [9] Sun, Y., Lin, L., Tang, D., Yang, N., Ji, Z., & Wang, X. (2015). Modeling Mention , Context and Entity with Neural Networks for Entity Disambiguation, (Ijcai), 1333-1339.

# References

---

- [10] [Zeng, D., Liu, K., Lai, S., Zhou, G., & Zhao, J. \(2014\). Relation Classification via Convolutional Deep Neural Network. \*Coling\*, \(2011\), 2335-2344.](#)
- [11] [Gao, J., Pantel, P., Gamon, M., He, X., & Deng, L. \(2014\). Modeling Interestingness with Deep Neural Networks.](#)
- [12] [Shen, Y., He, X., Gao, J., Deng, L., & Mesnil, G. \(2014\). A Latent Semantic Model with Convolutional-Pooling Structure for Information Retrieval. \*Proceedings of the 23rd ACM International Conference on Conference on Information and Knowledge Management – CIKM '14\*, 101-110.](#)
- [13] [Weston, J., & Adams, K. \(2014\). # T AG S PACE : Semantic Embeddings from Hashtags, 1822-1827.](#)
- [14] [Brandon Roher, Toy example](#)
- [15] [Santos, C., & Zadrozny, B. \(2014\). Learning Character-level Representations for Part-of-Speech Tagging. \*Proceedings of the 31st International Conference on Machine Learning, ICML-14\(2011\)\*, 1818-1826.](#)
- [16] [Zhang, X., Zhao, J., & LeCun, Y. \(2015\). Character-level Convolutional Networks for Text Classification, 1-9.](#)
- [17] [Zhang, X., & LeCun, Y. \(2015\). Text Understanding from Scratch. \*arXiv E-Prints\*, 3, 011102.](#)
- [18] [Kim, Y., Jernite, Y., Sontag, D., & Rush, A. M. \(2015\). Character-Aware Neural Language Models.](#)