

deskHPSDR TCI API Reference

Implementation Status Overview

Category	Command	Direction	Status	Notes
TRX/VFO	trx	RW	Implemented	TX/RX control
TRX/VFO	trx_count	R	Implemented	TRX count
TRX/VFO	vfo	RW+B	Implemented	Frequency control
TRX/VFO	vfo_lock	RW+B	Implemented	VFO lock
TRX/VFO	lock	RW+B	Implemented	Global lock
TRX/VFO	lock_common	RW+B	Implemented	Common lock
TRX/VFO	split_enable	RW+B	Implemented	Split operation
TRX/VFO	modulation	RW+B	Implemented	Operating mode
Audio	rx_volume	RW+B	Implemented	RX volume
Audio	volume	RW+B	Implemented	Master volume
Audio	rx_mute	RW+B	Implemented	RX mute
Audio	mute	RW+B	Implemented	Global mute
Audio	rx_bin_enable	RW+B	Implemented	Binaural audio
Audio	mon_enable	RW+B	Implemented	Monitor enable
Audio	mon_volume	RW+B	Implemented	Monitor volume
DSP	rx_filter_band	RW+B	Implemented	RX filter
DSP	rx_anf_enable	RW+B	Implemented	ANF
DSP	rx_nr_enable	RW+B	Implemented	Noise reduction
DSP	rx_nb_enable	RW+B	Implemented	SNB mapping
DSP	rx_nf_enable	RW+B	Implemented	Manual notch
DSP	agc_mode	RW+B	Implemented	AGC mode
DSP	agc_gain	RW+B	Implemented	AGC gain
SQL	sql_enable	RW+B	Implemented	Squelch
SQL	sql_level	RW+B	Implemented	Squelch level
Meters	rx_smeter	R+B	Implemented	S-meter
Sensors	rx_sensors_enable	RW	Implemented	RX sensors
Sensors	tx_sensors_enable	RW	Implemented	TX sensors
Tuning	rit_enable	RW+B	Implemented	RIT
Tuning	rit_offset	RW+B	Implemented	RIT offset
Tuning	xit_enable	RW+B	Implemented	XIT
Tuning	xit_offset	RW+B	Implemented	XIT offset
Digital	digu_offset	RW+B	Implemented	DIGU offset
Digital	digl_offset	RW+B	Implemented	DIGL offset
TX	drive	RW+B	Implemented	Drive power

Category	Command	Direction	Status	Notes
TX	tune	RW+B	Implemented	Tune mode
TX	tune_drive	RW+B	Implemented	Tune power
Audio/IQ	audio_start	RW	Implemented	Audio stream
Audio/IQ	audio_stop	RW	Implemented	Audio stream
Audio/IQ	audio_samplerate	RW+B	Implemented	Audio rate
Audio/IQ	audio_stream_channels	RW+B	Implemented	Channels
Audio/IQ	audio_stream_sample_type	RW+B	Implemented	Sample type
Audio/IQ	audio_stream_block_size	RW+B	Implemented	Block size
Audio/IQ	iq_samplerate	RW+B	Implemented	IQ rate
CW	cw_keyer_speed	RW+B	Implemented	CW speed
CW	cw_msg	RW	Implemented	CW text
CW	cw_terminal	RW+B	Implemented	CW terminal
CW	cw_macros*	RW	Implemented	CW macro family
Spots	spot	W	Implemented	Add/update spot
Spots	spot_delete	W	Implemented	Delete by callsign
Spots	spot_clear	W	Implemented	Remove all spots
System	ready	B	Implemented	Startup notification
System	start	B	Implemented	Startup notification
System	stop	RW+B	Implemented	Shutdown notification

Commands Not Implemented

Category	Command
DSP	rx_apf_enable
DSP	rx_dse_enable
DSP	rx_anc_enable
Spots	rx_clicked_on_spot
Spots	spot_select
System	app_focus
Audio	line_out_enable
Audio	line_out_volume

deskHPSDR Specific Behavior

Command	Behavior
rx_nr_enable	USB/LSB/CWU/CWL -> NR4, AM/SAM -> NR3, DIGI -> OFF
rx_nb_enable	Controls SNB only
rx_bin_enable	Disabled for DIGI modes and mono audio
rx_anf_enable	Disabled for DIGI modes
spot_delete	Deletion by callsign, no spot ID required
tx_sensors_enable	Transmitted only during active TX
rx_sensors_enable	Suppressed during TX unless duplex mode is active