

# Лабораторная работа №6

## Мандатное разграничение прав в Linux

---

Латыпова Диана


12 октября 2024

Российский университет дружбы народов, Москва, Россия

# Информация

---

- Латыпова Диана
- студент группы НФИбд-02-21
- Российский университет дружбы народов
- 1032215005@rudn.ru
- <https://github.com/dlatypova>



# Вводная часть

---

- Развить навыки администрирования ОС Linux
- Получить первое практическое знакомство с технологией SELinux
- Проверить работу SELinux на практике совместно с веб-сервером Apache

## **Теоретическая справка**

---

## SELinux (Security-Enhanced Linux)

- система управления доступом на уровне ядра, которая реализует обязательное управление доступом (MAC) в операционных системах Linux.

Использует три режима работы:

- Enforcing
- Permissive
- Disabled

Команды для управления и проверки статуса:

- `getenforce`
- `sestatus`

- один из самых популярных веб-серверов, который используется для обслуживания веб-сайтов и приложений

При работе с веб-сервером и SELinux важно отслеживать логи:

- `/var/log/messages`
- `/var/log/httpd/error_log`
- `/var/log/audit/audit.log`



# Выполнение лабораторной работы

---

# Команды getenforce и sestatus

```
[dlatihpova@user ~]$ getenforce
Enforcing
[dlatihpova@user ~]$ sestatus
SELinux status:                enabled
SELinuxfs mount:                /sys/fs/selinux
SELinux root directory:         /etc/selinux
Loaded policy name:              targeted
Current mode:                    enforcing
Mode from config file:           enforcing
Policy MLS status:               enabled
Policy deny_unknown status:      allowed
Memory protection checking:      actual (secure)
Max kernel policy version:       33
```

**Рис. 1: Пункт 1**

# service httpd status

```
[dlatihpova@user ~]$ service httpd status-
The service command supports only basic LSB actions (start, stop, restart, try-restart,
reload, reload-or-restart, try-reload-or-restart, force-reload, status, condrestart). Fo
r other actions, please try to use systemctl.
[dlatihpova@user ~]$ systemctl start httpd
[dlatihpova@user ~]$ systemctl enable httpd
Created symlink /etc/systemd/system/multi-user.target.wants/httpd.service → /usr/lib/sys
temd/system/httpd.service.
[dlatihpova@user ~]$ service httpd status
Redirecting to /bin/systemctl status httpd.service
● httpd.service - The Apache HTTP Server
   Loaded: loaded (/usr/lib/systemd/system/httpd.service; enabled; preset: disabled)
   Active: active (running) since Sat 2024-10-12 14:05:27 MSK; 37s ago
     Docs: man:httpd.service(8)
   Main PID: 112408 (httpd)
    Status: "Total requests: 0; Idle/Busy workers 100/0; Requests/sec: 0; Bytes"
      Tasks: 177 (limit: 12288)
     Memory: 26.7M
        CPU: 66ms
   CGroup: /system.slice/httpd.service
           └─112408 /usr/sbin/httpd -DFOREGROUND
             └─112417 /usr/sbin/httpd -DFOREGROUND
               └─112422 /usr/sbin/httpd -DFOREGROUND
                 └─112423 /usr/sbin/httpd -DFOREGROUND
                   └─112424 /usr/sbin/httpd -DFOREGROUND

Oct 12 14:05:27 user.localdomain systemd[1]: Starting The Apache HTTP Server...
Oct 12 14:05:27 user.localdomain systemd[1]: Started The Apache HTTP Server.
Oct 12 14:05:27 user.localdomain httpd[112408]: Server configured, listening on
lines 1-19/19 (END)...skipping...
● httpd.service - The Apache HTTP Server
   Loaded: loaded (/usr/lib/systemd/system/httpd.service; enabled; preset: disabled)
```

Рис. 2: Пункт 2

# Текущее состояние переключателей SELinux для Apache

```
[dlatihpova@user ~]$ sestatus -b httpd
SELinux status:                enabled
SELinuxfs mount:                /sys/fs/selinux
SELinux root directory:         /etc/selinux
Loaded policy name:              targeted
Current mode:                    enforcing
Mode from config file:          enforcing
Policy MLS status:              enabled
Policy deny_unknown status:     allowed
Memory protection checking:     actual (secure)
Max kernel policy version:      33

Policy booleans:
abrt_anon_write                  off
abrt_handle_event                off
abrt_upload_watch_anon_write    on
antivirus_can_scan_system       off
antivirus_use_jit                off
auditadm_exec_content            on
authlogin_nsswitch_use_ldap      off
authlogin_radius                 off
authlogin_yubikey                off
```

Рис. 3: Пункт 4

# Поросмотр статистики по политике

```
[dlatihpova@user ~]$ seinfo
Statistics for policy file: /sys/fs/selinux/policy
Policy Version:          33 (MLS enabled)
Target Policy:           selinux
Handle unknown classes:  allow

Classes:      135
Sensitivities: 1
Types:        5145
Users:        8
Booleans:     356
Allow:        65504
Auditallow:   176
Type_trans:   271770
Type_member:  37
Role_allow:   40
Constraints:  70
MLS Constrain: 72
Permissives:  4
Defaults:     7
Allowxperm:   0
Auditallowxperm: 0
Ibendportcon: 0
Initial SIDs: 27
Genfscon:     109
Netifcon:     0
Permissions:  457
Categories:   1024
Attributes:   259
Roles:        15
Cond. Expr.:  388
Neverallow:   0
Dontaudit:    8682
Type_change:  94
Range_trans:  5931
Role_trans:   417
Validatetrans: 0
MLS Val. Tran: 0
Polcap:       6
Typebounds:   0
Neverallowxperm: 0
Dontauditxperm: 0
Ibpkeycon:    0
Fs_use:       35
Portcon:      665
Nodecon:      0
```

Рис. 4: Пункт 5

- `ls -Z /var/www/html/test.html` — показывает контекст безопасности файла


```
[dlatihpova@user ~]$ ls -lZ /var/www
total 0
drwxr-xr-x. 2 root root system_u:object_r:httpd_sys_script_exec_t:s0 6 Aug 8 19:30 cgi-bin
drwxr-xr-x. 2 root root system_u:object_r:httpd_sys_content_t:s0 6 Aug 8 19:30 html
[dlatihpova@user ~]$ ls -lZ /var/www/html
total 0
```

Рис. 5: Пункты 6-8

```
[dlatihpova@user ~]$ su
Password:
[root@user dlatihpova]# touch /var/www/html/test.html
[root@user dlatihpova]# nano /var/www/html/test.html
[root@user dlatihpova]# cat /var/www/html/test.html
<html>
<body>test</body>
</html>
[root@user dlatihpova]# exit
exit
[dlatihpova@user ~]$ ls -lZ /var/www/html
total 4
-rw-r--r--. 1 root root unconfined_u:object_r:httpd_sys_content_t:s0 33 0
-t 12 14:17 test.html
```

Рис. 6: Пункты 9-10

## Файл test.html (2)



```
GNU nano 5.6.1 /var/www/html/test.html Modified
<html>
<body>test</body>
</html>
```

Рис. 7: Содержимое файла test.html




Рис. 8: Пункт 11



- `chcon -t` — изменяет тип контекста

```
[dlatihpova@user ~]$ su
Password:
[root@user dlatihpova]# chcon -t samba_share_t /var/www/html/test.html
[root@user dlatihpova]# exit
exit
[dlatihpova@user ~]$ ls -Z /var/www/html/test.html
unconfined_u:object_r:samba_share_t:s0 /var/www/html/test.html
```

Рис. 9: Пункт 13

# Просмотр log-файлов веб-сервера Apache

```
[dlatihpova@user ~]$ ls -l /var/www/html/test.html
-rw-r--r--. 1 root root 33 Oct 12 14:17 /var/www/html/test.html
[dlatihpova@user ~]$ tail /var/log/messages
tail: cannot open '/var/log/messages' for reading: Permission denied
[dlatihpova@user ~]$ sudo tail /var/log/messages
[sudo] password for dlatihpova:
Oct 12 14:32:36 user systemd[1]: Created slice Slice /system/dbus-:1.1-org.fedoraproject.SetroubleShootPrivileged.
Oct 12 14:32:36 user systemd[1]: Started dbus-:1.1-org.fedoraproject.SetroubleShootPrivileged@0.service.
Oct 12 14:32:36 user setroubleShoot[113615]: SELinux is preventing /usr/sbin/httpd from getattr access on the file /var/www/html/test.html. For complete SELinux messages run: sealert -l da0927fd-c389-425d-ad90-c30be66cdc19
Oct 12 14:32:36 user setroubleShoot[113615]: SELinux is preventing /usr/sbin/httpd from getattr access on the file /var/www/html/test.html.#012#012***** Plugin restorecon (92.2 confidence) suggests *****#012#012If you want to fix the label. #012/var/www/html/test.html default label should be httpd_sys_content_t.#012Then you can run restorecon. The access attempt may have been stopped due to insufficient permissions to access a parent directory in which case try to change the following command accordingly.#0120n#012# /sbin/restorecon -v /var/www/html/test.h
```

Рис. 10: Пункт 15

# Работа с портами

- `semanage port -a -t` — добавляет порт к списку допустимых для Apache
- `semanage port -l | grep http_port_t` - просмотр списка портов, разрешённых SELinux
- `semanage port -d -t http_port_t -p` - удаляет привязку порта

```
[dlatihpova@user ~]$ sudo semanage port -a -t http_port_t -p tcp 81
Port tcp/81 already defined, modifying instead.
[dlatihpova@user ~]$ semanage port -l | grep http_port_t
ValueError: SELinux policy is not managed or store cannot be accessed.
[dlatihpova@user ~]$ sudo semanage port -l | grep http_port_t
http_port_t                tcp      81, 80, 31, 443, 480, 8000, 8009,
                             8443, 9000
peppasus_http_port_t       tcp      5988
[dlatihpova@user ~]$ systemctl restart httpd
[dlatihpova@user ~]$ curl ifconfig.me
37.18.92.241[dlatihpova@user ~]$ status httpdctl status httpd
bash: status: command not found...
[dlatihpova@user ~]$ curl ifconfig.me
37.18.92.241[dlatihpova@user ~]$ systemctl status httpdctl status httpd
Unit httpd.service could not be found.
Unit status.service could not be found.
• httpd.service - The Apache HTTP Server
Loaded: loaded (/usr/lib/systemd/system/httpd.service; enabled; preset
Active: active (running) since Sat 2024-10-12 14:58:52 MSK; 2min 20s
Docs: man:httpd.service(8)
Main PID: 114725 (httpd)
Status: "Total requests: 0; Idle/Busy workers 100/0;Requests/sec: 0
Tasks: 177 (limit: 12208)
Memory: 21.7M
CPU: 96ms
CGroup: /system.slice/httpd.service
├─114725 /usr/sbin/httpd -DFOREGROUND
├─114726 /usr/sbin/httpd -DFOREGROUND
├─114733 /usr/sbin/httpd -DFOREGROUND
├─114734 /usr/sbin/httpd -DFOREGROUND
└─114735 /usr/sbin/httpd -DFOREGROUND
```

Oct 12 14:58:53 user-localhost systemd[1]: Starting The Apache HTTP S

## Выводы

---

- Развиты навыки администрирования ОС Linux
- Получено первое практическое знакомство с технологией SELinux
- Проверена работа SELinux на практике совместно с веб-сервером Apache