



## **LABORATORY TEST REPORT LB 19-14**

**THIS TEST REPORT DOES NOT CONSTITUTE APPROVAL OR DISAPPROVAL OF THE  
EQUIPMENT, METHOD OR MATERIAL TESTED**

Date: June 16, 2014

**Report For: OEMSERV Hong Kong Limited**  
1002 10/F, Wang Lung Industrial Building  
48-56 Wang Lung Street (11 Lung Tak Street)  
Tsuen Wan, N.T., Hong Kong  
Tel.: +852 3565 0242 Fax: +852 3565 0240

Email: pjschabort@oemserv.com

**Test Specimens:** Level 1 Paper/Polyethylene Dunnage Bags

**Test Procedure:** (Extracted from General Information Bulletin No. 9, *Product Performance Profile for Pneumatic Dunnage*.)

### **2.4 Performance Measures**

#### **2.4.1 Level 1, Pneumatic Dunnage as Lateral Void Fillers and/or Load Securement in Certain Intermodal Applications**

##### ***Part A, Leak Test:***

Ten samples shall be inflated to 2.5 psig in a 12" void and remain thus for 19 days. Record the temperature and barometric pressure at the start and end of the test.

After 19 days pneumatic dunnage must retain a minimum of 1.5 psig, and the gauge pressure standard deviation of the 10 samples must not be greater than 0.15.

##### ***Part B, Burst Test:***

Five random samples from Part A shall be inflated to 8 psig in a 12" void. The bag must maintain 8 psig for one minute.

Damage Prevention and Loading Services  
Transportation Technology Center  
55500 DOT Road, Pueblo, CO 81001  
Phone: (719) 585-1817

## LB 19-14

### Level 1:

All samples were inflated to 2.5 psi using a calibrated digital pressure gauge.  
All samples were preconditioned a minimum of two days prior to inflation.

**Table 1 - Level 1**

<b>Inflation Start Date</b>	<b>05-22-14</b>	<b>Average Temperature (°F)</b>	<b>Average Relative Humidity</b>	<b>Average Barometric Pressure (PSIA)</b>	
<b>End Date</b>	<b>06-10-14</b>	<b>64.5</b>	<b>12.3%</b>	<b>12.11</b>	
<b>Sample #</b>	<b>Part A Leak Test</b>	<b>Part B Burst Test</b>	<b>Sample #</b>	<b>Part A Leak Test</b>	<b>Part B Burst Test</b>
<b>1</b>	<b>2.2</b>		<b>6</b>	<b>2.3</b>	
<b>2</b>	<b>2.3</b>	Pass	<b>7</b>	<b>2.3</b>	Pass
<b>3</b>	<b>2.2</b>		<b>8</b>	<b>2.2</b>	
<b>4</b>	<b>2.2</b>	Pass	<b>9</b>	<b>2.2</b>	
<b>5</b>	<b>2.2</b>		<b>10</b>	<b>2.3</b>	

### Conclusion:

All ten samples submitted met the requirements set forth in General Information Bulletin No. 9, *Product Performance Profile for Pneumatic Dunnage*.

Tom Feltault  
Sr. Manager Damage Prevention Engineering  
Damage Prevention & Loading Services



**Valve with Dust Cap**

Damage Prevention and Loading Services  
Transportation Technology Center  
55500 DOT Road, Pueblo, CO 81001  
Phone: (719) 585-1817