Safety Data Sheet

REFCOTEC
Where mold and metal meet

Prior Version Date: 18 March, 2014 **Revision Date:** 19 March, 2015 **Version** 2

1. IDENTIFICATION

Product Identifier
Product Name REFCOPART 8000

Other means of identification
SDS # SDP8000_20150319

Product Code P8000
UN/ID No UN1263

Recommended Product Use
Foundry Pattern Parting.

Supplier Contact Details
REFCOTEC, Inc
542 Collins Blvd
Orrville, OH 44667

Emergency Telephone Number
Company Phone Number Information Calls: 330-683-2200
Fax Number: 330-683-8200
Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Silver liquid **Physical State** Liquid **Odor** Characteristic of solvents

Classification

Germ cell mutagenicity	Category 1B
Aspiration toxicity	Category 1
Flammable Liquids	Category 2

Hazards Not Otherwise Classified (HNOC)
May be harmful in contact with skin

Signal Word
Danger

Hazard Statements
May cause genetic defects
May be fatal if swallowed and enters airways
Highly flammable liquid and vapor



Precautionary Statements - Prevention
Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Wear protective gloves/protective clothing/eye protection/face protection
Keep away from heat/sparks/open flames/hot surfaces. — No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof equipment
Use only non-sparking tools
Take precautionary measures against static discharge

Precautionary Statements - Response
If exposed or concerned: Get medical advice/attention
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
Do not induce vomiting
IN CASE OF FIRE: Use CO_2, dry chemical, or foam for extinction

Precautionary Statements - Storage
Store locked up
Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal
Dispose of contents/container to an approved waste disposal plant

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Solvent naphtha (petroleum), light aliphatic	64742-89-8	85-90
Aluminum	7429-90-5	10 Max.

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

First Aid Measures

General Advice	If exposed or concerned: Get medical advice/attention.
Eye Contact	Rinse with plenty of water.
Skin Contact	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration.

Ingestion IF SWALLOWED: call a poison control center or physician immediately. Do not induce vomiting.

Most important symptoms and effects

Symptoms Drowsiness. Dizziness. Loss of coordination. Prolonged or repeated skin contact may cause irritation. Overexposure may cause dizziness, headache, loss of motor skills, coughing, shortness of breath, dermatitis.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Pre-existing respiratory or dermal conditions may be aggravated by overexposure.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media
Water fog. Alcohol foam. Carbon dioxide (CO2). Dry chemical.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical
Highly flammable liquid and vapor. Unvented containers may rupture or explode when exposed to high heat due to pressure build-up. Move containers to cool area or keep cool with water stream.

Hazardous Combustion Products Carbon oxides.

Sensitivity to Static Discharge Take precautionary measures against static discharge.

Protective equipment and precautions for firefighters
Water stream may cause flame area to spread. Wear self-contained breathing apparatus (SCBA) in confined fire spaces.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Use personal protective equipment as required.

Environmental Precautions Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information. See Section 13: DISPOSAL CONSIDERATIONS.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up Eliminate all sources of ignition. Do not flush spills to watercourse. For small spills, absorb with sand, clay, or other inert absorbent. Contain larger spills with dikes or absorbents. Place unusable material into lidded containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing and eye/face protection. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion proof equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Do not reuse this container. Send to approved reconditioner for recycling.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed and store in a cool, dry and well-ventilated place. Store away from heat, sparks, open flame or any other ignition source. Store locked up.

Incompatible Materials Strong acids. Oxidizers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Aluminum 7429-90-5	TWA: 1 mg/m^3 respirable fraction	TWA: 15 mg/m^3 total dust TWA: 5 mg/m^3 respirable fraction	TWA: 10 mg/m^3 total dust TWA: 5 mg/m^3 respirable dust TWA: 5 mg/m^3 Al
Solvent Naphtha, Light Aliphatic 64742-89-8	Not specifically listed. Recommended, 100 PPM	Not specifically listed. Recommended, 400 mg/m3	

Appropriate engineering controls

Engineering Controls Ensure adequate ventilation, especially in confined areas. Local exhaust ventilation recommended. Use mechanical ventilation if TLV(s) for dusts or vapors are expected to be exceeded. Eyewash stations. Showers.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Chemical splash goggles.

Skin and Body Protection Do not use nitrile rubber, polyvinyl alcohol, or polyvinyl chloride. Aprons.

Respiratory Protection NIOSH approved for mineral dusts if dried product becomes airborne. Air purifying or SCBA if TLVs for vapors are exceeded.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Liquid		
Appearance	Silver liquid	**Odor**	Characteristic of solvents
Color	Silver	**Odor Threshold**	Not determined

Property	Values	Remarks • Method
pH	Not determined	
Melting Point/Freezing Point	Not determined	
Boiling Point/Boiling Range	53.9 °C / 129 °F	IBP
Flash Point	(-12.2) - (-9.4) °C / 10-15 °F	SFCC
Evaporation Rate	Not determined	

Flammability (Solid, Gas)	Liquid-Not Applicable
Upper Flammability Limits	12
Lower Flammability Limit	1.8
Vapor Pressure	33 @ 68°F
Vapor Density	Greater than 1 (heavier than air)
Specific Gravity	0.70-0.80
Water Solubility	Not miscible
Solubility in other solvents	Not determined
Partition Coefficient	Not determined
Auto-ignition Temperature	Not determined
Decomposition Temperature	Not determined
Kinematic Viscosity	Not determined
Dynamic Viscosity	Not determined
Explosive Properties	Not determined
VOC, Typical	88%, by weight

10. STABILITY AND REACTIVITY

Reactivity
Not reactive under normal conditions.

Chemical Stability
Stable under recommended storage conditions.

Possibility of Hazardous Reactions
None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid
High heat, spark, and open flames. Static discharge. Ignition sources. Keep out of reach of children.

Incompatible Materials
Strong acids. Oxidizers.

Hazardous Decomposition Products
Oxides of carbon.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact Avoid contact with eyes.

Skin Contact May be harmful in contact with skin.

Inhalation Avoid breathing vapors or mists.

Ingestion May be fatal if swallowed and enters airways.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Solvent naphtha (petroleum), light aliphatic 64742-89-8	-	= 3000 mg/kg (Rabbit)	-

Information on physical, chemical and toxicological effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity This product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.

Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity
Not determined

12. ECOLOGICAL INFORMATION

Ecotoxicity
The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Solvent naphtha (petroleum), light aliphatic 64742-89-8	4700: 72 h Pseudokirchneriella subcapitata mg/L EC50			

Persistence/Degradability
Not determined.

Bioaccumulation
Not determined.

Mobility
Not determined

Other Adverse Effects
Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and regulations.

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Aluminum 7429-90-5	Ignitable powder

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT: UN1263, Paint, 3, PG II

IATA: UN1263, Paint, 3, II

IMDG: UN1263, Paint, 3, II

15. REGULATORY INFORMATION

International Inventories
Not determined

Legend:
TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Fire Hazard	Yes

SARA 313

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Aluminum - 7429-90-5	7429-90-5	10 Max.	1.0

US State Regulations

California Proposition 65
This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Aluminum 7429-90-5	X	X	X

16. OTHER INFORMATION

Prior Issue Date:	18 March, 2014
Revision Date:	19 March, 2015
Revision Note:	New format

Disclaimer

The foregoing data has been compiled from sources which REFCOTEC, in good faith, believes to be dependable, accurate, and reliable to the best of our knowledge. However, REFCOTEC cannot make any warranty or representation respecting the accuracy or completeness of the data and assumes no responsibility for any liability or damages relating thereto. REFCOTEC cannot advise you regarding the protection of your employees, customers, or others. Users may consult OSHA.

End of Safety Data Sheet