1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Ashland P.O. Box 2219 Columbus, OH 43216	Regulatory Information Number Telephone Emergency telephone number	1-800-325-3751 614-790-3333 1-800-ASHLAND (1-800-274-5263)

Product name	ZIP-STIK® NC CORE PASTE
Product code	120911
Product Use Description	No data

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid, grey

DANGER! Flammable Liquid, Moderate skin irritant, moderate eye irritant, Carcinogen.

Potential Health Effects

Routes of exposure
Inhalation, Skin contact, Eye Contact

Eye contact
Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.

Skin contact
May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of skin, and skin burns.

Ingestion
Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

Inhalation

Breathing of vapor or mist is possible. This material is a dust or may produce dust. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Prolonged or repeated breathing of dust may result in progressive and permanent lung disease (fibrosis) which may cause death from respiratory and/or heart failure. Symptoms include coughing and difficult breathing which becomes worse with physical activity. Another form of fibrosis, acute silicosis, can occur with exposures to very high concentrations of respirable silica over shorter periods of time, sometimes as short as a few months. Symptoms of acute silicosis include progressive shortness of breath, fever, cough and weight loss. Acute silicosis is fatal.

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions), kidney, eye, Silicosis predisposes the individual to the development mycobacterial infections including tuberculosis or to fungal infections. This is most likely to occur after the age of 50 and in association with moderate to severe silicosis.

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), and death

Target Organs

Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: eye damage, kidney damage, lung damage, Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans: lung damage, chronic bronchitis, emphysema, kidney damage

Carcinogenicity

The International Agency for Research on Cancer (IARC) and the National Toxicology Program (NTP) have determined that there is sufficient evidence in humans for the carcinogenicity of inhaled crystalline silica in the form of quartz or cristobalite. In addition, IARC has determined that there is sufficient evidence for the carcinogenicity of quartz and cristobalite in experimental animals. Among individuals with silicosis, lung cancer occurs more frequently in those who smoke.

Reproductive hazard.

No data

Other information

There is some evidence that breathing respirable crystalline silica or the disease silicosis is associated with an increased incidence of immunological disorders and autoimmune diseases such as scleroderma (a disorder manifested by fibrosis of the lungs, skin and other internal organs), systemic lupus erythematosis and sarcoidosis (chronic inflammatory diseases).

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Concentration
QUARTZ / SAND	14808-60-7	>=50-<60%
ACETONE	67-64-1	>=30-<40%
BENTONITE	71011-26-2	>=1.5-<5%
PYROPHYLLITE	12269-78-2	>=1.5-<5%

4. FIRST AID MEASURES

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

Notes to physician

Hazards: No information available.
Treatment: No information available.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Dry chemical, carbon dioxide (CO2), water spray, alcohol-resistant foam

Hazardous combustion products

May form: carbon dioxide and carbon monoxide, various hydrocarbons

Precautions for fire-fighting

Material is volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations near the material handling point. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

For personal protection see section 8. Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source. Prevent from entering drains, sewers, streams or other bodies of water. Prevent from spreading. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

Environmental precautions

No data

Methods for cleaning up

No data

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.

Storage

No data

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

QUARTZ / SAND		14808-60-7	
ACGIH	time weighted average	0.05 mg/m3	Respirable fraction.
ACGIH NIC	time weighted average	0.025 mg/m3	Respirable fraction.
NIOSH	Recommended exposure limit (REL):	0.05 mg/m3	Respirable dust.
OSHA Z1A	time weighted average	0.1 mg/m3	Respirable dust.
US CA OEL	Time Weighted Average (TWA) Permissible Exposure Limit (PEL):	0.1 mg/m3	Respirable dust.
US CA OEL	Time Weighted Average (TWA) Permissible Exposure Limit (PEL):	0.3 mg/m3	Total dust.
OSHA Z1	Permissible exposure limit	5 mg/m3	Respirable fraction.
OSHA Z1	Permissible exposure limit	15 mg/m3	Total dust.
ACGIH	time weighted average	0.025 mg/m3	Respirable fraction.

ACETONE		67-64-1
ACGIH	time weighted average	500 ppm
ACGIH	Short term exposure limit	750 ppm
NIOSH	Recommended exposure limit (REL):	250 ppm
NIOSH	Recommended exposure limit (REL):	590 mg/m3
OSHA Z1	Permissible exposure limit	1,000 ppm
OSHA Z1	Permissible exposure limit	2,400 mg/m3

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Eye protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

Skin and body protection

To prevent repeated or prolonged skin contact, wear impervious clothing and boots. Wear resistant gloves such as: Neoprene nitrile rubber.

Respiratory protection

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH-approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Form	paste,
Color	grey
Odor	No data
Boiling point/range	No data
pH	No data
Flash point	1.40 °F / -17.00 °C
Evaporation rate	No data
Explosion limits	No data
Vapor pressure	No data
Vapor density	1
Density	1.49 g/cm3 @ 77 °F / 25 °C 12.4 lb/gal @ 77 °F / 25 °C
Solubility	No data
Partition coefficient (n-octanol/water)	No data
Autoignition temperature	No data

10. STABILITY AND REACTIVITY

Stability
Stable.

Conditions to avoid
None known.

Incompatible products
Avoid contact with strong oxidizing agents

Hazardous decomposition products
May form: carbon dioxide and carbon monoxide, various hydrocarbons

Hazardous reactions
Product will not undergo hazardous polymerization.

Thermal decomposition
No data

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity

ACETONE	LD 50 Rat: 5,800 mg/kg

Acute inhalation toxicity

ACETONE	LC 50 Rat: 16000 ppm, 4 h

Acute dermal toxicity

ACETONE	LD 50 Rabbit: 20,000 mg/kg

12. ECOLOGICAL INFORMATION

Aquatic toxicity

Acute and Prolonged Toxicity to Fish
No data
Acute Toxicity to Aquatic Invertebrates
No data

Environmental fate and pathways
No data

13. DISPOSAL CONSIDERATIONS

Waste disposal methods

Destroy by incineration in accordance with applicable regulations. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution Company, IC&S Environmental Services Group at 800-637-7922.

14. TRANSPORT INFORMATION

IMDG:
UN1133, ADHESIVES 3, II
IATA_P:
UN1133, Adhesives 3, II
IATA_C:
UN1133, Adhesives 3, II
CFR_ROAD:
UN1133, Adhesives 3, II
CFR_RAIL:
UN1133, Adhesives 3, II
CFR_INWTR:
UN1133, Adhesives 3, II
IMDG_INWTR:
UN1133, ADHESIVES 3, II
IMDG_ROAD:
UN1133, ADHESIVES 3, II
IMDG_RAIL:
UN1133, ADHESIVES 3, II

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

15. REGULATORY INFORMATION

California Prop. 65
WARNING! This product contains a chemical known in the State of California to cause cancer.
BENZENE
QUARTZ / SAND
WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.
BENZENE

SARA Hazard Classification Fire Hazard
Acute Health Hazard
Chronic Health Hazard

SARA 313 Component(s)

OSHA Hazards Flammable Liquid
Moderate skin irritant
Moderate eye irritant
Carcinogen

	Health	Flammability	Reactivity	Other
HMIS	1	3	0	
NFPA	1	3	0	

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).