SAFETY DATA SHEET

1. Identification

Product identifier	**Rapidur C 9-500**
Recommended use	Catalyst
Recommended restrictions	Not available
Manufacturer/Importer/Supplier/Distributer information	
Manufacturer:	Mancuso Chemicals Limited 5725 Progress Street Niagara Falls, ON, Canada L2G 0C1
Company telephone	1-905-357-3626
Emergency telephone	1-800-567-7455 (Terrapure Environmental)
Supplier	Refer to Manufacturer

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 3
Health hazards	Skin corrosion/irritation	Category 1
	Serious eye damage/irritation	Category 1
	Specific organ toxicity, single exposure	Category 3 (Respiratory system)
	Aspiration hazard	Category 1

Label elements

Signal word	Danger
Hazard statement	Flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes severe skin burns and eye damage. May cause respiratory irritation.
Precautionary statement	
Prevention	Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.
Response	If swallowed: Immediately call a poison center/doctor. Rinse mouth. Do NOT induce vomiting. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Call a poison center/doctor. Take off immediately all contaminated clothing and wash it before reuse. In case of fire: use dry sand, dry chemical or alcohol-resistant foam for extinction.
Storage	Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazards not otherwise classified	None known.
Supplemental information	None.

3. Composition/information on ingredients

Chemical name	Common name and synonyms	CAS Number	% w/w
Solvent Naphtha (Petroleum) Light Aromatic		64742-95-6	75-90
4 Phenylpropylpyridine		2057-49-0	5-15
Benzyldimethyl amine		103-83-3	1-10

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTER or doctor/physician.
Skin contact	Take off immediately all contaminated clothing. Wash off with soap and water. Get medical advice/attention if you feel unwell. Get medical attention if irritation develops and persists. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off immediately all contaminated clothing. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO_2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Do not allow run-off from firefighting to enter drains or water courses.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Firefighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Use water spray to cool fully closed containers.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Flammable liquid. Do not mix with strong acids or mineral acids.
Hazardous combustion products	Toxic fumes, gases or vapours may evolve on burning. Carbon oxides. Hydrocarbons. Nitrogen oxides (NOx).

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from open flames, hot surfaces and sources of ignition. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS)

8. Exposure controls/personal protection

Occupational exposure limits

US OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Naphthalene (CAS 91-20-3)	TWA	10 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
4-Phenylpropylpyridine	TLV	150.0 ppm for an 8 Hr. Workday

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
1,2,4-Trimethylbenzene (CAS 93-63-6)	TWA	25 ppm
1,3,5-Trimethylbenzene (CAS 108-67-8)	TWA	25 ppm

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full face piece.

Skin protection

Hand protection Wear appropriate chemical-resistant gloves.

Other Wear appropriate chemical-resistant clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full face piece

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid

Form Liquid

Color Brownish-yellow

Odor Mild typical

Odor Threshold Not available

pH Marginally Alkaline (Non Aqueous solution)

Melting point/Freezing point Not Applicable

Initial boiling point 100 °C

Flash point 49 ˚C (closed cup)

Evaporation rate Not available

Flammability (solid, gas)	Not available
Lower explosive limit	0.8 for aromatic hydrocarbons
Upper explosive limit	7.0 for aromatic hydrocarbons
Vapor pressure @ 20 ˚C	8mm Hg
Vapor density	Not available
Specific gravity	0.80 - 0.95
Solubility(ies)	
Water solubility	Low to Insoluble
Partition coefficient (water/octanol)	Not available
Auto-ignition temperature	869 ˚ F (Solvent)
Decomposition temperature	Not available
Viscosity	Not available

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong acids especially mineral acids and oxidizers.
Hazardous decomposition products	May form carbon dioxide, monoxide, hydrocarbons, nitrous oxides and aromatics.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause irritation to the respiratory system.
Skin contact	Causes severe skin burns.
Eye contact	Causes serious eye damage.
Ingestion	Causes digestive tract burns. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Components	**Species**	**Test Results**
Solvent Naphtha (Petroleum) Light Aromatic		
Acute		
Dermal LD50	Rabbit	>4,000 mg/kg
Inhalation LC50	Rat	>10,200 mg/m3, 4 hr.
Oral LD50	Rat	5,600 mg/kg
4-Phenylpropylpyridine		
Acute		
Dermal LD50	Rabbit	4000 mg/kg
Oral LD50	Rat	400 mg/kg
Benzyldimethyl amine		
Acute		
Dermal LD50	Rabbit	1660 mg/kg Rabbit
Inhalation LC50	Rat	2062 mg/m3 4 hrs Rat
Oral LD50	Rat	265 mg/kg Rat

Skin corrosion/irritation	Causes severe skin burns and eye damage.
Serious eye damage/eye irritation	Causes serious eye damage.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific organ toxicity	
Single exposure	May cause respiratory irritation.
Repeated exposure	Not classified.
Aspiration toxicity	May be fatal if swallowed and enters airways.

12. Ecological information

Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Hazards to aquatic environment (acute)	Not available.
Hazards to aquatic environment (long term)	Not available.
Persistence and degradability	Not available

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT	
UN Number	1993
Proper shipping name	Flammable Liquid N.O.S. (solvent naphtha, petroleum, light aromatic)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	
Packing group	III

IATA

UN Number	1993
Proper shipping name	Flammable Liquid N.O.S. (solvent naphtha, petroleum, light aromatic)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	III
Environmental hazards	

IMDG

UN Number	1993
Proper shipping name	Flammable Liquid N.O.S. (solvent naphtha, petroleum, light aromatic)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	III
Environmental hazards	
Marine pollutant	

15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)	Not regulated.
CERCLA Hazardous Substance List (40 CFR 302.4)	Naphthalene (CAS 91-20-3) Listed.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050	Not listed.
Superfund Amendments and Reauthorization Act of 1986 (SARA)	Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

16. Other information, including date of preparation or last revision

Issue date	July 13, 2015
Revision	0