REFCOTEC
Where mold and metal meet

Safety Data Sheet

Prior Issue Date: 10 January, 2013 **Revision Date:** 23 March, 2015 **Version** 2

1. IDENTIFICATION

Product Identifier

Product Name REFCOSTIX 6000 Red

Other means of identification

SDS # SDST6000R

Product Code ST6000R

Recommended use:

Core adhesive and mold sealants.

Supplier Details

REFCOTEC, Inc
542 Collins Blvd
Orrville, OH 44667

Emergency Telephone Number

Company Phone Number Information Calls: 330-683-2200
Fax Number: 330-683-8200

Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Thick red liquid **Physical State** Liquid **Odor** Characteristic of solvents

Classification

Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Flammable Liquids	Category 2

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor. Harmful if swallowed.
May cause drowsiness or dizziness. Causes serious eye irritation.
May cause respiratory irritation. Contains crystalline silica.



Precautionary Statements - Prevention
Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product
Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Keep away from heat/sparks/open flames/hot surfaces. — No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Call a poison center or doctor/physician if you feel unwell
IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
Rinse mouth
IN CASE OF FIRE: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage
Store in a well-ventilated place. Keep container tightly closed
Keep cool
Store locked up

Precautionary Statements - Disposal
Dispose of contents/container to an approved waste disposal plant

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Crystalline silica	14808-60-7	2-4
Acetone	67-64-1	30-32
Kaolin	1322-58-7	40-55
Iron Oxide	1309-37-1	1-5

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

First Aid Measures

Eye Contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Skin Contact	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
Ingestion	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. Rinse mouth.

Most important symptoms and effects

Symptoms	Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Loss of coordination. Overexposure may cause dizziness, headache, loss of motor skills, coughing, shortness of breath, dermatitis.

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Pre-existing respiratory or dermal conditions may be aggravated by overexposure.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media
Water fog. Alcohol foam. Carbon dioxide (CO2). Dry chemical.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical
Highly flammable liquid and vapor. Unvented containers may rupture or explode when exposed to high heat due to pressure build-up. Move containers to cool area or keep cool with water stream.

Hazardous Combustion Products Carbon oxides.

Sensitivity to Static Discharge Take precautionary measures against static discharge.

Protective equipment and precautions for firefighters
Water stream may cause flame area to spread. Wear self-contained breathing apparatus (SCBA) in confined fire spaces.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions	Use personal protective equipment as required.
Environmental Precautions	Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information. See Section 13: DISPOSAL CONSIDERATIONS.

Methods and material for containment and cleaning up

Methods for Containment	Prevent further leakage or spillage if safe to do so.
Methods for Clean-Up	Eliminate all sources of ignition. Do not flush spills to watercourse. For small spills, absorb with sand, clay, or other inert absorbent. Contain larger spills with dikes or absorbents. Place unusable material into lidded containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear protective gloves/protective clothing and eye/face protection. Wash face, hands, and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion proof equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Do not reuse this container. Send to approved reconditioner for recycling.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed and store in a cool, dry and well-ventilated place. Store away from heat, sparks, open flame or any other ignition source. Store locked up.

Incompatible Materials Strong acids. Oxidizers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Crystalline silica 14808-60-7	TWA: 0.025 mg/m^3 respirable fraction	TWA respirable fraction: (10)/(%SiO2 + 2) mg/m^3 TWA respirable fraction	IDLH: 50 mg/m^3 respirable dust TWA: 0.05 mg/m^3 respirable dust
Acetone 67-64-1	STEL: 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m^3	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m^3
Kaolin 1332-58-7	2 mg/m3 (respirable)	5 mg/m3 (respirable)	
Iron Oxide 1309-37-1	5 mg/m3 (respirable)	10 mg/m3 (respirable)	

Appropriate engineering controls

Engineering Controls Ensure adequate ventilation, especially in confined areas. Local exhaust ventilation recommended. Use mechanical ventilation if TLV(s) for dusts or vapors are expected to be exceeded. Eyewash stations. Showers.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Chemical splash goggles.

Skin and Body Protection Rubber gloves or vinyl gloves. Aprons.

Respiratory Protection NIOSH approved for mineral dusts. Air purifying or SCBA if TLVs for vapors are exceeded.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Liquid		
Appearance	Thick red liquid.	**Odor**	Characteristic of solvents
Color		**Odor Threshold**	Not determined

Property	Values	Remarks •Method
pH	Not determined	
Melting Point/Freezing Point	Not determined	
Boiling Point/Boiling Range	56.1 °C / 133 °F	IBP
Flash Point	(-17.8) - (-12.2) °C / 0-10 °F	TCC
Evaporation Rate	Not determined	
Flammability (Solid, Gas)	Liquid-Not Applicable	
Upper Flammability Limits	12.8	
Lower Flammability Limit	2.6	
Vapor Pressure	180 @ 68°F	
Vapor Density	Greater than 1 (heavier than air)	
Specific Gravity	1.40-1.50	
Water Solubility	Liquid portion miscible	
Solubility in other solvents	Not determined	
Partition Coefficient	Not determined	
Auto-ignition Temperature	465 °C / 869 °F	(acetone)
Decomposition Temperature	Not determined	
Kinematic Viscosity	Not determined	
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	

10. STABILITY AND REACTIVITY

Reactivity
Not reactive under normal conditions.

Chemical Stability
Stable under recommended storage conditions.

Possibility of Hazardous Reactions
None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid
High heat, spark, and open flames. Static discharge. Ignition sources. Keep out of reach of children.

Incompatible Materials
Strong acids. Oxidizers.

Hazardous Decomposition Products
Oxides of carbon.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact Causes serious eye irritation.

Skin Contact Avoid contact with skin.

Inhalation May cause respiratory irritation.

Ingestion Harmful if swallowed.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Crystalline silica 14808-60-7	= 500 mg/kg (Rat)	-	-
Acetone 67-64-1	= 5800 mg/kg (Rat)	-	-

Information on physical, chemical and toxicological effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity Crystalline Silica is considered to be a human carcinogen when in respirable form (dust / powder).

Chemical Name	ACGIH	IARC	NTP	OSHA
Crystalline silica 14808-60-7	A2	Group 1	Known	X

ACGIH (American Conference of Governmental Industrial Hygienists)
A2 - Suspected Human Carcinogen
IARC (International Agency for Research on Cancer)
Group 1 - Carcinogenic to Humans
NTP (National Toxicology Program)
Known - Known Carcinogen
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
X - Present

STOT - single exposure May cause respiratory irritation. May cause drowsiness or dizziness.

Numerical measures of toxicity
Not determined

12. ECOLOGICAL INFORMATION

Ecotoxicity
The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Acetone 67-64-1		4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L LC50 6210 - 8120: 96 h Pimephales promelas mg/L LC50 static 8300: 96 h Lepomis macrochirus mg/L LC50	EC50 = 14500 mg/L 15 min	10294 - 17704: 48 h Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h Daphnia magna mg/L EC50

Persistence/Degradability
Not determined.

Bioaccumulation
Not determined.

Mobility

Chemical Name	Partition Coefficient
Acetone 67-64-1	-0.24

Other Adverse Effects
Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and regulations.

US EPA Waste Number

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone 67-64-1		Included in waste stream: F039		U002

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Acetone 67-64-1	Ignitable

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT: UN1133, Adhesives, 3, PG II, RQ 5000 (Acetone)

IATA: UN1133, Adhesives, 3, II

IMDG: UN1133, Adhesives, 3, II

15. REGULATORY INFORMATION

International Inventories
Not determined

Legend:

TSCA *- United States Toxic Substances Control Act Section 8(b) Inventory*

DSL/NDSL *- Canadian Domestic Substances List/Non-Domestic Substances List*

EINECS/ELINCS *- European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances*

ENCS *- Japan Existing and New Chemical Substances*

IECSC *- China Inventory of Existing Chemical Substances*

KECL *- Korean Existing and Evaluated Chemical Substances*

PICCS *- Philippines Inventory of Chemicals and Chemical Substances*

AICS *- Australian Inventory of Chemical Substances*

US Federal Regulations

CERCLA

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone 67-64-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

SARA 311/312 Hazard Categories

Acute and Chronic Health Hazard
Fire Hazard

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Crystalline silica - 14808-60-7	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Crystalline silica 14808-60-7	X	X	X
Acetone 67-64-1	X	X	X

16. OTHER INFORMATION



Prior Issue Date: 21 March, 2014
Revision Date: 23 March, 2015
Revision Note: New format

Disclaimer

The foregoing data has been compiled from sources which REFCOTEC, in good faith, believes to be dependable, accurate, and reliable to the best of our knowledge. However, REFCOTEC cannot make any warranty or representation respecting the accuracy or completeness of the data and assumes no responsibility for any liability or damages relating thereto. REFCOTEC cannot advise you regarding the protection of your employees, customers, or others. Users may consult OSHA.

End of Safety Data Sheet