# Material Safety Data Sheet
# #513-W Power Mix ULSD Fuel Treatment Winterized

Issued: 10/5/98 Revised: 6/3/08

## SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**Frontier Performance Lubricants, Inc.**
**PO Box 1777**
**Lodi, CA 95241**
**800-807-4496**

**24 Hour Emergency Telephone Number**
**PERS: 800-633-8253**

| **Product Name** | **Product Number(s)** |
|---|---|
| Power Mix ULSD Fuel Treatment Winterized | 513-W |
| **Chemical Name** | **Use** |
| Mixture | Varies |

## SECTION 2: COMPOSITION / INFORMATION ON INGREDIENTS

| Components | CAS No. | % by Wt. | STEL(ACGIH) | TWA (ACGIH) |
|---|---|---|---|---|
| Petroleum Distillates | Mixture | >1% | | 500 ppm 8 Hours |
| Benzene, 1,2,4—Trimethyl- | 95-63-6 | 10.0%-19.9% | | 25 ppm |
| Benzene, 1,3,5-Trimethyl- | 108-67-8 | 9.9%-10.0% | | 25 ppm |
| Xylene | 1330-20-7 | 1.0%-4.9% | 150 ppm | 100 ppm |
| Cumene | 98-82-8 | 1.0%-4.9% | | 50 ppm |

## SECTION 3: HAZARD IDENTIFICATION

**EMERGENCY OVERVIEW**

- Prolonged exposure may cause skin irritation. Keep out of sewers and waterways. May cause eye irritation.

***Potential Health Effects***

**Eye:** May cause stinging irritation, tearing, or redness.

**Skin Contact:** Repeated or prolonged contact may cause dryness or irritation.

**Ingestion:** May cause mouth and throat irritation when swallowed; ingestion of large quantities may cause discomfort.

**Inhalation:** If used in applications where mist is generated, may cause irritation to nose and throat.

**Signs and Symptoms of Exposure:** Irritation to skin, watering or redness in eyes, discomfort, throat irritation if swallowed.

**Chronic Effects / Adverse Effects:** Trimethylbenzenes: Literature data indicate that long-term inhalation exposure causes blood effects in laboratory animals.
Naphthalene: Naphthalene exposure may cause severe dermatitis in sensitized persons. Ingestion of

naphthalene has caused hemolysis in humans deficient in glucose-6-phosphate dehydrogenase
Xylene: Adverse sysmptoms may include: Central nervous system, liver, kidneys and blood effects by inhalation and heart beat irregularity (arrythmia) and heart beat – increase. High exposures to xylene in some animal studies, often at levels toxic to the mother, affected embryo/fetal development. The significance of this finding to humans is not known.
2-Ethyl Hexanol: Adverse symptoms may include: liver, kidneys, lungs and heart effects by dermal route and immune system effects by ingestion route.

## SECTION 4: FIRST AID MEASURES

**Eye:** Flush with water. If irritation occurs call for medical assistance.

**Skin:** Remove contaminated clothing. Wash with soap and water. Call for medical attention if symptoms prevail.

**Ingestion:** DO NOT induce vomiting. Get medical assistance.

**Inhalation:** Remove person to fresh air. Call for medical attention if needed.

## SECTION 5: FIRE FIGHTING MEASURES

**Point Flash:** 167°F **Method:** ASTM D-93

**Flammable Limits (% by volume in air):** **Lower:** ND **Upper:** ND

**Extinguishing Media:** Dry chemical, carbon dioxide, water fog, foam

**NFPA Ratings:** Health – 1 Flammability – 2 Reactivity – 0

*(0 - Insignificant, 1 - Slight, 2 - Moderate, 3 - High, 4 - Extreme)*

*(0 - Insignificant, 1 - Slight, 2 - Moderate, 3 - High, 4 - Extreme)*

**Fire Fighting Instructions:** Wear protective clothing and self-contained breathing apparatus. Extinguish with foam, dry chemical, carbon dioxide.

**Combustion or Decomposition Products:** May cause dense smoke, oxides of carbon, sulfur and nitrogen, aldehydes and other products of incomplete combustion.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

| | |
|---|---|
| PERS Emergency Number (24 hrs): | (800) 633-8253 |
| PERS International Number | (801) 629-0667 |
| U.S. Coast Guard National Response Center: | (800) 424-8802 |

**Spill Procedures:** Personal Protective Equipment must be worn; see Section 8 for recommendations. Ventilate area if spilled in confined space or other poorly ventilated areas. Prevent entry into sewers and waterways. Pick up free liquid for recycle and/or disposal. Residual liquid can be absorbed on inert material. Check under Transportation and Labeling (DOT/CERCLA) and Other Regulatory Information Section (SARA) for hazardous substances to determine regulatory reporting requirements for spills.

## SECTION 7: HANDLING AND STORAGE

**Handling and Storage:** Avoid eye and prolonged skin contact as with all industrial materials. Wash thoroughly after handling. Follow all MSDS/label precautions after container is emptied because they may retain product residues. Store in a cool, dry place. Keep containers closed when not in use.

## SECTION 8: EXPOSURE CONTROLS - PERSONAL PROTECTION

***Personal Protective Equipment***

**Eye/Face Protection:** Use chemical goggles or face shield.

**Skin Protection:** Contact may be minimized by wearing protective clothing and oil resistant gloves.

**Respiratory Protection:** Use NIOSH/MSHA approved full face respirator with an organic vapor cartridge if the recommended exposure limit is exceeded. Use self-contained breathing apparatus for entry into confined space, for other poorly ventilated areas and large spill clean-up sites.

**Engineering Controls:** Good general ventilation should be sufficient to control airborne levels below exposure limits. A local exhaust is recommended in enclosed areas.

**Clothing Recommendation:** Long sleeve shirt is recommended. Wear a chemically protective apron when contact with material may occur. Do not wear rings, watches or similar apparel that could entrap the material and cause a skin reaction.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|---|
| **Appearance:** | Clear To Yellowish Liquid |
| **Odor:** | Petroleum Odor |
| **Specific Gravity (water = 1):** | 0.90 |
| **Viscosity cSt @ 100°C:** | ND |
| **Flash Point (ASTM D-93):** | 167°F |
| **pH (as is):** | ND |
| **pH (dilute) @ 5 %:** | ND |
| **Solubility in Water (%):** | 0 |
| **Vapor Pressure (mm Hg):** | ND |
| **Vapor Density (air = 1):** | ND |
| **Volatile Organic Compound:** | ND |

## SECTION 10: STABILITY AND REACTIVITY

| | |
|---|---|
| **Hazardous Decomposition Products:** | May cause dense smoke, oxides of carbon, sulfur and nitrogen, aldehydes and other products of incomplete combustion. |
| **Chemical Stability:** | Material is normally stable at room temperature and pressure. See the Handling and Storage section for further details. |
| **Conditions to Avoid:** | Excessive heat or flames |
| **Incompatibility with other Materials:** | Oxidizing or acidic materials |
| **Hazardous Polymerization:** | Will not occur |

## SECTION 11: TOXICOLOGICAL INFORMATION

No information available at present time.

## SECTION 12: ECOLOGICAL INFORMATION

No data are available on the adverse effects of this material on the environment. As a precaution, product

should be kept out of sewage and drainage systems and bodies of water.

## SECTION 13: DISPOSAL CONSIDERATIONS

Any disposal practice must be in compliance with local, state and federal laws and regulations. Empty containers must be handled with care due to product residue. Frontier Performance Lubricants Inc. will provide lists of companies which recycle or handle waste material to customers upon request. For information call (209) 334-6353

## SECTION 14: TRANSPORTATION INFORMATION

| | |
|---|---|
| **DOT Shipping Name:** | Combustible Liquid |
| **DOT Hazard Class:** | Class 85 |
| **DOT Packaging Group:** | PG III |
| **DOT/UN Identification:** | NA 1993 |
| **Additional Information:** | NMFC Code: 155250-1 |
| **IMDG Codes** | Not Regulated |

## SECTION 15: REGULATORY INFORMATION

**TSCA Status:** All components are listed in TSCA inventory.

**CERCLA Reportable Quantity:** There are no reportable quantities for any spill resulting from a single pail, drum or tote. The minimum spill to reach reportable quantities is approximately 1,787 gallons. Listed below are the minimum quantity thresholds for spills greater than 1,787 gallons:
Hazardous substances: Benzene: 10 lbs (4.538kg); Naphthalene: 100 lbs (45.38kg); Benzo[A]Pyrene 1 lb (0.4536kg); Toluene: 1,000 lbs (454.8kg); Ethylbenzene: 1,000 lbs (454.8kg); Styrene: 1,000 lbs (453.8kg); Cumene: 5,000 lbs (2,268kg)

**SARA Title III: Title III of the Superfund Amendments and Reauthorization Act of 1986:**

**Section 302 Extremely Hazardous Substances:** Not an extremely hazardous substance

**Section 311/312 Hazardous Categories:**

| | |
|---|---|
| **Immediate (Acute) Health Effects:** | Yes |
| **Delayed (Chronic) Health effects:** | Yes |
| **Fire Hazard:** | Yes |
| **Sudden Release of Pressure Hazard:** | No |
| **Reactivity Hazard:** | No |
| **Carcinogenicity Status:** | Constituents not listed by: IARC, NTP, OSHA |

## SECTION 16: OTHER INFORMATION

# Material Safety Data Sheet
# #513-W Power Mix ULSD Fuel Treatment Winterized

Issued: 10/5/98 Revised: 6/3/08

**Label Hazard Ratings:**

**Label Hazard Ratings:**

| NFPA | | HMIS |
|---|---|---|
| Fire - 2 | | Health - 1 |
| Health - 2 | Fire - 2 | |
| Reactivity - 0 | | Reactivity - 0 |
| Specific Hazard - none | | Personal Protection Index - C |

***THE INFORMATION AND RECOMMENDATIONS HEREIN ARE, TO THE BEST OF OUR KNOWLEDGE AND BELIEF, ACCURATE AND RELIABLE AS OF THE DATE ISSUED. FRONTIER PERFORMANCE LUBRICANTS INC. DOES NOT WARRANT OR GUARANTEE THEIR ACCURACY OR RELIABILITY, AND SHALL NOT BE LIABLE FOR ANY LOSS OR DAMAGE ARISING OUT OF THE USE THEREOF. THE INFORMATION AND RECOMMENDATIONS ARE OFFERED FOR THE USER'S CONSIDERATION AND EXAMINATION, AND IT IS THE USER'S RESPONSIBILITY TO SATISFY ITSELF THAT THEY ARE SUITABLE AND COMPLETE FOR ITS PARTICULAR USE.***