


ESP32 Pin-Out

ESP32 DEVKIT V1 – DOIT


version with 36 GPIOs



* Pins SCK/CLK, SDO/SD0, SDI/SD1, SHD/SD2, SWP/SD3 and SCS/CMD, namely, GPIO6 to GPIO11 are connected to the integrated SPI flash integrated on ESP-WROOM-32 and are not recommended for other uses.

ESP32 Pin-Out

ESP32 DEVKIT V1 – DOIT version with 30 GPIOs




ESP32 Pin-Out

GPIO	Input	Output	Notes
0	pulled up	OK	outputs PWM signal at boot
1	TX pin	OK	debug output at boot
2	OK	OK	connected to on-board LED
3	OK	RX pin	HIGH at boot
4	OK	OK	
5	OK	OK	outputs PWM signal at boot
6	x	x	connected to the integrated SPI flash
7	x	x	connected to the integrated SPI flash
8	x	x	connected to the integrated SPI flash
9	x	x	connected to the integrated SPI flash
10	x	x	connected to the integrated SPI flash
11	x	x	connected to the integrated SPI flash
12	OK	OK	boot fail if pulled high
13	OK	OK	
14	OK	OK	outputs PWM signal at boot
15	OK	OK	outputs PWM signal at boot
16	OK	OK	
17	OK	OK	
18	OK	OK	

19	OK	OK	
21	OK	OK	
22	OK	OK	
23	OK	OK	
25	OK	OK	
26	OK	OK	
27	OK	OK	
32	OK	OK	
33	OK	OK	
34	OK		input only
35	OK		input only
36	OK		input only
39	OK		input only

ESP32 Pin-Out (Wemos Lolin)



[https://github.com/FablabTorino/AUG-Torino/wiki/Wemos-Lolin-board-\(ESP32-with-128x64-SSD1306-I2C-OLED-display\)](https://github.com/FablabTorino/AUG-Torino/wiki/Wemos-Lolin-board-(ESP32-with-128x64-SSD1306-I2C-OLED-display))

ESP32 Pin-Out (TTGO OLED)

