



Lexpure[®]
PURIFIER SERIES

6
STAGE

CLASSIC PRO

10 Ltr.
STORAGE



WITH
SILVER NANO
TECHNOLOGY
(KILLS BACTERIA)
Works up to 48* Hours

ALKALINE RO

M.R.P. : ₹ 19,480/-
Incl. of all Taxes

6
STAGE

CLASSIC PLUS

10 Ltr.
STORAGE



WITH
SILVER NANO
TECHNOLOGY
(KILLS BACTERIA)

Works up to 48* Hours

ALKALINE RO

M.R.P. : ₹ 18,480/-
Incl. of all Taxes

5
STAGE

TAPURO PRO

08 Ltr.
STORAGE



ph
Balancer
TECHNOLOGY

ALKALINE RO

M.R.P. : ₹ 17,880 /-
Incl. of all Taxes

5
STAGE

TAPURO PLUS

08 Ltr.
STORAGE



ALKALINE RO

M.R.P. : ₹ 17,680/-
Incl. of all Taxes

5
STAGE

Silver

08 Ltr.
STORAGE



ph
Balancer
TECHNOLOGY

ALKALINE RO

M.R.P. : ₹ 15,499/-
Incl. of all Taxes

5
STAGE

Elite

08 Ltr.
STORAGE



ENHANCES
THE **TASTE** OF
WATER

RO

M.R.P. : ₹ 13,999/-
Incl. of all Taxes

5
STAGE

RO 25 MS

25-30
LPH



ENHANCES
THE TASTE OF
WATER

RO

M.R.P. : ₹ 34,880/-
Incl. of all Taxes

5
STAGE

RO 50 MS

50-55
LPH



ENHANCES
THE TASTE OF
WATER

RO

M.R.P. : ₹ 44,880/-
Incl. of all Taxes

REPLACEABLE CARTRIDGE KIT



M.R.P. : ₹ 1,599/-
Incl. of all Taxes

M.R.P. : ₹ 2,299/-
Incl. of all Taxes

SN SILVER NANO



SALIENT FEATURES

- Good residual effect, water can be stored for longer period of time. Even protects from secondary contamination.
- No algae & bio-fouling in storage tanks, tubes & taps
- No need to clean the tank.
- Bacteriological water quality as per IS10500.
- Dosage within IS10500, WHO, EU, USEPA standards.
- Suitable for 24V/36V and 48V DC
- Flow rate max 15 LpH / 25 LpH / 50 LpH
- Service life 7,500 lts / 7,500Lts / 15,000Lts
- Replaces UV, UF, Ozonation and chlorination.
- No change in PH, taste and odour
- Suitable for simple Non-RO water purifiers and RO purifiers
- Can be retrofitted to existing purifier also
- Product is Patent reserved

M.R.P. : ₹ 1,085/-
Incl. of all Taxes

#Standard Test Condition:

RO / RO+UV/SN + ALKALINE Water Purifiers

- Feed water Quality: TDS (max.) : 1000 mg/lit with NaCl, Pressure : 1.0 Kg/cm², Turbidity : Max. 1 NTU, Temperature: 25°C,
- Chlorine below 0.2 mg/litres, Iron below 0.3 mg/litres
- Pressure on membrane: 75 psi & Product recovery @ 25%
- Life: 6000# Liters.

#Actual performance may vary based on the input water conditions : TDS, Hardness, Pressure, Temperature & pH



LEXCRU WATER TECH PVT. LTD.

Corporate Office :

INDIA : D- 601/602, Six Floor, Saral Icon, Near. Hotel Flora, Opp. Reliance Petrol Pump,
S. P. Ring Road, Vastral - 382418, Ahmedabad, Gujarat, INDIA.



+91 9624597111



www.lexcru.com



sales@lexcru.com

