

Day 05: Python Django

Django: ORM

 $Summary: \ \ Today, \ we'll \ tackle \ the \ ORM \ of \ {\it Django}.$ 

# Contents

1	instructions	4
II	Today's specific rules	3
III	Exercise 00	5
IV	Exercise 01	6
$\mathbf{V}$	Exercise 02	7
$\mathbf{VI}$	Exercise 03	9
VII	Exercise 04	11
VIII	Exercise 05	13
IX	Exercise 06	15
$\mathbf{X}$	Exercise 07	17
XI	Exercise 08	19
XII	Exercise 09	21
XIII	Exercise 10	23

## Chapter I

#### Instructions

Unless there is an explicit contradiction, the following instructions will be valid for all days of this Python Django Piscine.

- Only this page will serve as reference; do not trust rumors.
- Watch out! This document could potentially change up to an hour before submission.
- These exercises are carefully laid out by order of difficulty from easiest to hardest. We will not take into account a successfully completed harder exercise if an easier one is not perfectly functional.
- Make sure you have the appropriate permissions on your files and directories.
- You have to follow the submission procedures for every exercise.
- Your exercises will be checked and graded by your fellow classmates.
- On top of that, your exercises will be checked and graded by a program called Moulinette. Moulinette is very meticulous and strict in its evaluation of your work. It is entirely automated and there is no way to negotiate with it. So if you want to avoid bad surprises, be as thorough as possible.
- Exercises in Shell must be executable with /bin/sh.
- You <u>cannot</u> leave <u>any</u> additional file in your directory than those specified in the subject.
- Got a question? Ask your peer on the right. Otherwise, try your peer on the left.
- Your reference guide is called Google / man / the Internet / ....
- Remember to discuss on the piscine forum of your Intra and on Slack!
- Examine the examples thoroughly. They could very well call for details that are not explicitly mentioned in the subject...

### Chapter II

# Today's specific rules

- You must use a python3 interpreter.
- Each exercise will be independent. If, among the required features, some have already been tackled in previous exercises, duplicate them in the current one.
- You must work in a postgresql database named djangotraining and create a role named djangouser, which password will be "secret", that will have all the rights for it.
- Your repository folder must be a Django project. The project must be named after the current day.
- We will use Django's application concept to separate the exercises: Today's exercises must be located in a specific Django application named after the matching exercise and located at the root of the repo.
- The Django project must be properly configured to meet the exercise's requirements. You will not be able to change the configurations during evaluation.
- You can't turn-in any migration with your work.
- In each exercise which cart mentions ORM, you must use the Django's ORM. You mustn't write any line of SQL.
- In each exercise which cart mentions SQL, you must use the psycopg2 library and run all the requests in SQL.

Here is a typical structure example for the repo of a student named krichard, about the day d42, including 2 exercises:

```
krichard
    .git
    .gitignore
   |-- __init__.py
    -- settings.py
   -- urls.py
   |-- wsgi.py
    -- admin.py
    -- apps.py
    -- forms.py
       __init__.py
     - models.py
     - tests.py
    -- urls.py
     -- views.py
   ex01
    -- admin.py
     -- apps.py
     -- forms.py
       __init__.py
models.py
     -- tests.py
     -- urls.py
   -- views.py
    manage.py
```



Be smart: factor your code and make it easy to use. You'll save some time.

### Chapter III

#### Exercise 00

	Exercise 00	
/	Exercice 00: SQL - building a table	
Turn-in directory : $ex00/$		
Files to turn in:		/
Allowed functions:		

Create a Django application named ex00 as well as an inside view that must be accessed at the following URL: 127.0.0.1:8000/ex00/init.

This view must create an SQL table in Postgresql with the help of the psycopg2 library and return a page containing "OK" if successful. Otherwise, it must return an error message describing the problem.

The SQL table must fit this description:

- It must be named ex00\_movies.
- It must be created only if it doesn't already exist.
- It must only include the following fields:
  - o title: unique, variable character chain, 64 byte maximum size, non null.
  - episode\_nb: full, PRIMARY KEY.
  - o opening\_crawl: text, can be null, no size limit.
  - o director: variable character chain, non null, 32 bytes maximum size.
  - o producer: variable character chain, non null, 128 bytes maximum size.
  - release\_date: date (without time), non null.

# Chapter IV

### Exercise 01

H	Exercise 01
Exercise 01	: ORM - building a table
Turn-in directory : $ex01/$	
Files to turn in:	
Allowed functions:	

Create an application named  $\tt ex01$ . In it, create a <code>Django</code> model named <code>Movies</code> with this fields exactly:

- title: unique, variable character chain, 64 byte maximum size, non null.
- episode\_nb: full, PRIMARY KEY.
- opening\_crawl: text, can be null, no size limit.
- director: variable character chain, non null, 32 bytes maximum size.
- producer: variable character chain, non null, 128 bytes maximum size.
- release\_date: date (without time), non null.

This model also must redefine the <code>\_\_str\_\_</code> method so that it sends back the <code>title</code> attribute.

### Chapter V

#### Exercise 02

	Exercise 02	
/	Exercise 02: SQL - Data insertion	
Turn-in directory : $ex02/$		
Files to turn in:		
Allowed functions:		

You must create an Django application named ex02. In this application, the accessible views via the follolwing urls:

• 127.0.0.1:8000/ex02/init: must create a table with the very same specifications as the one required for the ex00 except it will be named ex02 movies.

It must return a page displaying "OK" if successful. Otherwise, it should display a message describing the problem.

- 127.0.0.1:8000/ex02/populate: must insert the following data in the table created by the previous view:
  - o episode\_nb: 1 title: The Phantom Menace director: George Lucas producer: Rick McCallum release\_date: 1999-05-19
  - o episode\_nb: 2 title: Attack of the Clones director: George Lucas producer: Rick McCallum release\_date: 2002-05-16
  - episode\_nb: 3 title: Revenge of the Sith director: George Lucas producer: Rick McCallum - release\_date: 2005-05-19
  - o episode\_nb: 4 title: A New Hope director: George Lucas producer: Gary Kurtz, Rick McCallum release\_date: 1977-05-25
  - o episode\_nb: 5 title: The Empire Strikes Back director: Irvin Kershner producer: Gary Kurtz, Rick McCallum release\_date: 1980-05-17

- o episode\_nb: 6 title: Return of the Jedi director: Richard Marquand producer: Howard G. Kazanjian, George Lucas, Rick McCallum release\_date: 1983-05-25
- o episode\_nb: 7 title: The Force Awakens director: J. J. Abrams producer: Kathleen Kennedy, J. J. Abrams, Bryan Burk release\_date: 2015-12-11

It must return a page displaying "OK" for each successful insertion. Otherwise, it must display an error message stating the problem.

• 127.0.0.1:8000/ex02/display: must display all the data included in the ex02\_movies table in an HTML table, including the eventual void fields.

If there is no available data, or an error, the page must simply display "No data available".

# Chapter VI

#### Exercise 03

	Exercise 03	
/	Exercice 03: ORM - data insertion	
Turn-in directory : $ex03/$		
Files to turn in:		
Allowed functions:		

Create a new Django app named ex03. Inside it, create a Django model identical to the one created in the ex01.

This app must include the accessible views via the following URLs:

- 127.0.0.1:8000/ex03/populate: must insert the model of this application, the following data:
  - o episode\_nb: 1 title: The Phantom Menace director: George Lucas producer: Rick McCallum release\_date: 1999-05-19
  - o episode\_nb: 2 title: Attack of the Clones director: George Lucas producer: Rick McCallum release date: 2002-05-16
  - o episode\_nb: 3 title: Revenge of the Sith director: George Lucas producer: Rick McCallum release\_date: 2005-05-19
  - o episode\_nb: 4 title: A New Hope director: George Lucas producer: Gary Kurtz, Rick McCallum release\_date: 1977-05-25
  - o episode\_nb: 5 title: The Empire Strikes Back director: Irvin Kershner producer: Gary Kurtz, Rick McCallum release\_date: 1980-05-17
  - o episode\_nb: 6 title: Return of the Jedi director: Richard Marquand producer: Howard G. Kazanjian, George Lucas, Rick McCallum release\_date: 1983-05-25

Django: ORM

o episode\_nb: 7 - title: The Force Awakens - director: J. J. Abrams - producer: Kathleen Kennedy, J. J. Abrams, Bryan Burk - release\_date: 2015-12-11

It must return a page displaying "OK" for each successful insertion. Otherwise, it must display an error message stating the problem.

• 127.0.0.1:8000/ex03/display: must display all the data included in the Movies table in an HTML table, including the eventual void fields.

If there is no available data, or an error, the page must simply display "No data available".



During the evaluation, the migration will be carried out before the tests.

### Chapter VII

#### Exercise 04

	Exercise 04	
/	Exercise 04: SQL - Data deleting	
Turn-in directory : $ex04/$		/
Files to turn in:		
Allowed functions:		

Create an app named  $\tt ex04$ . It must contain the accessible views via the following URLs:

• 127.0.0.1:8000/ex04/init: must create a table with the very same specifications as the one required for the ex00 app except it will be named ex04\_movies.

It must return a page displaying "OK" for each successful insertion. Otherwise, it must display an error message stating the problem.

• 127.0.0.1:8000/ex04/populate: must insert the data described in the exercise ex02 in the table created in the previous view.

This view must reinsert any deleted data.

It must return a page displaying "OK" for each successful insertion. Otherwise, it must display an error message stating the problem.

• 127.0.0.1:8000/ex04/display: must display all the data included in the ex04\_movies table in an HTML table, including the eventual void fields.

If there is no available data, or an error, the page must simply display "No data available".

• 127.0.0.1:8000/ex04/remove: must display an HTML form containing a drop-down list of film titles and a submit button named remove.

The film titles are the ones contained in the  $ex04\_movies$  table.

When the form is validated, the selected film is deleted from the database and the form is redisplayed with the updated list containing the remaining films.

If there is no available data, or an error, the page must simply display "No data available".

# Chapter VIII

#### Exercise 05

	Exercise 05	
/	Exercice 05: ORM - Deleting data	
Turn-in directory : $ex05/$		
Files to turn in:		
Allowed functions:		/

Create a new Django app named ex05. Create a model identical to the one in ex01 inside it.

This app must include the accessible views via the following URLs:

• 127.0.0.1:8000/ex05/populate: must insert the data described in the exercise ex03 in the created application.

This view must reinsert any deleted data.

It must return a page displaying "OK" for each successful insertion. Otherwise, it must display an error message stating the problem.

• 127.0.0.1:8000/ex05/display: must display all the data included in the Movies table in an HTML table, including the eventual void fields.

If there is no available data, or an error, the page must simply display "No data available".

• 127.0.0.1:8000/ex05/remove: must display an HTML form containing a drop-down list of film titles and a submit button named remove.

The film titles are the ones contained in the Movies model of this application.

When the form is validated, the selected film is deleted from the database and the form is redisplayed with the updated list containing the remaining films.

If there is no available data, or an error, the page must simply display "No data available".



During the evaluation, the migration will be carried out before the tests.

### Chapter IX

#### Exercise 06

Exercise 06	
Exercise 06: SQL - Updating a data	
Turn-in directory : $ex06/$	
Files to turn in:	
Allowed functions:	

Create a new Django app named ex06. It must contain the accessible views via the following URLs:

- 127.0.0.1:8000/ex06/init: must create a table with the very same specifications as the one required for the ex00 app except it will be named ex06\_movies and will include the following additional fields:
  - created a datetime type (date and time), that, when created, must automatically set to the current date and time.
  - updated a datetime type (date and time), that, when created, must automatically set to the current date and time and automatically updates with each update thanks to the following trigger:

```
CREATE OR REPLACE FUNCTION update_changetimestamp_column()
RETURNS TRIGGER AS $$
BEGIN
NEW.updated = now();
NEW.created = OLD.created;
RETURN NEW;
END;
$$ language 'plpgsql';
CREATE TRIGGER update_films_changetimestamp BEFORE UPDATE
ON exO6_movies FOR EACH ROW EXECUTE PROCEDURE
update_changetimestamp_column();
```

• 127.0.0.1:8000/ex06/populate: must populate the table created in the previous view with the data described in the exercise doit peupler la table ex02.

It must return a page displaying "OK" for each successful insertion. Otherwise, it must display an error message stating the problem.

• 127.0.0.1:8000/ex06/display: must display all the data included in the ex06\_movies table in an HTML table.

If there is no available data, or an error, the page must simply display "No data available".

• 127.0.0.1:8000/ex06/update: must manage the sending and receipt of a form. The latter must allow to choose a film in a drop- down menu containing the films included in the ex06\_movies table and to write text in the second field. When validating the form, the view must replace the opening\_crawl field of the selected film with the text typed in the form in the ex06\_movies table.

If there is no available data, or an error, the page must simply display "No data available".

### Chapter X

#### Exercise 07

Exercise 07	
Exercise 07: ORM - Upd	ating a data
Turn-in directory : $ex07/$	
Files to turn in:	
Allowed functions:	

Create a new Django app named ex07. Create a model identical to the one in ex01 inside it, except you will add the following fields:

- created a datetime type (date and time), that, when created, must automatically set to the current date and time.
- updated a datetime type (date and time), that, when created, must automatically set to the current date and time and automatically updates with each update.

This app must contain the accessible views on the following URLs:

• 127.0.0.1:8000/ex07/populate: populates the model previously created with the same data as ex02.

It must return a page displaying "OK" for each successful insertion. Otherwise, it must display an error message stating the problem.

• 127.0.0.1:8000/ex07/display: displays all the data included in the Movies table in an HTML table.

If there is no available data, or an error, the page must simply display "No data available".

• 127.0.0.1:8000/ex07/update: must manage the sending and receipt of a form. The latter must allow to choose a film in a drop- down menu containing the films

included in the Movies table and to write text in the second field. When validating the form, the view must modify the opening\_crawl field of the selected film with the text typed in the form of the Movies model.

If there is no available data, or an error, the page must simply display "No data available".



During the evaluation, the migration will be carried out before the tests.

# Chapter XI

# Exercise 08

	Exercise 08	
	Exercise 08: SQL - Foreign Key	
Turn-in directory : $ex08/$		
Files to turn in:		/
Allowed functions:		

Create a new Django app named ex08. This app must contain the accessible views via the following URLs:

- 127.0.0.1:8000/ex08/init: Must create two tables.

  The first must be named ex08\_planets and include the following fields:
  - o id: serial, primary key
  - o name: unique, variable character chain, 64 byte maximum size, non null.
  - o climate: variable character chain.
  - o diameter: whole.
  - o orbital\_period: whole.
  - o population: large whole.
  - o rotation\_period: whole.
  - surface\_water: real.
  - o terrain: variable character chain, 128 bytes maximum size.

The second one must be called  $ex08\_people$  and include the following fields:

- o id: serial, primary key.
- o name: unique, variable character chain, 64 byte maximum size, non null.

- o birth\_year: variable character chain, 32 byte maximum size.
- o gender: variable character chain, 32 byte maximum size.
- eye\_color: variable character chain, 32 byte maximum size.
- o hair\_color: variable character chain, 32 byte maximum size.
- o height: whole.
- o mass: real.
- homeworld: variable character chain, 64 byte maximum size, foreign key, referencing the name column of the 08 planets table.
- 127.0.0.1:8000/ex08/populate: must populate both tables copying the content of the people.csv and planets.csv files in the matching tables, respectively: ex08\_people and ex08\_planets.

This view must return a page displaying "OK" for each successful insertion. Otherwise, it must display an error message stating the problem.

• 127.0.0.1:8000/ex08/display: displays all the characters' names, their homeworld as well as the climate, which is windy or moderately windy sorted in character's name alphabetical order.

If there is no available data, or an error, the page must simply display "No data available".



Get information about the psycopg2copy\_from method

### Chapter XII

#### Exercise 09

	Exercise 09	
/	Exercise 09: ORM - Foreign Key	
Turn-in directory : $ex09/$		
Files to turn in:		/
Allowed functions:		

Create a new Django app called ex09 and create two models inside. The first one will be named Planets and will contain the following fields:

- name: unique, variable character chain, 64 byte maximum size, non null.
- climate: variable character chain.
- diameter: whole.
- orbital\_period: whole.
- population: large whole.
- rotation\_period: whole.
- surface\_water: real.
- terrain: character chains.
- created a datetime type (date and time), that, when created, must automatically set to the current date and time.
- updated a datetime type (date and time), that, when created, must automatically set to the current date and time and automatically updates with each update.

This model also must redefine the \_\_str\_\_() method so that it returns the name attribute.

Django: ORM

The second model you will create must be named People and contain the following fields:

- name: character chain, 64 byte maximum size, non null.
- birth\_year: character chain, 32 byte maximum size.
- gender: character chain, 32 byte maximum size.
- eye color: character chain, 32 byte maximum size.
- hair\_color: character chain, 32 byte maximum size.
- height: whole.
- mass: real.
- homeworld: character chain, 64 byte maximum size, foreign key referencing the name column of this app's Planets table.
- created a datetime type (date and time), that, when created, must automatically set to the current date and time.
- updated a datetime type (date and time), that, when created, must automatically set to the current date and time and automatically updates with each update.

This model also must redefine the \_\_str\_\_() method so that it returns the name attribute.

In this app, you will also create a view that must be accessible at the following address: 127.0.0.1:8000/ex09/display.

This view must display all the characters' names, their homeworld as well as the climate, which is windy or moderately windy sorted in character's name alphabetical order in an HTML table.

If there is no available data, the view must display the following text: "No data available, please use the following command line before use:" followed by a command line.

This command line must be the one to be executed from the root of your repo in order to insert all the data included in the ex09\_initial\_data.json file (provided with today's resources) in the models previously created.

You will have to provide this files with your repo.



During the evaluation, the migration will be carried out before the tests.

# Chapter XIII

#### Exercise 10

	Exercise 10	
/	Exercise 10: ORM - Many to Many	
Turn-in directory : $ex10$	/	
Files to turn in:		/
Allowed functions:		

Create a new Django app named ex10 and create 3 models inside:

- Planets and People: Both these models must be identical to the ones in ex09.
- Movies: This model must be identical to the one in the ex01 except you must add the field characters.

This is a "many to many" type with the People model. It allows the listing of every character in a film included in the People table.

The necessary fixtures to populate the models are included in the ex10\_initial\_data.json file provided with today's resources.

In this app, you will also create a view accessible via the following URL: 127.0.0.1:8000/ex10. It must display a form featuring these mandatory fields:

- Movies minimum release date : date
- Movies maximum release date : date
- Planet diameter greater than : number
- Character gender: drop-down list showing the different values available in the gender field of the People model. The same value shouldn't be featured twice.

Once validated, the view must search, return and display the result(s).

A result is a character whose gender matches the 'character gender' field, with a film they're in, if the film was released between Movies minimum release date and Movies maximum release date, their planet if its diameter is greater or equal Planet diameter greater than.

If your research gives no result, the message "Nothing corresponding to your research" must appear. Each result must be displayed on a line with these elements (not necessarily in this order):

- Character's name
- Their gender
- Film title
- Name of homeworld
- Homeworld's diameter

For instance: the results for the female characters whose films were released between "1900-01-01" and "2000-01-01" and whose homeworld has a diameter greater than 11000 are:

- A New Hope Leia Organa female Alderaan 12500
- The Phantom Menace Padmé Amidala female Naboo 12120
- Return of the Jedi Leia Organa female Alderaan 12500
- Return of the Jedi Mon Mothma female Chandrila 13500
- $\bullet\,$  The Empire Strikes Back -Leia Organa female Alderaan 12500



Several characters can be in the same film and one character can appear in several films. This is called a many to many relation. In this case, an intermediate table must be created between these tables. Each row of this intermediate table is a (unique) cross-reference: the first references a row in the films' table. The second references a row in the characters' table (or the other way round). Once your models are built and your migrations achieved, you will be able to see this table via the postgre console.