Chapter 1

Performance Evaluation

The following section evaluates each of the elements developed (or attempted to be developed) and interrogates their performance relative to the following criteria:

- Convergence of a metric to a solution
- Convergence of a metric toward the analytical solution
- Stability of element in several loading states
- Suitability of element under various material parameters (E, ν)

As mentioned above, the primary elements of interest are the CSDAX4F (full integration) and CSDAX4R (reduced integration) elements. We attempted to develop a selective reduced integration element (CSDAX4S), however, as will be shown, the performance metrics failed so miserably, that the element is useless much more development work must take place in order for such an element to be functional.

1.1 Determining Differences Between Analytical and Numerical Solutions

Although much more rigorous methods could likely be applied to determining the difference between the analytical and numerical solution for FEM problems, the more simple the metric, the more easily understood it is. Therefore, we determined that an acceptable metric is the maximum displacement of the plate. This maximum deflection has well defined solutions (cataloged in great detail in Roark's solution manual).

In order to extract the maximum deflection from the FEM solution, it is critical to interrogate each node individually for its displacement in the Z axis. Therefore, the following function was constructed in order to interrogate each node for its displacement.

```
def get_max_disp(V,**kwargs):
    uy_max=0
    uy_max2=0
    Xi=array(V.mesh.coord)
    ui=array(V.steps.last.dofs.reshape(Xi.shape))
    for ym in ui[:,1]:
        aym=abs(ym)
        if uy_max < aym:
            uy_max=aym
            uy_max2=ym
    return uy_max2
```

If interrogating each individual point, and comparing each FEM point to an analytical solution, a more rigorous function that returns the x & y displacements as well as the original positions X and Y is:

```
def get_disp_pos(GP,V,**kwargs):
    Xi=array(V.mesh.coord)
```

```
    ui=array(V.steps.last.dofs.reshape(Xi.shape))
    ux = ui[GP,0]
    uy = ui[GP,1]
    X  = Xi[GP,0]
    Y  = Xi[GP,1]
    return ux,uy,X,Y
```

Finally, if an nx4 array is desired to pass to testing functions for analysis, the following function may come in use. We did not end up implementing these functions into any of the testing framework that we developed, however, if one desired to test all points against an analytical solution, this function would be useful.

```
def get_all_disp_pos(V,**kwargs):
    nnodes=V.numnod
    data = array(zeros((nnodes,4)))
    for ii in range(0,nnodes):
        data[ii,:]=get_disp_pos(ii,V)
    return data
```

1.2 Convergence

An error metric was developed which was the error between the numerical solution Y_{num} and the analytical solution Y_a. Although there are many error metrics, the one determined most useful for the purposes of determining convergence upon *a solution* is a simplistic difference error. This error, which will be utilized in the vertical axis of the plots in this section and can be summarized as:

$$error = Y_{FEM} - Y_a \tag{1.1}$$

The following listing provides a function for which one can pass an analysis system into in order to determine the errors associated with that analysis system. Note that this code also returns the number of elements and the percent error.

```
def Comp_Analysis(E,v,P,OD,h,inD=None,
                  NinX=None,NinY=None,eletyp=None,formula=None,
                  Model_Comparison_Function=None,A_Mod_Comp_Fun=None,**kwargs):
    d=dict({'E':E,'v':v,'P':P,'OD':OD,'h':h,'inD':inD,'NinX':NinX,'NinY':NinY,
            'eletyp':eletyp,'formula':formula})
    V=Model_Comparison_Function(**d)
    zFEM = get_max_disp(V)
    zANA = A_Mod_Comp_Fun(**d)
    err=(zFEM-zANA)#/zANA*100.
    err2=(zFEM-zANA)/zANA*100.
    print(Model_Comparison_Function)
    print(eletyp)
    print('Numerical Sol is: ',zFEM)
    print('Analytical Sol is:',zANA)
    print('Absolute Error is:',err)
    print('Percent Error is: ',err2)
    nele=V.numele
    return err,err2,nele
```

1.2.1 CSDAX4F- Full Integration

The full integration element was the most successful in converging in nearly all loading conditions. As can be seen from the series of figures following, the element seems to follow excellent h-refinement convergence. The primary driver in this h-refinement is the generic mesh density. However, if greater detail is applied to ensuring a very square element, instead of rectangular elements, convergence is much more rapid.

In addition to this mesh dependence, it is important to note that if the mesh density in the Z direction is increased without an increase in the R mesh density, the model fails to converge with h-refinement. However, when both are applied (as shown in the images below), h-refinement convergence is much more rapid.

It was generally observed that fewer than 4 elements in the Z directions were unsatisfactory for producing a mesh that gave believable results for the full integration element. Not a great deal of work was exerted toward interrogating this fact, but it is notable nonetheless.



Figure 1.1: H refinement of CSDAX4F under the loading condition described above. This loading condition was the axisymmetric plate with a central point load and clamped outer boundary.



Figure 1.2: H refinement of CSDAX4F under the loading condition described above. This loading condition was the axisymmetric plate with a central point load and pinned outer boundary.



Figure 1.3: H refinement of CSDAX4F under the loading condition described above. This loading condition was the axisymmetric plate with a uniform pressure load and clamped outer boundary.



Figure 1.4: H refinement of CSDAX4F under the loading condition described above. This loading condition was the axisymmetric plate with a uniform pressure load and pinned outer boundary.



Figure 1.5: H refinement of CSDAX4F under the loading condition described above. This loading condition was the axisymmetric washer with a point load on the inside diameter of the washer and clamped outer boundary.



Figure 1.6: H refinement of CSDAX4F under the loading condition described in section ???. This loading condition was the axisymmetric washer with a point load on the inside diameter of the washer and pinned outer boundary.



Figure 1.7: H refinement of CSDAX4F under the loading condition described in section ???.This loading condition was the axisymmetric washer with a uniform pressure load and clamped outer boundary.



Figure 1.8: H refinement of CSDAX4F under the loading condition described in section ???. This loading condition was the axisymmetric washer with a uniform pressure load and pinned outer boundary.

1.2.2 CSDAX4R- Reduced Integration

The reduced integration element struggled to converge in all loading situations. The root cause of this inconsistency is not clear, however, it is clear that whenever the pinned boundary condition is applied to the reduced integration element, the model fails to converge on a solution with h-refinement.



Figure 1.9: H refinement of CSDAX4R under the loading condition described above. This loading condition was the axisymmetric plate with a central point load and clamped outer boundary.



Figure 1.10: H refinement of CSDAX4R under the loading condition described above. This loading condition was the axisymmetric plate with a central point load and pinned outer boundary.



Figure 1.11: H refinement of CSDAX4R under the loading condition described above. This loading condition was the axisymmetric plate with a uniform pressure load and clamped outer boundary.



Figure 1.12: H refinement of CSDAX4R under the loading condition described above. This loading condition was the axisymmetric plate with a uniform pressure load and pinned outer boundary.



Figure 1.13: H refinement of CSDAX4R under the loading condition described above. This loading condition was the axisymmetric washer with a point load on the inside diameter of the washer and clamped outer boundary.



Figure 1.14: H refinement of CSDAX4R under the loading condition described in section ???. This loading condition was the axisymmetric washer with a point load on the inside diameter of the washer and pinned outer boundary.



Figure 1.15: H refinement of CSDAX4R under the loading condition described in section ???.This loading condition was the axisymmetric washer with a uniform pressure load and clamped outer boundary.

1.2.3 Comparing Convergence of Both Elements

The following plots compare the convergence of the CSDAX4F and CSDAX4R element types. Note that some plots (particularly the plots with pinned joints) have extreme scales due to the errors and non-convergence associated with the reduced integration element. This shows that there is clearly some malfunction in the operation of the pin constraint when operating on the reduced integration eleemnt. As mentioned earlier, there is no known solution to this as of yet.



Figure 1.16: Comparison of CSDAX4F and CSDAX4R under the loading condition described above. This loading condition was the axisymmetric plate with a central point load and clamped outer boundary.



Figure 1.17: Comparison of CSDAX4F and CSDAX4R under the loading condition described above. This loading condition was the axisymmetric plate with a central point load and pinned outer boundary.



Figure 1.18: Comparison of CSDAX4F and CSDAX4R under the loading condition described above. This loading condition was the axisymmetric plate with a uniform pressure load and clamped outer boundary.



Figure 1.19: Comparison of CSDAX4F and CSDAX4R under the loading condition described above. This loading condition was the axisymmetric plate with a uniform pressure load and pinned outer boundary.



Figure 1.20: Comparison of CSDAX4F and CSDAX4R under the loading condition described above. This loading condition was the axisymmetric washer with a point load on the inside diameter of the washer and clamped outer boundary.



Figure 1.21: Comparison of CSDAX4F and CSDAX4R under the loading condition described in section ???. This loading condition was the axisymmetric washer with a point load on the inside diameter of the washer and pinned outer boundary.



Figure 1.22: Comparison of CSDAX4F and CSDAX4R under the loading condition described in section ???.This loading condition was the axisymmetric washer with a uniform pressure load and clamped outer boundary.



Figure 1.23: Comparison of CSDAX4F and CSDAX4R under the loading condition described in section ???. This loading condition was the axisymmetric washer with a uniform pressure load and pinned outer boundary.

1.3 Convergence toward analytical solutions

Convergence toward analytical solutions is somewhat sketchy at this point. This is primarily because we are unsure if the analytical solutions are providing the appropriate response to what we are observing with the finite element solutions. Because the convergence plots above do not all go to zero, this shows that there is some problems with at least a few of the analytical solutions. The analytical solutions that look very good are the clamped and pinned boundary conditions on the uniform plate (no hole) with a uniform pressure load applied.

We are unsure, why the concentrated loads are not functioning properly, however, we suspect is has something to do with applying a concentrated load at the center of the axisymmetric element. At this point, r=0 and some rather strange things can begin to happen. Because the radius of the gauss integration point is very small, this may cause the FEM displacement to be too small. This is reflected in the h-refinement images shown in figures 1.1 and 1.2. In fact, in both of those figures, the error seems to converge to a slope rather than a level.

1.4 Functions utilized to determine convergence etc

The following listings are functions that are utilized in determining the convergence of the model.

```
import sys
import pdb
import matplotlib
sys.path.insert(0, '../')
from pyfem2 import *
from Definitions import *
from Definitions2 import *
from mpl_toolkits.mplot3d import Axes3D
from matplotlib import cm
from matplotlib import pyplot as plt

def find_convergence(Model_Comparison_Function,
                     A_Mod_Comp_Fun,
                     nstep=None,xmax=None,title=None,
```

```
                    saveas1=None,saveas2=None,
                    saveas3=None,saveas4=None,**kwargs):
    if nstep is None:
        nstep=7
    if xmax is None:
        xmax=200
    if title is None:
        title='Convergence on Model'
    if saveas1 is None:
        saveas1='Convergence_A.png'
    if saveas2 is None:
        saveas2='Convergence_F.png'
    if saveas2 is None:
        saveas2='Convergence_R.png'
    if saveas2 is None:
        saveas2='Convergence_S.png'
    pconv=dict({'P':40,
                'OD':23,
                'h':.4,
                'formula':1,
                'inD':23/2,
                'E':5e7,
                'v':0.4,
                'Model_Comparison_Function':Model_Comparison_Function,
                'A_Mod_Comp_Fun':A_Mod_Comp_Fun})
    ymax=int(pconv['h']*xmax/pconv['OD'])*3
    ninx=linspace(50,xmax,nstep)
    niny=linspace(3,ymax,nstep)

    er_f=zeros(nstep)
    ne_f=zeros(nstep)
    erp_f=zeros(nstep)
    for ii,nx in enumerate(ninx):
        pconv['NinX']=int(ninx[ii])
        pconv['NinY']=int(niny[ii])
        pconv['eletyp']=AxiSymmetricQuad4
        #er_f[ii],ne_f[ii]=Model_Comparison_Function(**pconv)
        er_f[ii],erp_f[ii],ne_f[ii]=Comp_Analysis(**pconv)

    er_r=zeros(nstep)
    ne_r=zeros(nstep)
    erp_r=zeros(nstep)
    for ii,nx in enumerate(ninx):
        pconv['NinX']=int(ninx[ii])
        pconv['NinY']=int(niny[ii])
        pconv['eletyp']=AxiSymmetricQuad4Reduced
        #er_r[ii],ne_r[ii]=Model_Comparison_Function(**pconv)
        er_r[ii],erp_r[ii],ne_r[ii]=Comp_Analysis(**pconv)

    er_s=zeros(nstep)
    ne_s=zeros(nstep)
    erp_s=zeros(nstep)
    for ii,nx in enumerate(ninx):
        pconv['NinX']=int(ninx[ii])
        pconv['NinY']=int(niny[ii])
        pconv['eletyp']=AxiSymmetricQuad4SelectiveReduced
        #er_s[ii],ne_s[ii]=Model_Comparison_Function(**pconv)
        er_s[ii],erp_s[ii],ne_s[ii]=Comp_Analysis(**pconv)

    plt.plot(ne_f,er_f,marker='o', linestyle='-', color='r',label='Full Int')
    plt.plot(ne_r,er_r,marker='o', linestyle='-', color='b',label='Red Int')
    #plt.plot(ne_s,er_s,marker='o', linestyle='-', color='g',label='Sel Red Int')
    plt.xlabel('Number of Elements')
    plt.ylabel('Error From Analytical')
    plt.title(title)
    plt.legend()
    plt.grid(True)
    plt.savefig(saveas1)
```

```
    plt.show()


    plt.plot(ne_f,er_f,marker='o', linestyle='-', color='r',label='Full Int')
    #plt.plot(ne_r,er_r,marker='o', linestyle='-', color='b',label='Red Int')
    #plt.plot(ne_s,er_s,marker='o', linestyle='-', color='g',label='Sel Red Int')
    plt.xlabel('Number of Elements')
    plt.ylabel('Error From Analytical')
    plt.title(title)
    plt.legend()
    plt.grid(True)
    plt.savefig(saveas2)
    plt.show()

    #plt.plot(ne_f,er_f,marker='o', linestyle='-', color='r',label='Full Int')
    plt.plot(ne_r,er_r,marker='o', linestyle='-', color='b',label='Red Int')
    #plt.plot(ne_s,er_s,marker='o', linestyle='-', color='g',label='Sel Red Int')
    plt.xlabel('Number of Elements')
    plt.ylabel('Error From Analytical')
    plt.title(title)
    plt.legend()
    plt.grid(True)
    plt.savefig(saveas3)
    plt.show()

    #plt.plot(ne_f,er_f,marker='o', linestyle='-', color='r',label='Full Int')
    #plt.plot(ne_r,er_r,marker='o', linestyle='-', color='b',label='Red Int')
    plt.plot(ne_s,er_s,marker='o', linestyle='-', color='g',label='Sel Red Int')
    plt.xlabel('Number of Elements')
    plt.ylabel('Error From Analytical')
    plt.title(title)
    plt.legend()
    plt.grid(True)
    plt.savefig(saveas4)
    plt.show()
```

The following listing describes one potential dictionary and function call of the above definition:

```
pdict=dict({'Model_Comparison_Function':Plate_Point_Pinned,
            'A_Mod_Comp_Fun':A_Plate_Point_Pinned,
            'nstep':nsteps,
            'xmax': 350,
            'title':'Convergence of Pinned Point Plate',
            'saveas1':'Conv_PlPoPi_1.png',
            'saveas2':'Conv_PlPoPi_2.png',
            'saveas3':'Conv_PlPoPi_3.png',
            'saveas4':'Conv_PlPoPi_4.png'})
find_convergence(**pdict)
```

1.5 FEM code

The following listing provides functions for each of the analysis systems described above. The naming convention is quite plain. Several FEM function definitions were not utilized in this report, however, they are given for future reference. One notable function is the thick walled pressure vessel function.

```
def Plate_Point_Pinned(E,v,P,OD,h,
                       NinX=None,NinY=None,eletyp=None,formula=None,
                       **kwargs):
    if eletyp is None:
        eletyp = AxiSymmetricQuad4
    if NinX is None:
        NinX = 100 #Number of elements in I (Diameter)
    if NinY is None:
        NinY = 4 #Number elements in J (Thickness)
    if formula is None:
        formula=1
```

```
    R=OD/2.0
    kp1=NinY*(NinX+1)+1 #Central point
    kp2=NinX+1          #Bottom outside edge
    mesh = RectilinearMesh2D(nx=NinX, ny=NinY, lx=R, ly=h)
    mat = Material('Material-1', elastic={'E':E, 'Nu':v})

    V = FiniteElementModel(mesh=mesh, jobid='PlatePointPinned')
    V.ElementBlock('ElementBlock1', ALL)
    V.AssignProperties('ElementBlock1', eletyp, mat, formulation=formula)

    #V.PrescribedBC(kp2,Y)
    step = V.StaticStep()
    step.PinNodes(kp2)
    #step.FixNodes(kp2)
    #step.PrescribedBC(kp2,Y)
    step = V.StaticStep()
    step.ConcentratedLoad(kp1, Y, -P)
    step.run()
    V.WriteResults()
    if not os.environ.get('NOGRAPHICS'):
        V.Plot2D(show=1, deformed=1)
    return V

def Plate_Point_Clamped(E,v,P,OD,h,
                        NinX=None,NinY=None,eletyp=None,formula=None,
                        **kwargs):
    if eletyp is None:
        eletyp = AxiSymmetricQuad4
    if NinX is None:
        NinX=100 #Number of elements in I (Diameter)
    if NinY is None:
        NinY=4 #Number elements in J (Thickness)
    if formula is None:
        formula=1
    R=OD/2.0
    #Find Keypoints of interest
    kp1=NinY*(NinX+1)+1 #Central point
    kp2=NinX+1          #Bottom outside edge

    mesh = RectilinearMesh2D(nx=NinX, ny=NinY, lx=R, ly=h)
    mat = Material('Material-1', elastic={'E':E, 'Nu':v})

    V = FiniteElementModel(mesh=mesh, jobid='PlatePointClamped')
    V.ElementBlock('ElementBlock1', ALL)
    V.AssignProperties('ElementBlock1', eletyp, mat, formulation=formula)

    step = V.StaticStep()
    step.FixNodes(IHI)
    step = V.StaticStep()
    step.ConcentratedLoad(kp1, Y, -P)
    step.run()
    V.WriteResults()
    if not os.environ.get('NOGRAPHICS'):
        V.Plot2D(show=1, deformed=1)
    return V

def Plate_Pressure_Pinned(E,v,P,OD,h,
                          NinX=None,NinY=None,eletyp=None,formula=None,
                          **kwargs):
    if eletyp is None:
        eletyp = AxiSymmetricQuad4
    if NinX is None:
        NinX = 100 #Number of elements in I (Diameter)
    if NinY is None:
        NinY = 4 #Number elements in J (Thickness)
    if formula is None:
        formula=1
    R=OD/2.0
```

```
    kp1=NinY*(NinX+1)+1 #Central point
    kp2=NinX+1          #Bottom outside edge
    mesh = RectilinearMesh2D(nx=NinX, ny=NinY, lx=R, ly=h)
    mat = Material('Material-1', elastic={'E':E, 'Nu':v})

    V = FiniteElementModel(mesh=mesh, jobid='PlatePressurePinned')
    V.ElementBlock('ElementBlock1', ALL)
    V.AssignProperties('ElementBlock1', eletyp, mat, formulation=formula)

    #V.PrescribedBC(kp2,Y)
    step = V.StaticStep()
    step.PinNodes(kp2)
    #step.FixNodes(kp2)
    #step.PrescribedBC(kp2,Y)
    step = V.StaticStep()
    step.Pressure(JHI, P)
    step.run()
    V.WriteResults()
    if not os.environ.get('NOGRAPHICS'):
        V.Plot2D(show=1, deformed=1)
    return V


def Plate_Pressure_Clamped(E,v,P,OD,h,
                           NinX=None,NinY=None,eletyp=None,formula=None,
                           **kwargs):
    if eletyp is None:
        eletyp = AxiSymmetricQuad4
    if NinX is None:
        NinX = 100 #Number of elements in I (Diameter)
    if NinY is None:
        NinY = 4 #Number elements in J (Thickness)
    if formula is None:
        formula=1
    R=OD/2.0
    kp1=NinY*(NinX+1)+1 #Central point
    kp2=NinX+1          #Bottom outside edge
    mesh = RectilinearMesh2D(nx=NinX, ny=NinY, lx=R, ly=h)
    mat = Material('Material-1', elastic={'E':E, 'Nu':v})

    V = FiniteElementModel(mesh=mesh, jobid='PlatePointPinned')
    V.ElementBlock('ElementBlock1', ALL)
    V.AssignProperties('ElementBlock1', eletyp, mat)

    step = V.StaticStep()
    step.FixNodes(IHI)
    step = V.StaticStep()
    step.Pressure(JHI, P)
    step.run()
    V.WriteResults()
    if not os.environ.get('NOGRAPHICS'):
        V.Plot2D(show=1, deformed=1)
    return V

def Washer_Point_Pinned(E,v,P,OD,h,
                        NinX=None,NinY=None,eletyp=None,inD=None,formula=None,
                        **kwargs):
    if eletyp is None:
        eletyp = AxiSymmetricQuad4
    if NinX is None:
        NinX = 50 #Number of elements in I (Diameter)
    if NinY is None:
        NinY = 4 #Number elements in J (Thickness)
    if inD is None:
        inD = OD/2.0
    if formula is None:
        formula=1
    R  = OD/2.0
```

```
    Ri = inD/2.0
    w  = R-Ri
    kp1=NinY*(NinX+1)+1 #Central point
    kp2=NinX+1          #Bottom outside edge
    mesh = RectilinearMesh2D(nx=NinX, ny=NinY, lx=w, ly=h,shift=[Ri,0])
    mat = Material('Material-1', elastic={'E':E, 'Nu':v})

    V = FiniteElementModel(mesh=mesh, jobid='WasherPointPinned')
    V.ElementBlock('ElementBlock1', ALL)
    V.AssignProperties('ElementBlock1', eletyp, mat)

    #V.PrescribedBC(kp2,Y)
    step = V.StaticStep()
    step.PinNodes(kp2)
    #step.FixNodes(kp2)
    #step.PrescribedBC(kp2,Y)
    step = V.StaticStep()
    step.ConcentratedLoad(kp1, Y, -P)
    step.run()
    V.WriteResults()
    if not os.environ.get('NOGRAPHICS'):
        V.Plot2D(show=1, deformed=1)
    return V

def Washer_Point_Clamped(E,v,P,OD,h,
                         NinX=None,NinY=None,eletyp=None,inD=None,formula=None,
                         **kwargs):
    if eletyp is None:
        eletyp = AxiSymmetricQuad4
    if NinX is None:
        NinX = 50 #Number of elements in I (Diameter)
    if NinY is None:
        NinY = 4 #Number elements in J (Thickness)
    if inD is None:
        inD = OD/2.0
    if formula is None:
        formula=1
    R  = OD/2.0
    Ri = inD/2.0
    w  = R-Ri
    kp1=NinY*(NinX+1)+1 #Central point
    kp2=NinX+1          #Bottom outside edge
    mesh = RectilinearMesh2D(nx=NinX, ny=NinY, lx=w, ly=h,shift=[Ri,0])
    mat = Material('Material-1', elastic={'E':E, 'Nu':v})

    V = FiniteElementModel(mesh=mesh, jobid='WasherPointClamped')
    V.ElementBlock('ElementBlock1', ALL)
    V.AssignProperties('ElementBlock1', eletyp, mat)

    step = V.StaticStep()
    step.FixNodes(IHI)
    step = V.StaticStep()
    step.ConcentratedLoad(kp1, Y, -P)
    step.run()
    V.WriteResults()
    if not os.environ.get('NOGRAPHICS'):
        V.Plot2D(show=1, deformed=1)
    return V

def Washer_Pressure_Pinned(E,v,P,OD,h,
                           NinX=None,NinY=None,eletyp=None,inD=None,formula=None,
                           **kwargs):
    if eletyp is None:
        eletyp = AxiSymmetricQuad4
    if NinX is None:
        NinX = 50 #Number of elements in I (Diameter)
    if NinY is None:
        NinY = 4 #Number elements in J (Thickness)
```

```
216     if inD is None:
217         inD = OD/2.0
218     if formula is None:
219         formula=1
220     R  = OD/2.0
221     Ri = inD/2.0
222     w  = R-Ri
223     kp1=NinY*(NinX+1)+1 #Central point
224     kp2=NinX+1          #Bottom outside edge
225     mesh = RectilinearMesh2D(nx=NinX, ny=NinY, lx=w, ly=h,shift=[Ri,0])
226     mat = Material('Material-1', elastic={'E':E, 'Nu':v})
227 
228     V = FiniteElementModel(mesh=mesh, jobid='WasherPressurePinned')
229     V.ElementBlock('ElementBlock1', ALL)
230     V.AssignProperties('ElementBlock1', eletyp, mat)
231 
232     #V.PrescribedBC(kp2,Y)
233     step = V.StaticStep()
234     step.PinNodes(kp2)
235     #step.FixNodes(kp2)
236     #step.PrescribedBC(kp2,Y)
237     step = V.StaticStep()
238     step.Pressure(JHI, P)
239     step.run()
240     V.WriteResults()
241     if not os.environ.get('NOGRAPHICS'):
242         V.Plot2D(show=1, deformed=1)
243     return V
244 
245 def Washer_Pressure_Clamped(E,v,P,OD,h,
246                             NinX=None,NinY=None,eletyp=None,inD=None,formula=None,
247                             **kwargs):
248     if eletyp is None:
249         eletyp = AxiSymmetricQuad4
250     if NinX is None:
251         NinX = 50 #Number of elements in I (Diameter)
252     if NinY is None:
253         NinY = 4 #Number elements in J (Thickness)
254     if inD is None:
255         inD = OD/2.0
256     if formula is None:
257         formula=1
258     R  = OD/2.0
259     Ri = inD/2.0
260     w  = R-Ri
261     kp1=NinY*(NinX+1)+1 #Central point
262     kp2=NinX+1          #Bottom outside edge
263     mesh = RectilinearMesh2D(nx=NinX, ny=NinY, lx=w, ly=h,shift=[Ri,0])
264     mat = Material('Material-1', elastic={'E':E, 'Nu':v})
265 
266     V = FiniteElementModel(mesh=mesh, jobid='WasherPressurePinned')
267     V.ElementBlock('ElementBlock1', ALL)
268     V.AssignProperties('ElementBlock1', eletyp, mat)
269 
270     step = V.StaticStep()
271     step.FixNodes(IHI)
272     step = V.StaticStep()
273     step.Pressure(JHI, P)
274     step.run()
275     V.WriteResults()
276     if not os.environ.get('NOGRAPHICS'):
277         V.Plot2D(show=1, deformed=1)
278     return V
279 
280 def Universal_Plate(E,v,P,OD,h,Plate=None,Pin=None,Point=None,
281                             NinX=None,NinY=None,eletyp=None,inD=None,
282                             formula=None,job=None,**kwargs):
283     if eletyp is None:
```

```
284         eletyp = AxiSymmetricQuad4
285     if NinX is None:
286         NinX = 50 #Number of elements in I (Diameter)
287     if NinY is None:
288         NinY = 4 #Number elements in J (Thickness)
289     if inD is None:
290         inD = OD/2.0
291     if formula is None:
292         formula=1
293     if Plate is None:
294         Plate = True
295     if Pin is None:
296         Pin = True
297     if Point is None:
298         Point = True
299     if job is None:
300         job = 'AxiSymPlate'
301     R  = OD/2.0
302     Ri = inD/2.0
303     w  = R-Ri
304     kp1=NinY*(NinX+1)+1 #Central point
305     kp2=NinX+1          #Bottom outside edge
306     mat = Material('Material-1', elastic={'E':E, 'Nu':v})
307 
308     #Case Structure for Plate vs Washer
309     if Plate:
310         #If Plate
311         mesh = RectilinearMesh2D(nx=NinX, ny=NinY, lx=R, ly=h)
312     else:
313         #If Washer
314         mesh = RectilinearMesh2D(nx=NinX, ny=NinY, lx=w, ly=h,shift=[Ri,0])
315 
316     V = FiniteElementModel(mesh=mesh, jobid=job)
317     V.ElementBlock('ElementBlock1', ALL)
318     V.AssignProperties('ElementBlock1', eletyp, mat)
319     step = V.StaticStep()
320     # Case Structure for Pined vs Fixed Outside Diameter
321     if Pin:
322         step.PrescribedBC(kp2,Y)
323     else:
324         step.FixNodes(IHI)
325 
326     step = V.StaticStep()
327     # Case Structure for Pressure vs Point loading
328     if Point:
329         step.ConcentratedLoad(kp1, Y, -P)
330     else:
331         step.Pressure(JHI, P)
332 
333     step.run()
334     #V.WriteResults()
335     if not os.environ.get('NOGRAPHICS'):
336         V.Plot2D(show=1, deformed=1)
337     return V
338 
339 
340 def Thick_Infinite_Cyl(E,v,P,OD,h,
341                        NinX=None,NinY=None,eletyp=None,inD=None,formula=None,
342                        **kwargs):
343     if eletyp is None:
344         eletyp = AxiSymmetricQuad4
345     if NinX is None:
346         NinX = 60 #Number of elements in I (Diameter)
347     if NinY is None:
348         NinY = 10 #Number elements in J (Thickness)
349     if inD is None:
350         inD = OD/2.0
351     if formula is None:
```

```
352         formula=1
353     R  = OD/2.0
354     Ri = inD/2.0
355     w  = R-Ri
356     kp1=NinY*(NinX+1)+1 #Central point
357     kp2=NinX+1          #Bottom outside edge
358     mesh = RectilinearMesh2D(nx=NinX, ny=NinY, lx=w, ly=h,shift=[Ri,0])
359     mat = Material('Material-1', elastic={'E':E, 'Nu':v})
360 
361     V = FiniteElementModel(mesh=mesh, jobid='InfiniteCylinder')
362     V.ElementBlock('ElementBlock1', ALL)
363     V.AssignProperties('ElementBlock1', eletyp, mat)
364 
365 
366     V.PrescribedBC(JLO,Y)
367     V.PrescribedBC(JHI,Y)
368 
369     #step = V.StaticStep()
370     #step.FixNodes(IHI)
371     step = V.StaticStep()
372     step.Pressure(ILO, P)
373     step.run()
374     V.WriteResults()
375     if not os.environ.get('NOGRAPHICS'):
376         V.Plot2D(show=1, deformed=1)
377     return V
```

Chapter 2

Unit Testing

In general, due to non-convergence poor fitting with the analytical solutions that we were unable to resolve, unit testing was not completed. However, many of the commented assertion statements could be uncommented if the analytical solutions and the numerical solutions were in the same ballpark. If run as is, all tests would fail.

Many more tests were planned, including tests of various poisson ratio, young's modulus, element type etc for each of the 8 loading conditions studied in this paper. The primary framework exists, however, is ultimately unsuccessful at this point.

```
import os
import numpy as np
import subprocess
import sys
import pdb
sys.path.insert(0, '../')
from pyfem2 import *
from Definitions import *
from Definitions2 import *

#This code utilizes the testing framework within python to run verification tests on the FEM solver that we have developed.

def test_1():
    # TEST CASE 1
    # Geometry: Flat circular plate with no holes
    # Supports: Simply supported at radius r
    # Loads:    Uniform pressure load across entire plate
    # ELEMENT TYPE: AxiSymmetricQuad4
    #
    # Objective of test:
    # Verify that element in development produces appropriate maximum
    # deflection at the center of the plate.
    # See schematic in documentation for more information.

    #### Problem Setup ####
    problem = dict({'E':1e6,
                    'v':0.3,
                    'P': 10,
                    'OD':23,
                    'h' : .4,
                    'eletyp':AxiSymmetricQuad4,
                    'formula':1})

    ####-----FEM-----####
    V=Plate_Pressure_Pinned(**problem)
    zFEM=get_max_disp(V)
    ####-----Exact-----####
    zANA=A_Plate_Pressure_Pinned(**problem)

```

```
40      print(zFEM)
41      print(zANA)
42      err=(zFEM-zANA)/zANA*100.
43      print(err)
44      #Compare the solutions
45      #Assert a tolerable error to pass/fail test
46      #assert np.allclose(zFEM,zANA, atol=1e-5)
47
48  def test_2():
49      # TEST CASE 2
50      # Geometry: Flat circular plate with no holes
51      # Supports: Cantilever or clamped edges at radius r
52      # Loads:  Uniform pressure load across entire plate
53      #
54      # Objective of test:
55      # Verify that element in development produces appropriate maximum deflection at the
        center of the plate.
56      # See schematic in documentation (XXXX) for more information.
57
58      #### Problem Setup ####
59      problem = dict({'E':1e6,
60                      'v':0.3,
61                      'P': 10,
62                      'OD':23,
63                      'h' : .4,
64                      'eletyp':AxiSymmetricQuad4,
65                      'formula':1})
66
67      ####-----FEM-----####
68      V=Plate_Pressure_Clamped(**problem)
69      zFEM=get_max_disp(V)
70      ####-----Exact-----####
71      zANA=-A_Plate_Pressure_Clamped(**problem)
72
73      print(zFEM)
74      print(zANA)
75
76      err=(zFEM-zANA)/zANA*100.
77      print(err)
78      #Compare the solutions
79      #Assert a tolerable error to pass/fail test
80      #assert np.allclose(zFEM,zmax, atol=1e-10)
81
82  def test_3():
83      # TEST CASE 3: Plate Point Pinned
84      # Geometry: Flat circular plate with no holes
85      # Supports: Simply supported at Ds
86      # Loads:  Force per circumference applied at Dl
87      #
88      # Objective of test:
89      # Verify that element in development produces appropriate maximum deflection at the
        center of the plate.
90      # See schematic in documentation (XXXX) for more information.
91
92      #### Problem Setup ####
93      problem = dict({'E':1e6,
94                      'v':0.3,
95                      'P': 100,
96                      'OD':23,
97                      'h' : .4,
98                      'eletyp':AxiSymmetricQuad4,
99                      'formula':1})
100
101     ####-----FEM-----####
102     V = Plate_Point_Pinned(**problem)
103     zFEM = get_max_disp(V)
104
105     ####-----Exact-----####
```

```
106     zANA = -A_Plate_Point_Pinned(**problem)
107
108     print(zFEM)
109     print(zANA)
110     err=(zFEM-zANA)/zANA*100.
111     print(err)
112     #Compare the solutions
113     #Assert a tolerable error to pass/fail test
114     #assert np.allclose(zFEM,zmax,atol=1e-10)
115
116 def test_4():
117     # TEST CASE 4 **********
118     # Geometry: Flat circular plate with no holes
119     # Supports: Cantilever or clamped edges at radius r
120     # Loads:  Point load at center of the plate
121     #
122     # Objective of test:
123     # Verify that element in development produces appropriate maximum deflection at the
        center of the plate.
124     # See schematic in documentation (XXXX) for more information.
125
126     #### Problem Setup ####
127     problem = dict({'E':1e6,
128                     'v':0.3,
129                     'P': 100,
130                     'OD':23,
131                     'h' : .4,
132                     'eletyp':AxiSymmetricQuad4,
133                     'formula':1})
134
135     ####-----FEM-----####
136     V = Plate_Point_Clamped(**problem)
137     zFEM = get_max_disp(V)
138
139     ####-----Exact-----####
140     zANA = A_Plate_Point_Clamped(**problem)
141
142     ####-----Error-----####
143     err=(zFEM-zANA)/zANA*100.
144     #assert np.allclose(zFEM,zANA,atol=2)
145
146 def test_5():
147     # TEST CASE 4: WITH HOLE
148     # Geometry: Flat circular plate with no holes
149     # Supports: Cantilever or clamped edges at radius r
150     # Loads:  Point load at center of the plate
151     #
152     # Objective of test:
153     # Verify that element in development produces appropriate maximum deflection at the
        center of the plate.
154     # See schematic in documentation (XXXX) for more information.
155
156     #### Problem Setup ####
157     problem = dict({'E':1e6,
158                     'v':0.3,
159                     'P': 100,
160                     'OD':23,
161                     'h' : .4,
162                     'eletyp':AxiSymmetricQuad4,
163                     'formula':1})
164
165     ####-----FEM-----####
166     V = Washer_Point_Pinned(**problem)
167     zFEM = get_max_disp(V)
168
169     ####-----Exact-----####
170     zANA = A_Washer_Point_Pinned(**problem)
171
```

```
172     ####-----Error-----####
173     err=(zFEM-zANA)/zANA*100.
174     #assert np.allclose(zFEM,zANA,atol=2)
```