

Azure Functions parameters

1. HTTP Trigger (Most Common)

a) Route Parameters

You can pass parameters directly in the URL.

```
[FunctionName("GetProduct")]
```

```
public IActionResult Run(  
    [HttpTrigger(AuthorizationLevel.Function, "get", Route = "products/{id}")] HttpRequest req,  
    int id)  
{  
    return new OkObjectResult($"Product Id: {id}");  
}
```

Call URL

GET https://<functionapp>.azurewebsites.net/api/products/10

b) Query String Parameters

```
[FunctionName("SearchProduct")]
```

```
public IActionResult Run(  
    [HttpTrigger(AuthorizationLevel.Function, "get")] HttpRequest req)  
{  
    string name = req.Query["name"];  
    return new OkObjectResult($"Product Name: {name}");  
}
```

Call URL

GET /api/SearchProduct?name=Laptop

c) Request Body (JSON Payload)

```
public class ProductDto
```

```
{
```

```
    public int Id { get; set; }
```

```
    public string Name { get; set; }
```

```
}
```

```
[FunctionName("CreateProduct")]
```

```
public async Task<ActionResult> Run(
```

```
    [HttpTrigger(AuthorizationLevel.Function, "post")] HttpRequest req)
```

```
{
```

```
    var body = await new StreamReader(req.Body).ReadToEndAsync();
```

```
    var product = JsonSerializer.Deserialize<ProductDto>(body);
```

```
    return new OkObjectResult(product);
```

```
}
```

Call Payload

```
{
```

```
    "id": 1,
```

```
    "name": "Keyboard"
```

```
}
```

2. Queue Trigger Parameters

Parameters are bound from the **queue message**.

```
[FunctionName("QueueProcessor")]
```

```
public void Run(
```

```
[QueueTrigger("orders-queue")] string orderMessage)
{
    Console.WriteLine(orderMessage);
}
```

If the queue message is JSON, deserialize it.

3. Timer Trigger Parameters

Timer triggers do not accept custom parameters, but you get **timer metadata**.

```
[FunctionName("TimerJob")]
public void Run([TimerTrigger("0 */5 * * * *")] TimerInfo timer)
{
    Console.WriteLine($"Next run: {timer.ScheduleStatus.Next}");
}
```

4. Blob Trigger Parameters

Blob metadata is passed automatically.

```
[FunctionName("BlobProcessor")]
public void Run(
    [BlobTrigger("uploads/{name}")] Stream blob,
    string name)
{
    Console.WriteLine($"Blob name: {name}");
}
```

5. Passing Secure Parameters (Keys / Secrets)

For **configuration or secrets**, do not pass them in method calls.

Use:

- **Application Settings**
- **Azure Key Vault**

```
string conn = Environment.GetEnvironmentVariable("SqlConnection");
```

Key Concept to Remember

Azure Functions **do not accept parameters like normal method calls**.
Parameters are **injected via triggers and bindings**.

Quick Summary

Trigger Type How Parameters Are Passed

HTTP	Route, Query String, Body
Queue	Queue message
Blob	Blob name, metadata
Timer	TimerInfo only
Service Bus	Message payload
