

Shenzhen Damiao Technology Co., Ltd.

Motor Module Selection Guide

| Type                                                                                                           | Motor Model              | Rated Torque (Nm) | Peak Torque (Nm) | No-load Speed (rpm)           | Rated Speed (rpm) | Gear Ratio | Dimensions Diameter*Height (mm)         | Weight (g) | Supply Voltage (V) | Recommended operating Voltage Range (V) | Rated Phase Current (A) | Peak Phase Current (A) | Rated Power (W)                        | Pole Pairs | Slots | Communication Interface | Encoder Type                              | Drive Configuration | Phase-to-Phase Resistance (Ω) | Phase-to-Phase Inductance (uH) | Flux Linkage (Wb) | Rotor Inertia (Kg·m²×2) | Torque Ratio | Torque Constant (Nm/A) | Maximum Drive Current (A) | Default θMAX (rad) | Default θMAX (rad/s) | Default θMAX (Nm) | Speed Constant(Kv) (rpm/V) |
|----------------------------------------------------------------------------------------------------------------|--------------------------|-------------------|------------------|-------------------------------|-------------------|------------|-----------------------------------------|------------|--------------------|-----------------------------------------|-------------------------|------------------------|----------------------------------------|------------|-------|-------------------------|-------------------------------------------|---------------------|-------------------------------|--------------------------------|-------------------|-------------------------|--------------|------------------------|---------------------------|--------------------|----------------------|-------------------|----------------------------|
| Joint Motor<br>DM -<br>[L = Stator Diameter + Gear Ratio] -<br>[Encoder] (E, ZE) + Communication Interface     | DM-J3507-2EC             | 0.8               | 3                | 460                           | 150               | 7          | 46*37.9                                 | ≈150       | 24                 | 15-30                                   | 3                       | 8.3                    | 12.6                                   | 14         | 24    | CAN, CANFD              | Magnetic Encoder Dual Encoder             | Integrated          | 0.8                           | 235                            | 0.0037            | 8.70E-06                | 1            | 0.5439                 | 10.261194                 | 12.566             | 50                   | 5                 | 106.4341497                |
|                                                                                                                | DM-J3507-2EC(48V)        | 0.8               | 3                | 910                           | 150               | 7          | 46*37.9                                 | ≈150       | 48                 | 15-52                                   | 3                       | 8.3                    | 12.6                                   | 14         | 24    | CAN, CANFD              | Magnetic Encoder Dual Encoder             | Integrated          | 0.8                           | 235                            | 0.0037            | 8.70E-06                | 1            | 0.5439                 | 10.261194                 | 12.566             | 50                   | 5                 | 106.4341497                |
|                                                                                                                | DM-J4310-2EC V1.1        | 3                 | 7                | 200                           | 120               | 10         | 57*46                                   | ≈300       | 24                 | 15-32                                   | 2.5                     | 7.5                    | 37.7                                   | 14         | 24    | CAN, CANFD              | Magnetic Encoder Dual Encoder             | Integrated          | 0.65                          | 340                            | 0.0045            | 1.80E-05                | 1            | 0.945                  | 10.261194                 | 12.5               | 30                   | 10                | 87.51252308                |
|                                                                                                                | DM-J4310-2EC V1.1 (48V)  | 3                 | 7                | 400                           | 120               | 10         | 57*46                                   | ≈300       | 48                 | 15-52                                   | 2.5                     | 7.5                    | 37.7                                   | 14         | 24    | CAN, CANFD              | Magnetic Encoder Dual Encoder             | Integrated          | 0.65                          | 340                            | 0.0045            | 1.80E-05                | 1            | 0.945                  | 10.261194                 | 12.5               | 30                   | 10                | 87.51252308                |
|                                                                                                                | DM-J4310-2EC V1.2        | 3.5               | 12.5             | 200                           | 120               | 10         | 57*46                                   | ≈325       | 24                 | 15-32                                   | 4.9                     | 20                     | 44.0                                   | 14         | 24    | CAN, CANFD              | Magnetic Encoder Dual Encoder             | Integrated          | 0.58                          | 320                            | 0.0044            | 2.00E-05                | 1            | 0.924                  | 20.522388                 | 12.5               | 30                   | 10                | 89.50144406                |
|                                                                                                                | DM-J4310-2EC V1.2 (48V)  | 3.5               | 12.5             | 450                           | 120               | 10         | 57*46                                   | ≈325       | 48                 | 15-52                                   | 4.8                     | 20                     | 44.0                                   | 14         | 24    | CAN, CANFD              | Magnetic Encoder Dual Encoder             | Integrated          | 0.58                          | 320                            | 0.0044            | 2.00E-05                | 1            | 0.924                  | 20.522388                 | 12.5               | 30                   | 10                | 89.50144406                |
|                                                                                                                | DM-J4310P-2EC            | 3.5               | 12.5             | 200                           | 120               | 10         | 57*49.05                                | ≈325       | 24                 | 15-32                                   | 4.9                     | 20                     | 44.0                                   | 14         | 24    | CAN, CANFD              | Magnetic Encoder Dual Encoder             | Integrated          | 0.58                          | 320                            | 0.0042            | 1.90E-05                | 1            | 0.882                  | 20.522388                 | 12.5               | 30                   | 10                | 93.76341759                |
|                                                                                                                | DM-J4310P-2EC (48V)      | 3.5               | 12.5             | 450                           | 120               | 10         | 57*49.05                                | ≈325       | 48                 | 15-52                                   | 4.8                     | 20                     | 44.0                                   | 14         | 24    | CAN, CANFD              | Magnetic Encoder Dual Encoder             | Integrated          | 0.58                          | 320                            | 0.0042            | 1.90E-05                | 1            | 0.882                  | 20.522388                 | 12.5               | 30                   | 10                | 93.76341759                |
|                                                                                                                | DM-J4340-2EC             | 9                 | 27               | 52.5                          | 36                | 40         | 57*53.3                                 | ≈362       | 24                 | 15-32                                   | 3                       | 8                      | 33.9                                   | 14         | 24    | CAN, CANFD              | Magnetic Encoder Dual Encoder             | Integrated          | 0.88                          | 360                            | 0.00485           | 2.00E-05                | 1            | 4.074                  | 10.261194                 | 12.5               | 8                    | 28                | 81.19718637                |
|                                                                                                                | DM-J4340-2EC (48V)       | 9                 | 27               | 100                           | 36                | 40         | 57*53.3                                 | ≈362       | 48                 | 15-52                                   | 2.5                     | 9                      | 33.9                                   | 14         | 24    | CAN, CANFD              | Magnetic Encoder Dual Encoder             | Integrated          | 0.88                          | 360                            | 0.00485           | 2.00E-05                | 1            | 4.074                  | 10.261194                 | 12.5               | 8                    | 28                | 81.19718637                |
|                                                                                                                | DM-J4340-2EC V1.1        | 12                | 40               | 56                            | 36                | 40         | 57*53.3                                 | ≈362       | 24                 | 15-32                                   | 4.11                    | 19.85                  | 45.2                                   | 14         | 24    | CAN, CANFD              | Magnetic Encoder Dual Encoder             | Integrated          | 0.72                          | 290                            | 0.0043            | 1.97E-05                | 1            | 3.612                  | 20.522388                 | 12.5               | 10                   | 28                | 91.58287299                |
|                                                                                                                | DM-J4340-2EC V1.1 (48V)  | 12                | 40               | 112                           | 36                | 40         | 57*53.3                                 | ≈362       | 48                 | 15-52                                   | 4.11                    | 19.85                  | 45.2                                   | 14         | 24    | CAN, CANFD              | Magnetic Encoder Dual Encoder             | Integrated          | 0.72                          | 290                            | 0.0043            | 1.97E-05                | 1            | 3.612                  | 20.522388                 | 12.5               | 10                   | 28                | 91.58287299                |
|                                                                                                                | DM-J4340P-2EC            | 9                 | 27               | 52.5                          | 36                | 40         | 57*56.5                                 | ≈375       | 24                 | 15-32                                   | 3                       | 8                      | 33.9                                   | 14         | 24    | CAN, CANFD              | Magnetic Encoder Dual Encoder             | Integrated          | 0.88                          | 360                            | 0.00485           | 2.00E-05                | 1            | 4.074                  | 10.261194                 | 12.5               | 8                    | 28                | 81.19718637                |
|                                                                                                                | DM-J4340P-2EC (48V)      | 9                 | 27               | 100                           | 36                | 40         | 57*56.5                                 | ≈375       | 48                 | 15-52                                   | 2.5                     | 9                      | 33.9                                   | 14         | 24    | CAN, CANFD              | Magnetic Encoder Dual Encoder             | Integrated          | 0.88                          | 360                            | 0.00485           | 2.00E-05                | 1            | 4.074                  | 10.261194                 | 12.5               | 8                    | 28                | 81.19718637                |
|                                                                                                                | DM-J4340P-2EC V1.1       | 12                | 40               | 56                            | 36                | 40         | 57*56.5                                 | ≈362       | 24                 | 15-32                                   | 4.11                    | 19.85                  | 45.2                                   | 14         | 24    | CAN, CANFD              | Magnetic Encoder Dual Encoder             | Integrated          | 0.72                          | 290                            | 0.0043            | 1.97E-05                | 1            | 3.612                  | 20.522388                 | 12.5               | 10                   | 28                | 91.58287299                |
|                                                                                                                | DM-J4340P-2EC V1.1 (48V) | 12                | 40               | 112                           | 36                | 40         | 57*56.5                                 | ≈362       | 48                 | 15-52                                   | 4.11                    | 19.85                  | 45.2                                   | 14         | 24    | CAN, CANFD              | Magnetic Encoder Dual Encoder             | Integrated          | 0.72                          | 290                            | 0.0043            | 1.97E-05                | 1            | 3.612                  | 20.522388                 | 12.5               | 10                   | 28                | 91.58287299                |
|                                                                                                                | DM-J6006-2EC             | 4                 | 11               | 226@24V<br>408@48V            | 150               | 6          | 76*36.5                                 | ≈335       | 24-48              | 15-52                                   | 5.96                    | 17.6                   | 62.8                                   | 14         | 24    | CAN, CANFD              | Magnetic Encoder Dual Encoder             | Integrated          | 0.435                         | 270                            | 0.0058            | 5.80E-05                | 1            | 0.7308                 | 20.52238806               | 12.5               | 45                   | 20                | 67.89764722                |
|                                                                                                                | DM-J6248P-2EC            | 30                | 97               | 600@24V<br>115@48V            | 40                | 48         | 76*62.5                                 | ≈628       | 24-48              | 15-65                                   | 11.3                    | 38.7                   | 125.7                                  | 14         | 24    | CAN, CANFD              | Magnetic Encoder Dual Encoder             | Integrated          | 0.17                          | 85                             | 0.0033            | 5.40E-05                | 1            | 3.3264                 | 41.044777                 | 12.5               | 20                   | 150               | 119.3352587                |
|                                                                                                                | DM-J8006-2EC V1.1        | 8                 | 20               | 194.2@24V<br>392.8@48V        | 120               | 6          | 96*40                                   | ≈559       | 24-48              | 15-52                                   | 9                       | 21                     | 100.5                                  | 21         | 36    | CAN, CANFD              | Magnetic Encoder Dual Encoder             | Integrated          | 0.4                           | 215                            | 0.0054            | 1.15E-04                | 1            | 1.0206                 | 41.04477612               | 12.5               | 45                   | 40                | 48.61806838                |
|                                                                                                                | DM-J8009-2EC             | 20                | 40               | 168@24V                       | 100@24V           | 9          | 98*61.7                                 | ≈896       | 24-48              | 15-52                                   | 18.6                    | 40                     | 209.4                                  | 21         | 36    | CAN, CANFD              | Magnetic Encoder Dual Encoder             | Integrated          | 0.145                         | 80                             | 0.00445           | 1.95E-04                | 1            | 1.261575               | 41.04477612               | 12.5               | 45                   | 54                | 58.99720657                |
|                                                                                                                |                          | 20                | 40               | 335@48V                       | 200@48V           | 9          | 98*61.7                                 | ≈896       | 24-48              | 15-52                                   | 18.6                    | 40                     | 418.9                                  | 21         | 36    | CAN, CANFD              | Magnetic Encoder Dual Encoder             | Integrated          | 0.145                         | 80                             | 0.00445           | 1.95E-04                | 1            | 1.261575               | 41.04477612               | 12.5               | 45                   | 54                | 58.99720657                |
|                                                                                                                | DM-J8009P-2EC            | 20                | 40               | 168@24V                       | 100@24V           | 9          | 98*61.7                                 | ≈963       | 24-48              | 15-52                                   | 18.6                    | 40                     | 209.4                                  | 21         | 36    | CAN, CANFD              | Magnetic Encoder Dual Encoder             | Integrated          | 0.145                         | 80                             | 0.00445           | 1.95E-04                | 1            | 1.261575               | 41.04477612               | 12.5               | 45                   | 54                | 58.99720657                |
|                                                                                                                |                          | 20                | 40               | 335@48V                       | 200@48V           | 9          | 98*61.7                                 | ≈963       | 24-48              | 15-52                                   | 18.6                    | 40                     | 418.9                                  | 21         | 36    | CAN, CANFD              | Magnetic Encoder Dual Encoder             | Integrated          | 0.145                         | 80                             | 0.00445           | 1.95E-04                | 1            | 1.261575               | 41.04477612               | 12.5               | 45                   | 54                | 58.99720657                |
|                                                                                                                | DM-J8009P-2EC V1.1       | 20                | 40               | 168@24V                       | 100@24V           | 9          | 98*61.7                                 | ≈950       | 24-48              | 15-52                                   | 18.6                    | 40                     | 209.4                                  | 21         | 36    | CAN, CANFD              | Magnetic Encoder Dual Encoder             | Integrated          | 0.145                         | 80                             | 0.00445           | 1.95E-04                | 1            | 1.261575               | 41.04477612               | 12.5               | 45                   | 54                | 58.99720657                |
|                                                                                                                |                          | 20                | 40               | 335@48V                       | 200@48V           | 9          | 98*61.7                                 | ≈950       | 24-48              | 15-52                                   | 18.6                    | 40                     | 418.9                                  | 21         | 36    | CAN, CANFD              | Magnetic Encoder Dual Encoder             | Integrated          | 0.145                         | 80                             | 0.00445           | 1.95E-04                | 1            | 1.261575               | 41.04477612               | 12.5               | 45                   | 54                | 58.99720657                |
|                                                                                                                | DM-J10010-2EC            | 40                | 150              | 75@24V                        | 50@24V            | 10         | 112*62<br>(Max. Overall Dimension: 120) | ≈1485      | 24-48              | 15-52                                   | 18.4                    | 80.2                   | 209.4                                  | 21         | 36    | CAN, CANFD              | Magnetic Encoder Dual Encoder             | Integrated          | 0.125                         | 100                            | 0.00825           | 5.50E-04                | 1            | 2.59875                | 100                       | 12.5               | 20                   | 200               | 31.82273567                |
|                                                                                                                |                          | 40                | 150              | 150@48V                       | 100@48V           | 10         | 112*62<br>(Max. Overall Dimension: 120) | ≈1485      | 24-48              | 15-52                                   | 18.4                    | 80.2                   | 418.9                                  | 21         | 36    | CAN, CANFD              | Magnetic Encoder Dual Encoder             | Integrated          | 0.125                         | 100                            | 0.00825           | 5.50E-04                | 1            | 2.59875                | 100                       | 12.5               | 20                   | 200               | 31.82273567                |
|                                                                                                                | DM-J10010L-2EC           | 40                | 120              | 100@24V                       | 70@24V            | 10         | 120*53<br>Height (Excluding Dowel Pin)  | ≈1375      | 24-48              | 15-52                                   | 23.5                    | 95                     | 293.2                                  | 21         | 36    | CAN, CANFD              | Magnetic Encoder Dual Encoder             | Integrated          | 0.11                          | 85                             | 0.00635           | 5.56E-04                | 1            | 2.00025                | 99.7                      | 12.5               | 25                   | 200               | 41.34449909                |
|                                                                                                                |                          | 40                | 120              | 200@48V                       | 100@48V           | 10         | 120*53<br>Height (Excluding Dowel Pin)  | ≈1375      | 24-48              | 15-52                                   | 23.5                    | 95                     | 418.9                                  | 21         | 36    | CAN, CANFD              | Magnetic Encoder Dual Encoder             | Integrated          | 0.11                          | 85                             | 0.00635           | 5.56E-04                | 1            | 2.00025                | 99.7                      | 12.5               | 25                   | 200               | 41.34449909                |
|                                                                                                                | DM-J10422P-2EC           | 100               | 400              | 120                           | 100               | 22         | 110*89.9                                | ≈2700      | 48                 | 20-65                                   | 44.5                    | 165                    | 1047.2                                 | 16         | 36    | CAN, CANFD              | Inductive Encoder Dual Encoder            | Integrated          | 0.081                         | 38                             | 0.00599           | 5.64E-04                | 1            | 3.16272                | 165                       | 12.566             | 20                   | 500               | 57.52596889                |
|                                                                                                                | DM-J8520P-2EC            | 50                | 176              | 124                           | 120               | 20         | 90*70                                   | ≈1392      | 48                 | 20-65                                   | 13.86                   | 41.6                   | 628.3                                  | 16         | 32    | CAN, CANFD              | Inductive Encoder Dual Encoder            | Integrated          | 0.1                           | 75                             | 0.00651           | 1.49E-04                | 1            | 3.38976                | 82                        | 12.566             | 20                   | 300               | 53.67298437                |
|                                                                                                                | DM-J6216L-2EC            | 10                | 45               | 260                           | 200               | 16         | 67*62.5                                 | ≈740       | 24-48              | 15-52                                   | 7.48@24V<br>7.74@48V    | 39.5@24V<br>27@48V     | 209.4                                  | 10         | 24    | CAN, CANFD              | Inductive + Magnetic Encoder Dual Encoder | Integrated          | 0.16                          | 184                            | 0.00510           | 4.91E-05                | 1            | 1.224                  | 82.5                      | 12.566             | 40                   | 70                | 108.103705                 |
|                                                                                                                | DM-J6216P-2EC            | 10                | 48               | 260                           | 200               | 16         | 67*62.5                                 | ≈740       | 24-48              | 15-52                                   | 7.45@24V<br>7.6@48V     | 36@24V<br>70@48V       | 209.4                                  | 10         | 24    | CAN, CANFD              | Inductive + Magnetic Encoder Dual Encoder | Integrated          | 0.16                          | 184                            | 0.00510           | 4.91E-05                | 1            | 1.224                  | 82.5                      | 12.566             | 40                   | 70                | 108.103705                 |
| Separable Motor<br>DM -<br>[S = Stator Diameter + Gear Ratio] -<br>[Encoder] (E, ZE) + Communication Interface | DM-S3519-1EC             | 3.5               | 7.8              | 435                           | 395               | 19.2032    | 42*91.5                                 | ≈396       | 24                 | 15-32                                   | 9.2                     | 20.5                   | 144.8                                  | 7          | 12    | CAN, CANFD              | Hall Encoder Incremental Encoder          | separate            | 0.2                           | 55                             | 0.00225           | 1.80E-05                | 1            | 0.4536756              | 20.52238806               | 12.5               | 200                  | 10                | 350.0500923                |
|                                                                                                                | DM-S3235-1EC             | 1.35              | 5                | 560                           | 380               | 25         | 28*77.6                                 | ≈172       | 24                 | 15-60                                   | 5                       | 13                     | 53.7                                   | 7          | 12    | CAN, CANFD              | Hall Encoder Incremental Encoder          | separate            | 0.292                         | 75                             | 0.0014            | 3.80E-05                | 1            | 0.3675                 | 20.523388                 | 12.5               | 200                  | 10                | 562.5805055                |
| Hub Motor<br>DM - [H = Stator Diameter + Height]                                                               | DM-H6215                 | 1                 | 2                | 320                           | 120               | 1          | 68*42.5                                 | ≈360       | 24                 | 15-32                                   | 2.5                     | 4.3                    | 12.6                                   | 14         | 24    | CAN, CANFD              | Hall Encoder Incremental Encoder          | Integrated          | 2.5                           | 2000                           | 0.022             | 1.80E-04                | 1            | 0.462                  | 10.261194                 | 12.5               | 30                   | 10                | 17.90028881                |
|                                                                                                                | DM-H3510                 | 0.1               | 0.454            | 1670                          | 500               | 1          | 42*31.5                                 | ≈116       | 24                 | 15-32                                   | 1.1                     | 3.94                   | 5.2                                    | 14         | 24    | CAN, CANFD              | Magnetic Encoder Absolute                 | Integrated          | 3.25                          | 0.685                          | 0.011             | 1.74E-05                | 1            | 0.231                  | 10.261194                 | 12.5               | 280                  | 1                 | 35.80057762                |
|                                                                                                                | DM-H65                   | 6                 | 21.5             | 260@24V<br>395@36V<br>480@48V | 120               | 1          | 171*66.3                                | ≈3150      | 24-48              | 20-65                                   | 9.4                     | 33.6                   | 250<br>(6 Nm, 400 rpm @ 48V (S2 Duty)) | 15         | 27    | CAN, CANFD              | Inductive Encoder Absolute                | external            | 0.42                          | 750                            | 0.024964          | 1.68E-03                | 1            | 0.56169                | 41.044777                 | 12.566             | 100                  | 40                | 14.72330544                |

| Type                                                                                                      | Motor Model     | Rated Torque (Nm) | Peak Torque (Nm) | No-load Speed (rpm)            | Rated Speed (rpm) | Gear Ratio | Dimensions Diameter*Height (mm) | Weight (g) | Supply Voltage (V) | Recommended operating Voltage Range (V) | Rated Phase Current (A) | Peak Phase Current (A) | Rated Power (W) | Pole Pairs | Slots | Communication Interface | Encoder Type                   | Drive Configuration | Phase-to-Phase Resistance (Ω) | Phase-to-Phase Inductance (μH) | Flux Linkage (Wb) | Rotor Inertia (Kg*m²) | Torque Ratio | Torque Constant (Nm/A) | Maximum Drive Current (A) | Default PMAX (rad) | Default VMAX (rad/s) | Default TMAX (Nm) | Speed Constant(KV) (rpm/V) |
|-----------------------------------------------------------------------------------------------------------|-----------------|-------------------|------------------|--------------------------------|-------------------|------------|---------------------------------|------------|--------------------|-----------------------------------------|-------------------------|------------------------|-----------------|------------|-------|-------------------------|--------------------------------|---------------------|-------------------------------|--------------------------------|-------------------|-----------------------|--------------|------------------------|---------------------------|--------------------|----------------------|-------------------|----------------------------|
| Hub Motor<br>DM - [H + Stator Diameter + Height]                                                          | DM-H55          | 3.5               | 9                | 587@24V<br>863@36V<br>1185@48V | 350               | 1          | 141*66.9                        | ≈2100      | 24-48              | 20-65                                   | 13.05                   | 33.55                  | 128.3           | 10         | 18    | CAN, CANFD              | Inductive Encoder Absolute     | external            | 0.281                         | 336                            | 0.018163          | 2.07E-03              | 1            | 0.272445               | 41.04477                  | 12.566             | 100                  | 40                | 30.35450616                |
|                                                                                                           | DM-G6220        | 1.3               | 2.7              | 300                            | 110               | 1          | 68*41.5                         | ≈493.5     | 24                 | 15-32                                   | 2.3                     | 4.6                    | 15.0            | 14         | 24    | CAN, CANFD              | Magnetic Encoder Absolute      | Integrated          | 3                             | 3000                           | 0.028             | 1.25E-04              | 1            | 0.588                  | 10.261194                 | 12.5               | 45                   | 10                | 14.06451264                |
| Hollow Gimbal<br>DM - (G + Stator Diameter + Height)                                                      | DM-G6220 (48V)  | 1.3               | 4.9              | 650                            | 110               | 1          | 68*41.5                         | ≈493.5     | 48                 | 15-52                                   | 0.8                     | 7.82                   | 15.0            | 14         | 24    | CAN, CANFD              | Magnetic Encoder Absolute      | Integrated          | 2.84                          | 2376                           | 0.028             | 1.25E-04              | 1            | 0.588                  | 10.261194                 | 12.5               | 45                   | 10                | 14.06451264                |
|                                                                                                           | DM-G8518        | 1.9               | 8.78             | 1290@24V                       | 1000@24V          | 1          | 96*52.5                         | ≈831       | 24-48              | 20-54                                   | 9.55A                   | 36.1                   | 199.0           | 16         | 36    | CAN, CANFD              | Inductive Encoder Absolute     | Integrated          | 0.225                         | 105                            | 0.0065            | 1.86E-04              | 1            | 0.156                  | 82.089554                 | 12.566             | 300                  | 15                | 53.01239379                |
|                                                                                                           |                 | 1.9               | 8.78             | 2590@48V                       | 2000@48V          | 1          | 96*52.5                         | ≈831       | 24-48              | 20-54                                   | 9.55A                   | 36.1                   | 397.9           | 16         | 36    | CAN, CANFD              | Inductive Encoder Absolute     | Integrated          | 0.225                         | 105                            | 0.0065            | 1.86E-04              | 1            | 0.156                  | 82.089554                 | 12.566             | 300                  | 15                | 53.01239379                |
| Harmonic Drive joint motor<br>DM - [JH + Size] - [Gear Ratio] - [Encoder1E/2E] + Communication Interface] | DM-JH11-51-2EC  | 3.2               | 7.8              | 60                             | 40                | 51         | 52*60                           | ≈345       | 24-48              | 20-54                                   | 2.23                    | 4.26                   | 13.4            | 7          | 12    | CAN, CANFD              | Inductive Encoder Dual Encoder | Integrated          | 1.1                           | 538                            | 0.0048            | 6.30E-06              | 0.6          | 1.54224                | 10.261194                 | 12.5               | 10                   | 12                | 164.0859808                |
|                                                                                                           | DM-JH11-101-2EC | 4.8               | 10.5             | 30                             | 20                | 101        | 52*60                           | ≈345       | 24-48              | 20-54                                   | 2.3                     | 3.6                    | 10.1            | 7          | 12    | CAN, CANFD              | Inductive Encoder Dual Encoder | Integrated          | 1.1                           | 538                            | 0.0048            | 6.30E-06              | 0.65         | 3.30876                | 10.261194                 | 12.5               | 10                   | 30                | 164.0859808                |
|                                                                                                           | DM-JH14-51-2EC  | 5.4               | 18               | 60                             | 40                | 51         | 70*70                           | ≈775       | 24-48              | 20-54                                   | 4.89                    | 13.7                   | 22.6            | 10         | 18    | CAN, CANFD              | Inductive Encoder Dual Encoder | Integrated          | 0.243                         | 170                            | 0.0053518         | 6.00E-05              | 0.5          | 2.04707498             | 41.044777                 | 12.566             | 10                   | 50                | 103.0168924                |
|                                                                                                           | DM-JH14-101-2EC | 7.8               | 28               | 30                             | 20                | 101        | 70*70                           | ≈775       | 24-48              | 20-54                                   | 4.12                    | 10.97                  | 16.3            | 10         | 18    | CAN, CANFD              | Inductive Encoder Dual Encoder | Integrated          | 0.243                         | 170                            | 0.0053518         | 6.00E-05              | 0.45         | 3.6486101              | 41.044777                 | 12.566             | 10                   | 50                | 103.0168924                |
|                                                                                                           | DM-JH17-51-2EC  | 16                | 24               | 60                             | 40                | 51         | 80*70                           | ≈985       | 24-48              | 20-54                                   | 4.62                    | 12.94                  | 67.0            | 10         | 18    | CAN, CANFD              | Inductive Encoder Dual Encoder | Integrated          | 0.161                         | 107                            | 0.00625           | 9.38E-05              | 0.5          | 4.78125                | 41.044777                 | 12.566             | 20                   | 80                | 88.21262327                |
|                                                                                                           | DM-JH17-101-2EC | 24                | 54               | 30                             | 20                | 101        | 80*70                           | ≈985       | 24-48              | 20-54                                   | 6.31                    | 16.85                  | 50.3            | 10         | 18    | CAN, CANFD              | Inductive Encoder Dual Encoder | Integrated          | 0.161                         | 107                            | 0.00625           | 9.38E-05              | 0.5          | 9.46875                | 41.044777                 | 12.566             | 20                   | 80                | 88.21262327                |
| Direct Drive Motor<br>DM - (D + Stator Diameter + Height) - [ Encoder1E/2E] + Communication Interface ]   | DM-D5730 -1EE   | 0.65              | 1.9              | 1500                           | 1100              | 1          | 57*95.2                         | ≈628       | 24-48              | 20-55                                   | 5.4                     | 16.2                   | 74.9            | 14         | 24    | CAN, CANFD EtherCAT     | Inductive Encoder Absolute     | Integrated          | 0.17                          | 85                             | 0.00617           | 6.00E-05              | 1            | 0.12957                | 20.522388                 | 12.5               | 420                  | 5                 | 63.82598928                |
|                                                                                                           | DM-D5730 -1EC   | 0.65              | 1.9              | 1500                           | 1100              | 1          | 57*95.2                         | ≈628       | 24-48              | 20-55                                   | 5.4                     | 16.2                   | 74.9            | 14         | 24    | CAN, CANFD              | Inductive Encoder Absolute     | Integrated          | 0.17                          | 85                             | 0.00617           | 6.00E-05              | 1            | 0.12957                | 20.522388                 | 12.5               | 420                  | 5                 | 63.82598928                |