

## Acceptable



Human Written: (A) The relationship between the deep neural network's performance and the data size we used. We fixed the activation function as RELU and the number of hidden layers as 3, with 200 nodes in each layer. (B) The performance comparison of the deep neural network using different activation functions.

Generated: The performance of the model with different data and activation function. A: The performance of the model with different ratio of the data. B: The performance of the model with different activation function.


## **Over Simplification**



Human Written: Our point cloud diffusion model architecture. Images are fed through a frozen, pretrained CLIP model, and the output grid is fed as tokens into the transformer. Both the timestep \$t\$ and noised input \$x\_t\$ are also fed in as tokens. The output tokens corresponding to \$x\_t\$ are used to predict \$\epsilon\$ and \$\Sigma\$.

**Generated:** Architecture of the proposed model.

## **Contextual Misinterpretation**




Human Written: Performance on the Decompensation task for various values of \$\alpha\$ in \$\NCLY\$.

Results are averaged over 5 runs and trained with the Decompensation labels. In blue, we show the contrastive accuracy. For \$\alpha > 0.95\$ it drops because pre-text task becomes too hard explaining SCL's low performances.

Generated: AUPRC and contrastive accuracy of the end-to-end model and the \$\alpha\$-weighted model on the test set of the 20 Newsgroups dataset. The contrastive accuracy is the average accuracy of the contrastive predictions. The error bars show the standard

deviation.

## Recognition Error



**Human Written:** The testing accuracy of implementing ResNet and ResNet-B with the IC layer on the CIFAR10/100 datasets with respect to the training epochs.

Generated: Comparison of the test error curves of ResNet-110, ResNet-164, and ResNet-164 on CIFAR10 and CIFAR100.