UniCoRN: Unified Commented Retrieval Network with LMMs

Maximilian Jaritz Matthieu Guillaumin Sabine Sternig Loris Bazzani Amazon.com

Abstract

Multimodal retrieval methods have limitations in handling complex, compositional queries that require reasoning about the visual content of both the query and the retrieved entities. On the other hand, Large Multimodal Models (LMMs) can answer with language to more complex visual questions, but without the inherent ability to retrieve relevant entities to support their answers. aim to address these limitations with UniCoRN, a Unified Commented Retrieval Network that combines the strengths of composed multimodal retrieval methods and generative language approaches, going beyond Retrieval-Augmented Generation (RAG). We introduce an entity adapter module to inject the retrieved multimodal entities back into the LMM, so it can attend to them while generating answers and comments. By keeping the base LMM frozen, UniCoRN preserves its original capabilities while being able to perform both retrieval and text generation tasks under a single integrated framework. To assess these new abilities, we introduce the Commented Retrieval task (CoR) and a corresponding dataset, with the goal of retrieving an image that accurately answers a given question and generate an additional textual response that provides further clarification and details about the visual information. We demonstrate the effectiveness of UniCoRN on several datasets showing improvements of +4.5% recall over the state of the art for composed multimodal retrieval and of +14.9% METEOR / +18.4% BEM over RAG for commenting in CoR.

1. Introduction

Multimodal retrieval, the task of retrieving relevant information across text, visual and other modalities, has gained significant attention in recent years [8, 14, 21, 25, 26, 28, 40, 47, 53, 68, 69, 82, 89, 92, 95, 96, 98] demonstrating strong performance on a variety of tasks in supervised, zero-shot, and out-of-domain applications. However, recent methods still struggle to capture complex, compositional requests that require specific reasoning about visual content. On the other hand, LMMs [1, 4, 18, 19, 23, 41, 56, 57, 62, 64, 75, 81, 87, 90, 99] can deal with complex visio-linguistic re-




Figure 1. <u>Commented retrieval</u>. Given an query image and question, UniCoRN can retrieve an image from a database and can produce a textual answer that offers further clarification and details.

quests with language output, without the inherent ability to retrieve and output relevant images to support the answer. This raises an intriguing question for which we seek to make advancements in our work: *How can we integrate the multimodal reasoning capabilities of LMMs with the retrieval capabilities of composed multimodal models?*

Let us consider a user asking "what is the larval state of this butterfly?" as in Fig. 1. The model must not only recognize the species of butterfly, but also understand the query and find an image depicting the corresponding caterpillar stage, which has little visual similarity with the query. While prior work [2, 6, 16, 29, 32, 33, 36, 37, 78] has explored composed retrieval techniques for such structured requests, these approaches have limitations in providing comprehensive responses. On the other hand, Visual Question Answering (VQA) methods [3, 5, 30, 34, 70–72, 86, 88], even when leveraging LMMs, are restricted to answering solely with language. An ideal model should both retrieve a relevant image and generate explanatory text that complements and further explains the visual information. Referring back to Fig. 1, the model returns an image of the butterfly's larval stage and a comment, e.g. "The larval stage of the Old World swallowtail is a caterpillar, which can be seen feeding on a wild carrot plant in the image.". We refer to this novel multimodal task as Commented Retrieval (CoR).

In this work, we propose UniCoRN, a novel Unified Commented Retrieval Network that leverages the complementary strengths of discriminative cross-modal matching and generative language models to perform CoR. First, we present a retrieval module that aligns the hidden state of LMMs with the retrieval space of CLIP models. This allows us to integrate the deep visio-linguistic reasoning of LMMs with powerful multimodal and cross-modal retrieval capabilities. The retrieval model is trained to be aware of the complex answers and comments, rather than simple image captions like in previous work [42, 55, 83]. Second, we introduce an entity adapter module to inject the retrieved entities back into the LMM, so they can condition the generated answers and comments. This technique enables interleaved, integrated multimodal output at inference time, which goes beyond post-processing of output tokens or prompt engineering of the LMM, e.g. with RAG [51]. By training these new modules for CoR, we strengthen the connection between the initial question and the retrieved entities, enabling the generation of more coherent and relevant textual responses. Notably, our contributions are additions to a frozen LMM, so, unlike [42, 55], we guarantee the preservation of all its original capabilities (such as captioning, VQA, grounding, and more) within our unified framework.

Existing multimodal tasks and datasets [17, 38, 45, 59, 85] have simplistic (1-3 words) answers that do not explain why and how the retrieved entity is relevant to the initial query, and thus are not well suited for training and evaluating models for CoR. In this work, we introduce two challenging human-curated CoR datasets based on the CIRR [58] and WikiWeb2M dataset [11], that blend aspects of composed retrieval and VQA. Given an input image and question, the goal is to retrieve from a large candidate pool the entity that answers the question, and produce an additional textual response that offers further clarification and details (Fig. 1). This task echoes research showing that humans learn better when they can jointly examine textual responses alongside the relevant visuals [61].

Our evaluations on diverse datasets for composed retrieval and commented retrieval show significant improvements of UniCoRN over state-of-the-art models. In particular, we show an average improvement for composed retrieval of +4.5% on Fashion-IQ, CIRR, OVEN, InfoSeek, and the proposed Wiki-CoR dataset in terms of recall when compared to UniIR [83]. Moreover, we show an improvement of +14.9% in terms of METEOR score over a RAG approach combining UniIR and InternVL2 on the CoR task.

2. Related Work

Instructable Retrieval. Multimodal representation for retrieval [8, 14, 25, 40, 47, 53, 68, 69, 82, 89, 92, 95, 96, 98] has been a prominent area of research demonstrating strong performance. To handle compositional requests that require reasoning about the visual content, recent work focused on composed retrieval [6, 7, 15, 29, 31, 44, 60, 73, 77, 79, 80, 84]. However, these methods focus on limited specific retrieval domains and can only follow predefined instruction

templates. To address this limitation, recent models have been made instructable [42, 44, 49, 55, 66, 83, 97] to capture richer multimodal relationships. MagicLens [97] is a simple instructable model trained on a curated large dataset including instructions, while UniIR [83] proposed training CLIP/BLIP variants conditioned on prompted instructions. While these approaches have demonstrated significant progress, they lack expressiveness in the multimodal output space due to the limitations of CLIP models. In contrast, methods based on LMMs [42, 55] that are fine-tuned for retrieval do not preserve the original capabilities of the LMMs. UniCoRN aims to overcome this issue and preserve capabilities by design by enabling a frozen LMM to retrieve relevant content and generate textual responses tailored to both the input question and the retrieved visual content.

Retrieval via Generation. LMMs [1, 4, 18, 19, 23, 41, 55– 57, 62, 64, 75, 81, 87, 90, 99] have demonstrated remarkable reasoning capabilities when processing language and visual elements (see survey in [91]). Recently, LMMs were combined with diffusion models to generate images along with textual answers [27, 46, 52, 74, 76, 87, 93]. Despite providing an interesting user experience, the generated images are by nature not grounded to real entities, which is critical for retrieval applications, such as online shopping, news, or Wikipedia. These models are based on memoryintensive diffusion models and trained with a reconstruction objective that is not in line with retrieval. In contrast, Uni-CoRN uses a retrieval approach that preserves the factuality of the images that are shown to the user, while commenting them in a generative way. It is lightweight, as it does not use diffusion models, and the LMMs are frozen, thus preserving their reasoning capabilities of other non-retrieval tasks.

Retrieval-Augmented Generation (RAG). The parametric way that language models are trained and store knowledge limits the ease to expand or revise their memory with more recent information. RAG [24, 35, 43, 48, 50] and Multimodal RAG [12, 13, 39, 66, 67, 88, 94] have been proposed as a non-parametric way to provide up-to-date knowledge to an LMM by adding relevant content to the prompt before processing by the LMM. Using this augmented prompt, the LMM can select, summarize and alter the entities to generate its output. UniCoRN differs from traditional RAG in that it processes user input via the LMM to build a better query and outputs the retrieved entity unaltered. Then, UniCoRN's entity adapter module is trained to feed optimized entity representations to the LMM, which guides the extraction of the information necessary to answer the request.

Commented Retrieval (CoR). CoR is an underexplored task that requires not only retrieving relevant images, as in composed retrieval, but also generating plausible textual answers that refer to the image and contain additional information. While preliminary work [42, 44, 66, 83] and datasets [17, 38, 63] focuse on some aspects of this task,

they have two key limitations: 1) The complexity of the textual answers is constrained, typically limited to a few words or basic captions. 2) The textual answers are aligned with the image, either providing redundant information (e.g., image captions) and failing to add useful complementary information. To fully cover the CoR task, we claim that the answers should be multimodal in nature, with the image and text working in tandem to provide a richer, more comprehensive response. The modalities should have a clear connection, yet offer complementary information that enhances the overall response. To alleviate the limitations of existing CoR datasets, we created two challenging human-curated ones that we hope will foster future research in this area.

3. UniCoRN

With UniCoRN, we propose to expand the capabilities of a frozen base LMMs with two novel interconnected modules: 1) Comment-aware retrieval, which is responsible for understanding the visio-linguistic representation of the query question and image, and projecting it to the target comment and image space for retrieval (Sec. 3.1); 2) Retrieval-aware generation, which learns to leverage the retrieved entity to generate an answer to the user question (Sec. 3.2).

3.1. Comment-aware Retrieval

Given a query text and image $q=(q^{\langle t\rangle},q^{\langle i\rangle})$, we aim to train a retrieval model R_{θ} , with parameters θ , that is capable of understanding q and retrieve a related target entity composed of text and image $d=(d^{\langle t\rangle},d^{\langle i\rangle})$, such that:

$$d = \underset{d' \in \mathcal{D}}{\operatorname{argmax}} \ R_{\theta}(q, d') \tag{1}$$

where \mathcal{D} is a database of multimodal entities (a.k.a documents). The best definition for the retriever R_{θ} depends on the target application. For cross-modal and multimodal retrieval, CLIP-like models [25, 26, 40, 68, 83] are the *defacto* choice based on their performance in diverse scenarios. However, they are limited in the visio-linguistic understanding capabilities, especially when moving to more complex applications like composed retrieval and commented retrieval. To address this limitation, we leverage the reasoning capabilities of LMMs in the training process of the retriever integrated with CLIP, as shown in Fig. 2.

The multimodal query q is fed into the base LMM to obtain its output hidden state $h=H_{\rm LMM}(q)$. In parallel, the query is fed into a multimodal encoder $\psi_{\rm MM}(q)=\psi^{\langle t\rangle}(q^{\langle t\rangle})+\psi^{\langle i\rangle}(q^{\langle i\rangle})$, where $\psi^{\langle t\rangle}$ and $\psi^{\langle i\rangle}$ are text and image CLIP-like encoders, respectively. Then, we define a Hidden State Adapter $\psi_{\rm LMM}$ to map h into the same space as $\psi_{\rm MM}$, as follows:

$$\psi_{\text{LMM}}(h) = \text{FC}(\text{GeLU}(\text{FC}(h)))$$
 (2)




Figure 2. <u>Comment-aware Retrieval</u>. The query is inputed to both a CLIP-trained image-text encoder and an LMM. The LMM representation is projected to the space of the image-text encoder. Alignment of query and targets is done using contrastive loss.

where FCs are fully connected layers and GeLU is the activation function. The final embedding for q combines the CLIP-based embeddings and the adapter output:

$$\psi(q) = \beta \cdot \psi_{LMM}(H_{LMM}(q)) + (1 - \beta) \cdot \psi_{MM}(q)$$
 (3)

where β is a learnable weight part of θ . Note, this scorefusion approach to CLIP is inspired by UniIR [83], where the authors show this is one of the most effective ways to combine multimodal inputs for multimodal retrieval.

Finally, we define R_{θ} as the dot product of query and document embeddings: $R_{\theta}(q,d) = \psi(q)^T \cdot \psi_{\text{MM}}(d)$. As shown in Fig. 2, the multimodal target documents are not using the LMM and therefore only use the multimodal encoder ψ_{MM} . This asymmetrical approach between query and document has several advantages: 1) it saves cost during the indexing phase by avoiding to use an expensive LMM on the potentially large pool of multimodal documents, and 2) it bridges the domain gap between the queries and the database via fine-tuning of the adapter. In contrast with other methods that use LMMs for indexing [42, 55], our method keeps indexing lightweight.

We train our retriever using contrastive loss [68]. Unlike previous work [42, 55, 83], we combine target captions and more complex target comments that cover aspects beyond the query and target images, as we will describe in Sec. 4. This makes our model aware of complex comments during training and thus will better fit with retrieval-aware generation as described in Sec. 3.2.

3.2. Retrieval-aware Generation

We now detail how we enable an LMM to ingest the query question and image, encode retrieved entities, and generate an answer to the question. The process is shown in Fig. 3.

3.2.1 Retrieved Entities as Input Modality

In essence, a Large Language Model (LLM) predicts the probability of the next token $\tau_n \in \{1, \dots, V\}$, where V is the vocabulary size, given an input sequence of n tokens:




Figure 3. <u>Retrieval-aware Generation</u>. The query image and text are fed to the LMM, which asks the retriever for relevant entities. The best entity is provided to the user and adapted into the LMM, so it can attend to it for generating a useful comment.

 $p(\tau_n|\tau_0,\ldots,\tau_{n-1})$. The first layer of the LLM projects the tokens into an input embedding space, mapping each of the V possible text tokens to a vector $\varphi^{\langle t \rangle}(\tau_k) = \phi_k^{\langle t \rangle} \in \mathbb{R}^d$, where d is the input embedding size of the LLM. Therefore, we can also see the LLM as predicting the next token based on a sequence of text-based embeddings:

$$p(\tau_n \mid \phi_0^{\langle t \rangle}, \dots, \phi_{n-1}^{\langle t \rangle}).$$
 (4)

LMMs [19, 56] extend this principle by adapting visual data into input image tokens $\tau^{\langle i \rangle}$ or embeddings $\phi^{\langle i \rangle}$. Notably, Eq. 4 is unchanged for LMMs, except that the inputs are now a mix of text $\phi^{\langle t \rangle}$ and image $\phi^{\langle i \rangle}$ embeddings in \mathbb{R}^d .

As described in Sec. 3.1, the retriever finds the most relevant multimodal document d_m in the database based on the multimodal query q and the projected hidden state of the LMM. As an important contribution of our method, we then inject d_m into the LMM as a new input modality $\langle r \rangle$ in order to condition the rest of the generation process, and therefore ensure that the model attends to it while generating the textual comment. This is important because of the finite nature of any database: the retrieved documents can substantially differ from the vector used as query. Thus, using solely the user input to condition the generation may lead to comments that are irrelevant to the retrieved entity.

Similarly to other input modalities, features of the retrieved document are extracted and adapted into the input embedding space of the LMM:

$$\varphi^{\langle r \rangle}(d_m) = [\phi_{m,0}^{\langle r \rangle}, \dots, \phi_{m,l_m}^{\langle r \rangle}] = \phi_m^{\langle r \rangle} \in \mathbb{R}^{d \times l_m}, \quad (5)$$

where l_m is the length of the representation of the document d_m . In this way, the LMM can attend to the retrieved data in addition to all previous inputs as it continues generation:

$$p(\tau_n \mid \cdots, \phi_k^{\langle t \rangle}, \cdots, \phi_p^{\langle i \rangle}, \cdots, \phi_m^{\langle r \rangle}, \cdots).$$
 (6)

However, the frozen LMM was not trained to distinguish entities that are retrieved from a database and treat them appropriately to generate a convincing answer. Thus, we make the entity adapter a trainable module as described next.

3.2.2 Entity Adapter Module

The definition of $\varphi^{\langle r \rangle}(d_m)$ depends on the nature of the dataset and the entities it contains: text, images, audio, video, pre-computed features, or any combination thereof. We propose to design an Entity Adapter module $\varphi_\xi^{\langle r \rangle}(d_m)$, as shown in Fig. 3, with parameters ξ , which can be finetuned on training data. More specifically for our CoR tasks, the entities are images, or multimodal combinations of images and text data (e.g. titles, captions, ...), that are used to generate the answer. As a consequence, the Entity Adapter treats the various modalities differently, i.e., $\varphi_\xi^{\langle r \rangle}(d_m) = (\varphi_\xi^{\langle i \rangle}(d_m^{\langle i \rangle}), \varphi_\xi^{\langle t \rangle}(d_m^{\langle t \rangle})).$ In our datasets, the textual components are notatural text, so we provide them directly to the LMM, without fine-tuning the token embeddings, i.e., $\varphi_\xi^{\langle t \rangle}(d_m) = \phi^{\langle t \rangle}$. For the visual part, we use the same architecture as the base LMM [19], with the adapter:

$$\varphi_{\varepsilon}^{\langle i \rangle}(d_m) = FC(GeLU(FC(LayerNorm(x_m)))), \quad (7)$$

where $\{x_m\}$ are the ViT image features of the variable number of tiles of the image of $d_m^{\langle i \rangle}$.

3.2.3 Training

To train our novel Entity Adapter, we leverage a dataset \mathcal{D} of ground-truth multimodal triplets (q,d,c), where q is the multimodal query, d is the ground-truth target document, and c is the ground-truth answer that relates the query and the target. The training of ξ is performed for the task of next token prediction of c, using the cross-entropy loss:

$$\mathcal{L}_{CE}(\xi) = \sum_{(q,d,c)\in\mathcal{D}} \sum_{\tau_n \in c} -\delta_n . \log(p_n(\xi)), \quad (8)$$

where $p_n(\xi) = p(\tau_n | \phi_q^{\langle i \rangle}, \phi_q^{\langle t \rangle}, \varphi_\xi^{\langle r \rangle}(d), \phi_0^{\langle t \rangle}, \ldots, \phi_{n-1}^{\langle t \rangle})$, and δ_n is the ground-truth distribution for τ_n . As shown in Fig. 3, in practice, all other parts of the model are kept frozen during training and only the adapter in Eq. 7 is trained. For faster convergence, this adapter is initialized from the pretrained visual adapter of the original LMM.

With this approach, despite keeping the base LMM frozen, we are achieving two objectives: 1) we align the multimodal entities with the LMM input embeddings, thus helping the LMM extract the relevant information from the entities and closing any domain gap between the data used to pre-train the LMM and the retrieval dataset, and 2) we encode commenting instructions in the adapter, thus optimizing the inputs to the LMM to bias it to generate useful, high-quality comments for documents of this dataset. As a consequence, we train separate, specialized Entity Adapters for different tasks and datasets.

4. Commented Retrieval (CoR) Task

As already discussed in related work, the related task of composed retrieval is well explored in the literature, and there exist a number of datasets for it. Some datasets for this task, e.g., CIRR [58] and Fashion-IQ [33], include multimodal queries, while the targets are only images. Other relevant datasets, e.g., OVEN [38] and InfoSeek [17], have both multimodal queries and targets, however the connection between inputs and outputs are simple high-level entities. Overall, existing datasets either lack target text altogether or feature overly simplistic textual responses that are directly related to the target image. These datasets are not well-suited to evaluate the full extent of the commented retrieval task, where the goal is not only to retrieve a relevant target image, but also to generate a detailed, complex textual response that refer to both the query and target image. Therefore, we propose a technique to automatically augment some existing datasets with textual answers and comments to the multimodal questions and image-only answers. In this work, we focus on 2 different domains, images of real-world object categories with CIRR [58] and Wikipedia concepts with WikiWeb2M [10], but the approach itself generalizes to other domains.

The proposed approach to obtain a tuple of a query image, a textual question, a target image and a textual answer for CoR is composed by three parts: 1) pair related images; 2) generate questions and answers related to those images; and 3) manual annotation to create a golden set for evaluation. We couple images that belong to similar concepts, which definition depends on the task. For CIRR, image pairs are already present in the original set, as images were grouped together based on visual similarity. For Wiki-Web2M, we pair images belonging to the same Wikipedia article, because that denotes a semantic link. We subsample a set of 50K samples for training and 2K for testing.

In the second step, we aim at generating questions and answers that can relate the two images, with the goal of simulating the behavior of a user that asks a question about an uploaded image, and obtain an answer with text and the target image supporting the text. We automatically generate these questions and answers by prompting using Anthropic Claude 3.5 Sonnet. For CIRR, the question is the textual modification instruction that is already included in the original set, so we only generate the textual answer. For WikiWeb2M, we generate a question-answer pair that is related to the query and target images, their captions and the Wikipedia article. This task is more challenging and results in noisier data. We name these datasets CIRR-CoR and Wiki-CoR, respectively, and show examples in Fig. 5.

Finally, we create golden sets for evaluation purposes by

asking annotators to validate the plausibility of the question and the quality of the generated text, manually adjusting them if necessary. We performed human auditing of the generated comments on the validation set of CIRR-CoR and found that $\sim\!97\%$ of the audited comments were marked as high quality. For the test set of Wiki-CoR, we conducted a manual review by filtering out image pairs that are not related to each other, questions that are irrelevant and comments that are not aligned with the question. In addition, annotators performed the necessary edits of the question and answer pairs to improve their quality. This results in a golden set of 695 out of 1768 ($\sim\!39\%$), showing the importance of having an annotation process for evaluation, that is often not considered in previous datasets.

5. Experiments

We evaluate the multimodal retrieval and commenting capabilities of our methods with respect to the state of the art in Sec. 5.1 and Sec. 5.2, respectively.

5.1. Retrieval Results

Implementation Details. We choose InternVL2-4B [19] as the base, frozen LMM and use it to extract hidden states $H_{LMM}(q)$ corresponding to queries. Specifically, we take the 3072-dimensional hidden state of the last transformer layer after processing of the last input token before generating the response. We train the encoder ψ_{MM} and adapter ψ_{LMM} using the UniIR framework [83] so as to align the queries and targets using contrastive loss [40] in two stages. First, we train the hidden state adapter exclusively to align them to UniIR embeddings, so we can obtain a good initialization. Second, as depicted in Fig. 2, we additionally unlock parameter β and the multimodal encoder, initialized from a pre-trained CLIP ViT-L-14 model [68]. We append instructions in the query as proposed by [83] and train a joint model on all 5 datasets², i.e Fashion-IQ, CIRR, OVEN, InfoSeek and Wiki-CoR. For Wiki-CoR, we randomly sample comment or caption as text with 50%/50% chance. We train for 40 epochs using learning rate 1e-5, batch size 55, effectively 110 thanks to gradient accumulation of 2, on a single host with 8×48GB NVIDIA L40S GPUs.

Metrics. We use standard *recall@k* metrics to measure the retrieval performance: we compute the neighbourhoods of the query vectors and verify if they contain the target image specified in the ground-truth annotations of the datasets. We compare with pretrained CLIP ViT-L-14 [68] and the state-of-the-art model UniIR CLIP_{SF} [83].

 $^{^{\}rm l}$ The Supplementary Material shows more examples of the datasets and the prompts used to generate them.

 $^{^2\}mbox{Fashion-IQ}, \mbox{CIRR}, \mbox{OVEN}, \mbox{ and InfoSeek}$ are a subset of M-BEIR [83] that has multimodal inputs.

	Fashion-IQ [33]			(CIRR [58	3]	(OVEN [38]		InfoSeek [17]		Wiki-CoR		Average		
	R@10	R@20	R@50	R@1	R@5	R@10	R@1	R@5	R@10	R@1	R@5	R@10	R@1	R@5	R@10	
CLIP (zero-shot) [68]	5.50	8.26	13.84	0.86	12.13	18.30	10.79	24.12	30.47	8.73	21.79	29.62	13.24	25.04	30.50	16.88
UniIR CLIP _{SF} [83]	24.59	32.22	43.66	9.50	45.01	58.61	49.50	68.86	74.56	27.08	49.04	58.24	21.73	40.72	46.76	43.34
UniCoRN (ours)	25.20	32.40	43.33	16.45	47.24	59.76	51.08	70.22	75.54	26.41	48.01	57.24	40.14	57.70	67.05	47.85

Table 1. Main results on retrieval. Retrieval results in terms of recall on different datasets while comparing with state of the art methods.

Results. The main results are shown in Table 1. First, we observe a low zero-shot performance on all datasets. This is in line with observations from previous work on composed retrieval [83, 97], which showed that CLIP models cannot easily compose multimodal features to match multimodal answers that are semantically different from the original query. Second, we see that UniCoRN is able to leverage the hidden states of the LMM, leading to improved performance, especially for the first ranks (recall@1 and 5), over all datasets but InfoSeek. We also show qualitative results of UniIR and UniCoRN in Fig. 4. In the first example, UniIR retrieves visually similar traditional clothing and headwear. Instead, UniCoRN correctly retrieves art forms from Bali and Java (mentioned in the captions), consistent with the query (Indonesia). In the challenging second example, the model needs to infer from the query image that it's a hair dryer and connect the textual "show in use". While UniIR fails, UniCoRN correctly retrieves the ground truth image on rank 3. Also the other examples on CIRR and OVEN show that UniCoRN is able to combine query and image text in an abstract way to retrieve visually dissimilar correct targets, while UniIR focuses on visual similarity.

Ablation Study. Table 2 shows an ablation study, where we train our model without Wiki-CoR and we remove the LMM adapter. For this analysis, we study recall@1 because this will be the retrieved image that the LMM will comment (Sec. 5.2). The inclusion of our adapter (row 1 vs 2) enhances performance across both datasets, leveraging LMM hidden states. This improvement comes at a negligible computational cost during inference since the LMM hidden state is computed already, highlighting our model's efficiency and effectiveness. When we do not train on Wiki-CoR data, we observe a big drop in performance, highlighting how distinctive Wiki-CoR is from other Wikipedia datasets such as OVEN and InfoSeek. Our model convincingly outperforms the zero-shot baseline (row 1 vs 4), showcasing its robust generalization capabilities and underscores the value of our training approach.

5.2. Commenting Results

Implementation Details. To implement retrieval-aware commenting, we need to modify standard LMM procedures, because we perform retrieval during generation and output images interleaved with text. We do so by extending the generation function of LMMs with the following

	CIRR [58]	Wiki-CoR
UniCoRN	16.45	40.14
w/o adapter	$\overline{16.35}$	39.14
w/o Wiki-CoR	17.29	23.02
w/o training (zero-shot)	0.86	13.24
UniIR CLIP _{SF} [83]	9.50	21.73

Table 2. Ablation study on retrieval. Retrieval results in terms of recall@1 on different dataset.

changes. First, we specify a retrieval token, the prediction of which will trigger the retriever R_{θ} . We use the start-of-sentence tag, as our commented retrieval datasets do not exhibit comments prior to retrieval. The retriever yields a reference to the target entity, which we process via feature extraction and the Entity Adapter to make the LMM understand the retrieved content. We convert all previously predicted output tokens to input embeddings and append the embedding of the retrieved entity, then feed this as input to the LMM for predicting the next tokens, until the end-of-sentence token is detected.

In addition, we train our Entity Adapters specifically so that InternVL2-4B processes retrieved content differently than content input by a user. We therefore fine-tune the Entity Adapters separately on CIRR-CoR and Wiki-CoR. For CIRR-CoR, we have 28,225 valid training conversations, where the retrieved entities are simply the target images. For Wiki-CoR, we have 50,126 valid training conversations, where the retrieved entities are Wikipedia images with caption, as well as metadata from the corresponding Wikipedia page (title, description). We train both adapters using the InternVL2 framework [19] for two epochs on a single host with $4\times$ L40S GPUs, using a learning rate of $1.0e^{-4}$, and evaluate on their respective evaluation sets as we described in Sec. 4.

Metrics. We evaluate the predicted comments with respect to the corresponding ground-truth (GT) comments in the golden test set using standard metrics for language understanding: i) METEOR [20], the harmonic mean of word precision and recall that takes into account stemming and synonymy; ii) BLEU [65], a metric with high correlation with human judgments of translation quality; iii) ROUGE-1 [54] (resp. ROUGE-2) measuring the overlap of words (resp, bi-grams) between the two comments.



Figure 4. Qualitative results retrieval. We show retrieved images for UniIR and UniCoRN on three datasets. Captions are not displayed because of space limits.

		CIR	R-CoR		Wiki-CoR							
	METEOR	BLEU	ROUGE-1	ROUGE-2	BEM	SigLIP-R@1	METEOR	BLEU	ROUGE-1	ROUGE-2	BEM	SigLIP-R@1
InternVL2 [19]	0.192	0.013	0.280	0.082	11.9%	41.4%	0.128	0.009	0.237	0.089	31.8%	49.1%
EchoSight [88] + InternVL2	0.311	0.038	0.397	0.119	31.6%	41.0%	0.204	0.018	0.276	0.065	16.2%	32.1%
UniIR CLIP _{SF} [83] + InternVL2	0.313	0.039	0.399	0.121	32.0%	42.6%	0.212	0.025	0.293	0.078	21.4%	41.2%
UniCoRN	0.444	0.115	0.516	0.280	50.4 %	45.1 %	0.379	0.128	0.446	0.196	39.3 %	66.3 %
UniCoRN retriever + RAG	0.318	0.041	0.400	0.123	33.7%	43.3%	0.236	0.037	0.323	0.098	28.7%	55.2%
UniCoRN w/o trained adapter	0.317	0.029	0.346	0.106	28.8%	33.7%	0.264	0.033	0.285	0.089	23.7%	52.4%
UniCoRN w/ shared adapter	0.407	0.060	0.392	0.181	55.9%	42.7%	0.374	0.127	0.447	0.195	39.3%	67.6%
UniCoRN w/ UniIR CLIP _{SF}	0.439	0.113	0.510	0.276	49.8%	44.0%	0.347	0.106	0.411	0.168	34.7%	55.4%
UniCoRN w/ GT target oracle	0.462	0.130	0.534	0.297	56.1%	55.9%	0.443	0.176	0.517	0.258	55.8%	92.1%

Table 3. Main results and ablation study on commenting. Commenting results by computing several language-based metrics between the predicted comments and the ground-truth (GT) ones on the CIRR-CoR and Wiki-CoR dataset. (Top) Comparison with the state of the art; (Middle) Ablation study for retrieval and generation in UniCoRN; (Bottom) Upper-bound using GT target documents as an oracle.

	Wiki-CoR								
	METEOR	BLEU	ROUGE-1	ROUGE-2	SigLIP-R@1				
UniCoRN	0.379	0.128	0.446	0.196	66.3%				
w/o Wikipedia desc.	0.302	0.069	0.386	0.143	55.1%				
image-only	0.295	0.065	0.379	0.137	50.6%				
caption-only	0.244	0.034	0.299	0.090	47.3%				
UniCoRN retr. + RAG	0.236	0.037	0.323	0.098	55.2%				
w/o Wikipedia desc.	0.227	0.032	0.321	0.098	51.5%				
image-only	0.198	0.028	0.314	0.094	49.6%				
caption-only	0.258	0.024	0.277	0.079	46.0%				

Table 4. Modality ablation study for entity encoding. We compare results on Wiki-CoR using UniCoRN and RAG when removing images, captions and Wikipedia descriptions when providing the entities to the model.

iv) BEM [9], a BERT-based [22] measure to evaluate the equivalence of answers to a question. We also use a separate vision-language model, namely ViT-SO400M-14-SigLIP-384 [96], to measure if the predicted comment can be used to retrieve the GT comment with high accuracy, thus measuring if they are specific and distinct from other comments. For this approach, we use again *recall@1*.

Results. In the top section of Table 3, we report the results for UniCoRN as well as three state-of-the-art LMM approaches that can produce comments based on multimodal inputs: i) InternVL2 [19], a state-of-the-art LMM that is prompted to generate a comment for the unseen image based only on the multimodal user query; ii) EchoSight [88], a state-of-the-art multimodal Retrieval-Augmented Generation (RAG) and re-ranking approach, using InternVL2 as the base LMM for comment generation. iii) a system with the state-of-the-art compositional retriever UniIR [83] that we use to build a multi-image multi-modal RAG prompt for InternVL2; The results show that InternVL2 is able to generate comments that contain relevant information (METEOR 0.192/0.128 on CIRR-CoR/Wiki-CoR resp.). This entails that the LMM is able to interpret the user query, justifying that its hidden state has indeed the potential to contribute to the retrieval component. However, the comments are not very similar to the ground-truth: this is clearly due to the absence of retrieval capabilities in InternVL2, which thus has to produce




Figure 5. Qualitative results. We show retrieved images and comments for UniIR with RAG and UniCoRN on two different datasets. Comments highlighted in red indicate responses that either do not answer the original question or are not related to the retrieved image.

a plausible comment without having access to any information about the content present in the retrieval dataset. Using EchoSight [88] or UniIR [83] to retrieve an entity and providing it in the prompt for InternVL2 improves results significantly on all metrics (e.g., METEOR 0.313/212), with a slight edge to the compositional retriever (UniIR) over the reranking one (EchoSight). This proves that conditioning the generation on actual retrieved images is critical to ensure the relevance of the comments, and explains the broad success of RAG methods. Then, using UniCoRN, we further improve to 0.444/0.379 METEOR. Notably, the improvements are consistent over all metrics on both datasets. These results show the effectiveness of our approach: without losing any other ability of InternVL2, UniCoRN is able to optimize its processing of user queries and retrieval results so as to output comments that are significantly better than static prompts built via RAG.

Ablation Study. In the middle section of Table 3, we further analyze the main contributions to the performance of UniCoRN. First, when using UniCoRN's retrieval results in a RAG prompt for InternVL2, we observe only a slight improvement over UniIR+RAG. Similarly, using UniCoRN's commenting abilities on UniIR retrieval results performs only slightly worse than our full UniCoRN. Thus, the improvements in retrieval are only a part of the contribution to the commenting performance. In contrast, using the pretrained input visual encoder from InternVL2 to encode retrieved documents does indeed drop the performance to the level for RAG. This highlights that our contribution of training dataset-specific entity embeddings makes the biggest contribution in making the base LMM provide more relevant and well-formatted comments. Training a share entity encoder leads to mixed results, with a slight improvement on BEM and SigLIP at the expense of other metrics.

In Table 4, we further decompose the contribution of the various modalities available in the retrieved documents. Since CIRR-CoR only has target images, we focus on Wiki-CoR, in which retrieved documents contain an image and its caption on Wikipedia, as well as the title and description of the corresponding page in Wikipedia as metadata. UniCoRN, like RAG, uses all information by default in our experiments (to build the Entity encoding, resp. the prompt). Using the UniCoRN retriever and the trained adapter, we show the drop of performance that occurs when removing, in turn, i) the Wikipedia title and description: -12.1% METEOR, relatively; ii) all textual inputs (*image-only*): -19.1%; iii) image and Wikipedia metadata (*caption-only*): -13.1%. Since the drops are consistent for all metrics and both comment generation models (RAG and UniCoRN) based on the same inputs³, we can therefore conclude that all three are needed to provide relevant answers.

Finally, we analyze the qualitative performance of UniIR with RAG and UniCoRN in Fig. 5 with success cases for UniCoRN. The first row shows an example where both models retrieve the correct image. However, the comments provided by RAG do not answer the question correctly, as indicated by the part of the comment highlighted in red. The second row presents an example where the UniIR model was unable to retrieve the correct image, and therefore it could not answer the question correctly. This is similar to the third example, where the UniIR model retrieved the wrong query image, yet provided a comment that follows the instructions but does not actually correspond to the retrieved image.

6. Conclusions

This work introduces UniCoRN, a Unified Commented Retrieval Network that unifies discriminative retrieval and generative commenting. We combined the strengths of composed multimodal retrieval methods with gen-

 $^{^3\}mathrm{Except}$ the caption-only version of RAG for the METEOR score, which does better without the image.

erative language capabilities, resulting in a system that surpasses traditional RAG techniques. Our approach preserves the original capabilities of the base LMM while extending its functionality to perform both retrieval and text generation tasks within a single framework. We introduced the CoR task and a corresponding dataset to evaluate these new abilities of LMMs. Future work could focus on further improving the integration of multimodal information, exploring additional tasks, and investigating the scalability of our approach.

References

- [1] Pravesh Agrawal, Szymon Antoniak, Emma Bou Hanna, Devendra Chaplot, Jessica Chudnovsky, Saurabh Garg, Theophile Gervet, Soham Ghosh, Amélie Héliou, Paul Jacob, et al. Pixtral 12b. arXiv preprint arXiv:2410.07073, 2024. 1, 2
- [2] Kenan E Ak, Ashraf A Kassim, Joo Hwee Lim, and Jo Yew Tham. Learning attribute representations with localization for flexible fashion search. In *CVPR*, 2018. 1
- [3] Peter Anderson, Xiaodong He, Chris Buehler, Damien Teney, Mark Johnson, Stephen Gould, and Lei Zhang. Bottom-up and top-down attention for image captioning and visual question answering. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 6077–6086, 2018. 1
- [4] AI Anthropic. The claude 3 model family: Opus, sonnet, haiku. *Claude-3 Model Card*, 2024. 1, 2
- [5] Stanislaw Antol, Aishwarya Agrawal, Jiasen Lu, Margaret Mitchell, Dhruv Batra, C Lawrence Zitnick, and Devi Parikh. Vqa: Visual question answering. In *Proceedings of the IEEE international conference on computer vision*, pages 2425–2433, 2015. 1
- [6] Alberto Baldrati, Marco Bertini, Tiberio Uricchio, and Alberto Del Bimbo. Effective conditioned and composed image retrieval combining clip-based features. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 21466–21474, 2022. 1, 2
- [7] Alberto Baldrati, Lorenzo Agnolucci, Marco Bertini, and Alberto Del Bimbo. Zero-shot composed image retrieval with textual inversion. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 15338–15347, 2023. 2
- [8] Hangbo Bao, Wenhui Wang, Li Dong, Qiang Liu, Owais Khan Mohammed, Kriti Aggarwal, Subhojit Som, Songhao Piao, and Furu Wei. Vlmo: Unified vision-language pre-training with mixture-of-modality-experts. *Advances in Neural Information Processing Systems*, 35:32897–32912, 2022. 1, 2
- [9] Jannis Bulian, Christian Carl Friedrich Buck, Wojciech Paweł Gajewski, Benjamin Boerschinger, and Tal Schuster. Tomayto, tomahto. beyond token-level answer equivalence for question answering evaluation. In EMNLP 2022, 2022. 7
- [10] Andrea Burns, Krishna Srinivasan, Joshua Ainslie, Geoff Brown, Bryan A Plummer, Kate Saenko, Jianmo Ni,

- and Mandy Guo. A suite of generative tasks for multilevel multimodal webpage understanding. *arXiv preprint arXiv:2305.03668*, 2023. 5
- [11] Andrea Burns, Krishna Srinivasan, Joshua Ainslie, Geoff Brown, Bryan A. Plummer, Kate Saenko, Jianmo Ni, and Mandy Guo. A suite of generative tasks for multi-level multimodal webpage understanding. In *The 2023 Confer*ence on Empirical Methods in Natural Language Processing (EMNLP), 2023. 2
- [12] Davide Caffagni, Federico Cocchi, Nicholas Moratelli, Sara Sarto, Marcella Cornia, Lorenzo Baraldi, and Rita Cucchiara. Wiki-llava: Hierarchical retrieval-augmented generation for multimodal llms. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) Workshops, pages 1818–1826, 2024. 2
- [13] Wenhu Chen, Hexiang Hu, Xi Chen, Pat Verga, and William W Cohen. Murag: Multimodal retrieval-augmented generator for open question answering over images and text. arXiv preprint arXiv:2210.02928, 2022. 2
- [14] Xi Chen, Xiao Wang, Lucas Beyer, Alexander Kolesnikov, Jialin Wu, Paul Voigtlaender, Basil Mustafa, Sebastian Goodman, Ibrahim Alabdulmohsin, Piotr Padlewski, et al. Pali-3 vision language models: Smaller, faster, stronger. arXiv preprint arXiv:2310.09199, 2023. 1, 2
- [15] Yanbei Chen, Shaogang Gong, and Loris Bazzani. Image search with text feedback by visiolinguistic attention learning. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), 2020. 2
- [16] Yanbei Chen, Shaogang Gong, and Loris Bazzani. Image search with text feedback by visiolinguistic attention learning. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 3001–3011, 2020. 1
- [17] Yang Chen, Hexiang Hu, Yi Luan, Haitian Sun, Soravit Changpinyo, Alan Ritter, and Ming-Wei Chang. Can pre-trained vision and language models answer visual information-seeking questions? *arXiv preprint arXiv:2302.11713*, 2023. 2, 5, 6
- [18] Zhe Chen, Weiyun Wang, Hao Tian, Shenglong Ye, Zhangwei Gao, Erfei Cui, Wenwen Tong, Kongzhi Hu, Jiapeng Luo, Zheng Ma, Ji Ma, Jiaqi Wang, Xiaoyi Dong, Hang Yan, Hewei Guo, Conghui He, Botian Shi, Zhenjiang Jin, Chao Xu, Bin Wang, Xingjian Wei, Wei Li, Wenjian Zhang, Bo Zhang, Pinlong Cai, Licheng Wen, Xiangchao Yan, Min Dou, Lewei Lu, Xizhou Zhu, Tong Lu, Dahua Lin, Yu Qiao, Jifeng Dai, and Wenhai Wang. How far are we to gpt-4v? closing the gap to commercial multimodal models with opensource suites, 2024. 1, 2
- [19] Zhe Chen, Jiannan Wu, Wenhai Wang, Weijie Su, Guo Chen, Sen Xing, Muyan Zhong, Qinglong Zhang, Xizhou Zhu, Lewei Lu, et al. Internvl: Scaling up vision foundation models and aligning for generic visual-linguistic tasks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 24185–24198, 2024. 1, 2, 4, 5, 6, 7
- [20] Michael Denkowski and Alon Lavie. Meteor universal: Language specific translation evaluation for any target language.

- In Proceedings of the EACL 2014 Workshop on Statistical Machine Translation, 2014. 6
- [21] Karan Desai, Maximilian Nickel, Tanmay Rajpurohit, Justin Johnson, and Shanmukha Ramakrishna Vedantam. Hyperbolic image-text representations. In *International Conference on Machine Learning*, pages 7694–7731. PMLR, 2023.
- [22] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina N. Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. 2018. 7
- [23] Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, et al. The llama 3 herd of models. arXiv preprint arXiv:2407.21783, 2024. 1, 2
- [24] Thibault Févry, Livio Baldini Soares, Nicholas FitzGerald, Eunsol Choi, and Tom Kwiatkowski. Entities as experts: Sparse memory access with entity supervision. arXiv preprint arXiv:2004.07202, 2020. 2
- [25] Yuting Gao, Jinfeng Liu, Zihan Xu, Jun Zhang, Ke Li, Rongrong Ji, and Chunhua Shen. Pyramidclip: Hierarchical feature alignment for vision-language model pretraining. Advances in Neural Information Processing Systems, 35:35959–35970, 2022. 1, 2, 3
- [26] Yuting Gao, Jinfeng Liu, Zihan Xu, Tong Wu, Wei Liu, Jie Yang, Ke Li, and Xing Sun. Softclip: Softer crossmodal alignment makes clip stronger. arXiv preprint arXiv:2303.17561, 2023. 1, 3
- [27] Yuying Ge, Sijie Zhao, Ziyun Zeng, Yixiao Ge, Chen Li, Xintao Wang, and Ying Shan. Making llama see and draw with seed tokenizer. *arXiv preprint arXiv:2310.01218*, 2023.
- [28] Shashank Goel, Hritik Bansal, Sumit Bhatia, Ryan Rossi, Vishwa Vinay, and Aditya Grover. Cyclip: Cyclic contrastive language-image pretraining. Advances in Neural Information Processing Systems, 35:6704–6719, 2022. 1
- [29] Sonam Goenka, Zhaoheng Zheng, Ayush Jaiswal, Rakesh Chada, Yue Wu, Varsha Hedau, and Pradeep Natarajan. Fashionvlp: Vision language transformer for fashion retrieval with feedback. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pages 14105–14115, 2022. 1, 2
- [30] Yash Goyal, Tejas Khot, Douglas Summers-Stay, Dhruv Batra, and Devi Parikh. Making the v in vqa matter: Elevating the role of image understanding in visual question answering. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 6904–6913, 2017. 1
- [31] Geonmo Gu, Sanghyuk Chun, Wonjae Kim, Yoohoon Kang, and Sangdoo Yun. Language-only training of zero-shot composed image retrieval. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 13225–13234, 2024. 2
- [32] Xiaoxiao Guo, Hui Wu, Yu Cheng, Steven Rennie, Gerald Tesauro, and Rogerio Feris. Dialog-based interactive image retrieval. In Advances in Neural Information Processing Systems, 2018.
- [33] Xiaoxiao Guo, Hui Wu, Yupeng Gao, Steven Rennie, and Rogerio Feris. The fashion iq dataset: Retrieving images

- by combining side information and relative natural language feedback. arXiv preprint arXiv:1905.12794, 2019. 1, 5, 6
- [34] Danna Gurari, Qing Li, Abigale J Stangl, Anhong Guo, Chi Lin, Kristen Grauman, Jiebo Luo, and Jeffrey P Bigham. Vizwiz grand challenge: Answering visual questions from blind people. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 3608–3617, 2018. 1
- [35] Kelvin Guu, Kenton Lee, Zora Tung, Panupong Pasupat, and Mingwei Chang. Retrieval augmented language model pretraining. In *International conference on machine learning*, pages 3929–3938. PMLR, 2020. 2
- [36] Xintong Han, Zuxuan Wu, Phoenix X Huang, Xiao Zhang, Menglong Zhu, Yuan Li, Yang Zhao, and Larry S Davis. Automatic spatially-aware fashion concept discovery. In *ICCV*, 2017.
- [37] Yuxin Hou, Eleonora Vig, Michael Donoser, and Loris Bazzani. Learning attribute-driven disentangled representations for interactive fashion retrieval. In *Proceedings of the IEEE/CVF International conference on computer vision*, pages 12147–12157, 2021. 1
- [38] Hexiang Hu, Yi Luan, Yang Chen, Urvashi Khandelwal, Mandar Joshi, Kenton Lee, Kristina Toutanova, and Ming-Wei Chang. Open-domain visual entity recognition: Towards recognizing millions of wikipedia entities. In *Proceedings* of the IEEE/CVF International Conference on Computer Vision, pages 12065–12075, 2023. 2, 5, 6
- [39] Ziniu Hu, Ahmet Iscen, Chen Sun, Zirui Wang, Kai-Wei Chang, Yizhou Sun, Cordelia Schmid, David A Ross, and Alireza Fathi. Reveal: Retrieval-augmented visual-language pre-training with multi-source multimodal knowledge memory. In Proceedings of the IEEE/CVF conference on computer vision and pattern recognition, pages 23369–23379, 2023. 2
- [40] Gabriel Ilharco, Mitchell Wortsman, Nicholas Carlini, Rohan Taori, Achal Dave, Vaishaal Shankar, Hongseok Namkoong, John Miller, Hannaneh Hajishirzi, Ali Farhadi, and Ludwig Schmidt. Openclip, 2021. 1, 2, 3, 5
- [41] Dongfu Jiang, Xuan He, Huaye Zeng, Cong Wei, Max Ku, Qian Liu, and Wenhu Chen. Mantis: Interleaved multi-image instruction tuning, 2024. 1, 2
- [42] Ziyan Jiang, Rui Meng, Xinyi Yang, Semih Yavuz, Yingbo Zhou, and Wenhu Chen. Vlm2vec: Training vision-language models for massive multimodal embedding tasks. arXiv preprint arXiv:2410.05160, 2024. 2, 3
- [43] Vladimir Karpukhin, Barlas Oğuz, Sewon Min, Patrick Lewis, Ledell Wu, Sergey Edunov, Danqi Chen, and Wentau Yih. Dense passage retrieval for open-domain question answering. arXiv preprint arXiv:2004.04906, 2020. 2
- [44] Shyamgopal Karthik, Karsten Roth, Massimiliano Mancini, and Zeynep Akata. Vision-by-language for training-free compositional image retrieval. *arXiv preprint* arXiv:2310.09291, 2023. 2
- [45] Sahar Kazemzadeh, Vicente Ordonez, Mark Matten, and Tamara Berg. Referitgame: Referring to objects in photographs of natural scenes. In *Proceedings of the 2014 con*ference on empirical methods in natural language processing (EMNLP), pages 787–798, 2014. 2

- [46] Jing Yu Koh, Ruslan Salakhutdinov, and Daniel Fried. Grounding language models to images for multimodal inputs and outputs. In *International Conference on Machine Learning*, pages 17283–17300. PMLR, 2023. 2
- [47] Janghyeon Lee, Jongsuk Kim, Hyounguk Shon, Bumsoo Kim, Seung Hwan Kim, Honglak Lee, and Junmo Kim. Uniclip: Unified framework for contrastive language-image pretraining. arXiv preprint arXiv:2209.13430, 2022. 1, 2
- [48] Kenton Lee, Ming-Wei Chang, and Kristina Toutanova. Latent retrieval for weakly supervised open domain question answering. arXiv preprint arXiv:1906.00300, 2019.
- [49] Matan Levy, Rami Ben-Ari, Nir Darshan, and Dani Lischinski. Chatting makes perfect: Chat-based image retrieval. Advances in Neural Information Processing Systems, 36, 2024.
- [50] Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, et al. Retrieval-augmented generation for knowledge-intensive nlp tasks. Advances in Neural Information Processing Systems, 33:9459–9474, 2020. 2
- [51] Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen tau Yih, Tim Rocktäschel, Sebastian Riedel, and Douwe Kiela. Retrieval-augmented generation for knowledge-intensive nlp tasks, 2021. 2
- [52] Huayang Li, Siheng Li, Deng Cai, Longyue Wang, Lemao Liu, Taro Watanabe, Yujiu Yang, and Shuming Shi. Textbind: Multi-turn interleaved multimodal instructionfollowing in the wild. 2023. 2
- [53] Junnan Li, Dongxu Li, Caiming Xiong, and Steven Hoi. Blip: Bootstrapping language-image pre-training for unified vision-language understanding and generation. In *Interna*tional conference on machine learning, pages 12888–12900. PMLR, 2022. 1, 2
- [54] Chin-Yew Lin. Rouge: A package for automatic evaluation of summaries. In *Text summarization branches out*, pages 74–81, 2004. 6
- [55] Sheng-Chieh Lin, Chankyu Lee, Mohammad Shoeybi, Jimmy Lin, Bryan Catanzaro, and Wei Ping. Mm-embed: Universal multimodal retrieval with multimodal llms. arXiv preprint arXiv:2411.02571, 2024. 2, 3
- [56] Haotian Liu, Chunyuan Li, Yuheng Li, and Yong Jae Lee. Improved baselines with visual instruction tuning, 2023. 1,
- [57] Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual instruction tuning, 2023. 1, 2
- [58] Zheyuan Liu, Cristian Rodriguez-Opazo, Damien Teney, and Stephen Gould. Image retrieval on real-life images with pre-trained vision-and-language models. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 2125–2134, 2021. 2, 5, 6
- [59] Zheyuan Liu, Cristian Rodriguez-Opazo, Damien Teney, and Stephen Gould. Image retrieval on real-life images with pretrained vision-and-language models. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 2125–2134, 2021. 2

- [60] Zheyuan Liu, Weixuan Sun, Yicong Hong, Damien Teney, and Stephen Gould. Bi-directional training for composed image retrieval via text prompt learning. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision (WACV)*, pages 5753–5762, 2024. 2
- [61] Richard E Mayer and Laura J Massa. Three facets of visual and verbal learners: Cognitive ability, cognitive style, and learning preference. *Journal of educational psychology*, 95 (4):833, 2003. 2
- [62] Brandon McKinzie, Zhe Gan, Jean-Philippe Fauconnier, Sam Dodge, Bowen Zhang, Philipp Dufter, Dhruti Shah, Xianzhi Du, Futang Peng, Floris Weers, et al. Mm1: Methods, analysis & insights from multimodal llm pre-training. arXiv preprint arXiv:2403.09611, 2024. 1, 2
- [63] Thomas Mensink, Jasper Uijlings, Lluis Castrejon, Arushi Goel, Felipe Cadar, Howard Zhou, Fei Sha, André Araujo, and Vittorio Ferrari. Encyclopedic vqa: Visual questions about detailed properties of fine-grained categories. In Proceedings of the IEEE/CVF International Conference on Computer Vision, pages 3113–3124, 2023. 2
- [64] OpenAI. Gpt-4 technical report, 2024. 1, 2
- [65] Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of the 40th Annual Meeting on Association for Computational Linguistics*, page 311–318, USA, 2002. Association for Computational Linguistics. 6
- [66] Jingyuan Qi, Zhiyang Xu, Rulin Shao, Yang Chen, Jing Di, Yu Cheng, Qifan Wang, and Lifu Huang. Rora-vlm: Robust retrieval-augmented vision language models, 2024.
- [67] Xiaoye Qu, Qiyuan Chen, Wei Wei, Jishuo Sun, and Jianfeng Dong. Alleviating hallucination in large vision-language models with active retrieval augmentation. arXiv preprint arXiv:2408.00555, 2024.
- [68] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. Learning transferable visual models from natural language supervision. *CoRR*, abs/2103.00020, 2021. 1, 2, 3, 5, 6
- [69] Christoph Schuhmann, Richard Vencu, Romain Beaumont, Robert Kaczmarczyk, Clayton Mullis, Aarush Katta, Theo Coombes, Jenia Jitsev, and Aran Komatsuzaki. Laion-400m: Open dataset of clip-filtered 400 million image-text pairs. arXiv preprint arXiv:2111.02114, 2021. 1, 2
- [70] Dustin Schwenk, Apoorv Khandelwal, Christopher Clark, Kenneth Marino, and Roozbeh Mottaghi. A-okvqa: A benchmark for visual question answering using world knowledge. In *European conference on computer vision*, pages 146–162. Springer, 2022. 1
- [71] Sanket Shah, Anand Mishra, Naganand Yadati, and Partha Pratim Talukdar. Kvqa: Knowledge-aware visual question answering. In *Proceedings of the AAAI conference* on artificial intelligence, pages 8876–8884, 2019.
- [72] Amanpreet Singh, Vivek Natarajan, Meet Shah, Yu Jiang, Xinlei Chen, Dhruv Batra, Devi Parikh, and Marcus Rohrbach. Towards vqa models that can read. In *Proceedings* of the IEEE/CVF conference on computer vision and pattern recognition, pages 8317–8326, 2019.

- [73] Yucheng Suo, Fan Ma, Linchao Zhu, and Yi Yang. Knowledge-enhanced dual-stream zero-shot composed image retrieval. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 26951–26962, 2024. 2
- [74] Chameleon Team. Chameleon: Mixed-modal early-fusion foundation models. arXiv preprint arXiv:2405.09818, 2024.
- [75] Gemini Team. Gemini 1.5: Unlocking multimodal understanding across millions of tokens of context, 2024. 1, 2
- [76] Changyao Tian, Xizhou Zhu, Yuwen Xiong, Weiyun Wang, Zhe Chen, Wenhai Wang, Yuntao Chen, Lewei Lu, Tong Lu, Jie Zhou, Hongsheng Li, Yu Qiao, and Jifeng Dai. Mm-interleaved: Interleaved image-text generative modeling via multi-modal feature synchronizer. arXiv preprint arXiv:2401.10208, 2024. 2
- [77] Sagar Vaze, Nicolas Carion, and Ishan Misra. Genecis: A benchmark for general conditional image similarity. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 6862–6872, 2023. 2
- [78] Nam Vo, Lu Jiang, Chen Sun, Kevin Murphy, Li-Jia Li, Li Fei-Fei, and James Hays. Composing text and image for image retrieval - an empirical odyssey. In CVPR, 2019. 1
- [79] Nam Vo, Lu Jiang, Chen Sun, Kevin Murphy, Li-Jia Li, Li Fei-Fei, and James Hays. Composing text and image for image retrieval-an empirical odyssey. In *Proceedings of* the IEEE/CVF conference on computer vision and pattern recognition, pages 6439–6448, 2019. 2
- [80] Yongquan Wan, Wenhai Wang, Guobing Zou, and Bofeng Zhang. Cross-modal feature alignment and fusion for composed image retrieval. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) Workshops, pages 8384–8388, 2024. 2
- [81] Peng Wang, Shuai Bai, Sinan Tan, Shijie Wang, Zhihao Fan, Jinze Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, et al. Qwen2-vl: Enhancing vision-language model's perception of the world at any resolution. arXiv preprint arXiv:2409.12191, 2024. 1, 2
- [82] Wenhui Wang, Hangbo Bao, Li Dong, Johan Bjorck, Zhiliang Peng, Qiang Liu, Kriti Aggarwal, Owais Khan Mohammed, Saksham Singhal, Subhojit Som, et al. Image as a foreign language: Beit pretraining for vision and vision-language tasks. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 19175–19186, 2023. 1, 2
- [83] Cong Wei, Yang Chen, Haonan Chen, Hexiang Hu, Ge Zhang, Jie Fu, Alan Ritter, and Wenhu Chen. Uniir: Training and benchmarking universal multimodal information retrievers. *arXiv preprint arXiv:2311.17136*, 2023. 2, 3, 5, 6, 7, 8
- [84] Hui Wu, Yupeng Gao, Xiaoxiao Guo, Ziad Al-Halah, Steven Rennie, Kristen Grauman, and Rogerio Feris. Fashion iq: A new dataset towards retrieving images by natural language feedback. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pages 11307–11317, 2021. 2
- [85] Hui Wu, Yupeng Gao, Xiaoxiao Guo, Ziad Al-Halah, Steven Rennie, Kristen Grauman, and Rogerio Feris. Fashion iq: A

- new dataset towards retrieving images by natural language feedback. In *Proceedings of the IEEE/CVF Conference on computer vision and pattern recognition*, pages 11307–11317, 2021. 2
- [86] Qi Wu, Damien Teney, Peng Wang, Chunhua Shen, Anthony Dick, and Anton Van Den Hengel. Visual question answering: A survey of methods and datasets. *Computer Vision and Image Understanding*, 163:21–40, 2017. 1
- [87] Shengqiong Wu, Hao Fei, Leigang Qu, Wei Ji, and Tat-Seng Chua. Next-gpt: Any-to-any multimodal llm. arXiv preprint arXiv:2309.05519, 2023. 1, 2
- [88] Yibin Yan and Weidi Xie. EchoSight: Advancing visual-language models with Wiki knowledge. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 1538–1551, Miami, Florida, USA, 2024. Association for Computational Linguistics. 1, 2, 7, 8
- [89] Lewei Yao, Runhui Huang, Lu Hou, Guansong Lu, Minzhe Niu, Hang Xu, Xiaodan Liang, Zhenguo Li, Xin Jiang, and Chunjing Xu. Filip: fine-grained interactive language-image pre-training. *arXiv preprint arXiv:2111.07783*, 2021. 1, 2
- [90] Jiabo Ye, Haiyang Xu, Haowei Liu, Anwen Hu, Ming Yan, Qi Qian, Ji Zhang, Fei Huang, and Jingren Zhou. mplug-owl3: Towards long image-sequence understanding in multi-modal large language models. *arXiv preprint arXiv:2408.04840*, 2024. 1, 2
- [91] Shukang Yin, Chaoyou Fu, Sirui Zhao, Ke Li, Xing Sun, Tong Xu, and Enhong Chen. A survey on multimodal large language models. arXiv preprint arXiv:2306.13549, 2023. 2
- [92] Jiahui Yu, Zirui Wang, Vijay Vasudevan, Legg Yeung, Mojtaba Seyedhosseini, and Yonghui Wu. Coca: Contrastive captioners are image-text foundation models. *arXiv preprint* arXiv:2205.01917, 2022. 1, 2
- [93] Lijun Yu, José Lezama, Nitesh B Gundavarapu, Luca Versari, Kihyuk Sohn, David Minnen, Yong Cheng, Vighnesh Birodkar, Agrim Gupta, Xiuye Gu, et al. Language model beats diffusion–tokenizer is key to visual generation. arXiv preprint arXiv:2310.05737, 2023. 2
- [94] Shi Yu, Chaoyue Tang, Bokai Xu, Junbo Cui, Junhao Ran, Yukun Yan, Zhenghao Liu, Shuo Wang, Xu Han, Zhiyuan Liu, et al. Visrag: Vision-based retrieval-augmented generation on multi-modality documents. arXiv preprint arXiv:2410.10594, 2024.
- [95] Xiaohua Zhai, Joan Puigcerver, Alexander Kolesnikov, Pierre Ruyssen, Carlos Riquelme, Mario Lucic, Josip Djolonga, Andre Susano Pinto, Maxim Neumann, Alexey Dosovitskiy, et al. A large-scale study of representation learning with the visual task adaptation benchmark. arXiv preprint arXiv:1910.04867, 2019. 1, 2
- [96] Xiaohua Zhai, Basil Mustafa, Alexander Kolesnikov, and Lucas Beyer. Sigmoid loss for language image pre-training. In *Proceedings of the IEEE/CVF International Conference* on Computer Vision, pages 11975–11986, 2023. 1, 2, 7
- [97] Kai Zhang, Yi Luan, Hexiang Hu, Kenton Lee, Siyuan Qiao, Wenhu Chen, Yu Su, and Ming-Wei Chang. Magiclens: Self-supervised image retrieval with open-ended instructions. *arXiv preprint arXiv:2403.19651*, 2024. 2, 6

- [98] Jinghao Zhou, Li Dong, Zhe Gan, Lijuan Wang, and Furu Wei. Non-contrastive learning meets language-image pretraining. *arXiv preprint arXiv:2210.09304*, 2022. 1, 2
- [99] Deyao Zhu, Jun Chen, Xiaoqian Shen, Xiang Li, and Mohamed Elhoseiny. MiniGPT-4: Enhancing vision-language understanding with advanced large language models. In *ICLR*, 2024. 1, 2