



redhat.
CERTIFIED
ENGINEER

Red Hat Certified Engineer (RHCE)

RHCE 7 Summary

Repositories and Host Allowance/Denial

man 5 hosts_access

vim /etc/yum.repos.d/rhce.repo

```
name=RHCE_RHEL7
baseurl=http://<baseurl>
enabled=1
gpgcheck=0
```

Can be done automatically with the command:

`sudo yum-config-manager --add-repo http://server.example.com/rep`

```
cat /etc/yum.repos.d/server.example.com_repo.rep
```

```
[server.example.com_repo]  
name=added from: http://server.example.com/repo  
baseurl=http://server.example.com/repo  
enabled=1
```

```
# yum repolist
```

1. Allow SSH for a domain and deny SSH to all the others:

```
# vim /etc/hosts.allow
```

```
sshd: .domain.com
```

```
# vim /etc/hosts.deny
```

```
sshd: ALL
```

2. Allow SSH for only specific IP and block all the others:

```
# vim /etc/hosts.deny
```

```
sshd: ALL EXCEPT 192.168.0.1
```

3. Denies all services to all hosts unless permitted in hosts.allow:

```
# vim /etc/hosts.allow
```

```
ALL: .foobar.edu EXCEPT terminalserver.foobar.edu
```

```
# vim /etc/hosts.deny
```

```
ALL
```

4. Access granted by default, redundant file hosts.allow

```
# vim /etc/hosts.deny
```

```
some.host.name, .some.domain
```

```
# vim /etc/hosts.deny
```

```
ALL EXCEPT in.fingerd: other.host.name, .other.domain
```

5. Rules can be also only in one file, for example:

```
# vim /etc/hosts.allow
```

```
ALL: .friendly.domain: ALLOW  
ALL: ALL: DENY
```

```
# vim /etc/hosts.allow
```

```
ALL: .bad.domain: DENY  
ALL: ALL: ALLOW
```

Recover root password

```
reboot
e
linux16...
rd.break enforcing=0
ctrl+x
switch_root:/# mount -oremount,rw /sysroot
switch_root:/# chroot /sysroot
sh-4.2# passwd root
Changing password for user root.
New passwd: mypassword
Retype new password: mypassword
passwd: all authentication token updated
successfully.
sh-4.2# exit
switch_root:/# exit
logout

...
[ OK ] Started Network Manager Script Dispatcher
Service.
[ OK ] Started Crash recovery kernel arming.
[ OK ] Reached target Multi-User System.

CentOS Linux 7 (Core)
Kernel 3.10.0-229.14.1.el7.x86_64 on an x86_64

vm login: root
Password: mypassword

# restorecon /etc/shadow
# setenforce enforcing
```

SERVICES

```
systemctl --failed --type=service
systemctl show <unit>
systemctl status <-l> <unit> <-l>
systemctl stop|start|restart|reload <unit>
systemctl mask|unmask <unit>
systemctl enable|disable <unit>
systemctl list-dependencies <unit>
systemctl list-units --type=service --all
systemctl list-unit-files --type=service
systemctl get-default
systemctl set-default <graphical|multi-
user|rescue|emergency>
systemctl isolate <graphical|multi-
user|rescue|emergency>
```

IPV4

```
nmcli dev status
nmcli con show <name>
nmcli con show --active
ip addr show <eth0> / ip a
ip link / ip l
nmcli con add con-name <name> type ethernet ifname
<eth0> ip4 xxx.xxx.xxx.xxx/24 gw4 xxx.xxx.xxx.xxx
nmcli con mod <name> ipv4.addresses "192.0.2.2/24
192.0.2.254"
nmcli con <up|down> <name>
nmcli dev status
nmcli dev dis <eth0>
nmcli con mod <name> +ipv4.dns xxx.xxx.xxx.xxx
    vim /etc/sysconfig/network-script/ifcfg-
<name>
nmcli con reload
nmcli con del <name>
```

```
hostname
hostnamectl set-hostname <name>
    vim /etc/hostname
hostnamectl status
ip route / ip r
ss -tulpn | grep sshd
```

IPV6

```
nmcli con add con-name <name> type ethernet ifname
<eth0> ip6 xxxx:xxxx:xxx:x:x:x/64 gw6
xxxx:xxxx:xxx:x:x:x
ip -6 route show
ping6 xxxx:xxxx:xxx:x:x:x
ping6 xxxx:xxxx:xxx:x:x:x<%eth1> for link-local
addresses and multicast groups
tracepath6 xxxx:xxxx:xxx:x:x:x
ss -A inet -n
netstat -46n
nmcli con mod <name> ipv6.method manual
```

TEAMING

man 5 nmcli-examples man 5 teamd.conf /usr/share/doc/teamd-1.25

```
nmcli con add con-name <team0> type team ifname
<team0> config '{ "runner": { "name": "
<activebackup|broadcast|loadbalance|roundrobin|lacp>"
}}'
```

Must be before **ipv4.method**

```
nmcli con mod <team0> ipv4.address xxx.xxx.xx.x/24
```

```
nmcli con mod <team0> ipv4.method manual  
nmcli con mod <team0> connection.autoconnect yes
```

or **autoconnect yes** during **con add**

```
nmcli con add con-name <team0-port1> type team-slave  
ifname <eth0> master <team0>  
nmcli con add con-name <team0-port2> type team-slave  
ifname <eth1> master <team0>
```

-con-name <teamX-portX> not necessary, default is **team-slave-
<IFACE>**

```
nmcli con up <team0>  
nmcli con up team0-port1  
nmcli con up team0-port2  
nmcli dev dis eth1  
teamdctl <team0> state  
teamdctl <team0> config dump  
teamnl <team0> ports  
teamnl <team0> options  
teamnl <team0> getoption activeport  
teamnl <team0> setoption activeport <2>
```

If you make a mistake:

```
nmcli con mod <team0> team.config '{"runner":  
{ "name": "activebackup" } }'
```

BRIDGING

```
nmcli con add con-name <bridge0> type bridge ifname  
<br0>  
b/ nmcli con add con-name <bridge0-port1> type  
bridge-slave ifname <eth0> master <br0>  
c/ nmcli con add con-name <bridge0-port2> type  
bridge-slave ifname <eth1> master <br0>  
brctl show
```

BRIDGE=brteam0 */etc/sysconfig/network-scripts/ifcfg-team*

FIREWALL

man 5 firewalld.richlanguage

Understand Zones

man firewalld.zones

```
systemctl mask <iptables|ip6tables|ebtables>  
firewall-cmd --set-default zone=  
<dmz|trusted|home|internal|work|public|external|block  
|drop>
```

- **trusted**=all incoming traffic allowed

- **home**=reject incoming unless matching outgoing, accept incoming ssh,mdns,ipp-client,samba-client,dhcpv6-client
- **internal**=same as home
- **work**=reject incoming unless matching outgoing, accept incoming ssh,ipp-client,dhcpv6-client
- **public**=reject incoming unless matching outgoing, accept incoming ssh,dhcpv6-client *[DEFAULT]*
- **external**=reject incoming unless matching outgoing, accept incoming ssh, masquerading enabled
- **dmz**=reject incoming unless matching outgoing, accept incoming ssh
- **block**=reject incoming unless matching outgoing
- **drop**=reject incoming unless matching outgoing, does not respond at all

Rules

/etc/firewall.d; /usr/lib/firewalld

```
firewall-cmd --<get-default-zone|set-default-
zone|get-zones|get-services|get-active-zones|list-
all>
firewall-cmd --<add|remove-rich-rule=RULE|query-rich-
rule=RULE|list-rich-rules>
firewall-cmd --<remove-service=SERVICE|remove-
port=PORT/PROTOCOL>
firewall-cmd --permanent --zone=<name> --add-
source=xxx.xxx.xx.x/24
firewall-cmd --timeout=60 --zone=<name> --add-
service=mysql
firewall-cmd --reload
firewall-cmd --remove-service=haproxy --zone=public
firewall-cmd --direct --get-all-rules
firewall-cmd --get-zone-of-interface=eth0
```

Rich Rules **rule source destination [service|port|masquerade|forward-port] log audit**

```
firewall-cmd --permanent --zone=<name> --add-rich-rule='rule family=ipv4 source address=xxx.xxx.xx.x/32 reject'
firewall-cmd --permanent --zone=<name> --add-rich-rule='rule family=ipv4 source address=xxx.xxx.xx.x/24 port=xxxx-xxxx protocol tcp <accept|reject|drop>'
firewall-cmd --add-rich-rule='rule service name=ftp limit value=2/m accept'
firewall-cmd --permanent --zone=<name> --add-masquerade
firewall-cmd --permanent --zone=<name> --add-rich-rule='rule family=ipv4 source address=xxx.xxx.xx.x/24 masquerade'
```

Logging

rule ... <log> prefix="ssh" level="<notice|emergency|alert|crit|error|warning|info|debug>" <audit> limit value="rate/duration"

Port Forwarding (Rich rule & Normal Rule)

```
firewall-cmd --permanent --add-rich-rule='rule family=ipv4 source address=xxx.xxx.xx.x/24 forward-port port=xx protocol=tcp to-port=xx to-addr=xxx.xx.xx.x'
firewall-cmd --permanent --zone=<name> --add-forward-port=port=<xxxx>:proto=<tcp>[:toport=<xxxx>:toaddr=<xxx.xxx.xx.x>]
firewall-cmd --<remove-rich-rule=RULE|query-rich-rule=RULE|list-rich-rules>
```

SELinux

man 8 semanage-fcontext

Install setools-console and list context

```
yum -y install setools-console  
seinfo -t | grep <string>
```

SELinux Policy Management port mapping tool

```
semanage port -l
```

```
semanage port -<a|d|m> -t http_port_t -p tcp <88>
```

m=same as removing & adding

```
yum -y install selinux-policy-devel
```

Create or update the manual page index caches

```
mandb
```

Same as apropos, search the manual page names and descriptions:

```
man -k _selinux
```

Generate SELinux man pages sepolcymanpage

```
sepolcymanpage -a
```

DNS

man unbound.conf

This is the old way of doing things, now handled by nmcli

```
vim /etc/resolv.conf
```

```
host -v -t A example.com
host -v -t AAAA a.root-servers.net
host -v -t A ipa-ca-server0.example.com
host -v -t PTR 172.25.0.10
host -v -t PTR 2001:503:ba3e::2:30
host -v -t <NS|SOA|MX|TXT> example.com
host -v -t SRV _ldap._tcp.server0.example.com
```

Installation

```
yum -y install unbound
systemctl start unbound
systemctl enable unbound
```

Configuration

```
vim /etc/unbound.conf
```

Default is only localhost

```
interface: 0.0.0.0
```

Default does not accept any connections

```
access-control: 172.25.0.0/24 allow
```

dot stands for the root domain

```
forward-zone:  
    name: "."
```

Forward query to what DNS

```
forward-addr: 172.25.254.254
```

Domains not configured with DNSSEC

```
domain-insecure: example.com
```

```
unbound-checkconf
systemctl restart unbound
firewall-cmd --permanent --add-service=dns
firewall-cmd --reload
unbound-control dump_cache > dump.out
unbound-control load_cache < dump.out
unbound-control flush_zone <example.com>
unbound-control flush <www.example.com>
getent hosts <example.com>
gethostip <example.com>
dig A <example.com>
dig @<dns.example.com> A <www.example.com>
dig +tcp A <example.com>
dig +dnssec DNSKEY <example.com>
```

POSTFIX AS NULL CLIENT

man 5 postconf

/usr/share/doc/postfix-

2.10.1/README_FILES/STANDARD_CONFIGURATION_README

```
cp /etc/postfix/main.cf ~/main.cf.orig
```

Needs a change of 6 variables

```
vim /etc/postfix/main.cf
```

Which NIC Postfix listens on for incoming/outgoing messages, can be “all”

```
inet_interfaces = loopback-only
```

```
inet_interfaces = all
```

e-mails will appear to come from this domain

```
myorigin = clientX.example.com
```

Forward all messages to this email server

```
relayhost = [server.example.com]
```

Which domains the mail server is an end point for, email address to a domain listed here is rejected

```
mydestination =
```

```
local_transport = error: local delivery  
disabled
```

Allo relay from these networks

```
mynetworks = 127.0.0.0/8, [::1]/128
```

```
postfix check
systemctl restart postfix
postconf <-e> 'VAR = VAL'
```

Show only configuration parameters that have explicit name=value settings in main.cf

```
postconf -n
```

```
firewall-cmd --permanent --add-service=smtp
postqueue -c
mail -s "serverX null client"
student@desktopX.example.com null client test
[ENTER].[ENTER]
```

Postconf Configuration

```
postconf -e "relayhost=[smtp1.example.com]"
postconf -e "inet_interfaces=loopback-only"
postconf -e "mynetworks=127.0.0.0/8 [::1]/128"
postconf -e "myorigin=desktop1.example.com"
postconf -e "mydestination="
postconf -e "local_transport=error: local delivery disabled"
```

iSCSI

Targets – server creating

man 8 targetcli

```
yum -y install targetcli
```

LVM:

```
fdisk <device> => type 8e  
pvcreate <partition>  
vgcreate <vgname> <partition>  
lvcreate -n <lvname> -L <size> <vgname>
```

Example: lvcreate (-l 100%FREE)

```
fdisk /dev/vdb => type 8e  
pvcreate /dev/vdb1  
vgcreate iSCSI_vg /dev/vdb1  
lvcreate -n disk1_lv -L 100m iSCSI_vg
```

```
targetcli  
systemctl start|enable target  
cd /backstores  
block/ create <block1> /dev/iSCSI_vg/disk1_lv  
block/ create <block2> /dev/vdb2  
block/ create <file1> /root/disk1_file 100M  
cd /iscsi  
create iqn.2017-07.com.example:server  
cd iqn.2017-07.com.example:server/tpg1  
acls/ create iqn.2017-07.com.example:  
<client.example.com>  
luns/ create /backstores/block/block1  
luns/ create /backstores/block/block2
```

```
luns/ create /backstores/fileio/file1
portals/ create 172.25.0.11
```

Or simply portals/ create without IP address

```
exit
firewall-cmd --permanent --add-port=3260/tcp
firewall-cmd --reload
```

Targets – client accessing

*/usr/share/doc/iscsi-initiator-utils-6.2.0.873 – Section 7.3 –
node.startup*

man 8 iscsiadm

```
yum -y install iscsi-initiator-utils
vim /etc/iscsi/initiatorname.iscsi
(InitiatorName=client.example.com)
systemctl restart iscsi
systemctl enable iscsi
iscsiadm -m discovery -t sendtargets -p
172.25.0.11:3260
```

Don't need port if it's default

```
iscsiadm -m node -T iqn.2017-07.com.example:server -p
172.25.0.11 -l

iscsiadm -m node -T iqn.2017-05.com.example:server1 -
p 127.25.1.11:3260 -o update -n node.startup -v
automatic
```

```
lsblk --scsi
fdisk /dev/sda
mkfs.xfs/ext4
blkid /dev/sda1 >> /etc/fstab
vim /etc/fstab
UUID=xxxxxx-xxxxxx-xxxxxx /mnt/iscsi xfs _netdev 0 2
```

_netdev is very important and it means mount after networking initialized

```
mount -av
cd /var/lib/iscsi/nodes; ls -lR
iscsiadm -m session -P 3
```

Targets – client disconnecting

```
rm /var/lib/iscsi/nodes/*iqn*
iscsiadm -m node -T iqn.2017-07.com.example:server -p
172.25.0.11 -u
iscsiadm -m node -T iqn.2015-10.com.example:server -p
172.25.0.11 -o delete
systemctl restart iscsi
lsblk
```

NFS

man exports

Server – Insecure

```
yum -y install nfs-utils
systemctl start nfs-server
systemctl enable nfs-server
mkdir /myshare
chown nfsnobody /myshare
vim /etc/exports
    /myshare client.example.com(rw)
    /myshare *.example.com
    /myshare server[0-20].example.com
    /myshare 172.25.0.0/16
    /myshare 172.25.11.10(rw,no_root_squash)
*.example.com(ro)
```

no_root_squash

By default, root on a NFS client is treated as user nfsnobody by the NFS server. That is, if root attempts to access a file on a mounted export, the server will treat it as an access by user nfsnobody instead. This is a security measure that can be problematic in scenarios where the NFS export is used as “/” by diskless clients and root needs to be treated as root.

```
exportfs -r<v>
firewall-cmd --permanent --add-services=nfs
firewall-cmd --reload
showmount -e <server>
```

Client – Insecure

```
yum -y install nfs-utils
systemctl enable nfs
mount server.example.com:/myshare /mnt/nfs
```

```
vim /etc/fstab
    nfserver:/sharename /mountpoint nfs defaults
0 0
```

Server – Secure

```
wget -O /etc/krb5.keytab
http://server.example.com/server.keytab
klist -k; kinit <user>
vim /etc/sysconfig/nfs
    (RPCNFSDARGS="-V 4.2")
systemctl restart nfs-server
systemctl restart nfs-secure-server
systemctl enable nfs-secure-server
vim /etc/exports
    /myseureshare
client.example.com(sec=krb5p,rw)
```

Uses nfsnobody, needs boolean nfsd_anon_write **sec=none** Using UID/GUID linux file permissions [default] **sec=sys** Kerberos and then Linux file permissions apply **sec=krb5** Adds checksums to the data transfers **sec=krb5i** Add encryption **sec=krb5p**

```
exportfs -r<v>
firewall-cmd --permanent --add-services=nfs
firewall-cmd --reload
```

Client – Secure

```
yum -y install nfs-utils
```

Important

```
systemctl start nfs-secure  
systemctl enable nfs-secure
```

```
wget -O /etc/krb5.keytab  
http://server.example.com/client.keytab  
mount -o sec=krb5p,v4.2  
server.example.com:/myseureshare /mnt/nfs  
vim /etc/fstab  
          serverx:/securenfs /mnt/seureshare nfs  
defaults,v4.2,sec=krb5p 0 0  
mount -av
```

SELinux

man 8 nfsd_selinux

Context Default:

- ***nfs_t*** – NFS server to access share, both readable and writable
- ***public_content_t*** – NFS and other services to read contents of the share

For writable, change context: *public_content_rw_t*

Doesn't survive FS relabel: **chcon -t public_content_t
/securenfs/testfile.txt**

Booleans

- ***nfs_export_all_ro*** [default=on],
- ***nfs_export_all_rw*** [default=on],

- ***nfsd_anon_write*** [default=off]. It must be enabled for public_content_rw_t e.g.:

setsebool -P nfsd_anon_write=on

SMB

man 5 smb.conf

Server

```
yum -y install samba samba-client  
cp /etc/samba/smb.conf ~/smb.conf.orig  
vim /etc/samba/smb.conf
```

Defaults that do not specifically define certain items

```
[global]  
workgroup=WORKGROUP
```

User-level security where user must be logged in, requires samba password

```
security=user  
hosts allow=172.25. .example.com
```

e.g. xxx.xx.x.x EXCEPT xxx.xx.x.x, e.g. xxx.xx.x.x/255.0.0.0; can be also **hosts deny=xxx.xx.x.x**

Name of the Share

```
[myshare]
    path=/sharedpath
    writable=<yes|no>
    write list=<user>
```

Even if writable is no

```
        valid users=<blank>|
<user>|@management|+users
```

By default empty, all users have access to the share. Specifies who can log in to the share.

```
[homes]
        read only=no
[printers]
```

```
testparm
groupadd <group>
useradd -s /sbin/nologin -G <group> <user>
```

Change a user's SMB password

```
smbpasswd -<a|x> <user>
```

List all samba accounts configured on the server


```
pdbedit -L
```

```
systemctl reload smb nmb  
systemctl enable smb nmb  
firewall-cmd --permanent --add-services=samba  
firewall-cmd --reload
```

Same as `chmod u+rw,g+rws,o+rx /sharedpath` **`chmod 2775 /sharedpath`**

Client – Single User

```
yum -y install cifs-utils  
vim /root/credentials.txt  
    username=<user>  
    password=<password>
```

Same as `chmod u+r credentials.txt` **`chmod 0400 /root/credentials.txt`**

By default it uses “`sec=ntlmssp`” **`mount -o <username=<user> | credentials=credentials.txt> //server.example.com/<sharename> /mnt/smb`**

```
smbclient -L server.example.com
```

Client – Multiuser

```
yum -y install cifs-utils
```

```
useradd <user>
su - <user>
```

Manage NTLM credentials in the keyring) **cifscreds**

<add|update|clear|clearall> -u <user> <server.example.com>

User must exist on the client and have corresponding SMB account on the server

```
mount -o multiuser,sec=ntlmssp,username=
<user>,credentials=<multiuser_file.txt>
//server.example.com/<sharename> /mnt/multiuser
    vim /root/multiuser_file.txt
        username=
<user_with_minimal_permissions_on_the_share>
        password=<password>
    vim /etc/fstab
        //serverX/sambashare /mnt/multiuser
cifs

credentials=/root/multiuser.txt,multiuser,sec=ntlmssp
0 0
mount -av
smbclient -L server.example.com -U <user>
```

SELinux

man 8 samba_selinux

Context:

- ***samba_share_t*** – SMB to access the share
- ***public_content_t* & *public_content_rw_t*** – accessible by other services as well

Boolean:

- ***smbd_anon_write*** [default=off] must be enabled if public_content_rw_t is applied.
- ***boolean for home dirs:***
 - samba_enable_home_dirs [default=off] on the server
 - use_samba_home_dirs [default=off] on the client

Example: `getsebool -a | grep -i <boolean_name>`

Permanent change to SE policy file on disk `setsebool -P samba_enable_home_dirs=on`

Special Permission	Effect on files	Effect on directories
u+s (suid) 4xxx	Executes as user who owns, not who runs	---
g+s (sgid) 2xxx	Executes as group that owns, not who runs	New files have group owner match group owner of the dir
o+t (sticky) 1xxx	---	Users who can write to the dir can only remove their own files

MARIADB

MariaDB [(none)]> help

```
yum -y groupinstall mariadb mariadb-client
systemctl start mariadb
systemctl enable mariadb
```

Set root passwd,remove anonym,disallow root login,remove testdb
mysql_secure_installation

```
vim /etc/my.cnf  
[mysqld]
```

If blank, only ipv4 is allowed

```
bind-address <::|0.0.0.0|blank>
```

1=not even localhost can connect,only socket

```
skip-networking <1|0>
```

Port number 3306 by default

```
port
```

```
firewall-cmd --permanent --add-rule=mysql  
firewall-cmd --reload  
mysql -u <root> -h <hostname> -p  
create|show|drop database <name>;  
use <name>;
```

Managing Users and Access Rights

MariaDB [(none)]> help grant

```

        create user
<user>@'<%|192.168.1.1%|localhost>' identified by
'<password>';
mysql -u <user> -h <hostname> -p
        grant select on <database.table> to
<user>@<hostname>;
        grant select on <database.*> to
<user>@<hostname>;
        grant select on < *.* > to <user>@<hostname>;
        grant <create,alter,drop> on <database.*> to
<user>@<hostname>;
        grant all privileges on < *.* > to
<user>@<hostname>;
        revoke <select,update,delete,insert> on
<database.table> from <user>@<hostname>;
        flush privileges;
        show grants for <user>@<hostname>;
        drop user <user>@<hostname>;

```

Backup – Logical

```

mysqldump -u root -p <dbname> > /tmp/dbname.dump
mysqldump -u root -p --<all-databases|add-drop-
tables|no-data|lock-all-tables|add-drop-databases> >
/tmp/all.dump

```

--all-databases will include all user information

Backup – Physical

```

mysqladmin variables | grep datadir
cat /etc/my.cnf | grep -i datadir
df /var/lib/mysql

```

/dev/mapper/vg0-mariadb shows 'vg0' is volume group and 'mariadb' is logical volume name

```
vgdisplay vg0 | grep free
tty0: mysql -u root -p
      tty0: flush tables with read lock;
tty1: lvcreate -L20G -s -n mariadb-backup
/dev/vg0/mariadb
```

-s=snapshot, must be large enough to hold the backup

```
tty0: unlock tables;
mkdir /mnt_snapshot
mount /dev/vg0/mariadb-backup /mnt_snapshot
tar cvzf mariadb_backup.tar.gz
/mnt_snapshot/var/lib/mysql
umount /mnt_snapshot
lvremove /dev/vg0/mariadb-backup
```

Restore – Logical

```
mysql -u root -p <dbname> < /backup/dbname.dump
```

Restore – Physical

```
systemctl stop mariadb
mysqladmin variables | grep datadir
rm -rf /var/lib/mysql/*
tar xvzf mariadb_backup.tar.gz /var/lib/mysql
```

Queries

```
show databases;
create table <scientists> (Number int,FirstN
varchar(20),LastN varchar(20));
select * from product;
select * from <table1>, <table2> where
'value1=1' and 'value2=2';
show tables;
describe|delete|insert|rename|select|update
<table>;
insert into <product> (name,price) values
('oracle',1000);
```

Do not insert values into "Auto Increment" fields

```
delete from <product> where <id=1>;
delete from <category> where name like
'Memory';
update <product> set <price=999> where
<id=1>;
select name,price,stock from product;
select * from product where price > 90;
select <field> from <table> where
<field>="x";
exit;
```

APACHE

<http://localhost/manual>

`yum -y install httpd httpd-manual`

```
grep -v '^#' /etc/httpd/conf.d/httpd.conf >  
/etc/httpd/conf.d/httpd_without_comments.conf  
cp /etc/httpd/conf/httpd.conf ~/httpd.conf.orig
```

Global server configuration

`vim /etc/httpd/conf/httpd.conf` Where are the config files

```
ServerRoot "/etc/httpd"
```

Can be 1.2.3.4:80, multiple ports must be specified on separate lines

```
Listen 80
```

If multiple are present, they will be alphabetically included

```
Include conf.modules.d/*.conf
```

```
User apache  
Group apache  
ServerAdmin root@localhost
```

Directives specific to the dir and all descendent dirs

```
<Directory />
```


.htaccess will not be used

```
AllowOverride none
```

Refuse to serve content from dir

```
Require all denied  
</Directory>
```

Where apache looks for files

```
DocumentRoot "/var/www/html"
```

```
<Directory "/var/www/">  
    AllowOverride none  
    Require all granted  
</Directory>  
<Directory "/var/www/html">  
    Options Indexes FollowSymLinks  
    AllowOverride none  
    Require all granted  
</Directory>
```

If this module is loaded, what happens

```
<IfModule dir_module>
```

This file will be used when the directory is requested

```
        DirectoryIndex index.html
    </IfModule>
```

Same as directory but for file wildcards

```
<Files ".ht*">
    Require all denied
</Files>
```

IT will go for /etc/httpd/logs/error_log, which is symlink to
/var/log/httpd/error_log

```
ErrorLog "logs/error_log"
LogLevel warn
CustomLog "logs/access_log" combined
```

Can be disabled by AddDefaultCharset Off

```
AddDefaultCharset UTF-8
```

Same as Regular include

```
IncludeOptional conf.d/*.conf (same as
regular include)
```

Validate the config files **httpd -t**

```
systemctl enable httpd
systemctl start httpd
firewall-cmd --permanent --add-service=http --add-
service=https
firewall-cmd --reload
semanage port -l | grep '^http_'
```

New DocumentRoot for group 'webmasters'

Same as `chmod u+rw, g+rws, o+rx /new/web`

```
mkdir -p -m 2775 /new/web
```

```
groupadd webmasters
chgrp webmasters /new/web
chmod 2775 /new/web
```

X=Keeps executable settings, directories allow directory search, **x**=executable

```
setfacl -R -m g:webmasters:rwX /new/web
setfacl -R -m d:g:webmasters:rwX /new/web
```

Rules are already in place to relabel `/srv/*/www`

```
semanage fcontext -a -t httpd_sys_content_t
"/new/web(/.*)"?"
```

Resets the context on the files AFTER you create them

```
restorecon -Rv /new/web
```

```
systemctl reload httpd
```

Private directory protected by password

```
<Directory /var/www/private>
```

Set basic authentication

```
AuthType basic  
AuthName "This site is protected. Enter password:"
```

Specifies the file with user/passwd

```
AuthUserFile /etc/httpd/conf/userpasswords  
Require user user1
```

Or simply valid-user for anyone in the userpasswords file

```
</Directory>  
htpasswd -bc /etc/httpd/conf/userpasswords user1  
p4ssw0rd  
chmod 0640 /etc/httpd/conf/userpasswords
```

```
chgrp apache /etc/httpd/conf/userpasswords
```

Together with AuthUserFile, you can use AuthGroupFile and Require group. Content of the group file is: `cat /etc/httpd/conf/grouppasswords: groupname: user1 user2 user3`. These users must be in userpasswords file

Virtual Hosts

```
vim /etc/httpd/conf.d/00-site1.conf
```

This block provides access to Document Root further down

```
<Directory /srv/site1/www>
    Require all granted
    AllowOverride none
</Directory>
```

This block must be considered for all connections on 192.168.0.1:80, can be *default*:80 or *:80 which will ALWAYS match for regular http traffic, effectively disabling the main server config from ever being used on port 80.

```
<VirtualHost 192.168.0.1:80>
```

Only applies for within this Virtual Host

```
DocumentRoot /srv/site1/www
```

Name-based virtual hosting, if multiple virtual hosts are defined, the one where hostname matches this will be used, it is best to always explicitly use this. It doesn't need to exist, if you need "match anything" – e.g. all other domains types of VirtualHosts

```
ServerName site1.example.com[:80]
```

If the virtual host needs to be used for more than one domain name, wildcards can be used e.g. *.example.com

```
ServerAlias site1
ServerAdmin root@site1.example.com
ErrorLog "logs/site1_error_log"
CustomLog "logs/site1_access_log"

combined
</VirtualHost>
```

```
httpd -D DUMP_VHOSTS
semanage fcontext -a -t httpd_sys_content_t
"/srv/site1/www(/.*)?"
restorecon -Rv /srv/site1/www
```

If there are multiple catch-all VirtualHosts, they will be executed alphabetically (e.g. 00-default.conf,default.conf,vhost.conf).

How the server selects the proper name-based virtual host? When a request arrives, the server will find the most specific virtual host argument based on IP/port used by the request. If there is more than one containing the best-match, Apache will further compare the ServerName and ServerAlias directives to the server name present in the request. If no matching ServerName/ServerAlias is found in the set of

virtual hosts, then the first listed virtual host that matches will be used.

Any request that does not match existing virtual host is handled by the global server configuration `/etc/httpd/conf/httpd.conf`, regardless of `hostname/ServerName`. When you add virtual host to an existing server and the virtual host match preexisting IP/port, request will now be handled virtual host. In this case, it is wise to create default virtual host with `ServerName` matching the base server.

Access Control Directives

`<RequireAll>` **`</RequireAll>`** – none must fail and at least one must succeed
`<RequireAny>` **`</RequireAny>`** – one or more must succeed
`<RequireNone>` **`</RequireNone>`** – none must succeed

If it is not enclosed in directives, it is automatically `<RequireAny>`

Examples

1. Address is an IP, partial IP, network/mask, network/CIDR, ipv4/ipv6

```
<RequireAll>
    Require all granted
    Require not ip 10.252.46.125
</RequireAll>
```

2. Address is FQDN or part of it, multiple may be provided

```
<RequireAll>
    Require all granted
    Require not ip 192.168.2.1
    Require not host phishers.example.com
    moreidiots.example
```

```
Require not host gov  
</RequireAll>
```

3.

```
Require all denied  
Require local
```

4. Only allows specific hostname

```
Require host test.example.com
```

5. Can be username / UID

```
Require User John
```

6. Can be groupname /GID

```
Require not user badjohn
```

7.

```
Require ip 192.168.0 15.2
```

SSL/TLS


```
yum -y install crypto-utils mod_ssl
genkey <www.example.com>
cp /etc/httpd/conf.d/ssl.conf ~/ssl.conf.orig
grep -v '^#' /etc/httpd/conf.d/ssl.conf >
/etc/httpd/conf.d/ssl_without_comments.conf
vim /etc/httpd/conf.d/ssl.conf
    Listen 443 https
```

If the private key uses passphrase

```
SSLPassPhraseDialog exec:/usr/libexec/httpd-
ssl-pass-dialog
    <VirtualHost _default_:443>
        SSLEngine on
```

ServerName **www.example.com[:443]** **Public Key**

```
        SSLCertificateFile
/etc/pki/tls/certs/www.example.com.crt
```

Private Key

```
        SSLCertificateKeyFile
/etc/pki/tls/certs/www.example.com.key
```

Copy of all CA Certificates

```
        SSLCertificateChainFile
/etc/pki/tls/certs/example-ca.crt
```

```
DocumentRoot /var/www/html
</VirtualHost>
```

This is the Default

```
ls -Zd /etc/pki/tls/
semanage fcontext -a -t cert_t "/etc/pki/tls(/.*)"
restorecon -Rv /etc/pki/tls/
```

Same as `chmod u+rw *.key`

```
chmod 0600 /etc/pki/tls/private/*.key
```

same as `chmod u+rw,g+r,o+r *.crt`

```
chmod 0644 /etc/pki/tls/certs/*.crt
```

HSTS – strict transport security

```
<VirtualHost *:80>
  ServerName...;ServerAlias...;DocumentRoot...
  Header always set Strict-Transport-Security
  "max_age=15768000"
  RewriteEngine on
  RewriteRule ^(/.*)$ https://%{HTTP_POST}$1
  [redirect=301]
</VirtualHost>
```

Dynamic content

1. CGI

```
vim /etc/httpd/conf/httpd.conf
```

First parameter is part of the URL, second is the location of the script.

```
ScriptAlias /cgi-bin/ "/var/www/cgi-  
bin/"
```

```
<Directory /var/www/html>  
    Options none  
    Require all granted  
</Directory>
```

SELinux fcontext: httpd_sys_script_exec_t, httpd_enable_cgi

2. PHP

```
yum -y install mod_php php php-mysql  
    <FilesMatch \.php$>  
        SetHandler application/x-  
httpd-php  
    </FilesMatch>  
    DirectoryIndex index.php
```

3. Python

```
yum -y install mod_wsgi  
vim /etc/httpd/conf/httpd.conf
```

A request for `www.example.com/myapp` will cause the server to run the WSGI application defined in `/srv/my.py`

```
WSGIScriptAlias /myapp "/srv/my.py"
```

SELinux fcontext: `httpd_sys_content_t`

SELinux

man 8 httpd_selinux

```
semanage port -l | grep '^http_'
```

Non-Standard HTTP Ports

```
semanage port -a -t http_port_t -p tcp 88
```

```
semanage fcontext -a -t httpd_sys_content_t  
"/srv/site1/www(/.*)"?"
```

Not before files are present

```
restorecon -Rv /srv/site1/www
```

Context:

httpd_sys_content_t – Dirs where Apache is allowed to access

httpd_sys_content_rw_t – Dirs where Apache is allowed to read/write

httpd_sys_script_exec_t – dirs that contain executable scripts **cert_t** –
Dirs where Apache is allowed to read SSL certificates

Booleans:

httpd_unified *[default=off]* – Simplified/unified policy when turned on

httpd_enable_cgi *[default=on]* – Allowed to run scripts

httpd_tty_comm *[default=off]* – Apache is allowed to access TTY, switch
on when using private key with passkey

httpd_can_network_connect_db *[default=off]* – If the database is on
remote host

httpd_can_network_connect *[default=off]* – If the known port number is
used for db connection

httpd_anon_write *[off]*, **httpd_sys_script_anon_write** *[off]* – If directory
that is using public_content_rw_t is being used by Apache

SHELL ENVIRONMENT

Global

```
/etc/profile  
/etc/profile.d/*.sh  
/etc/bashrc
```

User

```
~/.bash_profile, .bash_login, .profile  
~/.bashrc
```

1. **Profiles** are for setting and exporting of environment variables, as well as running commands that should only be run upon login. Usually, profiles are only executed in a login shell, whereas RCs are executed every time a shell is created, login or non-login
2. RCs are for running commands, setting aliases, defining functions and other settings that cannot be exported to sub-shells.

Supplied MYVAR are marked for automatic export to the environment of subsequently executed commands.

```
export MYVAR  
alias  
unalias  
function () {...}  
set  
unset
```

Bash

```
chmod +x script.sh
```

```
$VARIABLENAME vs. ${VARIABLENAME}  
$FIRST_$LAST = $FIRST_ + $LAST
```

```
    ${FIRST}_${LAST} = $FIRST +_ + $LAST
`CMD` == $(CMD)
$[<ARITHMETIC EXPRESSION>]
FOR <VARIABLE> in <LIST>; do
    <COMMAND>

...
    <COMMAND> referencing <VARIABLE>
DONE
```

Example:

```
cat file
    peter
    john
vim script.sh

#!/bin/bash
file=$(cat $1)
for i in $file; do
    echo $i
done
```

Troubleshooting:

```
bash -x <SCRIPT> or 'set -x' ... 'set +x'
bash -v <SCRIPT> or 'set -v' ... 'set +v'
```

- `$0` = script name itself
- `$1` = first argument of the script
- `$`, `@*` = all arguments
- `$#` = number of arguments
- `$?` = exit status/code (exit 0 -> exit 255)

Comparison:

["\$A" -eq "\$B"]; ... \$?

- *'eq'* or *'='* = equal
- *'ne'* or *'!='* = not equal
- *'gt'* = greater than
- *'ge'* = greater/equal than
- *'lt'* = less than
- *'le'* = less/equal than
- *'z'* = string is null
- *'n'* = string is not null
- *'b'* = file exists & block special
- *'c'* = file exists & character special
- *'d'* = is directory
- *'e'* = exists
- *'f'* = is regular file
- *'L'* = is symbolic link
- *'r'* = read permission granted
- *'s'* = non-zero size
- *'w'* = write permission granted
- *'x'* = execute permission granted
- *'ef'* = same device & inode
- *'nt'* = newer modification date
- *'ot'* = older modification date
- *&&* = AND
- *//* = OR

```
if <CONDITION>; then
    <CMD>
elif <STATEMENT>
else <STATEMENT>
fi
```



```
case <VALUE> in
    <PATTERN1>) <STATEMENT>;
    <PATTERN2>) <STATEMENT>;
    <PATTERN3>) <STATEMENT>;
    <*>) ;;
esac
```

Exercises

dbbackup

```
vim dbbackup
chmod +x dbbackup
```

```
#!/bin/bash
#RHCE page 341, guided exercise

#Variables
DBUSER=root
FMTOPTIONS='--skip-column-names -E'
COMMAND='SHOW DATABASES'
BACKUPDIR=/dbbackup

#Backup non-system databases
for DBNAME in $(mysql $FMTOPTIONS -u $DBUSER -e
"$COMMAND" | grep -v ^* | grep -v information_schema
| grep -v performance_schema); do
    echo "Backing up \"$DBNAME\""
    mysqldump -u $DBUSER $DBNAME >
$BACKUPDIR/$DBNAME.dump
done

#Add up size of all database dumps
for DBDUMP in $BACKUPDIR/*; do
```

```

        SIZE=$(stat --printf "%s\n" $DBDUMP)
        TOTAL=$(( $TOTAL + $SIZE ))
    done

#Report name, size, and percentage of total for each
#database dump
echo
for DBDUMP in $BACKUPDIR/*; do
    SIZE=$(stat --printf "%s\n" $DBDUMP)
    echo "$DBDUMP,$SIZE,$(( 100 * $SIZE / $TOTAL
])%"
done

```

mkaccounts.orig

```

vim mkaccounts.orig
chmod +x mkaccounts.orig

```

```

#!/bin/bash
#RHCE page 347, lab exercise

#Variables
NEWUSERSFILE=/tmp/support/newusers

#Loop
for ENTRY in $(cat $NEWUSERSFILE); do
    #Extract first, last and tier fields
    FIRSTNAME=$(echo $ENTRY | cut -d: -f1)
    LASTNAME=$(echo $ENTRY | cut -d: -f2)
    TIER=$(echo $ENTRY | cut -d: -f4)
    #Make account name
    FIRSTINITIAL=$(echo $FIRSTNAME | cut -c 1 |
tr 'A-Z' 'a-z')
    LOWERLASTNAME=$(echo $LASTNAME | tr 'A-Z' 'a-

```

```

z')
    ACCTNAME=$FIRSTINITIAL$LOWERLASTNAME
    #Create account
    useradd $ACCTNAME -c "$FIRSTNAME $LASTNAME"
done
TOTAL=$(cat $NEWUSERSFILE | wc -l)
TIER1COUNT=$(grep -c :1$ $NEWUSERSFILE)
TIER2COUNT=$(grep -c :2$ $NEWUSERSFILE)
TIER3COUNT=$(grep -c :3$ $NEWUSERSFILE)
TIER1PCT=$(( $TIER1COUNT * 100 / $TOTAL ))
TIER2PCT=$(( $TIER2COUNT * 100 / $TOTAL ))
TIER3PCT=$(( $TIER3COUNT * 100 / $TOTAL ))

#Print the report
echo "\"Tier 1\", \"$TIER1COUNT\", \"$TIER1PCT%\""
echo "\"Tier 2\", \"$TIER2COUNT\", \"$TIER2PCT%\""
echo "\"Tier 3\", \"$TIER3COUNT\", \"$TIER3PCT%\""

```

mkvhost

```

vim mkvhost
chmod +x mkvhost

```

```

#!/bin/bash
#RHCE page 363, guided exercise

#Variables
VHOSTNAME=$1
TIER=$2
HTTPDCONF=/etc/httpd/conf/httpd.conf
VHOSTCONFDIR=/etc/httpd/conf.vhost.d
DEFHOSTCONFFILE=$VHOSTCONFDIR/00-default-vhost.conf
VHOSTCONFFILE=$VHOSTCONFDIR/$VHOSTNAME.conf
WWWROOT=/srv

```

```

DEFVHOSTDOCR00T=$WWWROOT/default/www
VHOSTDOCR00T=$WWWROOT/$VHOSTNAME/www

#Check arguments
if [ "$VHOSTNAME" = '' ] || [ "$TIER" = '' ]; then
    echo "Usage: $0 VHOSTNAME TIER"
    exit 1
else

#Set support email address
    case $TIER in
        1)VHOSTADMIN='basic_support@example.com'
            ;;
        2)VHOSTADMIN='business_support@example.com'
            ;;
        3)VHOSTADMIN='enterprise_support@example.com'
            ;;
        *)echo "Invalid tier specified."
            exit 1
            ;;
    esac
fi

#Create conf directory one time if non-existent
if [ ! -d $VHOSTCONFDIR ]; then
    mkdir $VHOSTCONFDIR
    if [ $? -ne 0 ]; then
        echo "ERROR: Failed creating
$VHOSTCONFDIR."
        exit 1
    fi
fi

#Add include one time if missing
grep -q '^IncludeOptional conf\.vhosts\.d/\*\\.conf$'
$HTTPDCONF
if [ $? -ne 0 ]; then
    #Backup before modifying
    cp -a $HTTPDCONF $HTTPDCONF.orig

```

```

        echo "IncludeOptional conf.vhosts.d/*.conf"
>> $HTTPDCONF
        if [ $? -ne 0 ]; then
            echo "ERROR: Failed adding include
directive."
            exit 1
        fi
    fi

#Check for default virtual host
if [ ! -f $DEFVHOSTCONFFILE ]; then
    cat <<DEFCONFEOF > $DEFVHOSTCONFFILE
<VirtualHost _default_:80>
    DocumentRoot $DEFVHOSTDOCR00T
    CustomLog "logs/default-vhost.log" combined
</VirtualHost>
<Directory $DEFVHOSTDOCR00T>
    Require all granted
</Directory>
DEFCONFEOF
fi

if [ ! -d $DEFVHOSTDOCR00T ]; then
    mkdir -p $DEFVHOSTDOCR00T
    restorecon -Rv /srv/
fi

#Check for virtual host conflict
if [ -f $VHOSTCONFFILE ]; then
    echo "ERROR: $VHOSTCONFFILE already exists."
    exit 1
elif [ -d $VHOSTDOCR00T ]; then
    echo "ERROR: $VHOSTDOCR00T already exists."
    exit 1
else
    cat <<CONFEOF > $VHOSTCONFFILE
<Directory $VHOSTDOCR00T>
    Require all granted
    AllowOverride None

```

```

</Directory>
<VirtualHost *:80>
    DocumentRoot $VHOSTDOCR00T
    ServerName $VHOSTNAME
    ServerAdmin $VHOSTADMIN
    ErrorLog "logs/${VHOSTNAME}_error_log"
    CustomLog "logs/${VHOSTNAME}_access_log"

    common
</VirtualHost>
CONFEOF

    mkdir -p $VHOSTDOCR00T
    restorecon -Rv $WWWROOT
fi

#Check config and reload
apachectl configtest &> /dev/null
if [ $? -eq 0 ]; then
    systemctl reload httpd &> /dev/null
else
    echo "ERROR: Config error."
    exit 1
fi

```

mkaccounts

```

vi mkaccounts
chmod +x mkaccounts

```

```

#!/bin/bash
#RHCE page 370, lab exercise

#Variables
OPTION=$1

```

```

NEWUSERSFILE=/tmp/support/newusers

case $OPTION in
    '')
        ;;
    -v) VERBOSE=y
        ;;
    -h) echo "Usage: $0 [-h|-v]"
        echo
        exit
        ;;
    *) echo "Usage: $0 [-h|-v]"
        echo
        exit 1
        ;;
esac

#Test for dups and conflicts
ACCTEXIST=''
ACCTEXISTNAME=''
if [ $? -eq 0 ]; then
    ACCTEXIST=y
    ACCTEXISTNAME="$(grep ^$ACCTNAME: /etc/passwd
| cut -f5 -d:)"
fi
if [ "$ACCTEXIST" = 'y' ] && [ "$ACCTEXISTNAME" =
"$FIRSTNAME $LASTNAME" ]; then
    echo "Skipping $ACCTNAME. Duplicate found."
elif [ "$ACCTEXIST" = 'y' ]; then
    echo "Skipping $ACCTNAME. Conflict found."
else
    useradd $ACCTNAME -c "$FIRSTNAME $LASTNAME"
    if [ "$VERBOSE" = 'y' ]; then
        echo "Added $ACCTNAME."
    fi
fi

#Loop
for ENTRY in $(cat $NEWUSERSFILE); do
    #Extract first, last and tier fields
    FIRSTNAME=$(echo $ENTRY | cut -d: -f1)

```

```

        LASTNAME=$(echo $ENTRY | cut -d: -f2)
        TIER=$(echo $ENTRY | cut -d: -f4)
        #Make account name
        FIRSTINITIAL=$(echo $FIRSTNAME | cut -c 1 |
tr 'A-Z' 'a-z')
        LOWERLASTNAME=$(echo $LASTNAME | tr 'A-Z' 'a-
z')

        ACCTNAME=$FIRSTINITIAL$LOWERLASTNAME
        #Create account
        useradd $ACCTNAME -c "$FIRSTNAME $LASTNAME"
done
TOTAL=$(cat $NEWUSERSFILE | wc -l)
TIER1COUNT=$(grep -c :1$ $NEWUSERSFILE)
TIER2COUNT=$(grep -c :2$ $NEWUSERSFILE)
TIER3COUNT=$(grep -c :3$ $NEWUSERSFILE)
TIER1PCT=$(( $TIER1COUNT * 100 / $TOTAL ))
TIER2PCT=$(( $TIER2COUNT * 100 / $TOTAL ))
TIER3PCT=$(( $TIER3COUNT * 100 / $TOTAL ))

#Print the report
echo "\"Tier 1\", \"$TIER1COUNT\", \"$TIER1PCT%\""
echo "\"Tier 2\", \"$TIER2COUNT\", \"$TIER2PCT%\""
echo "\"Tier 3\", \"$TIER3COUNT\", \"$TIER3PCT%\""

```

myusers

```

vi myusers
chmod +x myusers

```

```

#!/bin/bash
#RHCE page 419, comprehensive review lab

if [ $# -eq 0 ]; then
    echo "$(basename $0) userlist"

```



```

        echo "$ (basename $0) userinfo <USERNAME>"
    fi

    case $1 in
        userlist) grep -v ':/sbin/nologin$'
/etc/passwd | cut -d: -f1 | sort
                ;;
        userinfo) if [ "$2" == "" ]; then
                    echo "Please specify a
username"
                    exit 132
                fi
                if ! getent passwd $2 &> /dev/null;
then
                    echo "Invalid user"
                    exit
                fi
                getent passwd $2 | cut -d: -f7
                ;;
        *) exit
        ;;
    esac

```