FRC 2023 CHARGED UP -- Robot Design Deep Dive

Each profile comes from the team's own public material: CAD (Onshape, GrabCAD, Fusion 360, STEP), technical binders, code, and Chief Delphi release and reveal threads. Performance data comes from The Blue Alliance.

The CHARGED UP design landscape

The game

CHARGED UP is a cone and cube game. Robots collect CONES and CUBES from the floor or from the SINGLE and DOUBLE SUBSTATIONS. Robots score them on the three rows of the GRID (hybrid, mid, high) to make LINKS. In the endgame, robots DOCK and ENGAGE on the CHARGE STATION. Many designs used an arm, a telescoping arm or an elevator with an end effector for cones and cubes. Auto-balance on the CHARGE STATION was part of most top autonomous routines.

How to use this document

The first section lists the profiled robots in the top 30 by Local EPA. The second section lists the other profiled robots. Each profile gives the archetype, the subsystems, vision, endgame, autonomous routines, the public CAD or binder, and lessons for students. A star marks a study pick. Each study pick has downloadable CAD or a full technical binder and one specific design lesson. "Unconfirmed" means the public material does not state the detail. It does not mean the robot does not have it.

About the EPA numbers

The Statbotics data API is offline. EPA is Local EPA (approx): it was computed from The Blue Alliance match data with the open-source Statbotics model (github.com/avgupta456/statbotics). The rank order follows Statbotics. The absolute values can differ from statbotics.io. Records are win-loss-tie totals from official events on The Blue Alliance.

Profiled robots at a glance (sorted by Local EPA)

	Team	Robot	EPA	Rank	Record	Archetype	Public design
■	**5940 BREAD**	Pain d' Epi	**74**	#3	40-9	Tilted Dyneema elevator; cube/cone floor intake whose spring-loaded co	Onshape CAD
	6329 The Bucks' Wrath	Shock	**74**	#2	55-14	Two-position tipping elevator; dual-motor intake with a wrist; SDS MK4	CD thread
■	**2056 OP Robotics**	UPPERCUT	**73**	#4	61-8	Arm with gas-shock shoulder hold; driver-set cone/cube intake modes; u	Tech binder
■	**2910 Jack in the Bot**	Phantom	**73**	#6	69-16	Shoulder-pivot 2-stage cascade-rigged telescoping arm; floor and shelf	Onshape CAD
■	**3005 RoboChargers**		**73**	#5	58-12	Tower-mounted chain-driven arm with a turnbuckle-tensioned pivoting ge	Onshape CAD
	1678 Citrus Circuits	Tangerine Tumbler	**71**	#10	62-7-1	Roller end effector on a pivoting elevator; notched frame; MK4i swerve	Onshape CAD
	4414 HighTide	Tsunami	**71**	#8	60-10-1	Slanted elevator with a v4b and intake; before Chezy Champs changed to	CD thread
■	**111 WildStang**		**70**	#16	38-5-1	Lift, belt-driven arm and wrist with a cone-wedging gripper; double su	Onshape CAD
	930 Mukwonago BEARs	Cubert Conelius	**70**	#12	47-13-1	Belted roller claw on a pivot; roller intake; continuous-rigged angled	Onshape CAD
■	**2075 Enigma Robotics**	Cypher	**69**	#18	55-15	Arm with shoulder and elbow joints; ground cube intake; Limelight loca	Onshape CAD
	1577 Steampunk	Jesko	**68**	#19	51-12	Arm with telescoping extension; ground intake for tipped cones added a	CD thread
■	**6036 Peninsula Robotics**	Dum-E	**68**	#21	49-18-1	Arm and ground intake with chain drives	GrabCAD
	125 NUTRONs		**66**	#23	62-25-3	Multi-stage telescoping arm (52 in of extension per a team reply) with	CD thread
■	**254 The Cheesy Poofs**	BREAKDOWN	**66**	#28	36-5	Roller claw on a tilted 3-stage 'Laterator' and rear vertical elevator	Tech binder
■	**2767 Stryke Force**	Snake Eyes	**66**	#29	52-14	Arm with bevel-gear claw on a carbon fiber elevator pivoted by printed	Onshape CAD
	3467 Windham Windup		**66**	#25	55-17-4	Double-jointed arm (per interview summary) with pneumatic claw and wri	CD thread
	7157 μBotics	Tai Lung	**65**	#33	33-11-1	65 deg elevator with an arm (one Falcon, 80:1); fork buddy climb	Onshape CAD
	4499 The Highlanders	Iceman	**64**	#39	50-14	Arm with an articulating wrist; roller intake; A-frame tower with tie	Onshape CAD
■	**5460 Strike Zone**	VIPER	**64**	#44	64-28	Claw with Onyx-printed gears on a 2-Falcon carbon fiber arm; Falcon in	Onshape CAD
	972 Iron Claw	Vertigo	**63**	#53	40-27	Roller manipulator on a powered wrist; deployable roller intake; angle	Onshape CAD
	1114 Simbotics	Simbot Scizor	**63**	#50	49-16	Wheeled two-finger claw on a double-jointed arm; three Limelight 2 cam	Onshape CAD
	1727 REX	INCLINE	**63**	#45	51-17-1	Roller intake on a pivoting chain-driven elevator with gas spring assi	Onshape CAD
■	**6672 Fusion Corps**	TARS	**62**	#64	55-19	Pivoting arm with forearm and wrist gearboxes; live-roller cone and cu	Onshape CAD
■	**3357 COMETS**	Kushida	**61**	#79	63-20	3-stage elevator with a geared arm; floor-first intake; 21x26 in chain	GrabCAD
	95 Grasshoppers	Clarke	**60**	#93	30-18	Pneumatic gripper on carbon fiber pivot arm; compliant polycarbonate r	Onshape CAD
■	**341 Miss Daisy**	Miss Daisy XXI	**59**	#105	42-19-1	Belt-driven telescoping arm; roller-claw intake on a 120-deg locking w	Onshape CAD
	695 Bison Robotics	Goldmodule	**59**	#109	52-11	Cascading elevator with an Everybot intake (per Behind the Bumpers); s	Drive folder / doc
■	**1706 Ratchet Rockers**	Whiplash	**59**	#111	38-11-1	Cone and cube shooter; Limelight driver assist; swerve with frame corn	Onshape CAD

	Team	Robot	EPA	Rank	Record	Archetype	Public design
■	**4795 Eastbots**	HYDRA	**59**	#106	50-15-1	Roller claw on a wrist; mid-level scorer, no high cones; roller bar cu	Onshape CAD
	6328 Mechanical Advantage		**58**	#116	48-23	Roller end effector on a two-link arm; pivoting roller intake; SDS MK4	Onshape CAD
■	**8177 Vector**	Velocity	**58**	#112	36-24-2	Triple-roller intake for tipped/standing cones and cubes on a NEO wris	Onshape CAD
	971 Spartan Robotics	Doffle	**57**	#142	29-16	Two-roller end effector on a multi-DOF arm with wrist roll, on a tall	Onshape CAD
■	**2337 EngiNERDs**	Vision	**57**	#145	45-17-1	Shoulder, elbow and wrist arm with rope-driven elbow and cable-driven	Onshape CAD
	177 Bobcat Robotics	The Bobcat	**54**	#191	48-19	Double-jointed arm on an angled elevator; swerve	Onshape CAD
	1102 M'Aiken Magic		**54**	#200	45-21	Roller head on a long pivoting arm on an angled truss tower; SDS MK4i	Onshape CAD
	2713 Red Hawk Robotics		**54**	#180	34-21-1	Roller gripper on a four-bar, on a tilted Dyneema-driven elevator; MK4	Onshape CAD
■	**3847 Spectrum**	X-Ray 2023	**54**	#182	44-20	Cube shooter (per Behind the Bumpers); elevator with a slide and arm/i	CAD release
■	**955 Ctrl C**		**53**	#212	44-28	Roller claw on an extension that cannot reach the floor; ground cube i	Onshape CAD
■	**2881 Lady Cans**	SCoRpion	**53**	#222	34-26	Two-lead-screw pivoting and extending arm with a suction-cup end effec	GrabCAD
■	**401 Copperhead Robotics**	Mushussu	**52**	#251	42-21-1	Double-sided arm (250-deg rotation, 30 in extension) with a 330-deg be	Onshape CAD
	1351 TKO		**52**	#260	19-7	Wheeled end effector on a vertical elevator that also intakes; A-frame	Onshape CAD
■	**7461 Sushi Squad**		**52**	#256	36-25	Claw on a chain-driven pivot arm with pneumatic extension; intake with	Onshape CAD
	2582 PantherBots		**51**	#268	35-24-2	Roller intake on a pivot at the end of a cross slide, on a tilted belt	Onshape CAD
	2877 LigerBots		**51**	#282	25-24	Pivoting 2-stage telescoping arm with cascade rigging and constant-for	Onshape CAD
■	**4201 The Vitruvian Bots**	Gridlock	**51**	#279	26-14	3-stage rope-driven elevator; 180-deg virtual 4-bar with 3-roller inta	Onshape CAD
■	**1561 Roboducks**	Duck N' Cover V2	**50**	#327	39-20	Cube-only: pivoting arm with a cube shooter/intake; SDS MK4i L2 swerve	CAD download
	4561 TerrorBytes	Fulcrum	**48**	#356	45-16-2	Double-jointed arm on MAX Tube; Everybot-inspired intake added at Stat	Onshape CAD
	1714 MORE Robotics		**47**	#402	26-15	Elevator; new intake, elevator carriage and wrist in place of the shou	Onshape CAD
	4392 The Deceivers	Achilles	**47**	#392	32-26	Funnel cone holder with roller wheels on a two-joint arm (shoulder and	Onshape CAD
■	**131 CHAOS**		**42**	#560	20-25	Extender on linear sliders with a wrist and a light roller gripper; 1/	CD thread
	4322 Clockwork		**42**	#571	16-9	Floor pickup limited to cubes; arm on a pivot shaft with a chain; swer	Onshape CAD
	3136 O.R.C.A.		**41**	#600	25-21	Tilted 3-stage elevator, intake on the middle carriage; narrow frame o	Onshape CAD
	293 SPIKE		**39**	#710	26-16-2	Cable-actuated claw on a single pivot arm on a T-slot tower; tank driv	Onshape CAD
	1018 Pike RoboDevils		**39**	#687	11-18	Single-joint 'Sushi arm' planned for low/mid scoring and substation pi	Onshape CAD
	3739 Oakbotics	Blue Steel	**39**	#697	20-28	Intake redesigned after week 1; MAXSwerve chassis	GrabCAD
	1072 Harker Robotics		**38**	#767	20-18	Inclined elevator with no end effector in the CAD; pneumatic wheel arm	Onshape CAD
■	**3926 MPArors**	Snowdrift	**38**	#734	14-17	Low-goal cycler with one intake for both pieces; slim modified KoP tan	Onshape CAD

	Team	Robot	EPA	Rank	Record	Archetype	Public design
	1710 The Ravonics Revolution	SlipSTream	**37**	#821	27-20	Pneumatic claw with self-leveling pads; 2-roller intake; double-jointe	Fusion 360 CAD
	4488 Shockwave	Supercell	**37**	#820	22-25	Top and bottom roller claw on a long arm that pivots atop a fixed angl	Onshape CAD
	342 Burning Magnetos		**36**	#879	29-24	Roller gripper claw on a single-pivot arm from a tall tower; 6-wheel t	Onshape CAD
	8738 Slice		**35**	#905	28-23	Arm on an elevator; Kit of Parts tank drivetrain; offseason rebuild ad	Onshape CAD
■	**555 Montclair Robotics**		**34**	#987	18-24	3-stage cascade elevator with horizontal scissor 'stinger', printed pn	Onshape CAD
■	**3737 Roto Raptors**	BB Mantis	**20**	#2221	12-16-2	Passive claw on a cord-extended arm; through-robot handling; all motor	Drive folder / doc
■	**9062 Critical Circuits**	Bryce	**19**	#2368	15-34	Long-range dual-flywheel cube shooter, two side roller intakes, 38 x 2	Onshape CAD
	663 Power Sharks	MAKO	**18**	#2546	11-12	Pneumatic claw on a motorized wrist, pneumatic arm extender, electric	Onshape CAD
	7125 Tigerbotics	Killua	**9**	#3243	9-15	Pneumatic pincer with compliant wheels on a pivot arm; angled three-st	Onshape CAD

■ = study pick: downloadable CAD or a full technical binder, and one specific design lesson. EPA is Local EPA (approx), computed from The Blue Alliance match data. Records are win-loss-tie totals from official events.

Top-30 robots by Local EPA

■ Study pick | **5940 BREAD** Pain d' Epi | USA-CA | **Local EPA 74 (#3)** | 40-9

Tilted Dyneema elevator; cube/cone floor intake whose spring-loaded cone roller sets the handoff orientation

SCORING (CONE / CUBE) End effector receives cones from the floor intake in a set orientation.	**INTAKE** Floor intake for cubes and cones. The beta robot had a cube-only floor intake; the cone roller was added later. The cone layout rotates the 3 in polycarbonate roller about the intake pivot and adds a 2 in flex wheel shaft that spins opposite the other rollers. Surgical tubing pulls the 2 in roller outward; when a cone is in far enough the rollers lock and the 2 in roller pivots about the 3 in roller to a hard stop. The team states another motor would have put the robot over the weight limit.
ARM / ELEVATOR Tilted elevator, adapted from a 2022 off-season project elevator. That project tested a belted elevator; the team chose Dyneema instead because it was easier to package, routed through the tubes, and the belt gearbox took more space.	**DRIVETRAIN** Swerve: the team lists swerve offsets among possible causes of the same playoff failure.
ENDGAME Unconfirmed	**AUTONOMOUS** The team added cone floor pickup so auto could place 2 cones and a cube for a high link, instead of a preloaded cone and two cubes. They expected many Championship matches to tie at 193 points and be decided by auto. They state supercharging later reduced the value of this. At Central Valley, a practice-match auto failed; AdvantageKit log replay showed a wrong heading target, traced to how the code flipped it.
VISION AprilTag vision: the team lists it among possible causes when the robot lost control in a division playoff match.	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- Try passive geometry before adding a motor, as in the spring-loaded cone roller.
- Off-season projects can feed the season: the team says the project elevator helped them build quickly.
- Log everything and replay it: the replay let the electrical team fix the robot before the next Curie playoff match.

Onshape CAD: Onshape CAD · CAD and code release (CD) · Onshape CAD · Code (GitHub) · Behind the Bumpers video

---

Profile | **6329 The Bucks' Wrath** Shock | USA-ME | **Local EPA 74 (#2)** | 55-14

Two-position tipping elevator; dual-motor intake with a wrist; SDS MK4i drivetrain; 24 x 24 in frame

SCORING (CONE / CUBE) Dual-motor intake with a wrist. The wrist is driven by Falcon motors; its position comes from their internal encoders after the robot starts each match in the same position.	**INTAKE** Dual-motor intake with a wrist (see scoring). The Behind the Bumpers summary mentions in-fill intake wheels.
ARM / ELEVATOR Two-position tipping elevator. The Behind the Bumpers summary describes a two-stage cascading elevator. Extension is driven by Falcon motors and measured with their internal encoders.	**DRIVETRAIN** SDS MK4i modules. Frame is 24 in x 24 in, set by the team as a design rule.
ENDGAME Unconfirmed	**AUTONOMOUS** Autonomous Award at the Rhode Island event.
VISION Unconfirmed	**PUBLIC CAD / DESIGN** Reveal thread (CD)

LESSONS FOR STUDENTS

- Motor internal encoders can be enough for position control if the robot starts each match in the same position; the team reused this scheme on its 2024 robot.

CD thread: Reveal thread (CD) · Reveal thread (CD) · Behind the Bumpers (CD) · Team post on the elevator and wrist control (2024 thread, CD)

■ Study pick

2056 OP Robotics UPPERCUT

Canada

Local EPA 73 (#4)

61-8

Arm with gas-shock shoulder hold; driver-set cone/cube intake modes; upward Limelight; MK4i swerve

SCORING (CONE / CUBE) The driver set cone or cube mode; the robot had no colour sensor. LEDs flash white when a game piece is acquired. This tells the driver the robot holds it when the intake is out of view.	**INTAKE** Intake with side rollers and a top roller. The driver chose cone or cube mode, because the side roller speeds and the top roller position differed by game piece. In cone mode a beam break sensor detected the cone and the intake clamped onto it automatically. In cube mode the rollers stopped when the cube hit a bumper switch at the back of the intake. The OP names 'single substation floor pickups' as a case where the driver cannot see the intake or the game piece.
ARM / ELEVATOR Arm on a shoulder pivot. Gas shocks went over centre to hold the shoulder pivot in the starting configuration. The top pivot point attaches to 1/8 in box beam. On the practice bot a crack formed there and the tube wall deformed. The team added 1/4 in aluminum plates with four #8 bolts. The OP names Loctite 609 as the retaining compound used to remove backlash.	**DRIVETRAIN** Swerve. The team released STL covers for its swerve modules, and the file name names MK4i. The covers kept foreign material out; the team removed the top cover to inspect each module before and after each event. To grease a module, the team put grease on the end of a zip tie, fed it into the gearbox with the middle cover on, and turned the wheels. A Pigeon 2 gyro showed no noticeable drift over a match.
ENDGAME Unconfirmed	**AUTONOMOUS** The OP reports that Phoenix Pro time sync improved the accuracy and repeatability of the odometry. Autonomous Award at the Archimedes Division and at ONT District Newmarket.
VISION One Limelight in the drivetrain, angled up to track cone nodes and AprilTags. No game piece detection in auto or teleop; the team states it did not need it.	**PUBLIC CAD / DESIGN** Technical binder (PDF)

LESSONS FOR STUDENTS

- Use the practice robot to find structural failures, as the team did with the top pivot mount.

Tech binder: Technical binder (PDF) · Technical binder release thread (CD) · Technical binder (PDF) · Swerve module covers (STL zip) · Behind the Bumpers thread (CD) · Behind the Bumpers video

■ Study pick

2910 Jack in the Bot Phantom

USA-WA

Local EPA 73 (#6)

69-16

Shoulder-pivot 2-stage cascade-rigged telescoping arm; floor and shelf pickup; SDS Mk4i L3 swerve, 26x28 frame

SCORING (CONE / CUBE) The robot scores on all three levels. The cone sits in the intake and the robot ejects it to score, so the intake also acts as the end effector.	**INTAKE** Picks up cones and cubes from the ground and the shelf, including fallen-over cones. A Time of Flight sensor on the inner wall of the intake measures where the cone sits.
ARM / ELEVATOR 2-stage cascade-rigged telescoping arm on a shoulder pivot. Cord on pulleys on the first stage drives the second stage from the first stage's motion. An A-frame structure with a dead-axle main pivot is part of the low-backlash design. Joints use only the integrated Falcon encoders, with REV ION gears for a tight fit on hex shafts.	**DRIVETRAIN** SDS Mk4i L3 swerve on a 26x28 frame perimeter. Three gearings were run: standard L3, L3 with a 16T pinion, and L3 with an 18T pinion. The robot weighs about 90 lbs without ballast and is under 17 in tall when stowed.
ENDGAME Auto balancing on the Charge Station.	**AUTONOMOUS** 3 game piece autonomous and auto balancing, listed as separate features. Paths come from PathPlanner. The team did not use the PathPlanner marker system; custom code runs commands in parallel or in sequence with path following.
VISION Two angled cameras, used constantly in teleop to relocalize the robot on the field. Camera model and coprocessor: Unconfirmed.	**PUBLIC CAD / DESIGN** 'Phantom' CAD (Onshape)

LESSONS FOR STUDENTS

- Sequence arm joints to limit tipping: the code does not extend the arm until the shoulder is within an allowed distance of its setpoint.
- A telescoping stage can be driven without its own motor; trace the cord and pulleys that drive stage two.
- Driver-assisted scoring: the robot PIDs to the nearest column, and it ejects only when X, Y, yaw and pitch pass strict thresholds. The team reports the driver was often faster.
- Path-following feedforward can be tuned by hand: the team turns off path PID, tunes velocity feedforward on a slow straight path, then acceleration feedforward, and repeated this for each of the drive gearings.

Onshape CAD: 'Phantom' CAD (Onshape) · CAD and tech binder release (CD) · Robot reveal (CD) · Code release (CD) · Code (GitHub) · Tech binder (PDF) · Behind the Bumpers video

---

■ Study pick

3005 RoboChargers

USA-TX

Local EPA 73 (#5)

58-12

Tower-mounted chain-driven arm with a turnbuckle-tensioned pivoting gearbox; wrist (per Behind the Bumpers)

SCORING (CONE / CUBE) Fully articulating wrist, per the Behind the Bumpers video description.	**INTAKE** 'On the fly' intake, per the Behind the Bumpers video description.
ARM / ELEVATOR Chain-driven arm on a tower. The arm gearbox plates react off an aluminum cross tube at the base of the tower, and 2 turnbuckles tension the chain. The mount is a slip fit on the tube with collars holding it axially, so the whole gearbox pivots around the tube. This also gives some side-to-side play to adjust chain tracking. A reply in the thread mentions an Onyx-printed e-chain support on a telescoping part of the arm.	**DRIVETRAIN** Swerve on 4 REV MAXSwerve modules with 3 in wheels. The BOM names NEO and NEO 550 motors with SPARK MAX controllers (per CAD).
ENDGAME No endgame mechanism in the CAD (per CAD).	**AUTONOMOUS** Unconfirmed
VISION Unconfirmed	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- The team took the pivoting gearbox mount from heavy equipment practice: it makes it easier to keep the shafts parallel, and rotational motion typically needs fewer and simpler parts than a linear adjuster.
- One cross tube does two jobs, structure and pivot. The team says they wanted the cross member for structure anyway.
- The team expected to adjust chain tension often because of the force from the fast arm, so the adjustment is part of the mount.
- The team presents the working model as an example of a well-organized but practical FRC CAD model.

Onshape CAD: Onshape CAD · CAD release (CD) · Onshape CAD · Behind the Bumpers (CD) · Behind the Bumpers video

Profile	1678 Citrus Circuits Tangerine Tumbler USA-CA	Local EPA 71 (#10) 62-7-1

Roller end effector on a pivoting elevator; notched frame; MK4i swerve

SCORING (CONE / CUBE) Roller end effector at the top of the elevator. Three belt-linked rollers sit between side plates, with a bar below them (per CAD).	**INTAKE** No separate ground intake is in the CAD. One side of the frame has a notch with a gap in the bumpers (per CAD).
ARM / ELEVATOR Elevator on a pivot at one end of the frame. The elevator uses WCP-0897 bearing blocks and REV MAXTube. Two REV MAX Planetary gearboxes, 20DP gears and a #35 chain with a 54T sprocket are in this assembly (per CAD).	**DRIVETRAIN** Swerve with four SDS MK4i modules in the Falcon 500 configuration. CANcoders are in the modules (per CAD).
ENDGAME Unconfirmed	**AUTONOMOUS** Unconfirmed
VISION Unconfirmed	**PUBLIC CAD / DESIGN** Competition robot CAD (Onshape)

Onshape CAD: Competition robot CAD (Onshape) · CAD and code release (CD) · Competition robot CAD (Onshape) · CAD and code release page (team site) · Robot reveal 'Tangerine Tumbler' (CD) · Training resources (Google Drive) · Behind the Bumpers video

Profile	4414 HighTide Tsunami USA-CA	Local EPA 71 (#8) 60-10-1

Slanted elevator with a v4b and intake; before Chezy Champs changed to a 1323-style arm and wrist

SCORING (CONE / CUBE) At season events: a v4b with an intake. Before Chezy Champs the v4b and intake were replaced with a 1323-style arm and wrist, in the team's own style with the same roller locations. The new arm and wrist are 7075, light weighted to reduce mass.	**INTAKE** Intake plates are 7075-T6 aluminum; the plates took big hits without damage, though a front roller snapped. Rollers are 1.25 in polycarbonate tube with 1 in silicone tubing stretched over it, with Markforged-printed hubs glued in, on 3/8 in ThunderHex. The team added star wheels after seeing a pair on 1323's intake. The intake pivot runs on a single Falcon at about 30:1 in Motion Magic Voltage mode.
ARM / ELEVATOR Slanted elevator with WCP inline elevator blocks and a tensioned belt last stage. The team names worn constant force springs as the only major elevator issue; it was tensioned once. Before Chezy Champs the team added ballast low on the back of the elevator to prevent tipping.	**DRIVETRAIN** The Behind the Bumpers summary mentions custom swerve modifications.
ENDGAME Unconfirmed	**AUTONOMOUS** In season the robot scored two mid cones and one high cone in auto; after the Chezy Champs changes, two high cones without tipping. The Behind the Bumpers summary mentions on-the-fly dynamic trajectories. Autonomous Award at Ventura County.
VISION Changed before Chezy Champs: a tower was added to hold a Limelight for more reliable retro tape tracking, plus a rear-facing Limelight for cone tracking in auto. The team says a rear camera was hard to fit on the low side of the slanted elevator before the change.	**PUBLIC CAD / DESIGN** Reveal and design Q&A thread (CD)

LESSONS FOR STUDENTS

- Mechanical stiffness reduces tuning work: the team says PID effort approaches zero when a mechanism is light and has low backlash.
- Hex gear backlash can be removed with .002 in shim stock tape wrapped around 1-3 faces of the bore; the team posted photos of the process.
- On position subsystems the team prefers well-shimmed gears and chain to belts.
- The team builds without a lathe, cutting shafts on a cold saw and spacing them with COTS spacers and standoffs.

CD thread: Reveal and design Q&A thread (CD) · Reveal and design Q&A thread (CD) · Reveal video · Behind the Bumpers (CD) · Behind the Bumpers video

■ Study pick

111 WildStang

USA-IL

Local EPA 70 (#16)

38-5-1

Lift, belt-driven arm and wrist with a cone-wedging gripper; double substation loading; REV MAXSwerve

SCORING (CONE / CUBE) A gripper on a wrist scores cones and cubes. The gripper wedges on the funnel shape of a cone. After a cone trap in a Seven Rivers match, the team added a plastic closeout plate to the front of the robot. The team reports 11-12 teleop cycles after its Championship upgrades, scoring on the middle set of links.	**INTAKE** Loads at the double substation from the human player. Before the Championship, the team reviewed its season match video and found that substation pickup time was its biggest slowdown. Changed for the Championship: cones were fed on their side, an idea the team credits to team 324. The scoring auto-align code was reused to set the pickup pose at the substation, with the lift partly extended as a crumple zone.
ARM / ELEVATOR A lift with constant force springs, a belt-driven arm and a wrist with an encoder. The arm is backlash sensitive and uses MAX Planetary gearboxes. A wrist encoder broke from an impact at Seven Rivers; the team then supported the encoder axle on both ends. Rigging capstans are 3D prints sleeved in aluminum so rigging tension does not crush them.	**DRIVETRAIN** REV MAXSwerve. The team bought five modules in fall 2022 because SDS MK4i supply was uncertain; it ran SDS MK3 in 2021 and 2022. The drivetrain used NEOs. The team zeros modules in the REV fixture with only the bevel fork installed, and machined clearance pockets into the fixture.
ENDGAME The team mentions balancing at the end of a Seven Rivers playoff match.	**AUTONOMOUS** Added before the Championship: a 3-piece auto on the bump side, which kept it compatible with 7-game-piece alliance autos. The team uses its own path follower, which takes velocity, acceleration and direction from the path and handles rotation separately. TBA lists the Autonomous Award at the Seven Rivers Regional.
VISION Two Limelight cameras in a 'cross-eyed' layout. The second camera widened the field of view so a nearby AprilTag was always in sight, instead of relying on wheel odometry. Changed for the Championship: both cameras were turned up to see the loading station tag, about 35 deg cross-eyed and 10 deg above the horizon.	**PUBLIC CAD / DESIGN** 111 CAD (Onshape)

LESSONS FOR STUDENTS

- Use the shape of the game piece: the team says a cone fed on its side gives the gripper a larger target.
- Check the field of view at the scoring spots, where one camera would lose a nearby AprilTag.
- Split the controls by role: the driver chose when each robot action happened, and the operator chose what that action did. A team member says other students picked up driving easily at the fall driver tryouts.

Onshape CAD: 111 CAD (Onshape) · 111 CAD (Onshape) · Build blog (CD) · Code (GitHub) · Code release post (CD build blog) · Behind the Bumpers video

---

Profile

930 Mukwonago BEARs Cubert Conelius

USA-WI

Local EPA 70 (#12)

47-13-1

Belted roller claw on a pivot; roller intake; continuous-rigged angled elevator; SDS MK4i swerve

SCORING (CONE / CUBE) Manipulator with two jaws set in a V. Each jaw has rollers wrapped in orange belts. The manipulator pivots on a gear train at the top of a vertical post (per CAD).	**INTAKE** Roller intake at one end of the frame, with a roller of wheels across the frame width. It sits inside the bumper line in the CAD view (per CAD).
ARM / ELEVATOR Angled elevator in blue tubing, braced to the frame by a second tube. The CAD has an elevator gearbox subassembly and a carriage subassembly. A vertical post carries the manipulator at its top (per CAD).	**DRIVETRAIN** Swerve with 4 SDS MK4i modules. The module model in the CAD uses the Falcon 500 configuration (per CAD).
ENDGAME No endgame mechanism in the CAD (per CAD).	**AUTONOMOUS** Unconfirmed
VISION Unconfirmed	**PUBLIC CAD / DESIGN** Onshape CAD

Onshape CAD: Onshape CAD · CAD and code release (CD) · Onshape CAD · Code (GitHub) · Off-season robot CAD (Onshape) · Behind the Bumpers thread (CD) · Behind the Bumpers video

■ Study pick

2075 Enigma Robotics Cypher

USA-MI

Local EPA 69 (#18)

55-15

Arm with shoulder and elbow joints; ground cube intake; Limelight localization in auto

SCORING (CONE / CUBE) The Behind the Bumpers summary mentions a pass-through and a beater bar; the team posts do not describe the end effector.	**INTAKE** Ground cube intake, improved after the Muskegon event.
ARM / ELEVATOR Arm with shoulder and elbow joints. After Muskegon the team reduced backlash in both joints with clocked steel gears and Loctite 680 between gear bore and hex shaft. The top joint uses custom torque-transmission parts; the team considered MAXSpline and did not use it.	**DRIVETRAIN** Drivetrain optimized using Phoenix Pro.
ENDGAME Unconfirmed	**AUTONOMOUS** New autonomous routines after Muskegon, shown in a team video, with Limelight localization. Autonomous Awards at Muskegon and at the Michigan State Championship division.
VISION Limelight localization for autonomous, added after the Muskegon event.	**PUBLIC CAD / DESIGN** Onshape CAD (publication)

LESSONS FOR STUDENTS

- Prototype speed and parts on hand can drive part choice, as with the custom top-joint parts.
- Iterate between events: the team update, posted after its second district event, lists six changes made since its first event, from drivetrain tuning to carry handles.

Onshape CAD: Onshape CAD (publication) · Reveal and CAD/code release thread (CD) · Onshape CAD (publication) · Code (GitHub)

Profile

1577 Steampunk Jesko

Israel

Local EPA 68 (#19)

51-12

Arm with telescoping extension; ground intake for tipped cones added after week 1

SCORING (CONE / CUBE) Unconfirmed	**INTAKE** Ground intake added after ISR District Event #1 to pick up tipped cones without losing the existing intake function. Two outer bearings pass through the plates with shoulders facing out; the inner bearings sit inside with shoulders facing the 5 mm polycarbonate plate, which floats about 1.35 mm between them. The shaft is tapped and closed with end screws. The team names 95, 6328 and 2230 as inspirations.
ARM / ELEVATOR Arm with a telescoping extension. Both use Motion Magic with gravity feedforward. A team planner moves them together and adds at most 2 safe waypoints before the target to avoid the robot and the grid. A spring on the extension helps when the arm is vertical and pulls a cone, and speeds retraction and pickup; in horizontal mode it works against extension.	**DRIVETRAIN** Unconfirmed
ENDGAME Unconfirmed	**AUTONOMOUS** Autonomous Award at ISR District Event #1. A team mentor states the ground intake makes it easier to score multiple cones in auto.
VISION Unconfirmed	**PUBLIC CAD / DESIGN** Reveal thread (CD)

LESSONS FOR STUDENTS

- With the floating bearing mount, the polycarbonate flexes without bolt holes for the bearings.
- The team skipped a full motion profile and used a simple planner to coordinate the two joints.

CD thread: Reveal thread (CD) · Reveal thread (CD) · Behind the Bumpers thread with team replies (CD) · Season recap thread (CD)

■ Study pick

6036 Peninsula Robotics Dum-E

USA-CA

Local EPA 68 (#21)

49-18-1

Arm and ground intake with chain drives

SCORING (CONE / CUBE) Unconfirmed	**INTAKE** Ground intake. Its chain tensioner is cantilevered off the outer gearbox plate; the team states the chain load was low enough for this to work. In the future they would probably consider a larger center-to-center distance to add an inline tensioner. A rectangular cutout in the intake gearbox held the camera mounts used at the first 2 events.
ARM / ELEVATOR Arm with a chain run and idler sprockets. The team states the cantilevered tensioning likely caused excess wear on the standoffs the idler sprockets spin on, though not enough to need replacement. Their off-season redesign used tensioners inspired by team 33.	**DRIVETRAIN** Unconfirmed
ENDGAME Unconfirmed	**AUTONOMOUS** Autonomous Award at Idaho and Autonomous Action Award at CalGames.
VISION Cameras, moved from the intake gearbox to the back of the robot after the first 2 events for better field of view.	**PUBLIC CAD / DESIGN** GrabCAD CAD

GrabCAD: GrabCAD CAD · CAD release thread (CD) · STEP CAD (Google Drive) · GrabCAD CAD · Behind the Bumpers (CD)

Profile

125 NUTRONs

USA-MA

Local EPA 66 (#23)

62-25-3

Multi-stage telescoping arm (52 in of extension per a team reply) with wrist and claw; cube intake

SCORING (CONE / CUBE) Wrist and claw, per the Behind the Bumpers summary. Two SPARK MAX controllers sit in the end effector. The wrist and intake NEOs run on 30A protected circuits.	**INTAKE** Cube intake, per the Behind the Bumpers summary.
ARM / ELEVATOR Multi-stage telescoping arm, per the Behind the Bumpers summary. The arm is 23 in long fully collapsed, with 52 in of linear extension beyond that. End-effector wires run up the arm through a 4-wire power slip ring and a 4-wire CAN slip ring. A helix drum, driven off the arm extension gearbox, spools the cable; surgical tubing on about 8 in of cable keeps tension.	**DRIVETRAIN** On 2023-02-23 a team member gave the weight as 78 lb, with a 26 lb powder-coated steel belly pan still to be added as ballast.
ENDGAME Unconfirmed	**AUTONOMOUS** Unconfirmed
VISION Unconfirmed	**PUBLIC CAD / DESIGN** Behind the Bumpers thread (CD)

LESSONS FOR STUDENTS

- Test the cable drum drive ratio: the team states it took some tweaking.
- The tension element absorbs tolerance and direction changes in the cable path.

CD thread: Behind the Bumpers thread (CD) · Behind the Bumpers thread (CD) · Behind the Bumpers video

■ Study pick

254 The Cheesy Poofs BREAKDOWN

USA-CA

Local EPA 66 (#28)

36-5

Roller claw on a tilted 3-stage 'Laterator' and rear vertical elevator; linear floor intake; balance forks; MK4i swerve

SCORING (CONE / CUBE)
An all-in-one roller claw intakes and scores both cones and cubes from the same side of the robot. The team says it is lightweight and centers cones from the feeder station. The claw wheels are on dead axles: 3D printed pulleys with wheels pressed, glued or bolted on, with embedded 3/8 in ID bearings that spin on 3/8 in round standoffs held between the plates.

INTAKE
Floor intake that deploys linearly on 3D printed Markforged bushing blocks lined with thin teflon tape, in place of a 4-bar; the team credits 125's early robot reveal for the idea. The roller uses the same dead-axle construction as their 2022 robot. A Hall sensor on the retracted hard stop zeros the intake. A 10DP metal gear on a 3/8 in hex jackshaft drives a rack cut into the inner of two 1/4 in polycarbonate side plates. The rack skipped a few times; the team thinks that in a hard impact the plate bends up and the teeth skip over the gear. A pit reset took about 30 seconds. The team recalls that by Championship it reduced the plate clamp bolts to 2, so the plates could flex like leaf springs.

ARM / ELEVATOR
A vertical elevator at the back gives an 'up and in' pose at the feeder station; the team says most other teams had to approach the station slowly because of an extended arm or angled elevator. The elevator carries a 3-stage 'Laterator' with cascade rigging, tilted slightly upward to reach the high cone nodes. The elevator runs on 3/4 in OD, 1/4 in ID radial ball bearings. The Laterator uses 3/8 in OD, 1/4 in ID PEEK bushings rolling on dowel pins to save weight over steel ball bearings. The Laterator tubes are carbon fiber. The team believes many Laterator breaks came from holes drilled through the tubes. Screws thread into billet end plugs or into 1/8 in aluminum 8-32 nut plates slid inside the tube. The 10-32 screws that join the elevator uprights to the A-frame came loose often; the team names them as a source of lost lateral and torsional stiffness and does not recommend the joint.

DRIVETRAIN
Swerve on MK4i modules with Falcon motors; the team supported the Falcon shaft, as in 2022. Custom steel lower L-plates with a chamfer put weight down low and clear the Charge Station. CNC-milled wedges on the wheel yokes smooth the impact of driving over the cable protector. The battery sits in the middle of the swerve base. The robot weighed 115 lb without battery or bumpers and about 138 lb with both.

ENDGAME
A forks carriage for Charge Station balancing; a Hall sensor stops the fork motor when the forks are fully climbed. The team says that by Championship and Chezy Champs it found less use for the forks, because most drivers could triple balance fast. The forks stayed on to add weight at the back and reduce forward tipping.

AUTONOMOUS
A 3-piece auto on the bump (cable protector) side; the wheel wedges were added to make it more reliable. The elevator starts midway up on a small kickstand for a faster first placement. The team says same-side intake and scoring made auto harder, because the robot must spin while driving.

VISION
For game piece sensing, the team used Banner DQ12AB6LV retroreflective sensors, as in other years.

PUBLIC CAD / DESIGN
Technical binder (PDF)

LESSONS FOR STUDENTS

- Printed pulley practice: after a printed 18T 5mm HTD pulley sheared in 2022, the team used more aluminum pulleys and printed the rest in solid fill with about four 1/16 in shear-pin holes.
- The team says a linear floor intake may replace a 4-bar as its default. For the rack that skipped teeth, the team would cut teeth into both plates for full gear face width and extend the bearing block over the mesh.

Tech binder: Technical binder (PDF) · Technical binder and code release (CD) · Technical binder (PDF) · Code (GitHub) · Behind the Bumpers video · Behind the Bumpers thread (CD) · CAD progression post (CD)

■ **Study pick** **2767 Stryke Force** Snake Eyes
USA-MI

Local EPA 66 (#29)
52-14

Arm with bevel-gear claw on a carbon fiber elevator pivoted by printed sector gears; printed custom swerve

SCORING (CONE / CUBE) Claw with bevel gears in the end effector. Larger bevel gears in the claw were a change made between St. Joseph and Worlds. The team's later off-season post says they experimented with printed bevel gears on this end effector.	**INTAKE** The OP mentions cone intake from the floor with the smaller arm.
ARM / ELEVATOR Single-stage carbon fiber elevator. Printed Onyx sector gears pivot the elevator, and a printed Onyx gearbox on the elevator carriage moves the arm. The code lists a superstructure (shoulder) twist, left-right. The team added the elevator stage to reduce tilt of the first axis, shorten the second axis by a few inches and reduce the moment arm off the base. Before Worlds they fitted a larger, taller curved rack, which they call the 'Hedgehog', and made the elbow gearboxes more durable.	**DRIVETRAIN** Custom swerve, mostly printed in Onyx, on a chromoly steel frame. The initial weight was about 100 lb, with a 20 lb plate added under the belly pan for stability.
ENDGAME Unconfirmed	**AUTONOMOUS** The elevator-top camera was added for AprilTag viewing in auto.
VISION PhotonVision for AprilTag detection, and automatic game piece placement using AprilTags. A camera was added on top of the elevator before Worlds for a better view of AprilTags in auto. A light on the robot turns on during camera auto-alignment; a team member says this makes video review easier.	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- Some carbon fiber joints are glued after final assembly: holes in the tubes lead to grooves that the team fills with hot glue.
- Onshape workflow for a student CAD team: master sketches set the layout, each subassembly gets its own folder and document, one person owns the top assembly, and gear profiles come from FeatureScripts.

Onshape CAD: Onshape CAD · CAD and code release (CD) · Onshape CAD · Code (GitHub) · Robot reveal 'Snake Eyes' (CD) · Behind the Bumpers video

Profile	3467 Windham Windup USA-NH	Local EPA 66 (#25) 55-17-4

Double-jointed arm (per interview summary) with pneumatic claw and wrist; pneumatic cube shooter; SDS MK4i L2 swerve

SCORING (CONE / CUBE) A claw on a wrist; the Behind the Bumpers summary mentions several iterations of both. The claw is closed by a pneumatic cylinder for cones and is open for cubes; the cylinder is spring-loaded normally open. 3D-printed pulleys with aluminum inserts ran on the claw all season without a failure. The competition robot also carried a pneumatically deployed cube shooter that collects and scores cubes; the practice robot did not have one.	**INTAKE** 30A 4 in Thrifty compliant wheels. The team reports they gripped cones and cubes well, and chose them for price and the softest durometer: $7.50 per Thrifty wheel against $9 for WCP and $10 for AndyMark. The team kept them in service all season with Rubber Rejuvenator and never replaced them. The claw picks up from the Double Substation, and the cube shooter also collects cubes. The Behind the Bumpers summary (2023-02-28) mentions a new intake planned for Week 1; its design is unconfirmed.
ARM / ELEVATOR Double-jointed arm, per the Behind the Bumpers interview summary. A Behind the Glass video of a Week 0 playoff match shows the drive team working through arm issues. At the World Championship, pocketed aluminum claw gears replaced pocketed steel, saving about 0.44 lb and making the arm more stable in fast moves. The team also replaced MAXPlanetary 1/2 in hex output stages that gained slop, and re-shimmed a 24T hex sprocket on its shaft.	**DRIVETRAIN** Swerve on SDS MK4i modules with L2 gearing. The team states drivetrain speed limited them only at the World Championship. Swerve code was derived from Team 364's BaseFalconSwerve. At the New England District Championship the rear steel drive rail went back to aluminum and the two side drive rails changed to steel. The team made this change after the robot tipped over the back drive rail at Greater Boston, and to improve the center of gravity.
ENDGAME The Behind the Bumpers summary mentions auto balance.	**AUTONOMOUS** Path following with the PathPlanner application and library. At the District Championship the robot ran a 2.5 piece auto, and the team worked toward 3 pieces. The existing autos did not use PathPlanner Event Markers and Path Groups and lost about a second between each path and action; before Worlds the team worked to restructure them. The Worlds 3 piece attempt used the cube shooter for the second and third pieces, and the team reports it got close. The team debuted a 3-piece autonomous mode at the BattleCry off-season event. Autonomous Award at NE District North Shore.
VISION In November 2022 the team wrote it would likely use retro-reflective tape targeting instead of AprilTags; later posts do not say what ran.	**PUBLIC CAD / DESIGN** Build blog (CD)

LESSONS FOR STUDENTS

- Fix weak COTS parts at the source: the team replaced stock two-piece welded Falcon 500 shafts with one-piece 316 stainless 8mm keyed shafts after welds broke.
- Pick the failure state of a pneumatic: at Worlds a fitting failed and the cube shooter stayed down and cracked, but the normally open claw still scored cubes from the Double Substation.

CD thread: Build blog (CD) · Build blog (CD) · 2024 build blog with recap (CD) · Behind the Bumpers thread (CD) · Behind the Bumpers video · Behind the Glass video (Week 0)

Other profiled robots

Each has public CAD, a binder, code or a detailed release thread. Sorted by Local EPA. ■ marks the study picks.

Profile	7157 µBotics Tai Lung USA-CA	Local EPA 65 (#33) 33-11-1

65 deg elevator with an arm (one Falcon, 80:1); fork buddy climb

SCORING (CONE / CUBE) The intake and its carriage weigh 16 lbs together. Behind the Bumpers highlights the intake and wrist.	**INTAKE** The intake is the end effector on the elevator carriage at the front of the robot. In the CAD view it is folded up in front of the elevator. Its subassembly ('Intake Current') has top and bottom plates of polycarbonate and aluminum and two pneumatic cylinders. It also has NEO motors with 5 mm HTD belt pulleys, a Falcon 500 with 48T gears, and a REV Through Bore encoder (per CAD).
ARM / ELEVATOR The elevator is at 65 degrees to the horizontal, with its top about 70 in from the ground. The arm is about 19 in from pivot to the farthest point. The arm runs off a Falcon through a MAXPlanetary 20:1 gearbox and a 64:16 sprocket reduction, 80:1 overall.	**DRIVETRAIN** Swerve with 4 SDS MK4i modules. The module model in the CAD uses the Falcon 500 configuration. A CTRE CANivore and a Pigeon 2.0 are on the drivebase (per CAD).
ENDGAME Fork buddy climb. On 2023-03-28 the team posted a video of a successful iteration and planned to use it at Aerospace Valley.	**AUTONOMOUS** Unconfirmed
VISION The BOM includes Limelight 3 and Limelight 2 cameras. They are in the elevator subassembly (per CAD).	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- Read the reveal thread: the team answered design questions with numbers that the CAD alone does not state.

Onshape CAD: Onshape CAD · Onshape CAD · Robot reveal thread (CD) · Fork buddy climb test video (Google Drive) · Behind the Bumpers thread (CD)

Profile	4499 The Highlanders Iceman USA-CO	Local EPA 64 (#39) 50-14

Arm with an articulating wrist; roller intake; A-frame tower with tie rods; SDS MK4i swerve

SCORING (CONE / CUBE) Unconfirmed	**INTAKE** A separate intake assembly is in the CAD, low at one end of the robot (per CAD).
ARM / ELEVATOR Arm on a pivot at the top of an A-frame tower. Tie rods brace the tower. The arm has an outer tube and an inner perforated tube, with a belt along its length (per CAD).	**DRIVETRAIN** SDS MK4i swerve modules, 4 in the chassis BOM. The module BOM has Falcon 500 motors (per CAD).
ENDGAME No endgame mechanism in the CAD (per CAD).	**AUTONOMOUS** Unconfirmed
VISION Unconfirmed	**PUBLIC CAD / DESIGN** Robot CAD (Onshape)

Onshape CAD: Robot CAD (Onshape) · Robot CAD (Onshape) · Robot reveal 'Iceman' (CD) · Reveal video · Behind the Bumpers video

■ Study pick

5460 Strike Zone VIPER

USA-MI

Local EPA 64 (#44)

64-28

Claw with Onyx-printed gears on a 2-Falcon carbon fiber arm; Falcon intake that hands off cones; SDS MK4i swerve

SCORING (CONE / CUBE) Claw powered by a Falcon at 8.4:1 with Thrifty Bot wheels; 2.7 lbs at the reveal. By the State Championship the team cut a half pound from the end effector and relocated its motor to reduce rotational mass. All claw gears and pulleys are printed in Onyx filament to keep the arm's swinging inertia low.	**INTAKE** Deployed by a Falcon at 53.3:1 and driven by a Falcon at 3:1. The intake orients cones and cubes for a handoff to the claw. As of 2023-04-04 the team did not hand off cubes, because testing put the arm in vulnerable positions; it took cubes from the shelf to score high or mid.
ARM / ELEVATOR Arm powered by 2 Falcons at 140:1, with 3D printed joints and aluminum supports. The distal arm changed to 120:1 by the State Championship. The arm uses carbon fiber tubes from Clearwater Composites. Part 5460-FRC23-201-D07 began as two Onyx prints joined with 1/8 in dowel pins and epoxy. The prints split along layer lines, so the team changed the part to laser sintered Nylon 12.	**DRIVETRAIN** 26 in x 26 in on SDS MK4i L2 swerve modules, changed to L3 by the State Championship. After Championship the team added two Falcons for a 10-motor swerve: two 3-motor modules (L1 gears, 24t pinion) and two 2-motor modules (L3, 18t pinion), about 24 fps free speed. A relocating plate for the 18t pinion was machined from 3/8 aluminum. The CAD shows the robot as it was at the World Championship, before this change.
ENDGAME Unconfirmed	**AUTONOMOUS** Autonomous Award at FIM District Kettering University Event #1.
VISION Two Limelights first updated odometry from AprilTags, placed so one would always see at least two tags when scoring. This allowed zone-based gyro locks at the grid and the player station. The team dropped it after its week 3 Ontario event for lack of tuning time. It then used Limelight tracking of the vision tape on the node poles.	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- Scope cuts with stated reasons: the team dropped AprilTag alignment when it could not tune it in time.
- In the offseason drivetrain test, each module has a follower motor, and a driver-station switch can disable the extra motors. Two brownouts in 26 matches.
- The CAD is a SOLIDWORKS export to Onshape, and the team warns that some parts may be missing or appear incorrect.

Onshape CAD: Onshape CAD · Onshape CAD · CAD release thread (CD) · Reveal thread with specs (CD) · Reveal video · Behind the Bumpers video

---

Profile

972 Iron Claw Vertigo

USA-CA

Local EPA 63 (#53)

40-27

Roller manipulator on a powered wrist; deployable roller intake; angled telescoping elevator; MK4i swerve

SCORING (CONE / CUBE) A manipulator (Manipulator assembly) is on a powered wrist at the top of the elevator. The wrist has a planetary gearbox and a REV Through Bore Encoder. The views show a roller across the manipulator (per CAD).	**INTAKE** A roller intake extends out over the bumper on one side of the robot. It has two long rollers at its outer end and is driven by chain and belt from a pivot near the frame (per CAD).
ARM / ELEVATOR An angled elevator rises from the rear of the frame, with a support upright at mid-length. The inner stage telescopes out of the outer tube. The elevator gearbox is an AndyMark 2 Stage HD Falcon Sport with a Falcon 500. A constant force spring is on the elevator (per CAD).	**DRIVETRAIN** Swerve with four SDS MK4i modules in the Falcon 500 configuration, with CANcoders and a Pigeon 2 (per CAD).
ENDGAME No endgame mechanism in the CAD (per CAD).	**AUTONOMOUS** Unconfirmed
VISION Unconfirmed	**PUBLIC CAD / DESIGN** 'Vertigo' CAD (Onshape)

Onshape CAD: 'Vertigo' CAD (Onshape) · Season and off-season release (CD) · 'Vertigo' CAD (Onshape) · Tech binder (Google Doc) · Season recap video · Code (GitHub organization)

Profile	1114 Simbotics Simbot Scizor Canada	Local EPA 63 (#50) 49-16

Wheeled two-finger claw on a double-jointed arm; three Limelight 2 cameras; swerve

SCORING (CONE / CUBE) Two-finger claw at the end of the arm. Each finger carries stacked wheels linked by belts. A NEO 550 on a REV UltraPlanetary and one air cylinder are in the BOM (per CAD).	**INTAKE** No separate intake is in the CAD. The claw at the end of the arm is the only game piece mechanism (per CAD).
ARM / ELEVATOR Double-jointed arm. The lower arm pivots low on the frame. The upper arm pivots at the top of the lower arm. Chains run along both arm sections to the elbow and to the claw joint. NEO motors on gearboxes sit low in the frame at the arm base (per CAD).	**DRIVETRAIN** Swerve with four modules. Falcon 500 motors and CANcoders are in the modules. The BOM does not name the module model (per CAD).
ENDGAME No endgame mechanism in the CAD (per CAD).	**AUTONOMOUS** Unconfirmed
VISION Three Limelight 2 cameras. The BOM names a left mount, a right mount and a rear-facing mount (per CAD).	**PUBLIC CAD / DESIGN** Onshape CAD

Onshape CAD: Onshape CAD · Onshape CAD · CAD and code release (CD) · Code (GitHub) · Behind the Bumpers video

Profile	1727 REX INCLINE USA-MD	Local EPA 63 (#45) 51-17-1

Roller intake on a pivoting chain-driven elevator with gas spring assist; MAXSwerve

SCORING (CONE / CUBE) The roller intake at the top of the elevator also scores. It has 4 in WCP compliant wheels on hex shafts, driven by a NEO (per CAD).	**INTAKE** Roller intake (assembly Intake v_4) with 4 in WCP compliant wheels, at the top end of the elevator. A NEO drives it through gears and HTD pulleys (per CAD).
ARM / ELEVATOR Elevator with #25 chain drive and a MAXPlanetary gearbox. The elevator mounts on a pivot at its base, with an 80T gear on the pivot shaft. Gas springs (4138T585) connect the elevator to the frame. REV Through Bore encoders are in the BOM (per CAD).	**DRIVETRAIN** Swerve with REV MAXSwerve modules at the 4 corners. NEO and NEO 550 motors and Spark MAX controllers are in the BOM (per CAD).
ENDGAME No endgame mechanism in the CAD (per CAD).	**AUTONOMOUS** Unconfirmed
VISION Unconfirmed	**PUBLIC CAD / DESIGN** Robot CAD (Onshape)

Onshape CAD: Robot CAD (Onshape) · Robot CAD (Onshape) · Behind the Bumpers video

■ Study pick

6672 Fusion Corps TARS

USA-TX

Local EPA 62 (#64)

55-19

Pivoting arm with forearm and wrist gearboxes; live-roller cone and cube floor intake; swerve

SCORING (CONE / CUBE) The Behind the Bumpers summary describes an intake that pinches cones and cubes, moved by a multidirectional 'bicep' arm.	**INTAKE** Floor intake with live top and bottom rollers covered in tubing. The team states the floor pickup geometry makes the bottom roller touch a cone before the top roller, so the bottom roller must be live. The design took inspiration from the 3847 and 8177 Chief Delphi threads.
ARM / ELEVATOR Pivoting arm with forearm and wrist gearboxes. The lead programmer recalls that the wrist went from 100:1 (5:1, 5:1, 4:1) to three 3:1 stages plus a 2:1 sprocket, 54:1 total, to speed up the wrist and cut MAXPlanetary lash. The arm base gearing was also reduced for speed; exact ratios are in the code Constants file. Bent polycarbonate guards absorb hits from the arm if it goes astray.	**DRIVETRAIN** Swerve, run by custom swerve code built on the team's 2022 code, with wheel optimization and a closed-loop ramp limit to prevent wheel slip. The Behind the Bumpers summary mentions a 40lb ballast. The robot has a single driver.
ENDGAME Unconfirmed	**AUTONOMOUS** PathPlanner paths, with steps that let the team modify paths separately on each side of the field. Autonomous Award at the FIT District Fort Worth Event.
VISION A Limelight was mounted but never used. A Logitech webcam was meant to give the driver a view of the intake; the team says the driver never used it. No game piece detection.	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- Keep design history in the CAD: subsystem versions named .0 reached production and versions named .5 did not.
- Arm control without inverse kinematics: setpoint moves follow an algorithm that keeps the arm on a safe path through the robot.
- The release credits its sources, such as team 3015 for PathPlanner, and has a BOM.

Onshape CAD: Onshape CAD · CAD and code release (CD) · Onshape CAD · Code (GitHub) · Bill of materials (Google Sheets) · Behind the Bumpers video

■ Study pick

3357 COMETS Kushida

USA-MI

Local EPA 61 (#79)

63-20

3-stage elevator with a geared arm; floor-first intake; 21x26 in chain-in-tube tank drive

SCORING (CONE / CUBE) The CAD renders show a separate end effector on the arm.	**INTAKE** Floor intake; the Behind the Bumpers summary calls the design floor-intake-first. It picks up cones upright, tip-towards, and within about 70 degrees each way from tip-towards. Base-towards cones take two steps: flip to vertical, then intake. A team member said upright and tip-towards are the fastest.
ARM / ELEVATOR An elevator with a base stage, a 2nd moving stage and a 3rd output stage carries an arm. Wiring runs in energy chain 'A' from the base to the 2nd stage, then energy chain 'B' to the 3rd stage. The arm had no counterbalance and was geared at about 200:1 for the first events. Thin-wall tube bent a little near the elevator slots from the arm's inertial loads; the team reports no loss of function.	**DRIVETRAIN** Tank drive with chain-in-tube assemblies that the team says can be hot-swapped in 3 minutes. The team chose it over swerve for module supply, cost, limited swerve experience, and a goal of a practice drivetrain with a prototype intake by day 9. Black nitrile tread, held to the wheel with safety wire stitches, lasted multiple events.
ENDGAME The team says the drivetrain was built to cross the Charge Station many times per match.	**AUTONOMOUS** TBA lists the Autonomous Award at FIM District Calvin University and FIM District West Michigan.
VISION Unconfirmed	**PUBLIC CAD / DESIGN** GrabCAD CAD (STEP)

LESSONS FOR STUDENTS

- Motor standardization: the team kept NEO 550 motors with UltraPlanetary gearboxes on many actuations for weight, needed many revisions to make them reliable, and recommends all-NEO or all-Falcon for other teams.
- Arm loads reach the structure: the first arm drive gear was light-weighted steel, and it deformed.
- A simple part numbering scheme: Assembly-Subassembly-PartNum1-PartNum2, then the part name and the author's initials.

GrabCAD: GrabCAD CAD (STEP) · 'Kushida' CAD (GrabCAD, STEP) · Reveal and CAD release thread (CD) · Behind the Bumpers thread (CD) · Behind the Bumpers video · Reveal video

Profile

95 Grasshoppers Clarke

USA-VT

Local EPA 60 (#93)

30-18

Pneumatic gripper on carbon fiber pivot arm; compliant polycarbonate roller intake on rack slide; REV MAXSwerve

SCORING (CONE / CUBE) Pneumatic gripper ('mk2 mandible gripper') at the end of the arm, moved by an air cylinder (per CAD).	**INTAKE** The CAD holds more than one intake version ('alternate intake' and 'stephen intake'). The intake shown has two side arms with a roller at the end. The roller uses 2 in compliant wheels and 1 in sushi rollers. The intake moves on a linear shaft with a gear rack, driven by a REV MAXPlanetary. It also has a REV MAX 90 Degree Gearbox and polycarbonate intake plates. An energy chain carries its wires (per CAD).
ARM / ELEVATOR Two carbon fiber posts rise from the frame to a pivot axis at the top. The arm is a triangulated frame of carbon fiber tubes that pivots on this axis. The arm drive uses #25 chain on 32T sprockets (per CAD).	**DRIVETRAIN** Swerve with 4 REV MAXSwerve modules (3 in wheel) (per CAD).
ENDGAME No endgame mechanism in the CAD (per CAD).	**AUTONOMOUS** Unconfirmed
VISION Two Limelight 2 cameras on mirrored brackets, one on each post of the arm tower ('spar camera' assembly) (per CAD).	**PUBLIC CAD / DESIGN** Whole-robot CAD (Onshape)

Onshape CAD: Whole-robot CAD (Onshape) · Whole-robot CAD (Onshape) · Build thread (CD) · Photo album (imgur) · Video playlist (YouTube)

■ Study pick

341 Miss Daisy Miss Daisy XXI

USA-PA

Local EPA 59 (#105)

42-19-1

Belt-driven telescoping arm; roller-claw intake on a 120-deg locking wrist; SDS MK4i; 23x30 in frame

SCORING (CONE / CUBE) Roller-claw intake on a wrist with 120 deg of movement and a locking mechanism. The lock first used a 'comb' moved by servos; the servos failed, so the team changed to a small pneumatic piston. The robot scores cubes and cones at all 3 levels.	**INTAKE** The team collects cones from the single substation, the double substation, and from the floor when the cone lies on its side. Cubes are also collected.
ARM / ELEVATOR Belt-driven telescoping arm.	**DRIVETRAIN** SDS MK4i modules with Falcons for drive and steering. Frame is 23 in wide x 30 in long. Robot weight is 95 lb.
ENDGAME The team chose a 23 in x 30 in frame to better fit on the Charge Station with 2 full-size partners.	**AUTONOMOUS** Unconfirmed
VISION Unconfirmed	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- CAD, code and a design binder come from the same release, so you can trace one robot from design notes to model to software.

Onshape CAD: Onshape CAD · CAD, code and binder release (CD) · Onshape CAD · Code (GitHub) · Robot reveal thread (CD)

Profile

695 Bison Robotics Goldmodule

USA-OH

Local EPA 59 (#109)

52-11

Cascading elevator with an Everybot intake (per Behind the Bumpers); swerve

SCORING (CONE / CUBE) Unconfirmed	**INTAKE** Everybot intake, per Behind the Bumpers.
ARM / ELEVATOR Cascading elevator, per Behind the Bumpers.	**DRIVETRAIN** Swerve, per the team's code repository description.
ENDGAME Unconfirmed	**AUTONOMOUS** Unconfirmed
VISION Unconfirmed for this robot. The release post lists an off-season swerve and vision code rewrite as a separate project.	**PUBLIC CAD / DESIGN** CAD (Google Drive, STEP/IGES)

LESSONS FOR STUDENTS

- The team developed its code in public on GitHub, with conventions carried over from the Rapid React season.
- The CAD is released as STEP/IGES files, a neutral format that any CAD package can import.

Drive folder / doc: CAD (Google Drive, STEP/IGES) · CAD and code release (CD) · CAD (Google Drive, STEP/IGES) · Code (GitHub) · Behind the Bumpers thread (CD)

■ Study pick

1706 Ratchet Rockers Whiplash

USA-MO

Local EPA 59 (#111)

38-11-1

Cone and cube shooter; Limelight driver assist; swerve with frame corners cut to the module size

SCORING (CONE / CUBE) Cone and cube shooter. The team set out to shoot the game pieces instead of placing them, for a higher possible skill ceiling, and reached a working robot after a lot of trial and error.	**INTAKE** The Behind the Bumpers summary describes dual intakes.
ARM / ELEVATOR Elevator in a fixed vertical frame. A truss-plate arm hangs from a pivot shaft on the elevator carriage, with the shooter at its lower end. An energy chain runs along the arm. A dual NEO gearbox (BOM: 'DUAL NEO 6:1'), a chain assembly and a constant force spring spool are in the top-level BOM (per CAD).	**DRIVETRAIN** Swerve; the team calls its modules 'mk2'. The frame corners are cut to the module size. The team says this saved about 6 in of corner-to-corner diameter so the robot can rotate off defense more easily.
ENDGAME No endgame mechanism in the CAD (per CAD).	**AUTONOMOUS** The team won the Autonomous Award at the Central Missouri Regional.
VISION Limelight. A team member states the frame shape did not work as well as hoped for lining up on the grid, so the team used the Limelight to give the driver assistance on approach.	**PUBLIC CAD / DESIGN** Onshape CAD

Onshape CAD: Onshape CAD · Code and CAD release (CD) · Onshape CAD · Code (GitHub) · Robot reveal 'Whiplash' (CD) · Behind the Bumpers video

■ Study pick

4795 Eastbots HYDRA

USA-NC

Local EPA 59 (#106)

50-15-1

Roller claw on a wrist; mid-level scorer, no high cones; roller bar cube intake added in season

SCORING (CONE / CUBE) A roller claw on a wrist. The claw side plates are 1/8 in polycarbonate. During the season the team removed the aluminum scab plates and shortened the claw ('stumpy', replacing 'lanky'); the team credits the shorter claw for better cone pickup at the double substation. Dead-axle pulleys run on 3/16 in bore radial bearings (R3-2RS). The wrist has a pivot and a piston mount.	**INTAKE** Roller bar intake with mecanum rollers and a pressure-set deploy, added during the season; it hands cubes to the claw. The team says it added 2-3 game pieces to a typical teleop and sped up feeder cycles. After the state championship the team added top hardstops for cubes and increased the mecanum roller density. The Behind the Bumpers summary after the UNC Asheville event names a 'flail intake'.
ARM / ELEVATOR The Behind the Bumpers summary describes the robot as compact. At the state championship the team swapped a spare wrist and claw unit that had the wrong spacers; it bound in a match until the holes were drilled to clearance size.	**DRIVETRAIN** The team's recap describes strafing motions during pickups; the drive type is not named.
ENDGAME 'Landing gear' for the Charge Station, described in the Behind the Bumpers video.	**AUTONOMOUS** Roller bar cube pickups often failed in auto but worked in teleop. The team added small strafing and wiggling motions to every auto pickup, and the problem mostly stopped. The team says auto consistency was its weak point at the state championship.
VISION Unconfirmed	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- Limit the task list to what the team can do well; the team later named 'build simple but effective' as its motto.
- Debug the difference between auto and teleop: the team's hypothesis for the cube pop-outs was the absence of driver motion during pickup.
- Write failure reports with the fix for each, as the team did for the sheared electronics shelf standoffs.
- CAD, code and a technical binder were released together, so mechanism, software and documentation can be read side by side.

Onshape CAD: Onshape CAD · Onshape CAD · Technical binder (Google Doc) · Code (GitHub) · Build thread (CD) · Reveal 'HYDRA' (CD) · Behind the Bumpers video · 2024 Open Alliance thread with the release post (CD)

Profile	6328 Mechanical Advantage USA-MA	Local EPA 58 (#116) 48-23

Roller end effector on a two-link arm; pivoting roller intake; SDS MK4i swerve

SCORING (CONE / CUBE) End effector at the end of the arm. It has two rows of green compliant wheels, one above the other. The BOM also includes a NEO 550 motor on a REV UltraPlanetary gearbox (per CAD).	**INTAKE** Pivoting intake arm on the side of the frame opposite the end effector. A roller tube runs across the end of the arm. The CAD also has a subassembly named 'AUGER' (per CAD).
ARM / ELEVATOR Two-link arm on an A-frame tower near the middle of the frame. The first link pivots at the top of the tower. The second link pivots at the far end of the first link and carries the end effector. The joints use #25 chain on REV MAXSpline sprockets, with REV Through Bore encoders. The first joint has its own gearbox subassembly with a NEO (per CAD).	**DRIVETRAIN** Swerve with 4 SDS MK4i modules. The module model in the CAD uses the Falcon 500 configuration. A CTRE Pigeon 2.0 is in the electrical subassembly (per CAD).
ENDGAME No endgame mechanism in the CAD (per CAD).	**AUTONOMOUS** Unconfirmed
VISION Unconfirmed	**PUBLIC CAD / DESIGN** CAD (Onshape)

Onshape CAD: CAD (Onshape) · Build thread (CD) · CAD (Onshape) · Robot code (GitHub) · FieldConstants class (GitHub) · AdvantageKit (GitHub) · Behind the Bumpers video

■ Study pick	8177 Vector Velocity USA-TX	Local EPA 58 (#112) 36-24-2

Triple-roller intake for tipped/standing cones and cubes on a NEO wrist; 55 deg tilted elevator; MK4i L3 swerve

SCORING (CONE / CUBE) The triple-roller intake on the wrist is also the scoring end effector. The rollers turn in opposite directions for cones and cubes; the code sets the outtake direction from the last intake position. Intake hubs on the wrist axle are printed in Carbon Fiber PLA at nearly 100% infill, with printed TPU disks to spread the clamp load on the polycarbonate intake panel.	**INTAKE** Triple-roller design that takes tipped cones, standing cones and cubes (the team's programming update). In February testing the intake still took cones with the bottom roller about 1 in off the ground. LEDs flash yellow or purple to ask the human player for a cone or a cube.
ARM / ELEVATOR Tilted elevator at 55 deg from the horizontal with double chain rigging, a TTB constant force spring and WCP bearing blocks. The wrist rotates the intake on 1 NEO at 32:1, with a REV Through Bore encoder for absolute position. As of March the elevator had no absolute encoder due to supply issues; it returns to the same start position.	**DRIVETRAIN** Swerve on MK4i L3 modules. The chassis is 26 in x 26 in with a steel belly pan; the drive chassis weighs 60 lbs by itself for a low CG. One-piece bumpers.
ENDGAME Balance is part of the 1+balance auto path (March).	**AUTONOMOUS** PathPlanner trajectory following, the team's first season with it, using AprilTag and swerve encoder pose. As of 2023-03-20 the team ran 1+1 and 1+balance paths and planned a 1+1+1+balance path.
VISION A Limelight reads AprilTags, and the pose estimate combines this with the swerve drive encoders. A held driver button drives the robot to the grid and leaves the driver only left-right control to line up. An OpenCV cone-centering test was in early development in March 2023.	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- A constant force spring on the elevator countered gravity enough that the team held the elevator with a P-only loop and no feedforward.
- The wrist needed SysId feedforward (S, V, G, A). The team states gains calculated off the robot were inaccurate, and it switched gains when a cone added weight.
- Setpoints sequence the elevator and wrist moves. The team rewrote the move order after the intake caught on the level 2 cone pole.
- Driver load reduction: one score button serves cones and cubes.

Onshape CAD: Onshape CAD · Build thread (CD) · Onshape CAD · Code (GitHub organization) · OpenCV cone-centering test (GitHub) · Behind the Bumpers video · Robot video (March)

Profile	971 Spartan Robotics Doffle USA-CA	Local EPA 57 (#142) 29-16

Two-roller end effector on a multi-DOF arm with wrist roll, on a tall truss upright; tank drive

SCORING (CONE / CUBE) The end effector (SFR END EFFECTOR ASSEMBLY) is at the end of the arm. It has two long parallel rollers across its width (per CAD).	**INTAKE** The CAD has no separate intake assembly. The roller end effector on the arm is the only game piece mechanism in the CAD (per CAD).
ARM / ELEVATOR A two-link arm (proximal and distal tubes) is on a tall truss upright (Arm Upright Assembly). The wrist has a roll joint driven by a VersaPlanetary, with a 3-turn potentiometer for position. The arm links contain a capstan assembly and cable guides. A diagonal tube braces the upright to the frame (per CAD).	**DRIVETRAIN** Tank drive with left and right gearboxes in the bellypan. Falcon 500 is the main motor type in the BOM. The side view shows three wheels on each side. The frame has WCP cams and #25 chain (per CAD).
ENDGAME No endgame mechanism in the CAD (per CAD).	**AUTONOMOUS** Unconfirmed
VISION A camera assembly (Camera Main Assembly) has a front camera holder and a rear camera mount. The BOM does not name the camera model (per CAD).	**PUBLIC CAD / DESIGN** Onshape CAD

Onshape CAD: Onshape CAD · Onshape CAD · 2022 and CAD release thread (CD) · Team CAD page · Technical documentation (team site) · Reveal thread 'Doffle' (CD) · Behind the Bumpers video

■ Study pick	**2337 EngiNERDs** Vision USA-MI	**Local EPA 57 (#145)** 45-17-1

Shoulder, elbow and wrist arm with rope-driven elbow and cable-driven wrist; NEO 550 intake; SDS MK4i L3 swerve

SCORING (CONE / CUBE) Wrist end effector. Wrist: Falcon with MaxPlanetary (4:4:4), brake-cable driven from the belly of the robot. Intake rollers: NEO 550 with UltraPlanetary (5:4).	**INTAKE** NEO 550 with UltraPlanetary (5:4).
ARM / ELEVATOR Arm with shoulder, elbow and wrist. Shoulder: Falcon, MaxPlanetary (5:5:4), RT-25 belts (72:32). Elbow: same motor and reductions, rope driven from the shoulder pivot. Wrist as described under scoring.	**DRIVETRAIN** Swerve on SDS MK4i modules, L3 ratio.
ENDGAME Unconfirmed	**AUTONOMOUS** Unconfirmed
VISION The Behind the Bumpers summary mentions a vision system; not described in the team posts.	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- Belly pan hardware: asked about snagging on the Charge Station, the team says it typically puts button head cap screws or rivets on the bottom of the belly pan, or uses zip ties.

Onshape CAD: Onshape CAD · Reveal, spec list and CAD release thread (CD) · Onshape CAD · Behind the Bumpers (CD)

Profile	177 Bobcat Robotics The Bobcat USA-CT	Local EPA 54 (#191) 48-19

Double-jointed arm on an angled elevator; swerve

SCORING (CONE / CUBE) Unconfirmed	**INTAKE** The Behind the Bumpers video summary says the intake went through several iterations.
ARM / ELEVATOR A double-jointed arm mounted to an angled elevator. After the season, one student derived the kinematic equations for this layout with geometry and trig as a preseason project, to set scoring and intake positions more directly.	**DRIVETRAIN** Swerve; the team's first year with a swerve drivetrain. The code used Team 364's BaseTalonFXSwerve code.
ENDGAME Unconfirmed	**AUTONOMOUS** The team reports problems with its autos that it could not debug. This led it to add AdvantageKit logging for 2024.
VISION Limelights with AprilTags, chosen as the simplest option for the time available. The team later reported limited field of view and slightly inaccurate pose estimation due to the mounting.	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- Two code repositories (Bot 1 and Bot 2) are public for the same season.

Onshape CAD: Onshape CAD · Onshape CAD · Code, Bot 1 (GitHub) · Code, Bot 2 (GitHub) · 2024 build blog with links (CD) · Reveal thread (CD) · Behind the Bumpers thread (CD)

Profile	1102 M'Aiken Magic USA-SC	Local EPA 54 (#200) 45-21

Roller head on a long pivoting arm on an angled truss tower; SDS MK4i swerve

SCORING (CONE / CUBE) Roller head with wheels and a roller bar at the outer end of a long arm (per CAD).	**INTAKE** The arm lowers the roller head to the floor at the front of the robot (per CAD).
ARM / ELEVATOR Long truss arm ('Vertical Arm' and 'Horizontal Arm') that pivots on an angled tower ('Tower Sub-Assembly'). Two motors sit at the pivot; Falcon 500 is the only motor type in the BOM (per CAD).	**DRIVETRAIN** Swerve with four SDS MK4i modules (Falcon 500 configuration) and CANcoders (per CAD).
ENDGAME Unconfirmed	**AUTONOMOUS** Unconfirmed
VISION Unconfirmed	**PUBLIC CAD / DESIGN** Onshape CAD (Onshape sign-in needed)

Onshape CAD: Onshape CAD (Onshape sign-in needed) · CAD and code release thread (CD) · Onshape CAD (Onshape sign-in needed) · Code (GitHub)

Profile	2713 Red Hawk Robotics USA-MA	Local EPA 54 (#180) 34-21-1

Roller gripper on a four-bar, on a tilted Dyneema-driven elevator; MK4i swerve

SCORING (CONE / CUBE) Roller gripper at the end of a four-bar. It uses compliant wheels driven by NEO 550 motors through REV UltraPlanetary gearboxes (per CAD).	**INTAKE** The roller gripper on the four-bar is also the intake. The CAD shows it holding a cone (per CAD).
ARM / ELEVATOR Tilted elevator with a stage and a carriage on Thrifty bearing blocks. Dyneema rope on capstans and pulleys drives it, with two REV MAX Planetary gearboxes and two constant-force springs. A hall effect sensor and magnet are on the elevator. A four-bar on the carriage carries the gripper (per CAD).	**DRIVETRAIN** Swerve with 4 SDS MK4i modules and a CTRE Pigeon 2.0 gyro. The module models carry Kraken X60 motors, which were not sold until the next season, so the CAD was updated after the season; NEO and Falcon 500 module configurations also appear in the BOM (per CAD).
ENDGAME No endgame mechanism in the CAD (per CAD).	**AUTONOMOUS** Unconfirmed
VISION One Limelight 3 and one Limelight 2 on a Limelight wedge, plus OV2311 cameras on front and rear mounts, all on the elevator assembly. An Orange Pi 5 stack on the drivetrain is the coprocessor (per CAD).	**PUBLIC CAD / DESIGN** Robot CAD (Onshape)

Onshape CAD: Robot CAD (Onshape) · Robot CAD (Onshape)

■ Study pick	3847 Spectrum X-Ray 2023 USA-TX	Local EPA 54 (#182) 44-20

Cube shooter (per Behind the Bumpers); elevator with a slide and arm/intake; swerve

SCORING (CONE / CUBE) Cube shooting robot, per the Behind the Bumpers video title and description. The January sketch used a cone pinch intake that doubles as a ball (cube) intake, with a flywheel or roller to launch cubes in auto.	**INTAKE** The team unbolted the slide, arm and intake to ship the robot, and planned to carry a spare arm/intake from its practice robot on the plane. The kickoff plan was to load cones from the Human Player shelf and pick cubes from the floor.
ARM / ELEVATOR Elevator with a slide and arm. In January 2025 replies in the build blog, the team named external cantilevered pulleys as the main problem. By the end of the season these ran on ~2.75 in shoulder bolts through tube end caps, which still bent and sheared. The team also named the lower elevator mounting as a weak point.	**DRIVETRAIN** Swerve. In 2022 the team mounted MK4i modules below the frame rails so a whole module could drop out. It never swapped a whole module at an event. It then used a standard module mount, because modules below the frame rails would have raised the belly pan and electronics.
ENDGAME At an off-season event the post does not name, a bumper came off and the robot drove to the Charge Station before it could be disabled. Another user described the play; the team credits its drive coach for the call.	**AUTONOMOUS** Behind the Bumpers describes PathPlanner routines. The team posted a Chezy Champs 'Bump' side auton mode on 2023-09-29.
VISION The robot carries a camera rail that unbolts for shipping.	**PUBLIC CAD / DESIGN** Team CAD site (Onshape)

LESSONS FOR STUDENTS

- Kickoff trade study: the team states the shelf sits a bit higher than the mid cone node and that 15 of 27 nodes accept cubes.
- Failure note: the cantilevered pulleys need high belt tension. Avoid them, or check the shoulder bolts that carry them.
- Design for shipping: the slide, arm, intake and camera rail lie on the chassis without undoing wiring, except the RSL. The robot fit a 48x40x38 freight box.
- Software structure: the team's fall software plan makes every function, including auton and vision, its own subsystem, with template classes for rollers, arms and elevators. The team wrote that not all of it was implemented yet.

CAD release: Team CAD site (Onshape) · Build Blog (CD) · Team CAD site (Onshape) · Code site (GitHub) · Design review of X-Ray (video) · Behind the Bumpers video

■ Study pick

955 Ctrl C

USA-OR

Local EPA 53 (#212)

44-28

Roller claw on an extension that cannot reach the floor; ground cube intake added by DCMP; swerve

SCORING (CONE / CUBE) Roller claw on the extension mechanism. The team says it held game pieces securely.	**INTAKE** No ground intake at the district events. Ground cube intake was added by DCMP and the Championship. Earlier the team pursued a 'weedwacker' ground intake based on 2158's prototypes; the team says it was never going to work and that it spent too long on it.
ARM / ELEVATOR Extension mechanism that carries the roller claw. The team describes it as fast and simple, with few failures under impact loads. It was designed so it could not reach the ground, because the team assumed a ground intake would be too heavy to extend.	**DRIVETRAIN** Swerve, the team's first year with it; the team says it would not have done as well without it. Weight was 95.5 lb at SunDome against 124 lb for the 2022 robot, mostly from 1/16 in box tubing for most of the structure.
ENDGAME No endgame mechanism in the CAD (per CAD).	**AUTONOMOUS** Unconfirmed
VISION The robot assembly includes a Limelight 2 ('EL-3 limelight', 'Simplified Limelight 2 Camera') and a separate AprilTag camera part ('EL-7 april camera') (per CAD).	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- Stop work on a prototype that is not converging; the team names the 'weedwacker' intake as its example.
- Plan wiring and sensors with the other subteams: the team names missing wiring plans and design-programming miscommunication about sensors as a negative.

Onshape CAD: Onshape CAD · CAD release (CD) · Onshape CAD

■ Study pick

2881 Lady Cans SCoRpion

USA-TX

Local EPA 53 (#222)

34-26

Two-lead-screw pivoting and extending arm with a suction-cup end effector; swerve

SCORING (CONE / CUBE) Two suction cups near the end of the arm hold the cone or cube. The team chose them over a claw with compliance wheels after prototyping, because they carry less weight at the end of the arm. Early tests wrinkled the cube under vacuum; the team reports this was solved. The vacuum line under the arm is pneumatic tubing inside heat shrink, coiled around a PVC pipe with a heat gun so it acts like a spring.	**INTAKE** The first plan used hex-shaft rollers covered in silicone tubing. In build week 2 the team changed the plan to an intake like the Everybot intake. A four-bar linkage keeps the roller section parallel to the ground. It picks up both game pieces and drops them inside the robot for the arm, and no part of it rests on the floor. The team says the intake is the main difference between the build week 4 CAD and the final robot.
ARM / ELEVATOR Arm driven by two lead screws: one moves the arm up and the other extends it outward. The team started the season with a 0.5 in per turn lead screw, the same screw and 3:1 reduction as its 2022 robot. After testing and the first event it changed to a 1 in per turn lead screw to cut cycle time. The team notes it back-drives more, so it may need a brake or more software.	**DRIVETRAIN** Swerve, first used by the team in official competition. The four modules came from its 2022 off-season swerve bot. The robot was light, so the team planned a solid steel drivetrain to add weight and lower the center of gravity.
ENDGAME Buddy balance mechanism, still being machined in build week 5.	**AUTONOMOUS** Trajectory following with PathPlanner, first tested on the off-season swerve bot. In build week 2 the robot could not check that it held a game piece before scoring, which affected preload choice.
VISION AprilTags, first year of use. In build week 2 the cameras recognized tags and output an estimated position. The plan was to combine this with odometry.	**PUBLIC CAD / DESIGN** GrabCAD CAD (to build week 4)

LESSONS FOR STUDENTS

- The GrabCAD file stops at build week 4. Compare the CAD with the build thread for the final intake.

GrabCAD: GrabCAD CAD (to build week 4) · Build thread (CD) · GrabCAD CAD (to build week 4) · Behind the Bumpers video · 2024 build thread with recap (CD)

■ Study pick

401 Copperhead Robotics Mushussu

USA-VA

Local EPA 52 (#251)

42-21-1

Double-sided arm (250-deg rotation, 30 in extension) with a 330-deg belt-in-tube wrist; SDS MK4i L2 swerve

SCORING (CONE / CUBE) The end effector grabs a cone by its flange or tip from any orientation, from both sides. The robot scores cones and cubes out either side.	**INTAKE** No separate floor intake in the CAD. The end effector ('pasta roller') takes the game pieces. It has rows of 2 in Thrifty squish wheels on shafts between 2 side plates. 2 775pro motors in VersaPlanetary gearboxes drive the rollers through HTD belts (per CAD).
ARM / ELEVATOR Arm with 250 deg of rotation and 30 in of extension. A belt-in-tube driven wrist gives 330 deg of rotation.	**DRIVETRAIN** SDS MK4i L2 swerve modules.
ENDGAME No endgame mechanism in the CAD (per CAD).	**AUTONOMOUS** Unconfirmed
VISION Unconfirmed	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- Toggle switches also turn all LEDs on or off.
- The same thread has Onshape CAD for a battery cart (9 slots, 3x Dual Pro RS3 chargers, plasma cut 12 gauge steel) and a driver station with split-arcade joysticks.

Onshape CAD: Onshape CAD · CAD and tech binder release (CD) · Onshape CAD

Profile

1351 TKO

USA-CA

Local EPA 52 (#260)

19-7

Wheeled end effector on a vertical elevator that also intakes; A-frame superstructure; swerve

SCORING (CONE / CUBE) Wheeled end effector at the top of the elevator (BOM: 'intake v4'). A U-shaped frame holds 4 in and 3 in 30A flex wheels. One NEO drives the wheels through HTD belts. An E18-D80NK proximity sensor is in the assembly (per CAD).	**INTAKE** The same end effector at the top of the elevator is the intake. No separate ground intake is in the CAD (per CAD).
ARM / ELEVATOR Vertical elevator braced by an A-frame superstructure. A NEO drives it through a 40T gear and a #35 sprocket. REV Hall effect sensors and an energy chain are on the elevator (per CAD).	**DRIVETRAIN** Swerve with four corner modules. A Pigeon 2 is in the BOM. The BOM does not name the module model (per CAD).
ENDGAME No endgame mechanism in the CAD (per CAD).	**AUTONOMOUS** Unconfirmed
VISION Innomaker OV9281 cameras are in the BOM (per CAD).	**PUBLIC CAD / DESIGN** Competition robot CAD (Onshape)

Onshape CAD: Competition robot CAD (Onshape) · CAD release (CD) · Competition robot CAD (Onshape) · Competition robot STEP (Google Drive) · Offseason robot CAD (Onshape) · Training robot CAD (Onshape)

■ Study pick

7461 Sushi Squad

USA-WA

Local EPA 52 (#256)

36-25

Claw on a chain-driven pivot arm with pneumatic extension; intake with indexer handoff; Falcon 500 swerve

SCORING (CONE / CUBE) A claw on the end of the arm. The team shared Onshape documents for the alpha claw and the competition arm and claw in the build thread on 2023-03-13. Before the first event the team found claw problems with pulleys and advises against 18T PLA pulleys. In March the team posted cube shooting tests and asked if shooting cubes is a viable strategy.	**INTAKE** January plan: an over-the-bumper cube ground intake with indexing wheels that hands off to the arm, plus single substation cone pickup. The team planned to ignore tipped cones. The alpha intake used pneumatics. Before the first event the team fixed indexing and handoff problems: wheels did not spin because of pulley wear.
ARM / ELEVATOR Pivot arm with a pneumatic extension. The arm uses a large dead axle, #35 chain kept in tension and a large sprocket. The arm never flips, so backlash stays on one side; the team reports +/- 1-2 deg. Changed before the first event: a Spartan tensioner replaced a turnbuckle that lacked tension, and a steel hex shaft replaced aluminum to reduce bending. The absolute encoder pulley went to 1:1, and a fixed-bearing idler replaced a double-bearing floating idler that caused 2-3 deg of error. After the first event the team added quick exhaust valves to speed the extension, with retraction valves next.	**DRIVETRAIN** Swerve with Falcon 500 motors on the modules. The January plan named 2x1 tube swerve for competition; the alpha robot reused a 2x2 off-season chassis. The 3D-printed swerve corners crushed after two events. The team reprinted them with 4 walls and 40 percent infill and carries spares.
ENDGAME Charge Station auto-balance. In January tests, wheels set in an X shape held on polycarbonate with almost no slip. The first bang-bang auto-balance sometimes overshot, so in March the team began testing a PID-based version. The team advises that only one robot auto-levels at a time.	**AUTONOMOUS** On 2023-03-09 the robot ran a two-piece auto on the side without the cable bump ('non-berm side', in the team's words). By the first event the team had berm-side and 'normal side' autos with balance. The team posted a 3-piece auto on 2023-04-04.
VISION Vision measurements and wheel odometry feed a WPILib pose estimator for odometry-based auto-align to the grid. The team weights vision heavily because odometry drifted during defense. Auto-align for the Double Substation was planned in March.	**PUBLIC CAD / DESIGN** Onshape CAD (comp robot)

LESSONS FOR STUDENTS

- Feedforward can follow the arm state: the team schedules two kG values, one with the arm piston extended and one with it retracted.
- The REV Through Bore absolute encoder did not integrate with the SPARK MAX for this team; they read it through DIO.
- Keep the CAD main assembly current: late electrical belly pans and informal design reviews led to bad battery wire bends and poor PDH access.
- Drive the robot hard before events: long runs found a PDH fire, Falcon issues and a ripped CAN termination three weeks before competition.

Onshape CAD: Onshape CAD (comp robot) · Onshape CAD (comp robot) · Build thread (CD) · Arm design guide linked in the thread (CD) · Behind the Bumpers video

Profile	2582 PantherBots USA-TX	Local EPA 51 (#268) 35-24-2

Roller intake on a pivot at the end of a cross slide, on a tilted belt-driven elevator; WCP Swerve X

SCORING (CONE / CUBE) The roller intake (Intake V2) also scores. It has an upper and a lower row of compliant wheels. The CAD shows a cube held in it (per CAD).	**INTAKE** Roller intake (Intake V2) with upper and lower rows of compliant wheels. It pivots at the front end of the cross slide (per CAD).
ARM / ELEVATOR Tilted elevator with HTD5 belt drive, two REV MAX Planetary gearboxes and a constant-force spring. A horizontal cross slide on Thrifty bearing blocks sits on the elevator carriage and extends forward. A REV MAX Planetary drives the cross slide with a belt (per CAD).	**DRIVETRAIN** Swerve with 4 WCP Swerve X modules (corner mount, flipped belt). NEO motors, SPARK MAX controllers, CANcoders and a Pigeon 2 gyro are in the BOM (per CAD).
ENDGAME No endgame mechanism in the CAD (per CAD).	**AUTONOMOUS** Unconfirmed
VISION One Limelight 2 camera with a Limelight mount (per CAD).	**PUBLIC CAD / DESIGN** Onshape CAD

Onshape CAD: Onshape CAD · Onshape CAD · 2024 Open Alliance thread, mentions the drive base (CD)

Profile	2877 LigerBots USA-MA	Local EPA 51 (#282) 25-24

Pivoting 2-stage telescoping arm with cascade rigging and constant-force springs; swerve

SCORING (CONE / CUBE) In January 2023 the team prototyped a pneumatic linear pinch claw with rug-gripper material and a roller claw that pneumatics open and close. The team states the pinch claw needs no motors or wires at the top of the arm, and the roller claw allows touch-and-control. The posts do not state which claw went on the competition robot.	**INTAKE** The team chose a rotating arm so the robot could pick up game pieces from the ground. In January 2023 the team planned a U-shaped bumper so the arm could clear the bumper as it swings.
ARM / ELEVATOR Rotating 2-stage elevator on a pivot, chosen during CAD weekend in January 2023 after the team could not make a static arm work. The largest stage is 2.5 in box tube. Constant force springs and cascade rigging move the stages, which the team states puts less load on the motors. The pivot motors sit low on the chassis with an inline chain tensioner. In November 2023 the 9mm HTD belt that extends and retracts the arm sheared in a mock match.	**DRIVETRAIN** Swerve, finalized by the build leaders on 2023-01-11. The January plan gives a 25 x 30 in chassis. The belly pan is perforated polycarbonate in two zones and solid polycarbonate in the center, because the team could not find more perforated sheet.
ENDGAME The team chose the 25 x 30 in chassis so the robot would not need to beach on the ramp and three robots could fit on the Charge Station. Programmers had an auto leveling system working on the test chassis by 2023-01-30.	**AUTONOMOUS** Auto leveling on the Charge Station worked on the test chassis in January 2023.
VISION Unconfirmed	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- Settle arm geometry with skeleton sketches first: the team compared a static arm and a rotating arm and found the rotating geometry needed two stages.
- Size belts for match impacts; study the sheared arm belt.
- Let the drive team practice before the modules are ready: the team fitted 3D-printed 'swerve dummies' with caster wheels to the chassis.

Onshape CAD: Onshape CAD · Onshape CAD · Open Alliance build thread (CD) · 2024 Open Alliance thread, robot belt failure (CD) · Robot flyer (PDF) · Design process (PDF)

■ Study pick

4201 The Vitruvian Bots Gridlock

USA-CA

Local EPA 51 (#279)

26-14

3-stage rope-driven elevator; 180-deg virtual 4-bar with 3-roller intake; SDS MK4i L3 swerve

SCORING (CONE / CUBE) The release does not describe a separate scoring end effector. It names a 3-roller intake attached to the virtual 4-bar. The code uses a state machine for scoring, intaking and stowed states.	**INTAKE** 3-roller intake on the virtual 4-bar. It picks up ground cubes and cones, standing or tipped. Intake distance sensors to detect a game piece were developed but not fully used in season.
ARM / ELEVATOR 3-stage elevator with 5 ft of extension in under 1 second, per the team. It uses custom 3D printed pulleys and ropes inside 2 in x 1 in extrusions. A virtual 4-bar with fixed sprockets and chain gives 180 deg of motion.	**DRIVETRAIN** SDS MK4i L3 swerve. The drivetrain is 24 in x 24 in with a height of 4 1/4 in.
ENDGAME Unconfirmed	**AUTONOMOUS** Trajectory following with PathPlanner and 4 auto paths. Limelight pipelines adjust the chassis toward game pieces in auto. The autos also run in WPILib field simulation.
VISION Limelight pipelines find game pieces and adjust the chassis toward them in auto. AprilTag localization was developed but not fully used in season.	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- The release lists closest-node scoring and other features that were not ready in season. Read them as work in progress next to the competition code.

Onshape CAD: Onshape CAD · CAD and code release (CD) · Onshape CAD · Code (GitHub) · Behind the Bumpers thread (CD)

■ Study pick

1561 Roboducks Duck N' Cover V2

USA-OK

Local EPA 50 (#327)

39-20

Cube-only: pivoting arm with a cube shooter/intake; SDS MK4i L2 swerve; about 85 lb

SCORING (CONE / CUBE) Cube shooter/intake on a pivoting arm. For the final robot, the OP believes the shooter ratio is close to 1:1. The week 2 version was built from a piece of polycarbonate and two aluminum rods, with Falcons attached directly to the shooter. It was driven manually with joysticks. It popped cubes and broke chain. The week 6 version refines it.	**INTAKE** The shooter/intake on the arm collects cubes; the final robot does not handle cones. The week 1 robot had a four-bar intake with a floating roller, all aluminum, that weighed over 20 lb; the team scrapped it. The simplified week 1 robot used a ramp to funnel cubes from the single substation.
ARM / ELEVATOR Low pivoting arm, chosen to keep the robot low for fast cycles. The OP believes the arm uses a 20:1 AndyMark gearbox. For Tulsa the team added preset arm positions. The week 1 robot had a tower with a WCP telescoping arm driven by a winch; the team dropped the tower for week 2.	**DRIVETRAIN** Swerve on SDS MK4i modules in the L2 ratio. The team considered L3 but did not have time. The week 6 robot has a smaller drive base than the week 2 robot.
ENDGAME Charge Station balance. The team added balancing for week 2 and had a working balance auto at Tulsa (Green Country Regional).	**AUTONOMOUS** Balance auto from Tulsa onward. After Tulsa the team ran a three-piece auto on the bump side.
VISION Unconfirmed	**PUBLIC CAD / DESIGN** STEP CAD (zip)

LESSONS FOR STUDENTS

- Compute the ceiling of a narrow strategy before you build: the team found a cube-only robot could reach a theoretical 75 points.
- Weight affects acceleration: the OP credits the final robot weight for its acceleration.
- Scope to the time available: the week 1 robot weighed over 135 lb, and the team scrapped it days before competition.
- Secure CAN wiring: the team reports a CAN fault at Tulsa and a loose CAN wire that stopped the robot at Championship.

CAD download: STEP CAD (zip) · CAD release and season overview (CD) · STEP CAD (zip) · Code (GitHub) · Behind the Bumpers (CD)

Profile	4561 TerrorBytes Fulcrum USA-NC	Local EPA 48 (#356) 45-16-2

Double-jointed arm on MAX Tube; Everybot-inspired intake added at States; SDS MK4i swerve

SCORING (CONE / CUBE) At the first event the team stopped scoring high cones to limit stress on the arm joints. At Wake County they scored low for links when their data predicted a win and scored high in close matches.	**INTAKE** The first intake was horizontal because it could be mounted and tested sooner. Two days before the FNC State Championship they fitted an intake inspired by Everybot, 2910 and 7890, aiming for a touch-it, own-it intake. The new intake required set-points tuned in the pit.
ARM / ELEVATOR Double-jointed arm. V1 used REV MAX Tube and competed all season. V2 was planned as an arm modeled on 971's 2018 'Exotica' arm but was not fitted. The shoulder sprocket and chain wore and stripped at the first event; the team planned a second sprocket to reinforce the joint. After States they added absolute encoders to the joints, replacing limit switches used to zero at match start.	**DRIVETRAIN** SDS MK4i swerve modules, bought at the end of the 2022 season. The team chose swerve for mobility and speed on the open field. In the off-season they ran 3D-printed tread of TPU 95A at 30% gyroid infill on PLA+ hubs.
ENDGAME Unconfirmed	**AUTONOMOUS** Unconfirmed
VISION Unconfirmed for the season robot. The team planned to add a Limelight in the off-season for odometry testing.	**PUBLIC CAD / DESIGN** 'Neptune' off-season robot CAD (Onshape)

LESSONS FOR STUDENTS

- Size chain-driven arm joints with margin: after the shoulder sprocket stripped and bent, the team named design for manufacture as its focus for the next year.
- Make wear parts fast to swap: the team plans to make changing a bent or stripped sprocket easier on future robots.
- Absolute encoders make arm positions smoother.
- A late intake swap costs tuning time in the pit; the team decided not to change code in the pit in future.
- Ship the simpler version first: the V1 arm went to the programmers early.

Onshape CAD: 'Neptune' off-season robot CAD (Onshape) · Open Alliance thread with season recap (CD) · 'Neptune' off-season robot CAD (Onshape)

Profile	1714 MORE Robotics USA-WI	Local EPA 47 (#402) 26-15

Elevator; new intake, elevator carriage and wrist in place of the shoulder, added for Championship

SCORING (CONE / CUBE) Roller end effector at the end of the arm. It has a row of compliant wheels above two lower rollers. The CAD names it Vripper V1 (per CAD).	**INTAKE** The roller end effector is the only game piece mechanism in the CAD. There is no separate floor intake (per CAD).
ARM / ELEVATOR Tilted Configurable Thrifty Elevator with a base stage and a middle stage. An arm pivots at the top of the moving stage and carries the end effector. NEO motors with REV MAXPlanetary gearboxes are in the BOM (per CAD).	**DRIVETRAIN** Swerve with 4 SDS MK4i modules in the Falcon 500 configuration, for drive and steer. CANcoders on the modules and a CTRE Pigeon 2.0 gyro. Square frame (per CAD).
ENDGAME No endgame mechanism in the CAD (per CAD).	**AUTONOMOUS** Unconfirmed
VISION Unconfirmed	**PUBLIC CAD / DESIGN** Onshape CAD

Onshape CAD: Onshape CAD · CAD and code release thread (CD) · Onshape CAD · Code (GitHub) · Behind the Bumpers thread (CD) · Behind the Bumpers video

Profile	4392 The Deceivers Achilles USA-MI	Local EPA 47 (#392) 32-26

Funnel cone holder with roller wheels on a two-joint arm (shoulder and elbow); tank-style drive

SCORING (CONE / CUBE) End effector at the end of the upper arm. It has a funnel-shaped cone holder with rollers of 2 in Thrifty squish wheels below it (per CAD).	**INTAKE** No separate intake in the CAD. The end effector on the arm is the only game piece mechanism (per CAD).
ARM / ELEVATOR Two-joint arm. The lower arm has 2 uprights that pivot at the frame on a shoulder shaft driven by #25 chain. The upper arm is a single tube that pivots at the top of the lower arm. Long belts run up the lower arm to drive the elbow (per CAD).	**DRIVETRAIN** Tank-style drive with the wheels in a line along each side, under covers. No swerve modules are in the BOM. The BOM does not name the drive gearboxes (per CAD).
ENDGAME No endgame mechanism in the CAD (per CAD).	**AUTONOMOUS** Unconfirmed
VISION The BOM names Limelight 2 cameras. Camera units are on short posts at the front and rear of the frame (per CAD).	**PUBLIC CAD / DESIGN** Onshape CAD

Onshape CAD: Onshape CAD · Onshape CAD · Robot reveal 'Achilles' (CD) · Reveal video

■ Study pick	131 CHAOS USA-NH	Local EPA 42 (#560) 20-25

Extender on linear sliders with a wrist and a light roller gripper; 1/8 in steel belly plates as ballast; swerve

SCORING (CONE / CUBE) Roller gripper. The team describes it as rigid and light weight, and states more aggressive pocketing could have removed more weight. A REV UltraPlanetary drives the gripper with no issues.	**INTAKE** No separate ground intake is visible. The top-level BOM lists an intake entry, but the rendered views show no mechanism for it. The roller gripper at the end of the arm is the only game piece mechanism in the views (per CAD).
ARM / ELEVATOR An extender on linear sliders with needle rollers, plus a wrist. The team reports two needle roller failures over the season. In the previous season their GreyT Telescope had a bearing failure about every other match. The CAD shows REV UltraPlanetary gearboxes on the extension and wrist; the team found them not durable enough there. They changed the wrist to a 550 motor on a VersaPlanetary, and the season ended with an extension gearbox failure.	**DRIVETRAIN** Swerve; the team mentions the swerve modules and supports in the frame tubes. Electronics hang from a brain pan, which the team does not recommend because the shield was hard to remove. After Week 1 they addressed CG issues with 1/8 in steel belly plates that also served as the shield. #10-32 button head screws hold the plates into captive lock nuts: 8 screws on the battery box plate and 4 on the other.
ENDGAME The ballast mount had to hold when the robot flew over the Charge Station and landed on a cone.	**AUTONOMOUS** Unconfirmed
VISION Two Limelight 2 cameras on two chassis Limelight mounts. The CAD also models their fields of view (per CAD).	**PUBLIC CAD / DESIGN** CAD release (CD)

LESSONS FOR STUDENTS

- Study the roller gripper: the team recommends it as an example of a light, rigid roller system.
- Design the linear sliders for service: the team wants the next version replaceable without removing the side plates.
- The 'Pocket Nut Holder' is an aluminum block with 0.5 in hole spacing. The team describes flush-mount and stand-off versions.
- Plan service access early: removing the steel belly shield needed a drill, and fitting nut holders mid-season needed router-cut access holes in the tubing.

CD thread: CAD release (CD) · CAD release (CD) · Robot CAD (Onshape) · Pocket Nut Holder Part Studio (Onshape) · Team code (GitHub)

Profile	4322 Clockwork USA-CA	Local EPA 42 (#571) 16-9

Floor pickup limited to cubes; arm on a pivot shaft with a chain; swerve on SwerveX modules with Falcon 500 motors

SCORING (CONE / CUBE) Grabber at the end of a telescoping arm (WCP GreyT Telescope). The grabber has 2 parallel columns of stacked roller wheels that point down from a mounting plate (per CAD).	**INTAKE** Floor pickup worked only for cubes; the team states this was due to its intake design. The team cycled to the single substation and looked for ways to cut that trip time. In November 2023 the team printed two new intake braces and fitted one.
ARM / ELEVATOR Arm on a pivot shaft with a chain. In November 2023 the team replaced the arm pivot shaft. The arm chain was loose after that, and the team retensioned it.	**DRIVETRAIN** Swerve on Swerve X modules with Falcon 500 motors. The team states that defense against the robot was a major problem during the season. In the off-season the team built 3-motor swerve modules from the OpenSwerve design with NEO steering and a CANivore. In December 2023 it took one apart and started to assemble a 2-motor SDS MK4i module.
ENDGAME No endgame mechanism in the CAD (per CAD).	**AUTONOMOUS** The technical binder has a section on the autos.
VISION The technical binder has a section on the vision system.	**PUBLIC CAD / DESIGN** Robot CAD (Onshape)

LESSONS FOR STUDENTS

- Plan wire routes through structure: a December 2024 team post says many wires on the robot were damaged where they were crammed through a tube.
- An intake limit drives other choices: the team looked at drivetrain speed to cut single-substation cycle time.
- More drive motors need current limits: the team planned current and voltage monitoring because 3-motor swerve can draw more power than the breaker handles.

Onshape CAD: Robot CAD (Onshape) · CAD, code and binder thread (CD) · Robot CAD (Onshape) · Code (GitHub) · Technical Documentation (Google Drive)

Profile	3136 O.R.C.A. USA-VA	Local EPA 41 (#600) 25-21

Tilted 3-stage elevator, intake on the middle carriage; narrow frame on traction wheels (Jan 2023 build log plan)

SCORING (CONE / CUBE) The January plan holds game pieces in a separate intake on the elevator's middle carriage, not at the end of the elevator as on Cranberry Alarm's Ri3D robot.	**INTAKE** V1 took its actuation idea from team 3636: a plate and custom gears bolted to the arm. It had a flat top for cones, a diamond-shaped area for cubes and compliant wheels; the team judged it over-engineered. V2 used 2 in belting to grab cones and compliant wheels as 'claws' for cubes. V2 held cubes well but did not grab cones consistently from above bumper height.
ARM / ELEVATOR Tilted 3-stage elevator, chosen by vote from 17 concepts; the team cites Cranberry Alarm's Ri3D design. Sketch limits: first stage no longer than 56 in to fit the frame perimeter, about 35 deg to score within the extension limit, and a pivot from about 60 deg to about 35 deg. The team needed elevator angle control so a cone does not hit the poles. The team's 2024 log calls it an 'elevator on an elevator'.	**DRIVETRAIN** Traction wheels. The team rejected mecanum because it could be pushed and lose traction on the Charge Station; omni and pneumatic wheels were also rejected. Custom flipped gearboxes save space in a narrower, rectangular frame; v1 was built, then adjusted and re-cut.
ENDGAME The team chose a narrower robot so three robots can fit more easily on the 8 ft wide Charge Station for the Activation bonus.	**AUTONOMOUS** Unconfirmed
VISION Unconfirmed	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- Derive mechanism geometry from the rules first: the team sketched the elevator in Onshape before detailed CAD.
- A structured concept choice: the concepts came from Ri3D robots and 2018-2019 robots, with two rounds of voting. The team picked the tilted elevator because it was simple, the team had built an elevator before, and Ri3D had documented it.

Onshape CAD: Onshape CAD · Open Alliance build log (CD) · Onshape CAD · 2024 build log with recap (CD)

Profile	293 SPIKE USA-NJ	Local EPA 39 (#710) 26-16-2

Cable-actuated claw on a single pivot arm on a T-slot tower; tank drive

SCORING (CONE / CUBE) Claw with two curved fingers at the end of the arm. A bicycle cable puller and extension springs operate it (assemblies Cable Claw with extender arm, Bike Cable Puller) (per CAD).	**INTAKE** No separate intake in the CAD. The claw is the only game piece mechanism (per CAD).
ARM / ELEVATOR Single arm on a pivot at the top of an A-frame tower made of T-slot framing. The Pivot Mount and Motor Assembly drives the pivot. The arm assembly includes a 565 HTD belt (per CAD).	**DRIVETRAIN** Tank drive with two VEX two-Falcon transmissions, one per side. Falcon 500 motors. The side view shows four wheels per side. Frame of T-slot framing (per CAD).
ENDGAME No endgame mechanism in the CAD (per CAD).	**AUTONOMOUS** Unconfirmed
VISION Limelight 2 on a Limelight angle bracket (per CAD).	**PUBLIC CAD / DESIGN** Robot CAD (Onshape)

Onshape CAD: Robot CAD (Onshape) · Robot CAD (Onshape) · Legacy CAD release thread (CD) · Control system CAD (Onshape) · Control system thread (CD)

Profile	1018 Pike RoboDevils USA-IN	Local EPA 39 (#687) 11-18

Single-joint 'Sushi arm' planned for low/mid scoring and substation pickup; AM14U5 8-wheel kit chassis with NEOs

SCORING (CONE / CUBE) Not final in the January posts. A quick roller claw mock-up showed that cubes are easy to intake. A student's roller claw intake design did not get the cone compression right. In late January, students were working on how to integrate an Everybot-style pinch roller.	**INTAKE** Substation shelf pickup of cones and cubes was a 'need'. Floor pickup was on the will-not-do list, though the mock-up geometry might allow floor pickup of cubes. A student mock-up of the Everybot intake picked up cones at many angles.
ARM / ELEVATOR A 'Sushi arm': a single-joint arm optimized for low and mid scoring, with influence from 7461's single-joint dead-axle arm. A passover arm was tested with a wooden mock-up and dropped because each score took about 230 deg of arm motion. A pneumatic extension for the high cone node, as on Sushi Squad's Alpha bot, was under consideration.	**DRIVETRAIN** AM14U5 kit chassis with the 8-wheel XL Performance wheel kit and a 24 in frame width. The performance wheels kept the HiGrip track width while cutting 2 in of frame width. 10.86:1 EVO Slim 2-motor gearboxes with NEOs, chosen for a sprint distance of about 20 ft. Swerve was on the will-not-do list.
ENDGAME Dock and engage on the Charge Station in auto and endgame was a 'need'.	**AUTONOMOUS** Planned routine: score the preloaded piece, drive across the auto line, and dock and engage. Programmers were working on auto-balance in late January.
VISION Automated AprilTag alignment was listed as a 'want' in January.	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- Set a deadline for the needs on the list: the team set week 4-5.
- Use a physical mock-up when CAD capacity is short. The wooden arm also tested front-rear bias.
- Frame width is a design variable in this game: the team cut frame width to leave more room on the Charge Station.

Onshape CAD: Onshape CAD · Open Alliance build thread (CD) · Onshape CAD · Code (GitHub)

Profile	3739 Oakbotics Blue Steel Canada	Local EPA 39 (#697) 20-28

Intake redesigned after week 1; MAXSwerve chassis

SCORING (CONE / CUBE) Unconfirmed	**INTAKE** The release render shows the week 1 intake. At the Georgian event the team judged it a bottleneck, then designed, prototyped and built a new REV1 intake over the next week. The release post has an image of REV1.
ARM / ELEVATOR Unconfirmed	**DRIVETRAIN** MAXSwerve chassis, driving by week 2 of build season.
ENDGAME Unconfirmed	**AUTONOMOUS** 1.5 piece bump side auto, run through the DCMP playoffs.
VISION Unconfirmed	**PUBLIC CAD / DESIGN** GrabCAD CAD

LESSONS FOR STUDENTS

- Read the release post: the team credits its programmers for the control loops and autos.

GrabCAD: GrabCAD CAD · CAD and code release (CD) · GrabCAD CAD · Code (GitHub)

Profile	1072 Harker Robotics USA-CA	Local EPA 38 (#767) 20-18

Inclined elevator with no end effector in the CAD; pneumatic wheel arm; MK4 swerve

SCORING (CONE / CUBE) No end effector is modeled at the top of the elevator (per CAD).	**INTAKE** Unconfirmed
ARM / ELEVATOR Inclined elevator on two angled towers. Two WCP single stage gearboxes with Falcon 500 motors are in the BOM. A short arm near the elevator base carries two wheels at its end. A pneumatic cylinder and a gear pair are at its pivot. A Viair 90C compressor is in the BOM (per CAD).	**DRIVETRAIN** Swerve with four SDS MK4 modules. Falcon 500 drive and steer motors and CANcoders are in the modules. A Pigeon IMU is in the BOM (per CAD).
ENDGAME Unconfirmed	**AUTONOMOUS** Unconfirmed
VISION One Limelight 2 mounts on the elevator structure above the frame (per CAD).	**PUBLIC CAD / DESIGN** Onshape CAD

Onshape CAD: Onshape CAD · Onshape CAD · Code (GitHub) · 2024 build thread with links (CD)

■ Study pick

3926 MPArors Snowdrift

USA-MN

Local EPA 38 (#734)

14-17

Low-goal cycler with one intake for both pieces; slim modified KoP tank base, EVO Shifters, 8 in pneumatic wheels

SCORING (CONE / CUBE) Low goal only. The team planned to cycle game pieces from the substation to the hybrid nodes or to alliance partners. The cycle target was 8-10 full-field cycles a match, about 12 s each.	**INTAKE** One intake for both cones and cubes. The team rejected separate cone and cube intakes on opposite sides because two intakes on the small frame would have made it hard to mount the electronics and the battery. An early concept used four powered compliant wheels: a wider front pair for cubes and a narrower rear pair for cones. 7 in inside edge to inside edge worked for the outer black compliant wheels. The separate cube intake prototype used four compliant wheels, two stacked.
ARM / ELEVATOR No arm or elevator. The team prototyped a single-degree-of-freedom high-goal arm (inspired by 1503 and 179's 2011 robots) and dropped it. It cited the arm's constraints and its experienced leaders being spread too thin.	**DRIVETRAIN** Modified kit-of-parts drivetrain in its slimmest configuration. The team states it would run 'some form of tank drive' because its SDS swerve modules arrived too late. The team chose AndyMark EVO Shifters to cut time crossing midfield, and 8 in pneumatic wheels so it could drive over the Charge Station. Motors 'most likely' 4 or 6 NEO at the design stage.
ENDGAME The team aimed for a small, light robot so it could join a double balance and help enable a triple balance.	**AUTONOMOUS** Unconfirmed
VISION Unconfirmed	**PUBLIC CAD / DESIGN** 'Snowdrift' full assembly (Onshape)

LESSONS FOR STUDENTS

- A low-goal cycler can be a planned role: the team argued that a fast feeder lets a high-goal partner skip the slow, congested half of each cycle.
- Drivetrain plan follows the field: the team planned to cross the Charge Station repeatedly and leave the congested lanes free.

Onshape CAD: 'Snowdrift' full assembly (Onshape) · Open Alliance thread (CD) · 'Snowdrift' full assembly (Onshape) · Code (GitHub)

Profile

1710 The Ravonics Revolution SlipSTream

USA-KS

Local EPA 37 (#821)

27-20

Pneumatic claw with self-leveling pads; 2-roller intake; double-jointed arm on 6 NEOs; Mk4 swerve

SCORING (CONE / CUBE) Pneumatic claw with self-leveling pads. The team says the robot can score on all levels.	**INTAKE** 2-roller intake inside the frame perimeter, per the March 2023 reveal. The team's November 2023 CowTown report mentions an over-the-bumper intake belt that slid off and a broken pulley. The two sources differ; confirm in the CAD.
ARM / ELEVATOR Double-jointed arm driven by 6 NEOs. The team calls the gear ratio 'absurd' but does not state it. At CowTown the arm once failed to lift a game piece out of the intake in auto, and once did not respond properly to commands when a NEO wire disconnected at a junction.	**DRIVETRAIN** Mk4 swerve on an A-frame chassis, 28 in x 28 in. The robot weighs roughly 105 pounds.
ENDGAME Unconfirmed	**AUTONOMOUS** The CowTown report shows the auto sequence uses the arm to lift a game piece out of the intake.
VISION Unconfirmed	**PUBLIC CAD / DESIGN** Competition robot CAD (Fusion 360)

LESSONS FOR STUDENTS

- The team logs each match problem with cause and fix, for example a battery that started below 10V and driver controllers switched by the drive team. It uses a pre-match checklist, and spare belts are pre-made for belt wear.

Fusion 360 CAD: Competition robot CAD (Fusion 360) · Robot reveal 'SlipSTream' (CD) · Competition robot CAD (Fusion 360) · Reveal video · CowTown ThrowDown report (CD build thread)

Profile	4488 Shockwave Supercell USA-OR	Local EPA 37 (#820) 22-25

Top and bottom roller claw on a long arm that pivots atop a fixed angled tower; WCP Swerve X swerve

SCORING (CONE / CUBE) Roller claw at the end of the arm. It has a top roller and a bottom roller with compliant wheels between curved side plates. A VersaPlanetary gearbox with a 775 Pro motor mounts on the claw (per CAD).	**INTAKE** No separate floor intake in the CAD. The roller claw at the end of the arm takes the game pieces (per CAD).
ARM / ELEVATOR A single long arm pivots at the top of a fixed, angled tower. Belts run from the arm pivot down the tower to a large pulley near the frame. Two cylinders link the tower to the arm. The BOM has a VIAIR compressor and Clippard air tanks (per CAD).	**DRIVETRAIN** Swerve with 4 WCP Swerve X modules (tube mount, flipped gears below). The BOM has Falcon 500 motors and CANcoders (per CAD).
ENDGAME No endgame mechanism in the CAD (per CAD).	**AUTONOMOUS** Unconfirmed
VISION Limelight 2 on a shaft-clamp mount on the tower. The BOM also has an ELP camera mount on the tower (per CAD).	**PUBLIC CAD / DESIGN** Onshape CAD

Onshape CAD: Onshape CAD · Onshape CAD 'Supercell' · CAD and code release (CD) · Code (GitHub)

Profile	342 Burning Magnetos USA-SC	Local EPA 36 (#879) 29-24

Roller gripper claw on a single-pivot arm from a tall tower; 6-wheel tank drive

SCORING (CONE / CUBE) Gripper claw at the end of the arm, with green roller wheels along its jaws. A REV Color Sensor V3 is on a mount on the gripper. The BOM names a NEO 550 motor (per CAD).	**INTAKE** No separate intake in the CAD. The arm lowers the gripper into an opening in the front of the frame and bumpers (per CAD).
ARM / ELEVATOR Arm on a pivot shaft at the top of a tall upright tower. 2 MAXPlanetary gearboxes drive the arm through chain. The arm also has a driver link, a gas spring and a REV Through Bore Encoder (per CAD).	**DRIVETRAIN** 6-wheel tank drive with 6 in WCP wheels, 3 per side. 2 WCP single-speed gearboxes drive the wheels through #35 chain. The BOM names NEO motors with SPARK MAX controllers (per CAD).
ENDGAME No endgame mechanism in the CAD (per CAD).	**AUTONOMOUS** Unconfirmed
VISION Limelight 2 on a mount on the arm tower (per CAD).	**PUBLIC CAD / DESIGN** Onshape CAD (final assembly)

Onshape CAD: Onshape CAD (final assembly) · Onshape CAD (final assembly)

Profile	8738 Slice USA-NC	Local EPA 35 (#905) 28-23

Arm on an elevator; Kit of Parts tank drivetrain; offseason rebuild added a wrist and swerve

SCORING (CONE / CUBE) The team cut polycarbonate for its grabber mechanism in week 7 (post of 2023-03-01).	**INTAKE** The arm had a recorded state for picking up a cone from the double substation. The team built several intake prototypes in weeks 2-6.
ARM / ELEVATOR The team bought a single-stage Thrifty Bot elevator kit in week 2 and mounted its elevator in week 7. It also looked at a rack and pinion telescoping arm after problems with string-based designs in 2022, and printed a test rack segment. In season an arm on the elevator moved between recorded motor-angle states (stowed, high row, double substation) with positional PID on each motor. Changed in the offseason: the arm gained a wrist for 3 degrees of freedom, with code checks that keep the intake and wrist off the elevator.	**DRIVETRAIN** Kit of Parts drivetrain, built in weeks 2-5. The team first built a 20 in x 32 in KoP frame to test a narrow drivetrain, with the end pieces left uncut so it could go wider. The offseason write-up says the robot used tank drive in season. Changed in the offseason: upgraded to swerve, the team's first.
ENDGAME Programming tested automatic Charge Station balancing code in week 3 and posted a clip captioned 'Successful auto Charge Station balancing'. Early field modeling led the team to expect that large robots may not fit a side-by-side triple engagement, and it took this into the design.	**AUTONOMOUS** Programming debugged Pathweaver autos in December 2022, then started over with PathPlanner in week 2. It began testing the new auto code in week 5. The team won the Autonomous Award at FNC District Johnston County.
VISION Unconfirmed in season. Programming tested AprilTags on a Limelight 2+ in week 3 and researched PhotonVision.	**PUBLIC CAD / DESIGN** Robot CAD (Onshape)

LESSONS FOR STUDENTS

- Prototype before design decisions: the mentors asked for physical prototypes first.
- Offseason swerve bring-up: the code set angle motor inversion before the factory reset. Three workarounds hid the bug until the team moved the inversion after the reset.
- Offseason joystick shaping: a polynomial curve on x and y separately locked driving to the cardinal directions; applying it to the polar radius fixed it.

Onshape CAD: Robot CAD (Onshape) · Robot CAD (Onshape) · Open Alliance build thread (CD) · Blender design model (Google Drive) · Offseason write-up in the next build thread (CD) · Offseason robot CAD (Onshape) · Offseason code (GitHub)

■ Study pick

555 Montclair Robotics

USA-NJ

Local EPA 34 (#987)

18-24

3-stage cascade elevator with horizontal scissor 'stinger', printed pneumatic gripper, roller-bar intake; swerve

SCORING (CONE / CUBE)

Pneumatic gripper: plates between two arms clasp the game piece. The gripper is 3D printed in carbon fiber filled high-temp PLA to save weight, because it sits on the end of the stinger, which the team calls 'a giant cantilever'. Standard PLA prototypes came first; the team moved to CAD and 3D printing after slow metal and polycarbonate prototypes in Week 2. In Week 6 the preferred plate surface was pool noodle covered with sandpaper. The January plan had free-spinning plates so a cone turns to the scoring orientation.

INTAKE

Changed in week 7. The original deployable wheeled intake (the 'schwooper') folded with pneumatic cylinders. Its metal prototype used green AndyMark compliant wheels. In January a cone fed base first sometimes caught between the wheels; the team planned nylon blockers between them. In testing at team 4361 on 2023-02-25 the cylinders could not deploy the intake from their mounts, and the team removed it. The replacement is a roller bar with wheels like the 2022 intake, built in one week with no CAD; the plan added a sheet metal ramp that funnels pieces into a collection area for the gripper.

ARM / ELEVATOR

A 3-stage cascade elevator carries a horizontal scissor 'stinger'; the team chose this over an extending arm on 2023-01-29. The elevator was re-CADed three or four times to fix a bearing block issue, and the CAD was complete by 2023-02-19. The elevator is rigged with springs, rope and chain. Changed in week 8: new parts for the scissor actuation, which the team expected to extend and retract faster; the January plan used springs and a lead screw. The battery mounts in a vertical electronics stack that helps counterbalance the robot when extending.

DRIVETRAIN

Swerve. The team built an MK4i swerve drivetrain in the 2022 offseason and stated it would use swerve this season. A 2023-02-22 post refers to the drive modules and to two steel bars across the front that support the drivetrain. The frame perimeter is 27x30 in; it grew from 25x30 in after an inflated cube did not fit a 10 in opening.

ENDGAME

Auto balancing on the Charge Station worked in code by the Week 6 post (2023-02-19).

AUTONOMOUS

Charge Station auto balancing ran by 2023-02-19. TBA lists the Autonomous Award at FMA District Warren Hills; the team's post says the award was 'for the pretzel'.

VISION

Limelight with AprilTags tracked in 3D space. The team shorted one Limelight and broke another during build season, then got PhotonVision working. It wrote an interface that swaps between Limelight and PhotonVision by changing a few variables. At the District Championship it used a Limelight lent by team 341 after it chipped its own lens.

PUBLIC CAD / DESIGN

Robot CAD (Onshape)

LESSONS FOR STUDENTS

- Compare two architectures on paper first: the team framed elevator-plus-stinger as Cartesian (x then y) and the extending arm as polar (r then theta), and named the weak point of each.
- Prototype with an actual game piece before frame lock; the frame grew after an inflated cube did not fit.

Onshape CAD: Robot CAD (Onshape) · Build thread (CD) · Robot CAD (Onshape) · Code (GitHub) · Kickoff design document (Google Docs) · Intake failure design-meeting notes (Google Docs) · Mount Olive event report (Basecamp) · Warren Hills event report (Basecamp) · District Championship event report (Basecamp)

■ Study pick

3737 Roto Raptors BB Mantis

USA-NC

Local EPA 20 (#2221)

12-16-2

Passive claw on a cord-extended arm; through-robot handling; all motors on chassis; 3D-printed PETG swerve

SCORING (CONE / CUBE) Passive game piece claw that closes on contact. Cord on a spool driven by a 24:1 3D-printed cycloid gearbox resets the claw.	**INTAKE** The release lists through-robot game piece manipulation; a separate floor or substation intake is not described.
ARM / ELEVATOR Arm driven by a NEO through a chain input stage, a 48:1 3D-printed cycloid gearbox and a chain output stage, for the 200:1 the team needed with a cone at full extension. A gas shock relieves load on the arm motors, and a compliant arm joint withstands side impact. Arm extension uses cord on a 24:1 cycloid spool. The published CAD shows the later VEX spur-gear arm gearbox.	**DRIVETRAIN** 3D-printed PETG swerve modules bolted under a 3030 T-slot chassis. The released base design uses NEO drive and NEO 550 steer motors with a 4 in x 1.5 in wheel. The robot ran the team's TPU suspension tread wheels; the tread post states its 89 lb robot used 40% infill. All motors sit on the chassis for a low CG.
ENDGAME The tread pattern was designed for grip on the Charge Station; the team states it let the robot climb it with ease.	**AUTONOMOUS** Unconfirmed
VISION Unconfirmed	**PUBLIC CAD / DESIGN** CAD and LabVIEW code (Google Drive)

LESSONS FOR STUDENTS

- A cycloid with three discs at 120 deg offset keeps nearly full tooth engagement and runs balanced; the team states a PETG-printed version carries more torque than expected.
- Upgrading one spur gear can move the failure: a steel 18T penultimate gear moved the failure to the final aluminum gear.
- Suspension tread infill sets the contact patch: the team aims for about 1 in of flat on the carpet and uses more infill near max weight.
- A printed swerve module can be documented like a product: the release states size (5.35 x 7.02 x 9.11 in), weight (2.5 lbs without motors, gearboxes and controllers), five drive ratios and a full BOM.
- Choose fastening for printed parts: the team avoids carbon-fiber filament for health reasons and uses self-tapped threads with no brass inserts. Its 2026 posts give 4.5 mm holes for #10-32 screws, about 3x D deep for pull-out loads.

Drive folder / doc: CAD and LabVIEW code (Google Drive) · CAD and code release (CD) · CAD and LabVIEW code (Google Drive) · 3D-printed swerve release (CD) · Swerve CAD, BOM and instructions (Google Drive) · Suspension tread release (CD) · Suspension tread CAD (Google Drive)

■ Study pick

9062 Critical Circuits Bryce

Canada

Local EPA 19 (#2368)

15-34

Long-range dual-flywheel cube shooter, two side roller intakes, 38 x 22 in MK4i L2 swerve

SCORING (CONE / CUBE) Dual flywheel cube shooter: 4 in Colson wheels on 2x NEOs at 1:1, inclined 15 degrees. The team reports a 35 ft range that proved inaccurate at that distance. A 1-button launch sequence runs the sequencer and the shooter flywheel assemblies. Low scoring works by outtaking through the side intakes.	**INTAKE** Two side roller intakes for cubes, each 22 in wide. A pneumatic cone 'nose' gripper, similar to 2019 hatch grabbers, was removed before DCMP due to limited use and effectiveness.
ARM / ELEVATOR The team lists a 'stick arm' and states a 6.5 in center of gravity regardless of stick arm location. A sequencer feeds the shooter.	**DRIVETRAIN** Swerve on MK4i modules at the L2 ratio. 38 in by 22 in chassis with a 1/8 in steel belly pan; the team states it is the longest swerve to its knowledge.
ENDGAME Charge Station balance is part of the 2 piece autonomous mode.	**AUTONOMOUS** A 2 piece balanced autonomous mode plus 4 alternative autonomous modes.
VISION Limelight 2+ with auto-alignment for cube node AprilTags.	**PUBLIC CAD / DESIGN** Onshape CAD (the team calls it incomplete)

LESSONS FOR STUDENTS

- Report range and accuracy separately, as the team did for the shooter.
- Remove what does not earn its place: the full pneumatics system came off with the cone gripper.
- Compare with the offseason robot 'Bill' (MK4i L3 on a 24 in square chassis, linear actuator shoulder, 180:1 elbow on 2x NEOs) to see how the second design changed.

Onshape CAD: Onshape CAD (the team calls it incomplete) · Robot showcase and season overview (CD) · 'Bryce' CAD (Onshape) · Offseason robot 'Bill' thread (CD) · 'Bill' CAD (Onshape) · 'Bill' code (GitHub)

Profile

663 Power Sharks MAKO

USA-MA

Local EPA 18 (#2546)

11-12

Pneumatic claw on a motorized wrist, pneumatic arm extender, electric chain-driven elevator; 6 NEO 6WD

SCORING (CONE / CUBE) Pneumatic claw on a motorized wrist.	**INTAKE** The release post names no separate intake; the claw is the only game piece mechanism it names.
ARM / ELEVATOR Electric chain-driven elevator with a pneumatic arm extender.	**DRIVETRAIN** 6WD driven by 6 NEO motors.
ENDGAME Unconfirmed	**AUTONOMOUS** Unconfirmed
VISION Unconfirmed	**PUBLIC CAD / DESIGN** Concept robot CAD (Onshape)

LESSONS FOR STUDENTS

- Study how the CAD routes air and power to the end of the arm.

Onshape CAD: Concept robot CAD (Onshape) · CAD release thread (CD) · Concept robot CAD (Onshape)

Profile	7125 Tigerbotics Killua USA-TX	Local EPA 9 (#3243) 9-15

Pneumatic pincer with compliant wheels on a pivot arm; angled three-stage elevator; mecanum drive

SCORING (CONE / CUBE) Pincer end effector at the end of the arm. Two pneumatic cylinders move the pincer plates. Belt-driven 4 in compliant wheels are on the pincer shafts. The BOM includes NEO 550 motors (per CAD).	**INTAKE** No separate intake in the CAD. The pincer end effector is the only game piece mechanism. In the side view the arm holds it down at floor level in front of the frame (per CAD).
ARM / ELEVATOR Angled three-stage elevator (Configurable Thrifty Elevator) with constant force springs. It rises from the rear of the frame and leans out past the front. An arm of REV MAX Tube pivots on the elevator on a 60T #35 chain sprocket. A REV Through Bore encoder is on the elevator (per CAD).	**DRIVETRAIN** Mecanum drive on the 2022 Everybot chassis ('EB 2022 Chassis'). Four 6 in mecanum wheels, each driven by a NEO through an AndyMark Toughbox Micro gearbox (per CAD).
ENDGAME No endgame mechanism in the CAD (per CAD).	**AUTONOMOUS** Unconfirmed
VISION Unconfirmed	**PUBLIC CAD / DESIGN** Onshape CAD

Onshape CAD: Onshape CAD · Onshape CAD

Sources: the Spectrum 3847 CAD Collection, team CAD, binder and code releases, Chief Delphi release and reveal threads, and match data from The Blue Alliance. EPA is Local EPA (approx), computed independently. It is not official Statbotics data. "Unconfirmed" means the public material does not state the detail. Text marked (per CAD) was read from the team's Onshape CAD (parts list and rendered views) where no write-up states the detail.