FRC 2025 REEFSCAPE -- Robot Design Deep Dive

Each profile comes from the team's own public material: CAD (Onshape, GrabCAD, Fusion 360, STEP), technical binders, code, and Chief Delphi release and reveal threads. Performance data comes from The Blue Alliance.

The REEFSCAPE design landscape

The game

REEFSCAPE is a coral and algae game. Robots place CORAL (PVC tubes) on the four branch levels of the REEF (L1-L4). Robots score ALGAE (foam balls) in the PROCESSOR or the BARGE NET. In the endgame, robots park or climb a CAGE (shallow or deep). Many designs used an elevator or an arm to reach L4. Some top teams scored coral only and did not handle algae.

How to use this document

The first section lists the profiled robots in the top 30 by Local EPA. The second section lists the other profiled robots. Each profile gives the archetype, the subsystems, vision, endgame, autonomous routines, the public CAD or binder, and lessons for students. A star marks a study pick. Each study pick has downloadable CAD or a full technical binder and one specific design lesson. "Unconfirmed" means the public material does not state the detail. It does not mean the robot does not have it.

About the EPA numbers

The Statbotics data API is offline. EPA is Local EPA (approx): it was computed from The Blue Alliance match data with the open-source Statbotics model (github.com/avgupta456/statbotics). The rank order follows Statbotics. The absolute values can differ from statbotics.io. Records are win-loss-tie totals from official events on The Blue Alliance.

Profiled robots at a glance (sorted by Local EPA)

	Team	Robot	EPA	Rank	Record	Archetype	Public design
■	**2056 OP Robotics**	LIGHTNING	**123**	#1	68-7	Riveted sheet-metal arm; counter-rotating roller coral intake; 2D Apri	Tech binder
	1690 Orbit	Whisper	**114**	#2	62-9	Closed-belt differential elevator (variation of a community design)	Onshape CAD
■	**2910 Jack in the Bot**	Poi Pounder XXVI Spectre	**113**	#3	66-7	Shoulder, extension and wrist arm; reef-AprilTag auto-align; latch cli	Onshape CAD
■	**1678 Citrus Circuits**	SubLime	**109**	#4	57-8	Coral and algae end effectors; indexer; sideways elevator on Dyneema c	Onshape CAD
■	**1323 MadTown Robotics**		**106**	#5	53-3	Claw on a differential wrist; ground coral and algae intake with auto	Drive folder / doc
	694 StuyPulse	Aunt Mary	**99**	#11	47-8	Pivoting arm end effector on elevator; large pivoting roller intake; c	Onshape CAD
	5940 BREAD	Taiyaki	**97**	#12	46-5	Chain-driven elevator with a rolling chain tensioner; electronics moun	Onshape CAD
■	**422 The Mech Tech Dragons**	Wisp	**95**	#14	60-8	Polycarbonate coral-retention flap, coral ground intake (pivot began a	Onshape CAD
	1706 Ratchet Rockers	Singularity	**93**	#16	35-10-1	Roller end effector on a center elevator; station funnel; Thrifty Swer	Onshape CAD
■	**1778 Chill Out**	SubZero	**93**	#17	53-12	580 deg arm on a belt elevator; ground coral intake with auto handoff;	Onshape CAD
■	**604 Quixilver**	The Flush	**92**	#18	39-10	Single-stage elevator, arm and pivoting open-top gripper; full-width c	Onshape CAD
■	**3005 RoboChargers**	Relay	**91**	#19	56-9-2	Coral ejector and algae gripper on a 'laterator'; 3-stage chain-driven	Onshape CAD
	180 S.P.A.M.	Anemone	**90**	#23	44-6	Automated coral scoring, floor coral pickup, cage climb	Code (GitHub)
■	**5990 TRIGON**	TRIDOG	**90**	#22	46-13-2	Ground coral intake (about 7 kg); elevator on custom-machined bearing	Onshape CAD
■	**7407 Wired Boars**	Griptide	**90**	#24	55-13	Rotating end effector for L1-L4 coral; coral station intake; 3-stage e	Onshape CAD
■	**254 The Cheesy Poofs**	UNDERTOW	**89**	#26	42-7	Welded-tube wrist; 4-bar main intake; backup coral station funnel	Tech binder
■	**190 Gompei and the HERD**	StackUp (V1) and Redundancy (V2)	**88**	#30	68-19	Star-wheel coral outtake, closing funnel, 4-motor elevator, string cli	CD thread
■	**341 Miss Daisy**	Miss Daisy XXIII	**88**	#28	54-12	Claw on a lantern-gear shoulder with 180 deg wrist; coral floor intake	Onshape CAD
■	**9450 Velocity Raptors**		**88**	#27	50-17	Differential wrist under custom control code on an elevator; 3 piece L	Onshape CAD
■	**1732 Hilltopper Robotics**	Private	**86**	#34	41-17	4x L4 coral auto with QuestNav localization; algae handoff	Onshape CAD
	111 WildStang		**85**	#39	39-7	Arm with coral gripper and algae wheels on an elevator; over-the-bumpe	Onshape CAD
■	**1114 Simbotics**	Simbot Suzuki	**83**	#52	43-22	Station-fed coral elevator; reef algae removal; deep cage climber adde	Onshape CAD
■	**581 Blazing Bulldogs**	Zuma	**82**	#59	33-16	Champs: claw on a slip-ring arm with unlimited rotation; ground coral	Onshape CAD
■	**6800 Valor**	Deadlock	**82**	#57	59-10	Funnel; 3-stage elevator; 3 non-drive motors pre-Worlds, 5 at Worlds;	Onshape CAD
■	**9496 LYNK**	Chimney Rock (Rocky)	**81**	#69	72-7-2	Passive gas-strut algae manipulator; reef AprilTag coral alignment; lo	Onshape CAD
■	**971 Spartan Robotics**	Fiddler	**80**	#84	30-18	Funnel end effector chosen over suction; stiffened elevator with arm a	Onshape CAD
	2630 Thunderbolts	Atlas	**80**	#86	47-16-1	L4 coral scorer with algae into the net; 4 L4 coral auto in 14.3 s	Onshape CAD
	2137 The Oxford RoboCats	Guillotine	**79**	#88	47-16	Coral end effector on an elevator; station funnel; climber with roller	Onshape CAD

	Team	Robot	EPA	Rank	Record	Archetype	Public design
■	**3467 Windham Windup**		**79**	#89	49-19-1	Coral claw on an elevator; algae in horns or a lower claw; no floor in	Onshape CAD
■	**2930 Sonic Squirrels**	Holocentrus	**78**	#100	46-22	Elevator robot; 100+ short Choreo paths; PhotonVision auto-align on 4	Onshape CAD
■	**695 Bison Robotics**	Goldfish	**76**	#124	26-14	Elevator coral scorer, ramp-fed pivoting arm, modified Everybot climbe	Onshape CAD
■	**3128 The Aluminum Narwhals**	Gillbert	**76**	#122	31-13	Sensorless counter-rotating coral end effector on an elevator; interch	Drive folder / doc
■	**5460 Strike Zone**	TITAN	**75**	#141	52-12-2	Rotating coral claw with a BAG motor in a carbon tube; continuous elev	Onshape CAD
	9442 Miso Mechanics		**75**	#133	37-23	End effector and pivoting algae arm; over-the-bumper algae intake; thr	Onshape CAD
■	**294 Beach Cities Robotics**	Sacabambaspis	**73**	#160	27-18	Pivoting wrist with pass-through side rollers; station hopper; 3-stage	Onshape CAD
■	**6995 NOMAD**	Mariana	**73**	#163	54-16	Two-sided ground 'hand' for coral and algae on an elevator and pivot;	Onshape CAD
	9432 Team 8-Bit		**71**	#192	38-11	Coral arm with algae intake on a two-stage elevator; station funnel; c	Onshape CAD
	2491 NoMythic		**70**	#205	30-10	Coral end effector, algae roller arms, coral funnel, multi-stage eleva	Onshape CAD
	2877 LigerBots	Hydra	**70**	#210	42-24	Coral floor pickup to L1 in work; algae floor intake removed in March	Onshape CAD
■	**3061 Huskie Robotics**	Calypso	**70**	#220	25-15	Coral scorer on a four-stage elevator; side-to-side funnel; barge alga	Onshape CAD
	5026 Iron Panthers	The Grim Reefer	**70**	#206	32-10	Human load funnel (per a 1678 mentor's reply)	Onshape CAD
■	**6328 Mechanical Advantage**		**70**	#209	44-21	End effector on a tilted 3-stage string-rigged elevator; coral hopper;	CD thread
	1540 Flaming Chickens		**69**	#234	33-27	Arm and end effector on elevator; pivoting star-wheel intake; hook cli	Onshape CAD
	3414 Hackbots	Levi	**69**	#233	34-26	Fixed-angle coral end effector and a separate algae mechanism on an el	CD thread
	5419 Berkelium	Argonaut	**69**	#227	27-17	Coral end effector; elevator with a pivot; climb; auto-align to each r	Onshape CAD
■	**1156 Under Control**	Ultralisk	**68**	#243	32-12	Swerve with an always-on heading PID set by the right-stick angle	Onshape CAD
	1787 The Flying Circuits		**68**	#252	20-8-1	Telescoping pivot arm mounted low at the back of the robot; arm pivot	Onshape CAD
■	**8159 Golden Horn**	Serpentheim	**66**	#295	32-11	Coral funnel and a separate algae system; two cameras; deep cage climb	Onshape CAD
■	**4795 Eastbots**		**64**	#314	41-19	Elevator and chain-driven arm with a motorized wrist (added for DCMP);	Onshape CAD
	418 Purple Haze		**62**	#362	36-24	Coral scorer/algae remover ('Thagomizer'); side-biased funnel; sideway	Onshape CAD
	1153 Timberwolves	Lagotto	**62**	#369	46-24	1-stage elevator scoring coral L1-L3 and algae in processor and barge;	Onshape CAD
■	**587 The Hedgehogs**		**61**	#372	38-20-2	Hopper-fed coral scorer on an elevator with a pass-through wrist; full	Onshape CAD
	955 Ctrl C		**61**	#371	32-14	Elevator with a carriage pivot; station funnel into a coral indexer; c	Onshape CAD
	2813 Gear Heads	Maelstrom	**60**	#415	26-18	Pivoting roller claw on an elevator; pivoting roller intake arm; winch	Onshape CAD
	233 The Pink Team	Bubbly Anemone Enemy (BAE)	**58**	#458	36-17-1	Coral shooter, floor algae collector, chain-and-Dyneema cascade elevat	Onshape CAD
	1710 The Ravonics Revolution	Dobson	**57**	#483	25-13	Elevator robot for coral L1-L4; algae claw for reef algae and barge; g	Fusion 360 CAD
■	**3357 COMETS**	Tempel	**56**	#490	23-21	Wrist with coaxial roller drive; ground coral; sideways belt-in-tube e	GrabCAD

	Team	Robot	EPA	Rank	Record	Archetype	Public design
	3847 Spectrum	Gamma Ray	**55**	#515	51-13-1	Elevator plus an arm with a 'bicep' segment; climb ballasted to hang l	Onshape CAD
	555 Montclair Robotics		**53**	#572	25-18	Kickoff plan: coral/algae end effector; station-only coral; side-mount	Onshape CAD
	1714 MORE Robotics	Crush	**53**	#573	16-12	Mailbox coral end effector on an elevator; station funnel; algae rolle	Onshape CAD
	2485 Overclocked	Nessie	**53**	#581	20-16	Coral end effector fed by a bent polycarbonate ramp; elevator; cage cl	Onshape CAD
	3512 Spartatroniks	Charybdis	**53**	#557	16-9	Roller coral end effector on an elevator with 3 moving stages; low piv	Onshape CAD
	2423 The KwarQs	QwacKen	**52**	#619	22-20	Coral autoscoring with PathPlanner and PhotonVision	Onshape CAD
■	**3669 CarbonKnights**	Twitchy	**52**	#593	9-13-1	Two parallel carbon fiber tube elevators with 3D printed bearingless s	Onshape CAD
	6343 Steel Ridge		**52**	#624	30-27	Roller end effector on a pivoting arm; coral station funnel; two-stage	Onshape CAD
	1086 Blue Cheese	Stringray	**50**	#657	31-25-1	Coral L1-L4; algae from reef to net and processor; coral station intak	Onshape CAD
	2582 PantherBots		**50**	#678	34-13	Roller manipulator, ground intake, elevator, pivoting climber with gas	Onshape CAD
	525 Swartdogs		**49**	#716	15-8	Coral end effector with facing wheel stacks; station funnel; multistag	Onshape CAD
	663 Power Sharks	Thresher	**49**	#689	20-19-2	Coral-only scorer; single-stage elevator with a pivoting arm; based on	Onshape CAD
	8410 Oyster River Overdrive		**48**	#726	19-21-1	Carriage coral holder and algae arm; two-stage elevator; pivot arm and	Onshape CAD
	4192 Jaguar Robotics	Iris	**47**	#769	14-36-1	Coral end effector on chain-driven elevator; flex-wheel intake; compli	Onshape CAD
	2470 Team BJORG		**45**	#841	17-18	Roller end effector on arm, coral station chute, tilted elevator, hang	Onshape CAD
	4561 TerrorBytes		**45**	#858	34-13-1	Roller end effector on a wrist; pivoting elevator; climber; SDS MK4i s	Onshape CAD
	9418 Pastabots		**43**	#960	27-21	Differential wrist	Onshape CAD
	1740 Cyber Colonels		**42**	#988	12-17-1	January plan: coral-only, RustHOUNDS Ri3D-style pivoting dunk arm on a	Onshape CAD
	7525 Pioneers		**42**	#1007	21-15	Angled roller coral mechanism on the carriage; station funnel and pass	Onshape CAD
■	**614 Night Hawks**	Stand Mixer	**41**	#1010	19-24-1	2-in-1 ground coral intake (L1 hold or pass-through) feeding a 'Canal'	Onshape CAD
	114 Eaglestrike	Theseus	**38**	#1154	14-12	Roller end effector on a pivot arm; wide front pivoting ground intake;	Onshape CAD
	246 Lobstah Bots	Beluga	**38**	#1146	23-19	Roller end effector, coral station ramp and funnel, two-stage elevator	Onshape CAD
	4488 Shockwave	Riptide	**38**	#1145	17-11	Belted roller end effector on a wrist; three-stage telescoping pivot a	Onshape CAD
	7312 T3	Nessie	**35**	#1349	24-18	Belted coral/algae end effector; elbow and wrist pivots; 3-stage GreyT	Onshape CAD
	2079 4H ALARM Robotics		**29**	#1774	9-19-1	Top-down roller end effector on a wrist; rear coral funnel; 2-stage ca	Onshape CAD
	7691 TSA All Stars		**25**	#2124	18-24-1	Arm end effector on an elevator; pivoting ground coral intake; side al	Onshape CAD
	3481 Bronc Botz	Justice	**23**	#2295	13-26	Coral outtake on a chain-driven elevator; over-the-bumper coral ground	Onshape CAD
	847 PHRED		**22**	#2423	10-17	Elevator with an elevator-mounted intake; pneumatics; build thread rep	Onshape CAD
	1595 The Dragons	King Ghidorah	**22**	#2469	12-22	Boat-hook lift chosen for a low CG; small 21x21x24 in frame	Onshape CAD

	Team	Robot	EPA	Rank	Record	Archetype	Public design
	2577 Pingry Robotics		**20**	#2631	14-13	Roller end effector on pivot arm, coral funnel ramp, elevator, WCP Swe	Onshape CAD
■	**1806 S.W.A.T.**	Atom	**10**	#3554	9-16	Rebuilt mid-season toward a 2056-style coral/algae claw on an arm; cus	Onshape CAD

■ = study pick: downloadable CAD or a full technical binder, and one specific design lesson. EPA is Local EPA (approx), computed from The Blue Alliance match data. Records are win-loss-tie totals from official events.

Top-30 robots by Local EPA

■ Study pick **2056 OP Robotics** LIGHTNING — Canada — **Local EPA 123 (#1)** — 68-7

Riveted sheet-metal arm; counter-rotating roller coral intake; 2D AprilTag auto-align; swerve

SCORING (CORAL / ALGAE) Scoring uses a 'dunk' step that the driver triggers after auto-align. The driver keeps this step so the robot can rescore after a miss and lose a second or two, not a full cycle.	**INTAKE** Roller intake with top rollers and a bottom roller that turn in opposite directions; a small 1:1 gearbox reverses the bottom roller. The front roller floats, and coral compression changes with coral orientation. WCP stretch star wheels sit on 1.5 in OD, 1/8 in wall polycarbonate tube. Changed after practice from 1.25 in OD, 1/16 in wall tube after the tube bent in practice and the wheels migrated and slipped. The polycarbonate pivot is clamped with aluminum plates that spread bolt loads in impacts.
ELEVATOR / ARM The arm is a riveted and formed 1/16 in aluminum structure. The robot uses 5052 aluminum sheet at 1/16 in and 1/8 in depending on load. The team drives pivots with large aluminum sprockets on a dead axle and chain: #25 for light-duty and #35 for heavy-duty pivots.	**DRIVETRAIN** Swerve with fully custom control and odometry, not CTRE's generated swerve code. Phoenix Pro features: FOC, fused CANcoder and time synchronization.
ENDGAME Unconfirmed	**AUTONOMOUS** Waypoints are hard-coded points, with no path-planning interface. The tolerance per waypoint ranges from 1.5 in to 48 in, depending on the action. In auto, the robot computes the coral position and generates a drive point with a heading that points at the coral. Auto selection inputs are read only after a 3 s timer in disabled, so the driver cannot change them between auto and teleop.
VISION Limelight with 2D AprilTag tracking only; no MegaTag 1 or MegaTag 2. Distance comes from an interpolating tree map of tag area to measured distance. Auto-align drives to a pose relative to the reef tag for L2-L4 and uses global pose for L1. A drive-to-point controller runs two PID loops, on translation and rotation error, with an aggressive slew rate limiter.	**PUBLIC CAD / DESIGN** Technical binder (PDF)

LESSONS FOR STUDENTS

- Drawings can document a robot without a CAD model; follow the part revisions through the season.
- The aluminum plates act as large washers; without them, side impacts can crack the polycarbonate at the bolt holes.
- The team prefers chain to 5M HTD belt on pivots because chain is less likely to skip under shock loads, and designs in a chain tensioner, such as the inline turnbuckle tensioner used on the intake.

Tech binder: Technical binder (PDF) · Binder release thread (CD) · Technical binder (PDF) · CAD drawing package (PDF) · Auto-align approach post (CD) · Intake slow-motion video (Google Photos)

Profile **1690 Orbit** Whisper — Israel — **Local EPA 114 (#2)** — 62-9

Closed-belt differential elevator (variation of a community design)

SCORING (CORAL / ALGAE) Unconfirmed	**INTAKE** Full-width floor intake at the front: two rows of blue compliant star wheels on a pivoting linkage (per CAD).
ELEVATOR / ARM One elevator tower at the center of the frame, braced by two diagonal struts to the frame. Kraken X60 and Kraken X44 motors are in the BOM (per CAD).	**DRIVETRAIN** Swerve with four modules on a square frame. Kraken X60 and Kraken X44 motors are in the BOM; the module model is not named (per CAD).
ENDGAME Unconfirmed	**AUTONOMOUS** Unconfirmed
VISION One Limelight 3G on a Limelight holder assembly (per CAD).	**PUBLIC CAD / DESIGN** Onshape CAD (Onshape sign-in needed)

Onshape CAD: Onshape CAD (Onshape sign-in needed) · CAD release (CD) · Onshape CAD (Onshape sign-in needed) · Top-level x_t files (Google Drive) · Reveal thread (CD) · Reveal video · Behind the Bumpers video

■ Study pick

2910 Jack in the Bot Poi Pounder XXVI Spectre

USA-WA

Local EPA 113 (#3)

66-7

Shoulder, extension and wrist arm; reef-AprilTag auto-align; latch climber with automated climb; swerve

SCORING (CORAL / ALGAE) End effector on the arm wrist. It holds coral straight, as the intake delivers it, or horizontal in an L1-optimized position, and it also handles algae. Scoring uses one button for a 'base' setpoint and one for a 'top' setpoint. Translation, rotation, release, wait and backout are all automated.	**INTAKE** The team never used coral station intaking during teleop. On station loading, a team reply says it is better to drive firmly into the station and guarantee the load than to risk wheel slip leaving the robot short.
ELEVATOR / ARM Arm with a shoulder pivot, an extension and a wrist. The code treats each as its own subsystem, which the team says gives cleaner compartmentalization. Shoulder and wrist are commanded by angle. Positions come from the built-in Kraken encoders on the shoulder, extension and wrist. A re-homing button was used at most twice in the season, after heavy arm impacts; it mainly saves time in driver practice. The arm code ran on the team's 2023 robot before bring-up.	**DRIVETRAIN** Swerve. A skew compensation constant corrects drift off center when the robot rotates while translating. The code uses voltage targets, not duty cycle, so output holds as battery voltage drops; the reply does not say which motors.
ENDGAME Climber with latches and climber intake wheels. The climb is fully automated once the bar is in the latches. The code detects the bar from the speed and current of the climber intake wheel motor, and the team reports no false positives.	**AUTONOMOUS** Autonomous Award at PNW District Auburn, Sammamish and the PNW DCMP. The team mentions a 'mark auto' and tested code to knock algae off the mark; that code was not used.
VISION Cameras read reef AprilTags. There is no pose estimator: the code hard-resets swerve odometry to camera poses, and only while auto-aligning, when the robot is stable. The team reports vision as accurate at the scoring position, with more error farther out. Drivers switch between pose-based and rotation-based reef selection; LEDs show purple for pose-based and yellow for rotation-based.	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- A plain PID auto-align with a velocity cap and friction compensation can be enough: the team tried trapezoidal profiles and dynamic path following and kept PID.
- Relocalize only when the data is good, not during fast traversals.
- Give drivers a fallback when odometry drifts.
- Motor data can replace a sensor, as the climber shows.
- Bind buttons to robot state: one button does four things depending on the piece held (straight coral, horizontal coral, algae, none). Drivers use Xbox controllers with back paddles.

Onshape CAD: Onshape CAD · CAD and tech binder release (CD) · Onshape CAD · Tech binder (Google Drive) · Code (GitHub) · Code release thread (CD) · Robot reveal (CD) · Reveal video

■ Study pick

1678 Citrus Circuits SubLime

USA-CA

Local EPA 109 (#4)

57-8

Coral and algae end effectors; indexer; sideways elevator on Dyneema cable at 3:1; swerve

SCORING (CORAL / ALGAE) The team's SystemCore thread lists separate beam breaks for a coral end effector and an algae end effector. All scoring runs on one controller through back paddles, with an autoscore function.	**INTAKE** The SystemCore thread lists an indexer beam break.
ELEVATOR / ARM Sideways elevator driven by Dyneema cable at a 3:1 reduction; the OP gave the ratio in the reveal thread, correcting a reader's 4:1 estimate. The team has used the same cable (CBKnot 7/64 in Dyneema, about 1600 lb tensile strength) on all its string elevators since 2018. The elevator support plate and the sponsor panel protect the cable. It stretched slightly and was re-tensioned when loose; the team replaced it once during the season. The sideways layout let the stages rock front to back with the elevator up, which hurt L4 accuracy. The design lead measured the gap and cut new stage 0 top spreader plates with offset holes. Most of the loose-fit slop went away; the middle-stage tubes still deflect under drive acceleration.	**DRIVETRAIN** Swerve. The SystemCore thread traces a fault on the back left module of the practice robot 'Omega' to a faulty MPM port for its CANcoder. The robot runs two CAN loops, one on the roboRIO and one on a CANivore.
ENDGAME Climber subassembly named 'Poof Climber' at the rear of the robot. Pivoting arms carry a cross bar across the robot width (per CAD).	**AUTONOMOUS** The reveal thread links a video of an auto routine in development (2025-02-25).
VISION Two Limelight 4 cameras with Limelight fan models. One mounts at the top of the elevator and faces forward. One mounts at the rear and faces rearward (per CAD).	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- Measure slop before you redesign.
- The team uses Dyneema cable as a lighter option for powering the elevator. Plan for re-tensioning.
- Bent parts: the team makes all bent aluminum parts from 5052 sheet, which it describes as more ductile than 6061, and reports no cracking.
- Two near-identical robots: the team 'leap-frogged' updates, so one robot was upgraded while the other ran driver practice and software. The practice robot 'Omega' later tested a new controller.

Onshape CAD: Onshape CAD · Onshape CAD · CAD, code and strategy release thread (CD) · CAD and code release page · Robot reveal (CD) · SystemCore test thread (CD) · Auto in development (video)

■ Study pick

1323 MadTown Robotics

USA-CA

Local EPA 106 (#5)

53-3

Claw on a differential wrist; ground coral and algae intake with auto handoff; elevator on a pivot; swerve

SCORING (CORAL / ALGAE) A claw on a differential wrist scores coral and algae. The team runs the wrist in CTRE differential mode and lists its hurdles: fitting parts in the carriage, belt slip, and enough encoder wrap for a 1:1 reading. It used standard bevel gears, not spiral, and says it would try herringbone-style bevels next time. A retroreflective Banner sensor on a CANdi in the claw detects both pieces. The end effector motor runs in PWM mode to avoid a long CAN stub, after stator and current limits were set over CAN. A forum question names the motor as an X44; the team's answer does not restate the model.	**INTAKE** Ground intake for coral and for algae. A diffuse Banner sensor on a CANdi sees the coral; the robot then lifts, hands off and enters a scoring state on its own. Ground algae hands off from the ground intake to the claw the same way. Reef algae pickup runs from a driver trigger: the robot squares up and follows a path to the ball, which lets the co-driver focus on lowering the coral intake.
ELEVATOR / ARM The code models each position as a SuperstructureState with four values: elevator, elevator pivot, wrist pitch and wrist roll. A 'choreographer' compares current and target positions and builds a command that moves between them safely. Elevator tube is mainly .060 in wall for weight; each stage is about 21.25 in tall. Thinner 12/14 AWG wire and Alpha Wire let the team drop from a 15 x 30 mm to a 15 x 15 mm e-chain.	**DRIVETRAIN** Swerve, frame perimeter about 112 in. A forum user read WCP X2 modules in two configurations from the tech binder; a team member stated the mix was for space and packaging. The A-frame tube support uses a 3/16 in aluminum plate with custom nut plates inside the 2x2 in box tube, plus a .090 in bent aluminum plate. The team uses the top of the swerve plate as structure, an idea it credits to 4414.
ENDGAME Unconfirmed	**AUTONOMOUS** Autonomous Award at the Silicon Valley Regional. Autos start from a pre-defined path; Limelight object tracking builds a new path to the coral, which the team says happens 99.9% of the time. The camera tracks the ball and checks its height off the ground to confirm the coral is still there. The team has used the built-in Limelight model since 2023.
VISION Three Limelight 4 cameras. Two read AprilTags without the Hailo accelerator; the team saw better performance without it. The third runs object detection in auto only. Every camera has a milled heat sink; two of the three have fans.	**PUBLIC CAD / DESIGN** Tech Binder (Google Drive)

LESSONS FOR STUDENTS

- Plan the weight budget early. The team cut weight with WCP SRPP, more pocketing, plastic and titanium bolts, drilled shafts, thinner plates and wire, and 3D-printed parts in place of metal, down to 0.01-0.05 lb at a time.
- Run the practice robot hard and print its parts in a weaker material: PETG HF parts fail earlier than the Markforged Onyx parts on the competition robot, which sees only a few auto tunes and matches.
- Wire Banner sensors through a CANdi: the team states detection was faster than with sensors plugged into the roboRIO.
- Use object tracking to correct auto paths: the team says it would not grab the coral without it.

Drive folder / doc: Tech Binder (Google Drive) · Tech Binder (Google Drive) · Tech binder release thread (CD) · Reveal thread (CD)

Profile	694 StuyPulse Aunt Mary USA-NY	Local EPA 99 (#11) 47-8

Pivoting arm end effector on elevator; large pivoting roller intake; coral funnel; cage-capture climber; swerve

SCORING (CORAL / ALGAE) Main arm and shooter subassembly at the top of the elevator carriage. It pivots, with a WCP ThroughBore encoder powered by CANcoder on the pivot (per CAD).	**INTAKE** Two intakes. A large pivoting intake ('Froggy' subassembly) has truss side plates and a roller of compliant wheels at the tip; it holds a coral backing plate. A polycarbonate funnel at the top of the robot has three rollers driven by one motor through HTD belts (per CAD).
ELEVATOR / ARM Tall elevator at one end of the robot. Its gearbox uses a Kraken X60, and part names include spool spacers. Diagonal rods brace the top of the elevator to the frame (per CAD).	**DRIVETRAIN** Swerve with four WCP Swerve X2 modules. Kraken X60 motors with Talon FX, a Pigeon 2.0 and a CANivore are in the BOM. Square frame (per CAD).
ENDGAME Cage capture climber subassembly named 'Cage eater'. A Kraken X60 drives it through a MAXPlanetary, with a WCP encoder (per CAD).	**AUTONOMOUS** Unconfirmed
VISION Limelight 4 cameras. Two mount in the funnel subassembly on front and rear mounts (part names 'Frog LL Front' and 'Frog LL Back') (per CAD).	**PUBLIC CAD / DESIGN** Onshape CAD

Onshape CAD: Onshape CAD · Onshape CAD · Open Alliance build thread (CD) · Robot reveal thread (CD) · Reveal video

Profile	5940 BREAD Taiyaki USA-CA	Local EPA 97 (#12) 46-5

Chain-driven elevator with a rolling chain tensioner; electronics mounted upside down under removable panels

SCORING (CORAL / ALGAE) The CAD has separate End Effector and Indexer subassemblies. A Kraken X44, a beam break and CANrange sensors are in the BOM (per CAD).	**INTAKE** Ground intake at the front that folds out over the bumper. It is full robot width, with a roller and rows of star-shaped wheels. Two Kraken X60 motors in the intake subassembly drive it through spur gears and #25 chain. A CTRE magnetic encoder on a belt reads the intake position (per CAD).
ELEVATOR / ARM Elevator with a fixed Stage 0, a Stage 1 and a Stage 2 carriage (per CAD).	**DRIVETRAIN** Swerve drive with 4 WCP Swerve X2i modules. Kraken X60 motors are in the BOM. A Pigeon 2.0 and a CANivore are on the drivebase (per CAD).
ENDGAME A Climber subassembly is in the CAD (per CAD).	**AUTONOMOUS** Unconfirmed
VISION A Front Cams assembly on the drivebase holds OV2311 cameras. A Pi-Motel coprocessor mount is on the drivebase (per CAD).	**PUBLIC CAD / DESIGN** 'Taiyaki' CAD (Onshape)

Onshape CAD: 'Taiyaki' CAD (Onshape) · 'Taiyaki' CAD (Onshape) · Tech binder (Google Drive) · The Cookbook: competition documentation (Google Docs)

■ Study pick

422 The Mech Tech Dragons Wisp

USA-VA

Local EPA 95 (#14)

60-8

Polycarbonate coral-retention flap, coral ground intake (pivot began as algae roller), bellypan-keyed climber

SCORING (CORAL / ALGAE) A 1/16 in polycarbonate flap retains coral. The team balanced its stiffness so it holds coral at low current; at higher motor current the coral pushes through.	**INTAKE** Ground coral intake on a pivot. At the first few events the pivot ran as an algae over-the-bumper roller; the team then swapped to the coral ground intake. SplineXL OD hubs were machined down for a press fit on SplineXL extrusions. After the swap the team drilled and tapped a set screw into each hub.
ELEVATOR / ARM Unconfirmed	**DRIVETRAIN** The battery is held by a nylon strap with a zip tie as the buckle; a billet holder was left off to save weight.
ENDGAME Climber fastened to the bellypan: a 2x2 tube plug inside the climber takes the bellypan bolts, and the gearbox plate profiles key into the bellypan.	**AUTONOMOUS** Unconfirmed
VISION Pose estimation; the team does not say it is vision-based. It did not work on day 1 of the first event, despite working on a local practice field, and the team reworked it during that event.	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- A press fit that holds for one load case may need a set screw for the next.
- A home test does not show that pose estimation will be working at an event.
- Battery condition matters late in an event: the team reports brownouts 10+ times per match in DCMP playoffs after its batteries degraded.

Onshape CAD: Onshape CAD · CAD and tech binder release (CD) · Onshape CAD · Robot reveal (CD)

Profile

1706 Ratchet Rockers Singularity

USA-MO

Local EPA 93 (#16)

35-10-1

Roller end effector on a center elevator; station funnel; Thrifty Swerve

SCORING (CORAL / ALGAE) End effector with green compliant wheels on the elevator carriage, at the bottom of the funnel. LaserCAN distance sensors are in the BOM (per CAD).	**INTAKE** Polycarbonate funnel at the top of one side guides coral from the station down to the end effector (per CAD).
ELEVATOR / ARM Elevator on tall aluminum rails at the center of the frame, with a truss crossbar across the top. The elevator gearbox drives through pulleys (per CAD).	**DRIVETRAIN** Swerve drive with four Thrifty Swerve modules in the inverted configuration. Kraken X60 motors drive and steer each module (per CAD).
ENDGAME Unconfirmed	**AUTONOMOUS** Unconfirmed
VISION Limelight 4 camera (per CAD).	**PUBLIC CAD / DESIGN** Onshape CAD

Onshape CAD: Onshape CAD · Onshape CAD · Code (GitHub) · Teaser thread (CD) · Teaser video · Scouting whitepaper (Google Doc)

■ Study pick

1778 Chill Out SubZero

USA-WA

Local EPA 93 (#17)

53-12

580 deg arm on a belt elevator; ground coral intake with auto handoff; pose-based auto-align; no climber

SCORING (CORAL / ALGAE)
End effector on the arm, with a roller reduction of about 11:1. Current sensing detects coral; the team tuned a voltage that stalls the roller and still grips the coral. To score, the arm moves down with the elevator while the bumpers rest against the reef. Scoring is semi-automatic: when the driver releases the sticks, the robot drives to the nearest scoring position and picks the closer branch. The driver then presses a confirmation button to start the scoring sequence.

INTAKE
Ground coral intake. Wheels inside the intake center the coral, and the upper wheels spin it as it centers. One linebreak in the center detects coral; the intake then raises and hands off automatically. Two X60 motors drive it; the team says that is a lot of weight and plans X44s in future. The bottom roller has bearings but the team stopped it from spinning, which it says improves handoff and trough scoring. The intake zeros by current sensing.

ELEVATOR / ARM
Arm on a belt-driven elevator. The arm pivot has a 64.5:1 reduction. Software limits the arm to 290 deg left or right of straight down (580 deg range) and clamps the encoder range to 700 deg for safety. A WCP CAN throughbore encoder on a 2.22:1 reduction gives 800 deg of range and sets the arm position at match start; there are no hard stops. Arm wires pass through the pivot tube in wire wrap with slack. The elevator runs two open-end PolyBelt belts of about 13.5 ft, clamped to the carriage between aluminum and a profiled PLA part. Two motors with 9-tooth pinions drive 36-tooth gears, each on a shaft with a 24-tooth pulley. The carriage weighs about 7 lb, about 13.5 lb with the arm. The elevator zeros by current sensing. The team reports some elevator wobble and says the A-frame should have run to the corners.

DRIVETRAIN
Unconfirmed

ENDGAME
No climber. The robot was at max weight, a climber would have needed many parts lightened, and the team had about a week to build an untested climber. It used the time for LEDs and improvements to scoring, autos and the state machine.

AUTONOMOUS
The auto video shows the ground centering and handoff sequence.

VISION
Full-field pose estimation drives reef alignment.

PUBLIC CAD / DESIGN
Onshape CAD

LESSONS FOR STUDENTS

- Pick an absolute encoder ratio above 1 and not a whole number when an arm turns more than one revolution.
- One centered linebreak can trigger raise and handoff only if the coral is already centered by the time the intake is up.
- Use full-field pose, not tag tx/ty, when the scoring point is offset from the robot center.
- Decide late additions by weight and time, as the team did with the climber.

Onshape CAD: Onshape CAD · Onshape CAD · CAD and code release thread (CD) · Code (GitHub) · Reveal thread (CD) · Reveal video · Auto handoff video

■ Study pick

604 Quixilver The Flush

USA-CA

Local EPA 92 (#18)

39-10

Single-stage elevator, arm and pivoting open-top gripper; full-width coral funnel; winch climb; WCP X2i swerve

SCORING (CORAL / ALGAE)
Gripper pivots 180 deg on the arm, with 4 coral rollers and 2 algae rollers. Left and right sides run independently to turn coral sideways for L1; it scores up to 4 coral per side on L1. The open top lets coral rotate on exit for a shallower L4 angle and keeps the robot from catching on the reef. Wrist gearbox is shimmed to decrease backlash.

INTAKE
Full-width funnel of 4 mm corrugated plastic for loading from 3 sides of the robot. Two separately powered rollers (top and bottom) work with the gripper's left and right rollers to center coral in any orientation. A rear ramp unfolds to clear the climber and cage. No ground intake: a summer ground intake for The Flush went on the offseason robot instead, because it was hard to package with the climb.

ELEVATOR / ARM
Single-stage elevator with 2x2 in uprights, chain on both sides, 3:1 on two Kraken X60s for 28 in of travel; stator limit raised from 40A to 80A. Arm of 2x2 box tube with large gussets, 51:1, shimmed gearbox. The post lists the arm as one Kraken X60 and also as 2 motors at 35A; the team reports it ended at 1 motor at 100A.

DRIVETRAIN
WCP Swerve X2i modules on a 29 in x 29 in frame, sized for stability when reaching high. Drive ratio 5.9:1, chosen for an average sprint of about 18 ft. Polycarbonate and plywood panels shield electronics from falling coral.

ENDGAME
Climb stows under the funnel and weighs about 3.5 lb with motor and gearbox. Surgical tubing powers a spring-loaded extension. One Kraken X60 retracts it through a 15:1 winch and a 2:1 pulley, sized to lift the robot off the ground with a wide CG tolerance.

AUTONOMOUS
Autos reuse the teleop auto-scoring logic and are built by chaining scoring commands at different reef locations. Return trips to the coral station use pre-planned trajectories from Quikplan, the team's time-optimal swerve planner.

VISION
Two AprilTag localization modes. Reef tasks use only the closest tag plus swerve odometry, computed on the RoboRIO for low latency. Other tasks use all tags plus odometry in a particle filter on the driver station. Final alignment uses a trig method from tag distance and gyro angle, inspired by 6328; the team states the robot gets within about 1.5 cm and 1 deg of the target. The two misses came when the robot never saw the target tag, because there was no scoring lock-out for that case. Cameras mount on the elevator structure.

PUBLIC CAD / DESIGN
Onshape CAD

LESSONS FOR STUDENTS

- Build for automation first. The team stiffened and shimmed the mechanisms so software could score with low backlash.
- The single-button scoring sequence picks the closest reef face from velocity lookahead.
- The open-top gripper also gives more depth tolerance.
- Each gear ratio is given with its design target: study the drive, elevator and arm.

Onshape CAD: Onshape CAD · CAD and code release (CD) · Onshape CAD · Code (GitHub) · Behind the Bumpers video · Offseason 'Quixshot' reveal and CAD (CD)

■ Study pick

3005 RoboChargers Relay

USA-TX

Local EPA 91 (#19)

56-9-2

Coral ejector and algae gripper on a 'laterator'; 3-stage chain-driven elevator

SCORING (CORAL / ALGAE) A 'laterator' carries a coral ejector and an algae gripper. The coral ejector structure is mainly carbon fiber tube and MaxComposite. The laterator derailed when the robot climbed the reef. It also loosened side to side over the season, so the team shimmed it for an offseason event.	**INTAKE** The team's posts do not describe the coral or algae intake path; replies about a funnel and coral routing come from other users.
ELEVATOR / ARM 3-stage elevator. Chain drives it; the team says it chose chain mostly from familiarity. The bearing-to-gusset elevator hardstops started as Markforged Onyx parts and changed to MaxComposite to save weight. One Onyx hardstop deformed over time and was replaced.	**DRIVETRAIN** The design leaves a 0.25 in gap between frame and bumpers to ease bumper removal. Bumper spacers, mounted at under 8 in intervals, are missing from the CAD.
ENDGAME Climber V2 has 2 hook arms, a left and a right hook, and a hook lock (per CAD).	**AUTONOMOUS** Autonomous Award in the FIRST In Texas District Championship Apollo Division.
VISION Front and rear camera mounts are in the drivetrain. The BOM does not name a camera model (per CAD).	**PUBLIC CAD / DESIGN** Robot assembly CAD (Onshape)

LESSONS FOR STUDENTS

- MaxComposite works much like polycarbonate if it is laser cut, or router cut with the edges melted to seal the woven layers. The team warns it delaminates under edge loading.
- 3D printed PLA sprockets can run on low-torque joints. The team sets the wall count high enough that the teeth print solid.

Onshape CAD: Robot assembly CAD (Onshape) · Robot assembly CAD (Onshape) · Block CAD (Onshape) · Reveal thread (CD) · Reveal video

---

Profile

180 S.P.A.M. Anemone

USA-FL

Local EPA 90 (#23)

44-6

Automated coral scoring, floor coral pickup, cage climb

SCORING (CORAL / ALGAE) Coral scoring runs through an automated auto-score sequence. The controller rumbles when the sequence ends so the driver knows he has full control again. A pulsing rumble warns the driver when the drivetrain takes longer than normal to reach position.	**INTAKE** Picks up coral off the floor in auto. Sensors detect when a coral is fully in, and the controller rumbles so the driver can release the intake button.
ELEVATOR / ARM Unconfirmed	**DRIVETRAIN** Unconfirmed
ENDGAME Cage climber. The controller rumbles once when the climber deploys and continuously when it latches to the cage.	**AUTONOMOUS** Dynamic autos that track and pick up floor coral. Most moves (start to reef pole, reef pole to floor coral, floor coral to reef pole) use the DriveToPose command; PathPlanner handles only the curved move after the first coral. The team moved away from Choreo, used the previous season, because floor pickup needs flexible end points. Autos chain small commands with Triggers. Won Autonomous Awards at South Florida and in the Galileo Division.
VISION Limelight AprilTag vision and a coral detector for floor coral tracking. In simulation the team used PhotonVision's simulation for the Limelight AprilTag data and wrote a simulation layer for coral tracking.	**PUBLIC CAD / DESIGN** Code (GitHub)

LESSONS FOR STUDENTS

- The autos use Triggers that move the robot between states (intaking, scoring), so teleop automations could be reused without asProxy() calls.
- Use LEDs to show critical faults (camera not connected, mechanism out of position, no AprilTags) to team members on the field before field staff close the gates.

Code (GitHub): Code (GitHub) · Code release (CD) · Code (GitHub) · DriveToPose command (GitHub) · Behind the Bumpers (video) · Robot reveal (video)

■ Study pick

5990 TRIGON TRIDOG

Israel

Local EPA 90 (#22)

46-13-2

Ground coral intake (about 7 kg); elevator on custom-machined bearing blocks; 4 L4 coral auto

SCORING (CORAL / ALGAE) Scores coral on L4, as the 4 L4 autos show.	**INTAKE** Ground coral intake, about 7 kg (about 15.5 lb) after last-minute weight cuts. The weight includes its motors: 2 Falcons and one Kraken X60.
ELEVATOR / ARM Elevator on custom bearing blocks, based on 1678's 2023 bearing blocks and used by the team for two seasons. The team knew in the first week of the season it would use them and started machining them early. Each block needs two setups; a friend of the team machined the second setup for tighter tolerance.	**DRIVETRAIN** Swerve drive with 4 SDS MK4c modules with Kraken X60 motors and billet wheels. A Pigeon 2 is on the chassis (per CAD).
ENDGAME No endgame mechanism in the CAD. The chassis has a climber replacement profile and plate where a climber would mount (per CAD).	**AUTONOMOUS** 4 coral ground intake auto, run as a 4 L4 auto at the ISR District Championship. The team also reports a 10 coral auto as an alliance with 1690.
VISION OV-series cameras in printed cases. Two mount on the elevator on mirrored left and right mounts. One mounts on the intake behind a camera protector plate (per CAD).	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- A reused design can be planned early.
- Weigh each subsystem: the team recalls the full robot about 0.5 lb under the limit at its last inspection.

Onshape CAD: Onshape CAD · CAD release (CD) · Onshape CAD · Tech binder (Google Slides) · Code (GitHub) · Reveal thread (CD) · Behind the Bumpers video (FUN Robotics Network)

■ Study pick

7407 Wired Boars Griptide

USA-CT

Local EPA 90 (#24)

55-13

Rotating end effector for L1-L4 coral; coral station intake; 3-stage elevator; swerve; algae attempts dropped

SCORING (CORAL / ALGAE) Rotating end effector for L4, L3, L2 and L1 coral and for intaking (January plan, team post 2025-01-22). After Waterbury (week 2) the team planned a new end effector with a larger gripper and 2 separate Kraken X44s, for algae and supercycles. The team later states the end effector ended up different from that plan. The team states algae did not work at Hartford: the wrist swing and elevator jerk were too much even with a larger reduction on the algae motor. A second algae version added at DCMP pinched algae better but could not pull it off the reef, so the robot stayed coral-only.	**INTAKE** Coral station intake; the team decided against a ground intake because of complexity and to spend effort on software. After Waterbury the team planned to move the top VersaRoller back and add a larger polycarbonate deflector, so coral would hit the polycarbonate instead of bouncing off the roller. The team was not sure the deflector was needed; the final setup is unconfirmed. For Worlds the only change was a larger upper coral shield on the intake.
ELEVATOR / ARM 3-stage elevator (team post 2025-01-22). After Waterbury the team states a 12:1 gearing gave about a 1 second extension to L4, and planned a change to 9:1 to cut that time. Coral stuck in the robot twice at DCMP; the team added a piece of 'poly' on a bungee tied to the elevator to lift coral out, and states it was not needed after that.	**DRIVETRAIN** Swerve. The team states it used L1+ gearing for acceleration (2025-01-10), and its 2026 thread states it used custom swerve code before 2026.
ENDGAME January plan: deep cage climb through an 'Intake Climb' system that shares one geared rotation between the intake and the climb. The team's later posts do not state whether the robot climbed.	**AUTONOMOUS** Autonomous Award at NE Hartford. After Waterbury the team aimed for a 3.5 or 3.75 piece auto without speed changes. The team states it did not miss a coral in auto at Worlds (Milstein Division): 42 of 42.
VISION The team worked on PhotonVision in the preseason (December 2024 post). After Waterbury it planned driver feedback for auto-align, either LEDs at the goal pose or auto-score.	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- Scope from strategy: the team put L1-L4 coral first for its point value.
- At kickoff, groups defined 'A', 'B' and 'C' robot architectures, planned matches in 5 second increments, and played 4 mock matches before the team set its priorities.
- The team states it had no major electrical, mechanical or code failure all season.

Onshape CAD: Onshape CAD · Reveal thread (CD) · Build thread (CD) · Onshape CAD · Reveal video · Code (GitHub organization) · Season recap video

■ Study pick

254 The Cheesy Poofs UNDERTOW

USA-CA

Local EPA 89 (#26)

42-7

Welded-tube wrist; 4-bar main intake; backup coral station funnel

SCORING (CORAL / ALGAE) End effector of 1/4 in polycarbonate plates. It bolts to 1/4 in aluminum plates welded to the 2 in wrist tube; large fender washers spread bolt loads to stop the polycarbonate cracking. Breaks happened in the polycarbonate past this joint, so the team kept spare end effectors and swapped them at the bolted interface. Stud 'teeth' grip algae from below so it does not slip on the polycarbonate; the team says they interfered little, if at all, with grabbing.	**INTAKE** Two coral paths: a coral station intake fed by a polycarbonate funnel, and a main intake on a 4-bar linkage. A 1.25 in OD, 0.03 in wall aluminum tube jackshaft drives the 4-bar through custom billet hubs and a 20DP gear; the team says this stackup used many custom parts and was not serviceable. The funnel is cut from one polycarbonate sheet, with overlapping layers joined by double-sided tape. Flex wheels on the front two rollers were cut to fit the frame perimeter.
ELEVATOR / ARM The wrist rides on a carriage of 2x1 tubes. 1/4 in plates on the carriage hold two 20 mm ID x-contact thin-section bearings in a live-axle setup. A 50T 10DP gear drives the wrist, and a CANcoder reads a magnet in the end plug at 1:1. The pivot is a 2 in OD, 1/16 in wall 6061-T6 tube with welded CNC end caps. The wrist was redesigned for East Bay and Championship; the binder shows the final version. A team correction to the binder, for a gearbox whose subsystem the post does not name: the gearbox is only about 11:1 (two spur stages), and a capstan drum of standoffs (0.5 in hex to 5.5 in effective diameter) gives the rest of the reduction.	**DRIVETRAIN** Bumpers use 1/2 in plywood. Four 2 in tall, 1/8 in thick steel strips in the rear bumper sides add ballast against tipping; the team chose wood over HDPE because it was lighter, which let the steel sit lower. CAN wires ride on top of power wires and are sleeved to each drivebase CANcoder.
ENDGAME The cage sweeps through the robot, which forced subsystem placement.	**AUTONOMOUS** The team used the coral station intake in autonomous at Sacramento and East Bay. At Championship it ran loading station autos only, not a backside algae auto. Autonomous Award at East Bay, Sacramento and the Milstein Division.
VISION Left and right cameras pointed straight ahead with an overlapping region that sees the reef tag to about 5 in away (team reply, 2026-10-04). An auto-align was slightly off in one match.	**PUBLIC CAD / DESIGN** Technical binder (PDF)

LESSONS FOR STUDENTS

- Keep a backup game-piece path: the team says it could not predict how strategy would play out, and kept the coral station intake as a failsafe for when the main intake broke.
- Pick the architecture in order: the team breaks the game into cycles, chooses where to intake and score, sketches the robot as a black box, then picks subsystem styles.
- With an absolute encoder on a precision joint, no separate zeroing sensor is needed.
- Check joints after long practice. The team says it would add crush tubes or end plugs to the tube ends in the future.

Tech binder: Technical binder (PDF) · Binder and code release (CD) · Technical binder (PDF) · Code (GitHub) · Reveal thread (CD) · Match video

■ Study pick

190 Gompei and the HERD StackUp (V1) and Redundancy (V2)

USA-MA

Local EPA 88 (#30)

68-19

Star-wheel coral outtake, closing funnel, 4-motor elevator, string climber

SCORING (CORAL / ALGAE) The V2 coral outtake uses star wheels that grab the coral lip and flip it onto L4. The team added them because the coral sometimes did not flip up onto L4 when slightly too low. V2 also has an algae claw. It started with two X44 motors and ended with one X60 on the rollers, a larger claw gear ratio and a deeper 'C' shape, plus a 1.25 in grip-tape roller that is not in the CAD.	**INTAKE** Coral enters a funnel with belts that guide it. The funnel closes ('clapping funnel') to hold the coral when the robot moves in and out of the station quickly. On V2 the funnel also stores a coral passively while the robot holds algae. A photoelectric sensor (Allen-Bradley 42EF-D1MNAK-A2 RightSight) detects coral on the ramp. V2 added an over-the-bumper algae intake.
ELEVATOR / ARM Elevator. The team planned 6 motors for stow-to-L4 acceleration but ran 4 motors on both robots, because 6 would have saved about 20 ms. For V2 the team took weight out of the elevator gearbox and carriage.	**DRIVETRAIN** The team first lightened the front and back drive rails. For V2 it needed more weight savings, so it partial-depth pocketed the side rails after the robot was assembled. The climber-side rail was slightly bent at BattleCry at WPI.
ENDGAME String-and-grappling-hook cage climber. A 40 lb undamped pulling gas spring (Bansbach Easylift) pulls the deploy arm down; reeling the spool releases a retaining hook. A lightly sprung lock stops the arm folding back up. A redirector pulley keeps the fleet angle near constant so the string wraps the spool evenly. A spring-loaded 5-bar over-center linkage holds the hook on two billet blocks until string tension pulls it shut and releases it.	**AUTONOMOUS** Won the Autonomous Award at NE District URI and at the New England DCMP Ballard Division.
VISION Unconfirmed	**PUBLIC CAD / DESIGN** CAD release (CD)

LESSONS FOR STUDENTS

- A passive part can fix a placement problem: study the V2 star wheels.
- Check what extra motors buy, as the team did for the elevator.
- One degree of freedom can do two jobs: the closing funnel also moves out of the way for the climb.
- A string climber needs string management. Guide blocks also keep the string out of the gears.
- A second robot needs a weight budget: V2 found 10-15 lb for algae hardware, also from the funnel and 3/8 in thunder hex.

CD thread: CAD release (CD) · CAD release (CD) · V1 'StackUp' CAD (Onshape) · V2 'Redundancy' CAD (Onshape)

■ Study pick

341 Miss Daisy Miss Daisy XXIII

USA-PA

Local EPA 88 (#28)

54-12

Claw on a lantern-gear shoulder with 180 deg wrist; coral floor intake; continuous elevator; compact deep climber

SCORING (CORAL / ALGAE) Claw on a lantern-gear-driven shoulder with a 180 degree wrist. The wrist is belt driven to reduce backlash and weight on the arm; the team says it would try to remove the VersaPlanetary next time. The wrist zeros against a hard stop by current draw. A planned beam break was not fitted.	**INTAKE** Coral floor intake. Vertical passive rollers keep the coral from resting in any orientation but sideways; a wave plate blocks one jam position. Bent ramps and the roller layout center the coral. The outer 2 passive rollers have silicone tubing and the center one does not, so the coral spins until centered and then climbs to the claw. The team states it also takes perpendicular coral. A belted reduction keeps the surface speed of the wheel sets about equal. An algae intake exists.
ELEVATOR / ARM Continuous elevator driven by rope from a spool. Aluminum arms set the rope lead angle to the spool, and a second set of redirects near the top aligns the rope with the pulleys. Early tests without the arms had the rope double up or leave the spool. Elevator pulleys are printed CF-nylon with 2 bearings each (the OP believes R4-2RS). The shoulder lantern gear came from an Onshape generator, with about 20 thousandths removed from the tooth tips. A code 'superstructure' keeps the arm from colliding with the robot and keeps the robot in acceptable states.	**DRIVETRAIN** Swerve with 4 WCP Swerve X2i modules (Low), modeled with Falcon motors. Rectangular frame with 1x1 rails, a bellypan and 1678-style bumper mounts. Pigeon 2.0 and CANivore are on the drivebase (per CAD).
ENDGAME Compact deep climber. The climber tensioner is printed CF-Nylon; the OP states it held up better than expected and is 'fairly certain' it was never replaced.	**AUTONOMOUS** Unconfirmed
VISION 2 Limelight 4 cameras in the drivebase, on a centered mount and a swerve corner mount under printed roofs. A Limelight 3 is also in the BOM on a mount named for the human player. A camera is visible high on the elevator in the side view (per CAD).	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- Control rope lead angle on a spool: with the redirect arms, the team had no spooling issues in competition.
- The three-robot plan (Alpha, Beta, Comp) was inspired by 1678. The Beta robot's coral intake, algae intake and elevator needed major revisions before Comp.

Onshape CAD: Onshape CAD · CAD, code and documentation release (CD) · Onshape CAD · Code (GitHub) · Design binder (Google Drive) · Worlds strategy document (Google Drive)

■ Study pick

9450 Velocity Raptors

USA-WA

Local EPA 88 (#27)

50-17

Differential wrist under custom control code on an elevator; 3 piece L4 ground auto

SCORING (CORAL / ALGAE) Differential wrist: another user calls it a 'diffy wrist', and the OP's reply about its control does not correct that. The team wrote its own control scheme instead of using the Phoenix 6 differential control requests, which it did not know existed. The OP says the CTRE controls are likely faster and advises using them.	**INTAKE** The February 2025 auto video is titled '3 Piece L4 Ground Auto'.
ELEVATOR / ARM Elevator. The team says it spent off-season time on elevator optimization.	**DRIVETRAIN** Swerve drive with four SDS MK4i modules, shown as simplified models. The module motors are not modeled. A Pigeon and a CANivore are in the drive base (per CAD).
ENDGAME Climber assembly at the end of the frame opposite the wrist. A tube arm carries a cage grabber at its top, with polycarbonate flaps near its base (per CAD).	**AUTONOMOUS** 3 piece L4 ground auto, shown 2025-02-11 before the Week 1 Glacier Peak event.
VISION Unconfirmed	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- Match the mechanism to the problem: the team says it does not plan to use differential mechanisms as its default for every problem, and it calls them niche.
- Strategy detail: at Chezy Champs the alliance scored algae in the processor instead of the net when it was behind on raw points; 5940 suggested the idea.

Onshape CAD: Onshape CAD · Onshape CAD · Code (GitHub) · 3 piece L4 ground auto video · CAD, code and binder release (CD)

Other profiled robots

Each has public CAD, a binder, code or a detailed release thread. Sorted by Local EPA. ■ marks the study picks.

■ Study pick

1732 Hilltopper Robotics Private

USA-WI

Local EPA 86 (#34)

41-17

4x L4 coral auto with QuestNav localization; algae handoff

SCORING (CORAL / ALGAE) Scores coral on L4. An algae handoff can also run in reverse in initial testing; net algae was not the week 1 focus, so the handoff was not yet tuned.	**INTAKE** Guarding was being added to keep coral out of the robot; a team member says it also helps the algae handoff.
ELEVATOR / ARM Tall chain-driven elevator. The elevator subassembly has two REV MAXPlanetary gearboxes, #25 chain, SDS elevator blocks and a constant force spring. A roller arm pivots at the top of the carriage. Diagonal braces run from the top of the elevator to the frame (per CAD).	**DRIVETRAIN** Swerve with four SDS MK4n modules (simplified models). Square frame (per CAD).
ENDGAME Climber subassembly with winch spools (AndyMark am-4647, for 2 in box tube). The CAD includes a cage model for reference (per CAD).	**AUTONOMOUS** 4-coral L4 autonomous using QuestNav.
VISION QuestNav localization. The team posted a QuestNav write-up in a separate Chief Delphi thread.	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- Keep game-piece paths apart, as the coral guarding shows.

Onshape CAD: Onshape CAD · CAD and code release (CD) · Onshape CAD · Code (GitHub) · Reveal thread (CD) · QuestNav write-up (CD)

Profile

111 WildStang

USA-IL

Local EPA 85 (#39)

39-7

Arm with coral gripper and algae wheels on an elevator; over-the-bumper star-wheel intake; climb arm; MAXSwerve swerve

SCORING (CORAL / ALGAE) End effector at the arm tip: a coral gripper (top, bottom and cap parts) with a LaserCAN sensor, and an algae intake with compliant wheels (per CAD).	**INTAKE** Over-the-bumper ground intake with a fixed section and a moving section. The moving section carries star-shaped roller wheels (per CAD).
ELEVATOR / ARM Elevator ('Lift') with a fixed stage, one extension stage and a carriage, moved by up and down rigging. A long arm with a truss section pivots on the carriage (per CAD).	**DRIVETRAIN** Swerve with four REV MAXSwerve 3in modules in Spectrum corners, with spiky MAXSwerve wheels. NEO Vortex drive motors and NEO 550 steer motors (per CAD).
ENDGAME A climb arm with a fly wire, driven through #35 chain from a 10T hub sprocket (per CAD).	**AUTONOMOUS** Unconfirmed
VISION Two Limelight 3 cameras on left and right mounts on the drive base (per CAD).	**PUBLIC CAD / DESIGN** Onshape CAD (Spectrum listing)

Onshape CAD: Onshape CAD (Spectrum listing) · Onshape CAD (Spectrum listing)

■ Study pick

1114 Simbotics Simbot Suzuki

Canada

Local EPA 83 (#52)

43-22

Station-fed coral elevator; reef algae removal; deep cage climber added mid-season via a pivoting funnel; swerve

SCORING (CORAL / ALGAE) A manipulator on the elevator scores coral; the team describes L4 placements. An algae mechanism removes algae from the reef; the team added it before the deep climber because it was easy to add. At Niagara College the manipulator caught a reef branch as the elevator lowered after an L4 placement and lost its position.	**INTAKE** Coral from the loading station through a funnel. No floor coral or ground algae intake: the team ranked both last on its priority list. It used no resources on floor coral. The team states it would add ground algae pickup early next time, while the change was still small.
ELEVATOR / ARM Elevator. The team designed the energy chain into the CAD, which it does not normally do. Three aluminum brackets support the energy chain; a planned Lexan piece was never installed.	**DRIVETRAIN** Swerve; 'Drive Maneuverability (Swerve)' is first on the team's priority list.
ENDGAME Deep cage climb, added after the Niagara College event. The funnel pivots down and the cage comes in from the side and twists into the robot. Climber pivot: 11T Kraken pinion, 11:80 then 18:80, 32.32:1 total. Plates broke at McMaster; at Provincials the chain sometimes sat on the 'wrong side' and the bumpers touched the ground.	**AUTONOMOUS** Unconfirmed
VISION Unconfirmed	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- Write a ranked ability list and use it to decide what to skip.
- Retrofitting a climber costs packaging: the elevator and funnel left no room for the cage.
- Design the energy chain into the CAD. The team states this gave a working energy chain all season.
- Compare the first code repository with the offseason command-based version in the second.

Onshape CAD: Onshape CAD · Onshape CAD · Code (GitHub) · Offseason command-based code (GitHub)

■ Study pick

581 Blazing Bulldogs Zuma

USA-CA

Local EPA 82 (#59)

33-16

Champs: claw on a slip-ring arm with unlimited rotation; ground coral intake with handoff; 2-stage elevator; swerve

SCORING (CORAL / ALGAE)
Claw driven by a Kraken X60 on a 12:1 reduction, with 3 in 30A durometer wheels on dead axles. Printed backstops add algae contact area and act as shims for coral-to-roller interference. A Banner sensor with retro-reflective tape detects coral and algae; the code auto-scores L2-L4 coral and algae in the net and processor. Changed for Champs: the team pushed the sides of the throat further out to hold algae without changing the coral grip. The team had made 4 claws by its Regional events and 6 claws by the Championship.

INTAKE
Ground coral intake. The team chose a 1323-style intake after seeing it at SVR, to cut mechanical development time and keep time for software and drive practice. The team had heard that wheel placement on 1690/2056-style intakes caused dead zones. Pivot: Kraken X44 on a 69.5:1 reduction, on a steel 10DP gear. Rollers: Kraken X44 on 5:1, in WCP SRPP plates with a Banner sensor. Changed before Champs: the top roller went from a tube roller to a hex shaft with flex wheels; the bottom roller is Cat-tongue wrapped aluminum.

ELEVATOR / ARM
2-stage sideways cascading elevator on 2 Kraken X60 at 5:1, with a 1 x 1 in 1/16 in wall diagonal brace. The carriage arm runs on one Kraken X44 at 9:1 through a custom 90T 10DP gear and a 6 in Kaydon X-contact bearing. A 6-channel slip ring allows unlimited rotation: 4 channels power the claw and 2 carry CAN.

DRIVETRAIN
29 x 29 in frame perimeter of 1/8 in wall aluminum tube. Four WCP X2i swerve modules with X3 gearing and eight Kraken X60. Two custom swerve covers carry Limelight mounts facing the reef. A dynamic cover of surgical tubing and rope stops coral lodging under the elevator.

ENDGAME
Cage climber deployed by a torsion spring, with latches that lock the cage in. The cage wheels went from 3 in to 4 in 30A durometer to speed up cage acquisition. A Maxplanet at 9:1 winches down, and a WCP ratchet plate prevents unspooling. A CANrange behind the latch starts the climb when it detects the cage. To deploy, the winch runs until the rope fully unspools and wraps the other way; a CANcoder reads the deploy angle, and the winch then runs to a maximum angle after the cage is grabbed.

AUTONOMOUS
Autos run on Trailblazer, the team's own tool: segments of points, actions and constraints, followed by an adaptive pure-pursuit controller. Reusable AutoBlocks hold the scoring and intaking steps. At Champs the robot ran only a 4-piece auto: the preload plus the three prestaged lollipops, found with vision.

VISION
4 Limelights, run by one state machine that switches all cameras between game-piece detection and tag filtering. A Limelight 4 runs a CPU ML model to find prestaged algae and so locate the prestaged coral. A Limelight 3 color pipeline finds coral at handoff. The team states that camera faults degrade automation without stopping scoring.

PUBLIC CAD / DESIGN
Champs robot CAD (Onshape)

LESSONS FOR STUDENTS

- Rebuild or modify: the team listed the Regional robot's faults (high CG when scoring, algae slipping, narrow intake, slow climb) and chose a rebuild over added subsystems.
- An arm with unlimited rotation needs motion planning. The A* edge costs use arm angle and elevator height changes.
- Vision can replace a centering mechanism: the camera reads coral Tx and an interpolation table sets the arm angle at handoff.
- Copy a proven mechanism to save time.
- Compare the two public robots; the first iteration of the Regional robot took 17 days.

Onshape CAD: Champs robot CAD (Onshape) · CAD and code release (CD) · Champs robot CAD (Onshape) · Champs robot code (GitHub) · Regional robot CAD (Onshape) · Regional robot code (GitHub) · Behind the Bumpers video · Champs robot reveal (CD) · Champs robot reveal video

■ Study pick

6800 Valor Deadlock

USA-TX

Local EPA 82 (#57)

59-10

Funnel; 3-stage elevator; 3 non-drive motors pre-Worlds, 5 at Worlds; swerve

SCORING (CORAL / ALGAE) The pre-Worlds scoring mechanism used 1 motor; the Worlds version uses 2. The Worlds mechanism is cut from 1/8 in SRPP, with added flanges to stiffen it. The team states the extra motor added little weight.	**INTAKE** The pre-Worlds version focused on simple, effective human loading. The Worlds version focused on improving ground algae and coral options and added a motor to power the funnel.
ELEVATOR / ARM 3-stage elevator with 1 motor, on the robot from the start to reduce degrees of freedom for controls. A tie rod runs from half height on the elevator stationary tubes to the 2 x 2 chassis frame rail. A planned X pair of tie rods was not built.	**DRIVETRAIN** Swerve.
ENDGAME 1 climber motor in both variants.	**AUTONOMOUS** 3-piece auto with L4 coral. At the state championship the robot scored 50 of 51 L4 coral in auto; the team gives a 98% success rate. Autonomous Award at Manor.
VISION Unconfirmed	**PUBLIC CAD / DESIGN** Onshape CAD

Onshape CAD: Onshape CAD · CAD release thread (CD) · Onshape CAD · Tech Packet (Google Drive) · Behind the Bumpers video · Reveal thread (CD)

■ Study pick

9496 LYNK Chimney Rock (Rocky)

USA-NC

Local EPA 81 (#69)

72-7-2

Passive gas-strut algae manipulator; reef AprilTag coral alignment; low-rider chassis on SDS L2 swerve

SCORING (CORAL / ALGAE) In week 1 the team prototyped a 'mortar style' coral shooter and rejected it. Shots were inconsistent; the physical angle did not change backspin; motor speed changed backspin but added inconsistency. The team also judged a hard coral shot unsafe for referees and human players.	**INTAKE** The algae manipulator deploys passively on a gas strut. The team linked a 25 lb, 4 in strut and states that strut force only sets deploy speed. After deployment, two polycarbonate pieces press on the aluminum extrusion to hold the manipulator in place. The January goal list set coral station pickup in under 1/2 second and listed ground coral intake as a non-goal.
ELEVATOR / ARM A 2026 team post describes the robot as '2[1]dof' in a statement that the team keeps degrees of freedom low. A team reply in July 2025 mentions a handoff channel whose gap matches the CAD.	**DRIVETRAIN** Swerve with SDS modules at the L2 ratio. The team calls the chassis a low rider and states it keeps algae from getting under the robot. The team runs its own Kraken Swerve Base code for CTRE hardware, with CANivore, FOC and an optional 250 Hz odometry thread.
ENDGAME The January goal list named a deep cage climb and listed the shallow cage as a non-goal.	**AUTONOMOUS** The January goal list set 3 coral in auto. The code post links PathPlanner and Choreo; the tool used for the final autos is unconfirmed.
VISION Vision is used mainly to align coral scoring to the reef AprilTags. A team mentor states that only the reef branch position relative to each face tag matters, so the team did not calibrate a field map with WPICal. PhotonVision is linked in the code post.	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- Fast odometry has a cost: the team says to use the optional odometry thread only with the swerve bus on a CANivore, because it raises CAN utilization.
- A passive mechanism can save a motor, as the gas-strut algae manipulator shows.
- Bumper build method: layered floor-tile foam glued with contact cement replaced pool noodles, and the team irons numbers directly onto fabric stapled over the new foam.

Onshape CAD: Onshape CAD · Onshape CAD · Build Log (CD) · Robot code (GitHub)

■ Study pick

971 Spartan Robotics Fiddler

USA-CA

Local EPA 80 (#84)

30-18

Funnel end effector chosen over suction; stiffened elevator with arm and wrist; swerve after tank in 2023-2024

SCORING (CORAL / ALGAE) Funnel end effector. The team evaluated suction but picked the funnel because it did not need a wrist at first, was reliable for algae, and had partial ground intake capability. The team later decided a wrist was needed and did not revisit suction.	**INTAKE** The team says it was committed to a human player intake early in the season. The funnel end effector had partial ground intake capability.
ELEVATOR / ARM Elevator carrying an arm assembly with a wrist; the team says the arm assembly weighed a lot. The elevator started as a stock Greyt elevator with two short stiffening rods and bottom gusset plates. The rods were lengthened after driving, partly inspired by Orbit. A lighter Championship rebuild was too flimsy, so the team thickened the top of the base, reduced lightening on the verticals and added U-shaped constraining plates.	**DRIVETRAIN** Swerve. A team member says defense in 2023 and 2024 drove the change from tank drive. The software team wrote custom swerve code from the ground up.
ENDGAME Unconfirmed	**AUTONOMOUS** Unconfirmed
VISION Five Raspberry Pi HQ Camera v2 cameras are in the drivetrain assembly, in camera boxes with hoods, with an SMC mirror part. An enclosure named Orin Box sits in the drivetrain. Field-of-view bodies in the CAD project out from two opposite sides of the robot. A user outside the team quotes a line on projecting a ray onto the floor to find coral distance; no team answer appears (per CAD).	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- A lighter elevator can cost stiffness.

Onshape CAD: Onshape CAD · CAD release (CD) · Onshape CAD · Technical documentation (PDF) · Reveal thread (CD) · Reveal video

---

Profile

2630 Thunderbolts Atlas

Israel

Local EPA 80 (#86)

47-16-1

L4 coral scorer with algae into the net; 4 L4 coral auto in 14.3 s

SCORING (CORAL / ALGAE) Scores coral on L4. Algae scoring into the net was added by 2025-03-01.	**INTAKE** No separate intake is in the CAD. The gripper at the end of the arm carries 2 sets of green compliant roller wheels and is the only game piece handler (per CAD).
ELEVATOR / ARM A main shaft is a fixed axle held at its ends with snap clips.	**DRIVETRAIN** Swerve with 4 SDS MK4i modules in the Falcon/Kraken configuration. Square frame of 60x40 profile with a bellypan. Pigeon 2 and CANivore are on the chassis (per CAD).
ENDGAME A fork assembly with 2 fork profiles and 2 latches pivots on the main shaft at the top of the rear tower. A NEO on a MAXPlanetary 3-stage and a #35 chain sprocket are in the same group. The CAD does not name it as a climber (per CAD).	**AUTONOMOUS** 4 L4 coral auto: 14.3 seconds from auto start to release of the last coral. It runs on the far side so it is compatible with other teams' 4-5 coral autos. The OP said in March that the first coral sometimes missed.
VISION The BOM has a base camera mount and a front camera mount on the arm gearbox. It names no camera model (per CAD).	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- Plan auto to fit partners, so their autos could run too.

Onshape CAD: Onshape CAD · CAD and tech binder release (CD) · Onshape CAD · Tech binder (Google Drive) · Reveal thread (CD) · 4 L4 coral auto video

Profile	2137 The Oxford RoboCats Guillotine USA-MI	Local EPA 79 (#88) 47-16

Coral end effector on an elevator; station funnel; climber with roller wheels; MK4n swerve

SCORING (CORAL / ALGAE) Coral end effector on the elevator carriage, below the funnel. CANrange sensors are in the BOM (per CAD).	**INTAKE** Funnel of polycarbonate plates at the top of the robot guides coral from the station to the end effector (per CAD).
ELEVATOR / ARM Elevator near the center of the frame with an outer and an inner stage, driven by an elevator gearbox with pulleys (per CAD).	**DRIVETRAIN** Swerve drive with four SDS MK4n modules (per CAD).
ENDGAME Second-version climber subassembly with a NEO through a REV MAX Planetary. The CAD shows a tall frame at one side with roller wheels at its top and a chain and gear drive (per CAD).	**AUTONOMOUS** Unconfirmed
VISION Two Limelight 3G cameras on left and right chassis camera mounts (per CAD).	**PUBLIC CAD / DESIGN** In-season CAD (Onshape)

Onshape CAD: In-season CAD (Onshape) · In-season CAD (Onshape) · Off-season CAD with new climber (Onshape) · Code (GitHub)

■ Study pick	3467 Windham Windup USA-NH	Local EPA 79 (#89) 49-19-1

Coral claw on an elevator; algae in horns or a lower claw; no floor intake; deep cage climber; Mk4i swerve

SCORING (CORAL / ALGAE) Coral claw with rollers. During the UNH event the team changed the claw to catch the coral as it came through. From QM 61 through playoffs it had zero elevator jams from coral sticking out the back of the claw. Algae is held in 'horns' or a lower claw. After the first district event the team added algae scoring into the net and a better coral hard stop. Before DCMP the net score became one motion: the robot rises and spits, so it does not hook on the net.	**INTAKE** No floor intake for coral or algae; the team states this hurt its play at the highest level. Coral enters the claw from a ramp. The ramp sagged and let coral catch and turn vertical, so the team moved it about an inch closer to the claw. Before DCMP the team made the horns the only way to take algae off the reef, after it practiced processor scoring from the horns.
ELEVATOR / ARM Elevator. Each mode had its own height setpoints, and at UNH the single driver switched between three modes: coral, algae in horns and algae in lower claw. Before DCMP the code used the robot's global pose to send the elevator to the algae height for the reef face in front of it. Holding the algae button moves the elevator straight from coral scoring height to algae pickup height.	**DRIVETRAIN** Swerve on Mk4i modules: in November 2025 the team states it ran Mk4i for the last three years. The wheels were MK4 billet wheels with black neoprene tread, replaced by molded TPU tread after the season.
ENDGAME Cage climber with a climber gearbox and a cage grabber. Climber failures cost ranking points and matches at UNH, and the team planned design changes to both parts before DCMP. The team's DCMP post refers to its alliance hanging from the deep cages.	**AUTONOMOUS** 3-coral auto. During the UNH event the team added code that watches the claw rollers for current spikes. On a spike the robot ends the command and restarts it, which jostles the coral so auto can continue. The team states the auto ran worse at the World Championship than at DCMP, largely because of automation changes made without enough time or a detailed plan.
VISION The code uses the robot's global pose to pick the elevator height for each reef face. The team runs auto-align code and planned before DCMP to make it handle coral between the robot and the reef.	**PUBLIC CAD / DESIGN** Robot CAD (Onshape)

LESSONS FOR STUDENTS

- Detect jams from motor current.
- Close geometry gaps where a game piece changes path.
- Reduce driver modes with automation.
- Plan changes between events.
- Make CAN faults easy to isolate: inline toggleable terminators (Thrifty CANjunction) cut diagnosis time.

Onshape CAD: Robot CAD (Onshape) · Robot CAD (Onshape) · Build blog (CD) · 2026 build blog with review (CD)

■ Study pick

2930 Sonic Squirrels Holocentrus

USA-WA

Local EPA 78 (#100)

46-22

Elevator robot; 100+ short Choreo paths; PhotonVision auto-align on 4 global-shutter cameras

SCORING (CORAL / ALGAE) PhotonVision aligns the robot to AprilTags; PathPlanner works with the Choreo paths and localization data. The team calls the result an almost fully automated scoring routine from anywhere on the field.	**INTAKE** Two of the four main cameras are for coral station detection.
ELEVATOR / ARM Elevator superstructure with many self-collision points, especially when moving under the elevator. The code divides the robot into sectors and moves through each one safely. Subsystem logic checks the robot state periodically and acts on it.	**DRIVETRAIN** Unconfirmed
ENDGAME A ThriftyCam helps the driver align to the cage.	**AUTONOMOUS** Over 100 short Choreo paths let the robot run autos that the drive team writes. PathPlanner works with the Choreo paths and vision localization. Autonomous Award at Glacier Peak.
VISION PhotonVision on two Orange Pi 5 coprocessors, with four AR0234 global-shutter USB 3.0 cameras: two for the reef, two for the coral station. A fifth camera, a ThriftyCam, helps the driver align to the cage. The team tested positions on an old robot against a mock reef and chose crossed views to lower AprilTag ambiguity. Two cameras did not run on USB 3.0; the team member does not recall bandwidth problems.	**PUBLIC CAD / DESIGN** Onshape CAD

Onshape CAD: Onshape CAD · CAD and code release (CD) · Onshape CAD · Code (GitHub)

■ Study pick

695 Bison Robotics Goldfish

USA-OH

Local EPA 76 (#124)

26-14

Elevator coral scorer, ramp-fed pivoting arm, modified Everybot climber; swerve; reef-repulsion auto-align

SCORING (CORAL / ALGAE) The coral mechanism, which the team calls the 'coralizer', is mostly 3D printed; the team states this made spares and replacements easier. Scoring is fully autonomous.	**INTAKE** Feeder station intake through a ramp and an indexer. The ramp and indexer pivot with a combined arm that also dislodges algae. Feeder station pickup can run autonomously.
ELEVATOR / ARM Elevator built from parts of several manufacturers' elevator kits. A combined pivoting arm handles coral and algae dislodge. After the first event the team started raising the elevator earlier during auto-align. All mechanism control loops run on the motor controllers.	**DRIVETRAIN** Swerve with a full Kraken drivebase. The four swerve modules ran on a CANivore bus through the team's CAN splice boards, which fit SDS or WCP modules.
ENDGAME Modified Everybot climber; the team states it worked well for them.	**AUTONOMOUS** All autos use the same auto-align system as teleop.
VISION Dual Limelight 4 running MegaTag2. Odometry runs at 200 Hz with a NavX2. This localization feeds the reef auto-align.	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- A simple auto-align can be enough. The repulsion field switches on only when a straight path to the target would hit the reef.
- Model a controller before coding it. The team published a Desmos proof of concept of the repulsion field that anyone can drag and animate.
- The CAN splice PCB design and Gerber files are public, with a stated parts cost of about $20 per board.

Onshape CAD: Onshape CAD · CAD and code release (CD) · Onshape CAD · Code (GitHub) · Reef repulsion model (Desmos) · Auto-align video · CAN splice PCB files (Google Drive)

■ Study pick

3128 The Aluminum Narwhals Gillbert

USA-CA

Local EPA 76 (#122)

31-13

Sensorless counter-rotating coral end effector on an elevator; interchangeable L1 coral and algae intakes

SCORING (CORAL / ALGAE) Coral end effector with front and back wheel sets about one coral length apart that spin in opposite directions. At the elevator stow position the wheels run all the time; the back wheels push the coral forward and the front wheels push it back to hold it. There is no beam break or banner sensor on the end effector. A slit in the top polycarbonate plate, bent down, acts as a one-way latch; the team member does not believe it is in the CAD.	**INTAKE** Coral loads from the coral station through a funnel into the end effector. A ground coral mechanism that scores only on L1 was added during the season for champs. Because of the weight limit, the coral and algae intakes are interchangeable and are not on the robot at the same time.
ELEVATOR / ARM An elevator carries the end effector. A reef algae remover stows inside the frame and snaps out on surgical tubing to a hard-stop locked position when the elevator first rises in auto. It extends 3.25 in from the frame, the same as the bumpers.	**DRIVETRAIN** Unconfirmed
ENDGAME Unconfirmed	**AUTONOMOUS** The algae remover deploys on the first elevator raise in auto. TBA lists the Autonomous Award at the San Diego Regional.
VISION A team member mentions work on auto align while the team sped up its autos.	**PUBLIC CAD / DESIGN** Technical binder (Google Doc)

LESSONS FOR STUDENTS

- Geometry can replace a sensor; with the counter-rotating wheel sets, the code needs no intake state change.
- Weight drives architecture, as the interchangeable intakes show.
- Review upgrades after the season: the barge algae addition cut coral scoring efficiency.

Drive folder / doc: Technical binder (Google Doc) · Technical binder (Google Doc) · Reveal thread (CD) · Reveal video

■ Study pick

5460 Strike Zone TITAN

USA-MI

Local EPA 75 (#141)

52-12-2

Rotating coral claw with a BAG motor in a carbon tube; continuous elevator with a 50 mm shaft arm; winch climber

SCORING (CORAL / ALGAE) Rotating coral claw. A BAG motor and VersaPlanetary Lite sit inside a carbon tube. The hex output shaft drives aluminum plates and 3D prints in the claw. A custom through-bore encoder housing holds a CANcoder for closed-loop position control.	**INTAKE** Asked about a ground intake, the OP replied 'no'.
ELEVATOR / ARM Continuous elevator with an arm on the carriage. The arm pivots on a 50 mm shaft on bearings bought from Amazon, the same setup as the team's 2023 arm joints, based on 971's 2018 arm. The main pivot has three bearings: two near the large pulley for the radial load and one at the shaft end to keep the joint parallel. SLS-printed Nylon 12 parts join the laser-cut pulley to the arm. The aluminum shoulder was machined from 2.5 in OD x 1.5 in ID round stock on a sponsor's CNC lathe. The arm belt has no adjustable tensioner: its path around the large pulley, the 30T pulley and two idlers was set to a slight undersize of a 650 mm (130T) belt. The idlers add wrap on the 30T pulley to prevent skipping. The elevator belt path length does not change, so it needs no tension spring; the team tensioned it before Week 1 and did not touch it after. A cross bar on the back of the elevator stops it from racking into a parallelogram. CF springs meant to hold the first stage down were removed; the carriage and arm weigh over 20 lb.	**DRIVETRAIN** WCP X2St modules, the mounting base for the team's WCP bumper mounts. Bumpers weigh about 30 lb with added weight plates to lower the center of gravity; the team says this helped it stay stable at full height.
ENDGAME Winch climber. A 3D-printed latch on the winch gearbox cross shaft holds a spliced Dyneema loop around the climber foot. In climb state the shaft turns 1 rotation in reverse and the cage centering device springs out.	**AUTONOMOUS** The team calls TITAN its most complex and automated machine.
VISION Unconfirmed	**PUBLIC CAD / DESIGN** Onshape CAD (imported from SolidWorks)

LESSONS FOR STUDENTS

- Build stiffness on purpose: the team advises pre-made bearing blocks, 6 in or more between bearing centers on overlapping stages, and a force diagram. Its force diagram led to the cross bar.
- The team weighed investment casting against machined parts and kept sheet metal plates and machined tube on the carriage.

Onshape CAD: Onshape CAD (imported from SolidWorks) · Reveal, CAD and binder thread (CD) · Onshape CAD (imported from SolidWorks) · Technical binder (Google Doc) · Reveal video

Profile	9442 Miso Mechanics USA-WA	Local EPA 75 (#133) 37-23

End effector and pivoting algae arm; over-the-bumper algae intake; three-stage elevator; WCP Swerve X2 swerve

SCORING (CORAL / ALGAE) End effector assembly (0400B) and a separate pivoting arm assembly (Arm Pivot). The arm pivot holds an algae model, algae side guards, a coaxial motor mount and a Kraken X44. It turns through #25 chain from a gearbox (per CAD).	**INTAKE** Over-the-bumper algae intake on a pivot (Algae Pivot and Algae Arm), with a row of rollers, a stub roller and a floating roller (per CAD).
ELEVATOR / ARM Elevator with a base and three moving stages, with two belts. Tie rods brace the top of the elevator to the frame (per CAD).	**DRIVETRAIN** Swerve drive with four WCP Swerve X2 modules on swerve risers. Kraken X60 motors are in the BOM. Two Pigeon 2.0 units and a CANivore are in the drivetrain (per CAD).
ENDGAME The document has deep climber assemblies (Deep Base and Deep Arm). They are not listed at the top level of the robot assembly, so the climber layout on the robot is not confirmed (per CAD).	**AUTONOMOUS** Unconfirmed
VISION Two Limelight 4 cameras. One is on a 3D printed mount on a plate in the drivetrain, with a cooler and a lens cover. The other is on a separate LL Mount assembly. Two CANrange sensors and a LaserCAN mount are in the arm pivot assembly (per CAD).	**PUBLIC CAD / DESIGN** Onshape CAD

Onshape CAD: Onshape CAD · Onshape CAD

■ Study pick

294 Beach Cities Robotics Sacabambaspis

USA-CA

Local EPA 73 (#160)

27-18

Pivoting wrist with pass-through side rollers; station hopper; 3-stage elevator tilted 3 deg forward

SCORING (CORAL / ALGAE) A pivoting wrist carries the coral and algae end effector. Coral passes through on side rollers; the team chose this because the side rollers worked on its test unit. The algae manipulator also changed to side rollers so it fit in the starting configuration. The robot handles coral and algae independently.	**INTAKE** Coral loads from the station into a low-powered hopper on the side opposite the scoring side. The kit-bot test phase showed the value of a wide acquisition zone under defense, so the team lowered the ramp into a hopper. No coral ground intake; the team states it could not implement the concepts it studied in its time and resources. An earlier concept had a 4-bar algae ground intake, which the team removed.
ELEVATOR / ARM 3-stage elevator, chosen to reach the barge and to reduce overall robot height. The elevator moved toward the front of the robot and tilts forward 3 deg. The tilt gives room to stow, reach out to the reef and leave room for the cage chain. The FUN Behind the Bumpers summary describes it as a continuous elevator.	**DRIVETRAIN** Unconfirmed
ENDGAME The concept-stage layout had a climb that pulled the cage into the hopper. The team's list of final-layout changes does not remove this climb. The FUN Behind the Bumpers summary describes a powered hopper with integrated climb.	**AUTONOMOUS** Unconfirmed
VISION The team states the oversized-elevator test phase showed that auto-drive routines for alignment were critical.	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- Set requirements before concepts. The team's four requirements (load one side and score the other, prioritize L2-L4, handle coral and algae independently, ground algae to the barge) ruled out several architectures.
- Build a test unit in parallel with the competition robot. The oversized-elevator phase taught the team continuous elevators.
- Packaging changes cascade. The end effector pushed the elevator toward the center and into the cage chain, which led to the forward move and the tilt.
- Fit the drive position to the robot. The team states that independent coral and algae handling suited driving from station 1, where it cycled through playoffs.

Onshape CAD: Onshape CAD · CAD, code and binder release thread (CD) · Onshape CAD · Code (GitHub) · Technical binder (PDF) · Annual report (PDF) · Behind the Bumpers video

■ Study pick

6995 NOMAD Mariana

USA-CA

Local EPA 73 (#163)

54-16

Two-sided ground 'hand' for coral and algae on an elevator and pivot; single-pole wheeled cage latch climb

SCORING (CORAL / ALGAE) A ground 'hand' end effector, reached after about 30 iterations of wheels and small changes. It scores coral on both sides of the robot at L3 and L4 and removes algae from the reef on both sides. The team expected 4-5 more cycles per match from it.	**INTAKE** Coral station intake at the Orange County Regional. The team switched to the ground hand for Championship because station intake suffered under heavy defense. The team thanks 9442 and 8033 for help with it.
ELEVATOR / ARM Elevator with a pivot. A Vortex motor drives a WCP rubber friction brake on an 8mm lead screw into a lathed aluminum hex hub. The hub is on the same shaft as an early pivot gear, so little force is needed. The 3D-printed pivot parts are PLA pro and carry no load; they act as spacers or axial constraints.	**DRIVETRAIN** Electronics mount under the robot behind a polycarbonate cover held by bolts into rivnuts; the team states access takes about 30 seconds. The team switched from REV to Kraken motors this season; the post does not say which mechanisms.
ENDGAME Wheel-based latch climber on a single cage pole, revived from an early prototype. The earlier hook climber held for less than 3 seconds. The grabber is angled up 12 degrees so it reaches outside the bumpers and pulls the eye bolt more than an inch lower. Expected climb time dropped from 15 s to 5-7 s.	**AUTONOMOUS** Autonomous Award at the Orange County Regional; Programming Award at Beach Blitz. A separate drivebase let software test auto cycles before the main robot was ready.
VISION Unconfirmed	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- The team states the single-pole wheeled grabber catches a corner at almost any approach angle, so it needs less alignment.
- Change geometry before adding parts: the team angled the existing grabber and did not build a two-pole version.

Onshape CAD: Onshape CAD · Onshape CAD · Behind the Bumpers video · Reveal video

---

Profile

9432 Team 8-Bit

USA-AZ

Local EPA 71 (#192)

38-11

Coral arm with algae intake on a two-stage elevator; station funnel; climber under the funnel; SDS MK4n swerve

SCORING (CORAL / ALGAE) Coral arm assembly with a coral roller and an algae section. The arm has a static part and a moving part, with long link plates beside the elevator. A Kraken X44 is in the BOM (per CAD).	**INTAKE** Polycarbonate funnel for coral from the station, on the side opposite the coral arm. The algae intake is part of the coral arm assembly. No ground coral intake is visible (per CAD).
ELEVATOR / ARM Two-stage elevator: a base, stage 1 and stage 2, with left and right belts. A custom gearbox drives it. Kraken X60 motors and MAXPlanetary parts are in the BOM (per CAD).	**DRIVETRAIN** Swerve drive with four SDS MK4n modules (two A and two B). The module parts include Kraken X60 spacer plates and Kraken spline gears. A CANivore is in the drive assembly. Square frame (per CAD).
ENDGAME The climber shares one assembly with the funnel (FUNNEL / CLIMB 2.0). It has a static part and a moving part below the funnel (per CAD).	**AUTONOMOUS** Unconfirmed
VISION The drive assembly holds a part named Left Camera on a camera base, and an OrangePi 5 case. The camera model is not named (per CAD).	**PUBLIC CAD / DESIGN** Competition robot CAD (Onshape)

Onshape CAD: Competition robot CAD (Onshape) · Competition robot CAD (Onshape)

Profile	2491 NoMythic USA-MN	Local EPA 70 (#205) 30-10

Coral end effector, algae roller arms, coral funnel, multi-stage elevator, cage climber, MK4i swerve

SCORING (CORAL / ALGAE) Coral end effector ('2025-CEE') with roller wheels, between the elevator and the funnel. Separate top and bottom algae arms each use a NEO 550 to drive 4 in compliant wheels (per CAD).	**INTAKE** A polycarbonate funnel on the rear guides coral from the station toward the coral end effector (per CAD).
ELEVATOR / ARM Elevator with a second stage and chain tensioner mounts. The algae arms mount on the front of the elevator (per CAD).	**DRIVETRAIN** Swerve drive with four SDS MK4i modules on swerve lowering blocks (per CAD).
ENDGAME Cage climber ('2025-CL') with its own gearbox plates. The CAD includes a cage path body to check clearance (per CAD).	**AUTONOMOUS** Unconfirmed
VISION Two Limelight 4 and two Limelight 3 cameras are in the drive assembly, on left and right Limelight plates. A rear distance sensor mount is also on the drive base (per CAD).	**PUBLIC CAD / DESIGN** Onshape CAD

Onshape CAD: Onshape CAD · Onshape CAD

Profile	2877 LigerBots Hydra USA-MA	Local EPA 70 (#210) 42-24

Coral floor pickup to L1 in work; algae floor intake removed in March

SCORING (CORAL / ALGAE) An end effector with several roller wheels sits on a chain-driven pivot at the top of the elevator. A separate L1 scorer assembly with a top end stop sits low on the frame (per CAD).	**INTAKE** The BOM names 2 coral side intake parts, an intake helper coral plate and printed top and bottom coral guides. No algae floor intake is in the CAD (per CAD).
ELEVATOR / ARM Elevator with 3 tube stages (S0, S1, S2) on 2x1 elevator corner bearing kits (am-4875). #25 chain drives it from a REV MAXPlanetary and an inline gearbox. A string pot mount is in the BOM. A diagonal tube braces the elevator to the frame (per CAD).	**DRIVETRAIN** Swerve with 4 SDS MK4i modules. The module assemblies show Kraken X60 and NEO motors, and the drivetrain holds 4 SPARK MAX controllers (per CAD).
ENDGAME Climber assembly with hooks and a hook lock (hook base, lock house, lock triangles and lock wings) and its own gearbox plates. A simple cage model is in the CAD (per CAD).	**AUTONOMOUS** Unconfirmed
VISION 3 cameras in the drivetrain assembly on a left, a right and a back camera mount. The BOM does not name the camera model (per CAD).	**PUBLIC CAD / DESIGN** 'Hydra' CAD (Onshape)

Onshape CAD: 'Hydra' CAD (Onshape) · CAD release thread (CD) · 'Hydra' CAD (Onshape) · Reveal thread (CD) · Reveal video · Code (GitHub) · Technical photos of Hydra (Flickr)

■ Study pick

3061 Huskie Robotics Calypso

USA-IL

Local EPA 70 (#220)

25-15

Coral scorer on a four-stage elevator; side-to-side funnel; barge algae manipulator; winch climb; SDS MK4n swerve

SCORING (CORAL / ALGAE)
Coral manipulator on the elevator scores or lightly shoots coral onto the reef. Prototype wheels were 2.25 in 40A AndyMark wheels, 1.5 in apart and 4 in inside-to-inside, chosen after intake, spit-out and hold tests. For L1 the team added a tab below the coral that hits it as it flips. Changed after Week 1: a separate algae manipulator for barge and processor, based on the Northern Lights algae removal mechanism; the team reports 100% on barge shots at Midwest.

INTAKE
A funnel feeds coral from one side of the robot to the other. At kickoff the team judged a coral ground intake not worth it; after Northern Lights it listed a possible ground intake as less important than barge algae. A horizontal-roller funnel jammed in testing, so the team began to prototype vertical rollers, inspired by 4451. At Northern Lights the funnel slowly bent and an over-tight belt caused the same fault; the planned changes for Midwest were to remove the two back wheels and to use star wheels around compliant wheels. Week 1 algae plan: a slap-down processor intake with polycarbonate tube rollers.

ELEVATOR / ARM
Four-stage, continuously rigged elevator on two Krakens, modeled on a 2023 Worlds-winning elevator. Play in the elevator made L4 inconsistent in auto at Midwest. At Championship the team found failed tube plugs and bolts in one stage, which let it parallelogram, and no bolts holding one side to its mount. The team replaced and threadlocked the hardware and upgraded failed ball joints on the elevator support tubes with hardened bolts.

DRIVETRAIN
Swerve on all SDS MK4n modules, chosen for packaging: a wide intake on one side and the elevator close to the outer rail on the other. Choreo analysis led the team to L2+ gearing for acceleration and short sprints. Code drives the robot the other way when it tips so it does not stay stuck on algae.

ENDGAME
Week 1 plan: an angled telescoping tube with a spring-deployed cage catcher; design requirements called for a shallow climb only. Changed in March after the cage stuck in the robot at Northern Lights: a 111-style climb clashed with the funnel in CAD, so the team used a design inspired by 190. Two stacked cage catchers grab one cage bar; the lower 'hand' sits on a wrist that rotates passively when the winch pulls the hook back, and a WCP ratchet plate locks it. A servo moves the funnel bottom out of the cage's path; early deploys, a snapped rope and bent limit switch mounts followed at Midwest and Championship.

AUTONOMOUS
A 3.5-coral auto by 2025-03-11, within 15 s; it ends with a sprint to the reef with the swerve modules in coast mode. After Midwest the team listed a 4-coral auto as the first priority.

VISION
Week 1 software plan: four cameras. Two front cameras on the elevator face inward toward each other for reef tags; two rear cameras on the swerve modules face outward. Late at Northern Lights the pose estimate drifted; the team suspected the cameras had moved and planned mounts that locate each camera exactly. Software added drive-to-pose for barge and processor.

PUBLIC CAD / DESIGN
Onshape CAD

LESSONS FOR STUDENTS

- Design requirements set the archetype: a Week 1 event made simplicity the top priority, so the team picked a funnel and vertical elevator with 2 degrees of freedom for scoring.
- Check a borrowed mechanism in your own CAD.
- Structural faults can look like control faults, as the elevator sway at Championship shows.
- Camera mounts are part of the vision system.
- Log analysis closes the loop: the team's log-analyzer reported a 7.04 s average cycle over 31 cycles in two Curie matches, and a 7.8 mm average lateral reef error at coral release.

Onshape CAD: Onshape CAD · Build thread (CD) · Onshape CAD · Code (GitHub) · 3061-lib (GitHub) · Testing videos (Google Drive) · Log-analyzer post in preseason thread (CD) · Log-analyzer tool (GitHub)

Profile	5026 Iron Panthers The Grim Reefer USA-CA	Local EPA 70 (#206) 32-10

Human load funnel (per a 1678 mentor's reply)

SCORING (CORAL / ALGAE) A pivoting arm at the top of the elevator carries the end effector. The arm subassembly has polycarbonate sides, 3 in compliant wheels, two beam break sensors and a Kraken X60 on an HTD belt. An Axon Mini servo moves a linkage and a part named Tongue (per CAD).	**INTAKE** A polycarbonate funnel subassembly at the rear takes coral from the station. Its tall angled side panels open upward. No ground intake is visible (per CAD).
ELEVATOR / ARM Multistage elevator on 2x1 tube uprights with a drag chain for wires. A belt at the top of the elevator drives the arm pivot (per CAD).	**DRIVETRAIN** Swerve with four SDS MK4i modules (simplified models). The module models do not name the motors (per CAD).
ENDGAME A climb subassembly with two hook parts is in the top level (per CAD).	**AUTONOMOUS** Unconfirmed
VISION The BOM names one Limelight 2 and a driver camera mount (per CAD).	**PUBLIC CAD / DESIGN** Onshape CAD

Onshape CAD: Onshape CAD · Onshape CAD · Reveal thread (CD) · Reveal video · Behind the Bumpers post (CD)

■ Study pick	6328 Mechanical Advantage USA-MA	Local EPA 70 (#209) 44-21

End effector on a tilted 3-stage string-rigged elevator; coral hopper; algae intake; climber arm; swerve

SCORING (CORAL / ALGAE) End effector subassembly on the elevator carriage. A separate algae intake subassembly is in the CAD (per CAD).	**INTAKE** The intake mounting plates attach to 3D-printed parts that have nylock nuts pressed into the back and are printed at high infill. The team reports no issues with them.
ELEVATOR / ARM 3-stage elevator with string rigging, driven by 2 Kraken X60 through its own gearbox (per CAD). The team makes the tube plugs for a pivot on a lathe and holds them with green Loctite. It reports no issues with that pivot and would add a roll pin through each plug in future, as 2056 does.	**DRIVETRAIN** A metal standoff runs through a printed support at the swerve bolt.
ENDGAME Climber arm subassembly with its own climber gearbox subassembly (per CAD).	**AUTONOMOUS** Autonomous Award at the NE District UNH Event.
VISION The team's vision moved past Orange Pi coprocessors, which gave better data plus object detection and video recording. Each camera sent at least 2-3 Gb/s of raw video. The camera mounts are TPU. The team corrects rotation estimates with vision data and does not trust the gyro alone.	**PUBLIC CAD / DESIGN** Build thread with CAD and code links (CD)

LESSONS FOR STUDENTS

- Design printed parts to the load path. The team prints nearly every loaded part in PLA+ with 5 walls, 5 floors, 5 ceilings and 75% infill. It tries to make load-bearing parts metal, or to add a metal support.
- Plan for wear. The team describes printed pulleys as wear items to replace about once an event.
- Code performance is a design choice. The team's code used the serial garbage collector with settings taken from 254. The code needs about 45 s to warm up, and a dashboard alert tells the drive team when it is safe to enable.
- Keep a design-review record. A team mentor posted an album of the design-feedback screenshots sent to the CAD students during the season.

CD thread: Build thread with CAD and code links (CD) · Build thread with CAD and code links (CD) · 25A Dev Bot CAD (Onshape) · 25B Comp CAD (Onshape) · 25C Comp CAD (Onshape) · 25D Comp CAD (Onshape) · 25O Comp CAD (Onshape) · Code (GitHub) · Offseason code (GitHub) · Design feedback album (Google Photos) · SystemCore Alpha thread, vision and code notes (CD) · Build thread, conference recordings post (CD)

Profile	1540 Flaming Chickens USA-OR	Local EPA 69 (#234) 33-27

Arm and end effector on elevator; pivoting star-wheel intake; hook climber; swerve

SCORING (CORAL / ALGAE) An end effector subassembly mounts on an arm subassembly. The arm rides on the elevator carriage. LaserCAN sensors are in the BOM (per CAD).	**INTAKE** Pivoting intake on two carbon fiber side plates. It has three roller shafts with 5 in Star Flex wheels, driven by HTD belts. A Falcon 500 and a REV MAXPlanetary are in the intake subassembly. The pivot uses #25 chain. In the CAD it is stowed upright inside the frame at one end (per CAD).
ELEVATOR / ARM Tall elevator near the center of the robot. Constant force springs are in the BOM. Diagonal braces run from the top of the elevator to the frame corners (per CAD).	**DRIVETRAIN** Swerve with four modules. The drivetrain subassembly names SDS MK4n modules (simplified models) and also SDS MK4i parts in the NEO configuration. Kraken X60 motors, a Pigeon 2.0 and a CANivore are in the BOM. Square frame (per CAD).
ENDGAME Climber subassembly with a 4481-style hook. A NEO 550 with a REV UltraPlanetary is also in the BOM (per CAD).	**AUTONOMOUS** Unconfirmed
VISION A Limelight 3 with a Limelight mount is in the BOM. The drivetrain subassembly also has four corner camera parts (Camera FL, FR, BL, BR); the BOM does not name their model (per CAD).	**PUBLIC CAD / DESIGN** Onshape CAD (competition robot)

Onshape CAD: Onshape CAD (competition robot) · Onshape CAD (competition robot) · Build thread (CD)

Profile	3414 Hackbots Levi USA-MI	Local EPA 69 (#233) 34-26

Fixed-angle coral end effector and a separate algae mechanism on an elevator; swerve

SCORING (CORAL / ALGAE) Stationary coral end effector set at 35 deg from the floor. At the first competition it sat at about 50 deg, chosen to balance L2/L3 and L4 scoring. The robot has separate coral and algae mechanisms.	**INTAKE** Foam coral blockers are on the robot.
ELEVATOR / ARM Elevator that reaches barge height. A cable chain carries wiring up to the coral and algae mechanisms. The elevator crushed the chain when coral fell into the front of the robot, and the chain swings when the elevator moves.	**DRIVETRAIN** Swerve, per the OP's description of the cable chain folding against the swerve module.
ENDGAME Climber with a 2x1 tube arm that pivots on a 2x1 post, a barb assembly, a guide, a hook and a leaf spring. A separate winch assembly has a spur gearbox and left and right motor mounts (per CAD).	**AUTONOMOUS** The release post links Autopilot, a holonomic motion control project the team developed this season.
VISION Arducam OV9281 cameras under camera covers, including covers at the left-front and right-front swerve modules. An Orange Pi 5 in a Hackbots case is the coprocessor. CANrange sensors are also in the BOM (per CAD).	**PUBLIC CAD / DESIGN** CAD release thread (CD)

LESSONS FOR STUDENTS

- Test cable chain routing with game pieces present: the first routing worked in testing but broke at competition.
- The revised routing also had a switched bend at the end and an outer polycarbonate guard. The OP calls the result mostly luck.
- Electrical standards as a document: the team's 2024-25 Electrical Manual covers connectors, CAN and soldering practice.

CD thread: CAD release thread (CD) · CAD release thread (CD) · Onshape CAD · Autopilot motion control thread (CD)

Profile	5419 Berkelium Argonaut USA-CA	Local EPA 69 (#227) 27-17

Coral end effector; elevator with a pivot; climb; auto-align to each reef branch

SCORING (CORAL / ALGAE) Coral end effector. The team states it focused on getting coral onto the reef rather than doing everything.	**INTAKE** Large pivoting U-shaped arm on one side of the frame with a roller of wheels across its outer end (per CAD).
ELEVATOR / ARM Elevator with a pivot; the release names both as subsystems.	**DRIVETRAIN** Swerve with four SDS MK4n modules and Kraken X60 motors (per CAD).
ENDGAME The release names a climb subsystem.	**AUTONOMOUS** The release lists an autonomous routine that scores 3 L4 coral.
VISION The release lists auto-align to each branch of the reef.	**PUBLIC CAD / DESIGN** Onshape CAD (Onshape sign-in needed)

LESSONS FOR STUDENTS

- Cross-check one mechanism across the CAD, code and technical binder.

Onshape CAD: Onshape CAD (Onshape sign-in needed) · CAD and code release thread (CD) · Onshape CAD (Onshape sign-in needed) · Code (GitHub) · Technical binder (Google Drive) · Season recap video

■ Study pick	1156 Under Control Ultralisk Brazil	Local EPA 68 (#243) 32-12

Swerve with an always-on heading PID set by the right-stick angle

SCORING (CORAL / ALGAE) End effector on the front of the elevator. It holds several roller wheels driven by belts and gears. An upper plate with a larger wheel extends up and forward from it (per CAD).	**INTAKE** The team set a design target for the intake: move coral from the Coral Station to the end effector in under 2 s while the robot moves.
ELEVATOR / ARM Elevator at the front of the frame, with nested tube stages and rigging along the uprights. A funnel chute above the rear of the frame slopes down toward the elevator (per CAD).	**DRIVETRAIN** Swerve. The drive always runs an orientation PID. The driver points the right stick at the wanted heading, and atan2 gives the target angle. A bumper button lets the driver spin the robot freely against defense.
ENDGAME Unconfirmed	**AUTONOMOUS** Unconfirmed
VISION Object detection, with driver buttons that cover its false positives and false negatives.	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- The team states the always-on orientation PID prevents heading drift.
- Keep a manual escape for defense. The team says spinning by circling the stick 'felt weird'.
- Plan the build by milestone: archetype decided at the end of Week 1, a master sketch that weekend, and a target of a mechanically complete robot by the first week of February. The team calls these the milestones it usually tries to reach.
- Give each subsystem a measurable target, as the team did for the intake.

Onshape CAD: Onshape CAD · CAD, code and tech binder release (CD) · Onshape CAD · Code (GitHub) · Technical binder (Google Drive) · Heading control code (GitHub) · Build season schedule (Google Sheets)

Profile | **1787 The Flying Circuits** | USA-OH | **Local EPA 68 (#252)** | 20-8-1

Telescoping pivot arm mounted low at the back of the robot; arm pivot on chain with inline turnbuckles

SCORING (CORAL / ALGAE) Combined intake and placer end effector at the tip of the arm, with compliant rollers and a polycarbonate side plate (per CAD).	**INTAKE** The end effector at the arm tip also acts as the intake. The CAD shows no separate floor or station intake (per CAD).
ELEVATOR / ARM Three-tube telescoping arm on a pivot support of VersaFrame tube. Two REV MAX Planetary gearboxes drive the pivot axle through #25 chain. A CANcoder reads the pivot angle (per CAD).	**DRIVETRAIN** Swerve drive with four SDS MK4i modules. Kraken X60 motors drive and steer each module (per CAD).
ENDGAME No endgame mechanism in the CAD (per CAD).	**AUTONOMOUS** Unconfirmed
VISION Unconfirmed	**PUBLIC CAD / DESIGN** Main assembly CAD (Onshape)

Onshape CAD: Main assembly CAD (Onshape) · Main assembly CAD (Onshape) · Code (GitHub) · Team videos (YouTube)

■ Study pick | **8159 Golden Horn** Serpentheim | Turkiye | **Local EPA 66 (#295)** | 32-11

Coral funnel and a separate algae system; two cameras; deep cage climb added after Week 2

SCORING (CORAL / ALGAE) Separate coral and algae scoring systems. The team says it designed the algae system so it did not interfere with coral scoring.	**INTAKE** Coral funnel and an algae intake. The team iterated both after Week 2 to cut cycle times.
ELEVATOR / ARM Elevator with a fixed stage, a middle stage and a carriage. The elevator assembly has #25 chain and 24T hub sprockets, plus pulleys and Dyneema tensioning cams. An elevator gearbox assembly sits at the base. A REV MAXPlanetary is in the BOM (per CAD).	**DRIVETRAIN** Swerve drive with four SDS MK4i modules. The BOM holds both Falcon 500 and Kraken X60 motor models, so the drive and steer motors are not confirmed. CANcoders, a Pigeon 2.0 and a CANivore are in the chassis. Square frame with full-perimeter bumpers (per CAD).
ENDGAME Deep cage climb, added after the Week 2 event.	**AUTONOMOUS** The team says frequent tag localization improves alignment and autos.
VISION Two cameras; the forum question the team answered calls them Limelights. A team mentor gives three reasons: see AprilTags when fully aligned to a branch, see at least one tag at all times, and keep scoring if one camera fails. The second camera mount is missing from the CAD assembly.	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- The strategy document is public, so trace the design choices back to its stated goals.

Onshape CAD: Onshape CAD · CAD, code and strategy release (CD) · Onshape CAD · Code (GitHub) · Game analysis and strategy (Google Doc) · Technical binder (Google Drive) · Robot showcase video

■ Study pick

4795 Eastbots

USA-NC

Local EPA 64 (#314)

41-19

Elevator and chain-driven arm with a motorized wrist (added for DCMP); passive coral funnel; WCP Swerve X Flipped swerve

SCORING (CORAL / ALGAE) Roller end effector with 2 in rollers on a wrist at the end of the arm. Changed before DCMP: a motorized wrist replaced the VFB so the team can set the outtake angle and score algae in the net. The team named a mismatch between the funnel feed angle and the rollers as a cycle-time bottleneck. A V3 end effector with three contact points gripped coral better but struggled to intake algae in manual testing, so the team planned to keep V2 with 1/8 in polycarbonate plates in place of 1/4 in.	**INTAKE** Passive funnel that accepts coral from all directions at the coral station. After the district events the team added a top plate to stop fast-fed coral passing through a gap in the arm. A MAXTube on the bottom plate stops coral bouncing out. The March 2025 post states the robot no longer gets an over-the-bumper algae intake.
ELEVATOR / ARM Elevator with a chain-driven arm. The end effector passes through the elevator; the team calls it a pass-through mechanism. Custom arm and wrist gearboxes reduce backlash and weight high on the robot; one custom gearbox holds both the wrist motor and the intake motor. Changed before DCMP: the VFB chain became a belt, the arm encoder moved to the top MAXSpline so arm position survives a skipped chain, and steel cables with a turnbuckle tension the elevator. Code holds arm and elevator setpoints for L1-L4.	**DRIVETRAIN** Swerve with WCP Swerve X Flipped modules. Changed in March 2025 from tube mount to corner mount for a wider wheelbase and less frame rail weight. Frame rails went from 3/16 in to 1/8 in wall.
ENDGAME Unconfirmed	**AUTONOMOUS** Unconfirmed
VISION Two AprilTag cameras compute the robot's position. Code includes automated commands that align to and score on the reef and barge.	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- Read the arm angle after the chain.
- Brace around a pass-through: crossed cables are not possible with the pass-through mechanism, so the team ran the steel cables on the side opposite the A-frame.
- Cut weight from wall thickness once loads are known, as on the frame rails and elevator uprights.
- Test a redesign before it goes on the robot.

Onshape CAD: Onshape CAD · Onshape CAD · Build thread (CD) · CAD and code release post (CD) · Team GitHub

Profile	418 Purple Haze	Local EPA 62 (#362)
	USA-TX	36-24

Coral scorer/algae remover ('Thagomizer'); side-biased funnel; sideways 1-stage elevator + arm; Everybot-style climber

SCORING (CORAL / ALGAE) 'Thagomizer' outtake. The team packaged coral scoring and algae removal on one shaft to keep it light.	**INTAKE** Coral station funnel, biased to one side to make room for the climber and to line up with the outtake. The first version jammed; the team removed the side wheels and bottom roller and changed the geometry. Ground intake prototypes did not go well in the first week, and the posts through build week 5 describe no ground intake.
ELEVATOR / ARM 'Armavator': a sideways one-stage elevator with an arm. The sideways layout biases the center of gravity for the climb. The team moved from a two-stage elevator to elevator plus arm to package algae removal with coral scoring. The moving assembly carries 4 beam break sensors, 1 NEO with a SPARK MAX and 1 Kraken X60.	**DRIVETRAIN** Swerve X2i modules with Kraken X60 drive and steering motors; the team's first season on CTRE hardware. 29 in x 29 in frame for a larger coral station intake area, with a 1/8 in aluminum belly pan. About 52.5 lb without bumpers and about 60 lb with bumpers. Bumpers use stacked EVA foam floor tiles with a 1678-style mount.
ENDGAME Cage climber based on the Everybot climber, with added guides that funnel the cage in. Tensioned elastic gives the hook one-way movement to catch the cage. Deep climb was in the week 2 archetype; the final climb type is unconfirmed.	**AUTONOMOUS** Unconfirmed
VISION The build thread mentions auto-alignment work.	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- An elevator plus arm can put two jobs on one mechanism, at a wiring cost: check the sensors and motors that ride on the moving assembly.
- Check pulley tooth counts in CAD against the parts: the team ordered wrong belts because modeled pulleys had extra teeth.
- More rollers do not always help a funnel.

Onshape CAD: Onshape CAD · Onshape CAD · Build thread (CD)

Profile	1153 Timberwolves Lagotto	Local EPA 62 (#369)
	USA-MA	46-24

1-stage elevator scoring coral L1-L3 and algae in processor and barge; ground algae intake; deep climb

SCORING (CORAL / ALGAE) Scores coral on L1, L2 and L3, and algae into the processor and the barge.	**INTAKE** Ground algae intake.
ELEVATOR / ARM 1-stage elevator.	**DRIVETRAIN** Swerve with 4 SDS MK4i modules in dropped corner mounts (BOM: Dropped MK4i). Kraken X60 motors are in the BOM. Square frame (per CAD).
ENDGAME Deep cage climb; the team reports it takes under 15 seconds.	**AUTONOMOUS** The team won its first Autonomous Award at the New England DCMP.
VISION Three camera assemblies in the top level: Camera Inward Looking, Camera R and Camera Mount 20 Degrees. The BOM does not name the camera model (per CAD).	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- The code link points to a branch named 'DCMP'. The post does not say which event the branch matches.

Onshape CAD: Onshape CAD · CAD release (CD) · Onshape CAD · Code (GitHub) · Teaser video

■ Study pick

587 The Hedgehogs

USA-NC

Local EPA 61 (#372)

38-20-2

Hopper-fed coral scorer on an elevator with a pass-through wrist; full-width slap-down algae intake for the processor

SCORING (CORAL / ALGAE) Coral end effector on a wrist that grips the coral from the inside with compliant wheels. The team chose the inside grip because it made the design smaller and easier to handle. The team planned polycarbonate plates and planned to add a switch sensor inside to detect a held coral. Status as of the 2025-02-07 build update.	**INTAKE** Coral: a hopper at the coral station feeds the end effector. Tests showed a passive hopper worked as well as one with powered alignment wheels; a higher opening, an angle matched to the chute and a fully supported opening reduced bounce-outs. Algae: a slap-down intake that spans the full robot width, mounted under the hopper, picks algae off the ground for the processor.
ELEVATOR / ARM Elevator with a wrist that passes through it, so the robot loads on one side and scores on the other. The wrist rides up the elevator and reaches 8-10 inches above the carriage at full extension, for L4. It ran on chain at the time; the team was considering belt or direct gearing.	**DRIVETRAIN** 27 in x 27 in base. Printed spacers lower the drive base for a lower center of gravity.
ENDGAME No climber as of 2025-02-07; the strategy did not prioritize climbing. The team was designing a shallow climb (hook on the elevator) or a deep climb with a stationary hook inspired by 4481.	**AUTONOMOUS** Won the Autonomous Award at the FIRST North Carolina State Championship.
VISION Unconfirmed	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- Test a hopper before adding motors.
- Keep closely coupled subsystems in one CAD document.
- Moving the wheels inside the plates removed the need for wheel overlap.

Onshape CAD: Onshape CAD · Open Alliance build thread (CD) · Onshape CAD · Team GitHub

---

Profile

955 Ctrl C

USA-OR

Local EPA 61 (#371)

32-14

Elevator with a carriage pivot; station funnel into a coral indexer; compliant-wheel algae intake; MK4i swerve

SCORING (CORAL / ALGAE) The elevator carriage has a pivot plate near the top of the tower. Separate algae rollers with stacked compliant wheels sit on the side of the elevator opposite the funnel (per CAD).	**INTAKE** Funnel from the coral station: sloped plates above an indexer (Funnel Final Version and Indexer Assembly in the BOM). A coral sits horizontal under the funnel in the CAD. Adafruit beam break sensors are in the BOM. A separate Algae Intake Assembly has two stacks of compliant wheels on side plates, with a motor at the base (per CAD).
ELEVATOR / ARM Elevator Assembly on a tower of vertical rails near the robot center. A carriage with a pivot plate rides at the top of the tower in the render (per CAD).	**DRIVETRAIN** Swerve with four SDS MK4i modules and CANcoders on a square frame. The module configuration names Kraken X60 and NEO motor assemblies, four of each. SPARK MAX controllers and a CANivore are in the BOM (per CAD).
ENDGAME Unconfirmed	**AUTONOMOUS** Unconfirmed
VISION A Limelight 2 Camera is in the BOM, with a Limelight mount and other camera mounts. The document also has a separate Camera Case assembly. One camera bracket sits on the side of the elevator tower in the renders (per CAD).	**PUBLIC CAD / DESIGN** Onshape CAD

Onshape CAD: Onshape CAD · Onshape CAD · Team code (GitHub)

Profile	2813 Gear Heads Maelstrom USA-CA	Local EPA 60 (#415) 26-18

Pivoting roller claw on an elevator; pivoting roller intake arm; winch climber with claws and latch hook; MK4i swerve

SCORING (CORAL / ALGAE) Claw 300 has a claw arm on a claw pivot at the top of the elevator. The claw carries roller wheels and a curved polycarbonate hood (per CAD).	**INTAKE** Intake 600 is a pivoting intake arm on a fixed mount with 2 tensioners. A roller shaft with spaced wheels spans one side of the frame. The BOM does not say which game piece it takes (per CAD).
ELEVATOR / ARM Elevator with a base and one carriage, driven by its own gearbox. 2 turnbuckles brace it. The claw pivots at the top of the carriage (per CAD).	**DRIVETRAIN** Swerve with 4 SDS MK4i modules (configurable). Kraken X60 assemblies and Kraken spacers are in the module parts. Rectangular tube frame with a bellypan, carry handles and module covers (per CAD).
ENDGAME Climb 500 has a mount, a gearbox, claws, 2 gas springs and a latching hook. Cage hooks, down-latch hooks and a 2 in tube winch spool (am-4647) are in the BOM (per CAD).	**AUTONOMOUS** Unconfirmed
VISION A Limelight 3 sits on a test pivot and holder in the drivetrain. Arducam cameras with camera covers, a camera mount and a camera guard are also in the BOM (per CAD).	**PUBLIC CAD / DESIGN** 'Maelstrom' CAD (Onshape)

Onshape CAD: 'Maelstrom' CAD (Onshape) · CAD release (CD) · 'Maelstrom' CAD (Onshape) · Offseason 'LePrawn' CAD (Onshape) · Offseason CAD release thread (CD) · Configurable roller generator (Onshape)

Profile	233 The Pink Team Bubbly Anemone Enemy (BAE) USA-FL	Local EPA 58 (#458) 36-17-1

Coral shooter, floor algae collector, chain-and-Dyneema cascade elevator, deep climber

SCORING (CORAL / ALGAE) Coral shooter, the main mechanism ('Final Coral Shooter' sub-assembly). The alpha robot was too short to score on L4.	**INTAKE** Floor algae collector, the second mechanism ('Final Algae Collector' sub-assembly).
ELEVATOR / ARM Cascade elevator driven by 35 chain with Dyneema rope. Every elevator part was sized for 1000 lb of force, with six #4 screws and Dyneema rated to 3000 lb. Turnbuckles with jam nuts set chain tension and were checked each match. The CAD shows 25 chain, an idea the team considered to save 1 lb; the robot ran 35 chain the entire time.	**DRIVETRAIN** Swerve drive with four SDS MK4n modules. A Pigeon 2.0 and a CANivore are on the drive base (per CAD).
ENDGAME Deep climber ('Final Deep Climber' sub-assembly), on the final robot only. The mentor states it was the least reliable part of the robot because it was kept out of the alpha design.	**AUTONOMOUS** Unconfirmed
VISION An Orange Pi 5 mount and AprilTag camera mounts are in the CAD. The BOM does not name the camera model (per CAD).	**PUBLIC CAD / DESIGN** Final robot CAD (Onshape)

LESSONS FOR STUDENTS

- Pick the lift drive from the requirements: the mentor compares belt (compact, fewer failure points), chain (repeatable under load, heavier) and rope (light, harder to rig, abrades).
- A chain cascade lift can be low-backlash: the team reports position within one encoder tick on a REV quadrature encoder.
- A cascade lift gives a predictable center of gravity and loading case, which the mentor says makes PID tuning easier.
- An alpha robot only tests what it contains.
- Keep turnbuckles tight with thread locker too; the mentor also suggests safety wire.

Onshape CAD: Final robot CAD (Onshape) · CAD release (CD) · Final robot CAD (Onshape) · Alpha robot CAD (Onshape)

Profile	1710 The Ravonics Revolution Dobson USA-KS	Local EPA 57 (#483) 25-13

Elevator robot for coral L1-L4; algae claw for reef algae and barge; ground algae intake added for Champs

SCORING (CORAL / ALGAE) Scores coral on L1-L4 and algae in the barge; the team also practiced processor scoring. The team's match logs list coral per level. In Qual 15 it went 8 for 9 on L4 in teleop; the Qual 50 log lists 9 on L4. An algae claw takes algae off the reef; in one match the robot grabbed algae, threw it aside, then placed coral. The claw cracked during a Central Missouri match; the team fitted a spare, and the event machine shop made another plate.	**INTAKE** Before the Championship the team added a ground algae intake to Dobson.
ELEVATOR / ARM Elevator. At Central Missouri the team tensioned the elevator too tight and it could not extend fully. For that match it ran an L2 auto and scored mostly on L3; the elevator was then re-tensioned and re-tuned. In off-season autos the code raises the elevator before the robot reaches the reef.	**DRIVETRAIN** At Greater Kansas City the team had gyro drift; it used workarounds while the cause was found between matches, with help from the CSAs and CTRE.
ENDGAME The team states it improved its endgame for Greater Kansas City and climbed 3 times there.	**AUTONOMOUS** At Central Missouri the robot ran a 1-coral auto, with an L2 auto as a fallback; it first completed its 2-coral auto in Qual 33. The team states its scouting data showed the most consistent auto at Greater Kansas City. More center autos were added before the Championship. Off-season code reached a 3.5-coral auto, built with a string-driven auto builder from preset field positions and some on-the-fly pathfinding.
VISION A camera on a TPU mount feeds vision updates to odometry for alignment. At Central Missouri the sponsor plate flexed down and bent the mount, and vision put the robot a few inches off. In a later match the camera was misaligned again and the driver scored manually.	**PUBLIC CAD / DESIGN** Fusion 360 CAD

LESSONS FOR STUDENTS

- Keep body panels away from sensor mounts; the bent camera mount shows why.
- Record elevator tension settings, as the over-tensioned elevator shows.
- Bring spares of end effector plates, as the algae claw failure shows.
- Change the robot to fit the alliance, as the team did before the Championship.

Fusion 360 CAD: Fusion 360 CAD · Fusion 360 CAD · Build thread (CD) · Code (GitHub) · Teaser thread (CD) · 2026 build thread with the code post (CD)

■ Study pick

3357 COMETS Tempel

USA-MI

Local EPA 56 (#490)

23-21

Wrist with coaxial roller drive; ground coral; sideways belt-in-tube elevator; deep climb; 24x24 in frame

SCORING (CORAL / ALGAE) Coral rollers on a wrist. An outer shaft drives wrist position through a 20t/80t 32DP gear set. A shaft inside the 2x1 tube drives the rollers through a bevel gearset, then 20DP gears, then a belt and pulley set. The wrist rotates about the roller shaft; the OP compares the layout to a differential.	**INTAKE** Ground coral pickup. One CAD screenshot in the release post is titled 'Drivebase-AlgIntake'.
ELEVATOR / ARM Sideways-mounted elevator with a continuous belt-in-tube drive. UHMW slider pucks and clamping plates are similar to the team's 2022 and 2023 designs. The team replicated the gearbox and idler layout from a published COTS-compatible belt-in-tube elevator design and states it is easy to rig and tension.	**DRIVETRAIN** 24 in x 24 in frame perimeter. Bumpers have chamfered corners, meant to pivot and roll off defenders, and slide latches.
ENDGAME Deep cage climb with a deployable foot and arm. Surgical tubing pulls a lever arm, and a ratchet on the shaft holds the foot out. The team reported it as mostly functional but fussy to retract after the match, and named a torsion spring as a possible fix.	**AUTONOMOUS** Unconfirmed
VISION Unconfirmed	**PUBLIC CAD / DESIGN** In-season CAD (GrabCAD)

GrabCAD: In-season CAD (GrabCAD) · Reveal and CAD release thread (CD) · In-season CAD (GrabCAD) · Reveal video

Profile

3847 Spectrum Gamma Ray

USA-TX

Local EPA 55 (#515)

51-13-1

Elevator plus an arm with a 'bicep' segment; climb ballasted to hang level; 29.75 in square frame perimeter

SCORING (CORAL / ALGAE) A roller claw at the end of the arm scores game pieces. The claw side plates are named 'Coral Claw Plate' in the BOM. The claw has several roller shafts across its width. The BOM also has a 'Twist Gearbox' part (per CAD).	**INTAKE** The CAD shows no separate floor or station intake. The claw on the arm is the only game piece handler in the CAD (per CAD).
ELEVATOR / ARM Elevator on a tall tower at the middle of one side of the frame, with diagonal braces to the frame corners. A carriage with a large belt pulley rides on the tower. An arm with shoulder and elbow joints mounts on the carriage and carries the claw. Encoders are geared to the shoulder and the elbow. WCP ThroughBore encoders, REV MAXPlanetary and MAX 90 Degree gearboxes are in the BOM (per CAD).	**DRIVETRAIN** Swerve with four SDS MK4i modules and CANcoders. Kraken X60 motors and SDS Kraken motor spacers are in the BOM. Square frame with full-perimeter bumpers. A Pigeon 2.0 IMU is in the BOM (per CAD).
ENDGAME The '7. InClimb' subassembly sits along the side of the frame opposite the elevator. It has two pivoting arms with bent upper segments. A strap runs between the tops of the arms. A custom gearbox with a tensioner drives the arm pivot (per CAD).	**AUTONOMOUS** Unconfirmed
VISION In January the team said it had done little testing of a Quest 3S headset.	**PUBLIC CAD / DESIGN** Onshape CAD

Onshape CAD: Onshape CAD · Onshape CAD · Build blog (CD) · Code (GitHub) · Code structure video · Photo gallery

Profile	555 Montclair Robotics USA-NJ	Local EPA 53 (#572) 25-18

Kickoff plan: coral/algae end effector; station-only coral; side-mounted belted elevator (2x Kraken); deep 'hole climb'

SCORING (CORAL / ALGAE) A shoulder pivot at the top of the elevator carries the end effector. #35 chain drives the pivot and a REV Through Bore Encoder reads it. The end effector has pairs of green compliant wheels on both sides of the coral (per CAD).	**INTAKE** A sheet-metal chute with angled sides sits low inside the frame. The top level names an Intake Bottom Plate, two break beam sensors and a 2 in compliant wheel (per CAD).
ELEVATOR / ARM Belt-driven elevator with three MAXTube stages (S1, S2, S3). Stage 3 has a fixed belt clamp. Kraken X60 motors are in the BOM (per CAD).	**DRIVETRAIN** Swerve with four SDS MK4i modules (simplified models). The frame has a bellypan (per CAD).
ENDGAME The top level has cage alignment parts: Outer Cage Alignment, Cage Bottom Plate, Cage Gusset and Cage Alignment Bit (per CAD).	**AUTONOMOUS** Unconfirmed
VISION The top level has two Limelight 4 cameras, one Limelight 3 and a Limelight Mount. One camera model floats above the robot and is not mounted (per CAD).	**PUBLIC CAD / DESIGN** Robot CAD (Onshape)

Onshape CAD: Robot CAD (Onshape) · Robot CAD (Onshape) · Code (GitHub) · Weekly build vlogs (YouTube)

Profile	1714 MORE Robotics Crush USA-WI	Local EPA 53 (#573) 16-12

Mailbox coral end effector on an elevator; station funnel; algae roller; deep cage climber; MK4i swerve

SCORING (CORAL / ALGAE) Mailbox-style coral end effector on the elevator, driven through a REV MAX Planetary. A separate algae assembly with compliant wheels sits near the top of the robot (per CAD).	**INTAKE** Hinged funnel at the rear guides coral from the station into the end effector (per CAD).
ELEVATOR / ARM Elevator of perforated aluminum tube with an outer stage and a moving inner stage. A Thrifty constant force spring kit is on the elevator (per CAD).	**DRIVETRAIN** Swerve drive with four SDS MK4i modules. Falcon 500 motors are in the module assemblies (per CAD).
ENDGAME Deep climb assembly with a ratcheting climber planetary gearbox. The CAD shows an arm that extends past the frame on one side (per CAD).	**AUTONOMOUS** Unconfirmed
VISION Limelight 4 on a Limelight mount in the drivetrain assembly (per CAD).	**PUBLIC CAD / DESIGN** 'Crush' CAD (Onshape)

Onshape CAD: 'Crush' CAD (Onshape) · 'Crush' CAD (Onshape) · 'Squirt' offseason CAD (Onshape)

Profile	2485 Overclocked Nessie USA-CA	Local EPA 53 (#581) 20-16

Coral end effector fed by a bent polycarbonate ramp; elevator; cage climber

SCORING (CORAL / ALGAE) Coral end effector fed by a bent polycarbonate ramp.	**INTAKE** A bent polycarbonate ramp, added after Week 4, funnels coral into the end effector.
ELEVATOR / ARM Elevator. After Week 4 the team ran one motor for elevator extension; this is why the CAD shows interference between one elevator motor and the climber motor.	**DRIVETRAIN** Swerve drive with four SDS MK4n modules. A Pigeon 2.0 and two CANivores are on the drive base (per CAD).
ENDGAME Cage climber. After Week 4 the team changed the climber geometry to guide the cage around the subsystem.	**AUTONOMOUS** Unconfirmed
VISION A rear camera with a camera holder is in the CAD. An Orange Pi 5 case (Redux) is on the drive base. The BOM does not name the camera model (per CAD).	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- The team switched to Onshape to increase younger student involvement, because collaboration is easier.

Onshape CAD: Onshape CAD · Onshape CAD · Robot Magazine, Week 4 (Google Drive)

Profile	3512 Spartatroniks Charybdis USA-CA	Local EPA 53 (#557) 16-9

Roller coral end effector on an elevator with 3 moving stages; low pivoting roller arm; hook climber; MK4i swerve

SCORING (CORAL / ALGAE) A coral end effector sits at the top of the elevator. 2 Kraken X60 motors and HTD 5 mm belts drive its 4 in and 2 in compliant wheels. A pivoting arm with compliant wheels and a curved tube frame sits on top of it. Adafruit beam break sensors are in the BOM (per CAD).	**INTAKE** The CAD shows no coral floor intake. A sheet chute on the end effector is the only coral entry path visible. A pivoting arm with a long roller tube is mounted low on one side of the frame; the BOM does not say if it is an algae intake or a climb part (per CAD).
ELEVATOR / ARM Elevator with a base stage and first, second and third stages, shown extended. The coral end effector rides on the top stage (per CAD).	**DRIVETRAIN** Swerve with 4 SDS MK4i modules (simplified models) on MK4i corner mounting blocks. Square frame with a bellypan (per CAD).
ENDGAME The CAD has a climber subassembly with a hook assembly (per CAD).	**AUTONOMOUS** Unconfirmed
VISION An Orange Pi case (coprocessor) is in the drivetrain assembly. The BOM names no camera (per CAD).	**PUBLIC CAD / DESIGN** 'Charybdis' CAD (Onshape)

Onshape CAD: 'Charybdis' CAD (Onshape) · CAD and binder release (CD) · 'Charybdis' CAD (Onshape) · Technical binder (Google Slides) · Behind the Bumpers video

Profile	2423 The KwarQs QwacKen USA-MA	Local EPA 52 (#619) 22-20

Coral autoscoring with PathPlanner and PhotonVision

SCORING (CORAL / ALGAE) Claw with roller wheels on the elevator carriage ('Claw Assembly') (per CAD).	**INTAKE** Funnel from the coral station ('Funnel V2 Assembly') behind the elevator (per CAD).
ELEVATOR / ARM Elevator with a fixed stage and two moving stages (Elevator Stage 0, 1 and 2). NEO and NEO Vortex motors are in the BOM (per CAD).	**DRIVETRAIN** Swerve with four REV MAXSwerve modules (simplified models) and SPARK MAX controllers (per CAD).
ENDGAME Climber assembly on one side of the frame with a pivoting arm and a cross bar (per CAD).	**AUTONOMOUS** Unconfirmed
VISION PhotonVision for AprilTag detection.	**PUBLIC CAD / DESIGN** Robot CAD (Onshape) (Onshape sign-in needed)

Onshape CAD: Robot CAD (Onshape) (Onshape sign-in needed) · Robot CAD (Onshape) (Onshape sign-in needed) · Code (GitHub) · CAD and code release thread (CD) · Off-season 2020 robot CAD (Onshape) (Onshape sign-in needed) · Off-season robot code (GitHub)

■ Study pick	3669 CarbonKnights Twitchy USA-CA	Local EPA 52 (#593) 9-13-1

Two parallel carbon fiber tube elevators with 3D printed bearingless sliders; built without CNC

SCORING (CORAL / ALGAE) In offseason testing the team added a command that scores at the closest left or right reef pole using one Limelight.	**INTAKE** The CAD shows no separate floor intake. An Algae Grabber subassembly is a curved arm with two pairs of wheels at its end. The Coral Manipulator has a Coral Direction Reverser driven by one Kraken X44 (per CAD).
ELEVATOR / ARM Multistage elevator built from carbon fiber tubes and 3D printed parts, inspired by HighTide's 2023 elevator. The plastic parts slide directly on the tubes with no bearings. The team states linear bearings on a multistage would cost too much weight. Two elevators run in parallel on opposite sides of the robot.	**DRIVETRAIN** The team made drivetrain improvements before its San Diego offseason event.
ENDGAME Unconfirmed	**AUTONOMOUS** Unconfirmed
VISION Single Limelight using MegaTag2 pose data, made to work over the 2025-26 Christmas break. A 2023 attempt with MegaTag1 failed because the pose data was too noisy. The current code is on the LimelightTesting branch.	**PUBLIC CAD / DESIGN** 'Twitchy' robot CAD (Onshape)

LESSONS FOR STUDENTS

- Pose estimation changes between versions, as MegaTag1 and MegaTag2 show.
- Driver input is part of the design: the team built a controller from an Arduino and a RadioMaster radio's gimbals for finer low-speed control.

Onshape CAD: 'Twitchy' robot CAD (Onshape) · CAD and code release (CD) · 'Twitchy' robot CAD (Onshape) · Standalone elevator CAD (Onshape) · Code (GitHub) · Custom controller code (GitHub)

Profile	6343 Steel Ridge USA-WA	Local EPA 52 (#624) 30-27

Roller end effector on a pivoting arm; coral station funnel; two-stage elevator; pivoting climber; MK4i swerve

SCORING (CORAL / ALGAE) Roller end effector with compliant wheels at the end of a truss arm. The arm pivots at the top of the elevator carriage. A TTB cycloidal gearbox is in the Pivot + End Effector subassembly (per CAD).	**INTAKE** Angled polycarbonate funnel at the rear takes coral from the coral station and guides it down toward the elevator. Beam break mounts and a CANrange are in the BOM (per CAD).
ELEVATOR / ARM Two-stage elevator. The pivoting arm mounts on the carriage (per CAD).	**DRIVETRAIN** Swerve drive with 4 SDS MK4i modules (simplified models). Kraken X60 and Falcon 500 motors are in the BOM. A CANivore and a Pigeon 2.0 are on the drivetrain (per CAD).
ENDGAME Climber subassembly: a pivoting frame of two 2x1 tubes on a 1/2 in hex shaft, driven through #25 chain. A winch is also in the BOM (per CAD).	**AUTONOMOUS** Unconfirmed
VISION Two Limelight 4 cameras on mounts on the elevator structure. Two Limelight 3 cameras on 45 deg swerve cover mounts at the drivetrain corners (per CAD).	**PUBLIC CAD / DESIGN** Competition robot CAD (Onshape)

Onshape CAD: Competition robot CAD (Onshape) · Competition robot CAD (Onshape) · Offseason robot CAD (Onshape)

Profile	1086 Blue Cheese Stringray USA-VA	Local EPA 50 (#657) 31-25-1

Coral L1-L4; algae from reef to net and processor; coral station intake; deep cage climb

SCORING (CORAL / ALGAE) Scores coral on all 4 reef levels. Scores algae in the net and in the processor.	**INTAKE** Coral intake from the Coral Station. Removes algae from the reef.
ELEVATOR / ARM Elevator with a base, two stages and a carriage (ELEV-BASE, ELEV-STG1, ELEV-STG2, ELEV-CRGE2). Two 5M 15 mm belts run the stages. The carriage carries the end effector with green side plates on the front face (per CAD).	**DRIVETRAIN** Swerve with 4 WCP Swerve X2S modules. Kraken X60 and Kraken X44 motors are in the BOM (per CAD).
ENDGAME Climbs on the deep cage.	**AUTONOMOUS** Unconfirmed
VISION Two cameras on mounts in the drive base assembly. The BOM does not name the camera model. The CAD shows their fields of view toward the front (per CAD).	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- The release names capabilities, not mechanisms; the superstructure and end effector must be read from the CAD.

Onshape CAD: Onshape CAD · CAD and code release (CD) · Onshape CAD · Code (GitHub)

Profile	2582 PantherBots USA-TX	Local EPA 50 (#678) 34-13

Roller manipulator, ground intake, elevator, pivoting climber with gas spring, Swerve X

SCORING (CORAL / ALGAE) Roller manipulator at the front of the elevator, with a NEO motor, roller wheels and polycarbonate guide plates (per CAD).	**INTAKE** A 'Ground Intake Assy' sub-assembly is in the CAD (per CAD).
ELEVATOR / ARM Elevator with a base, a mid stage and a carriage. Belts are in the elevator assembly (per CAD).	**DRIVETRAIN** Swerve drive with four WCP Swerve X modules in flipped corner mounts (per CAD).
ENDGAME Pivoting climber at the rear. A MAX Planetary on a SplineXL tube turns the pivot, and a gas spring assists it. The climber has a hook and a shield (per CAD).	**AUTONOMOUS** Unconfirmed
VISION Limelight 3 and Limelight 2 cameras are in the CAD. One Limelight 2 mounts in the elevator assembly (per CAD).	**PUBLIC CAD / DESIGN** Main robot CAD (Onshape)

Onshape CAD: Main robot CAD (Onshape) · Main robot CAD (Onshape)

Profile	525 Swartdogs USA-IA	Local EPA 49 (#716) 15-8

Coral end effector with facing wheel stacks; station funnel; multistage chain elevator; deep hang; WCP Swerve X2 swerve

SCORING (CORAL / ALGAE) The End Effector (525-4000) sits below the funnel exit. Two vertical-axis stacks of flexible wheels face each other across the coral path. Two NEO 550 motors on VersaPlanetary gearboxes are in the BOM (per CAD).	**INTAKE** The Coral Funnel (525-3000) is two large angled plates that form a V-shaped chute at the top of the robot. No ground intake is visible (per CAD).
ELEVATOR / ARM Chain-driven elevator (525-2000) with a base, a 1st stage, a 2nd stage and a carriage. It has two #25 chains, two REV MAXPlanetary gearboxes, a potentiometer mount and a drag chain for wires. NEO Vortex motors and SPARK Flex controllers are in the BOM (per CAD).	**DRIVETRAIN** Swerve with four WCP Swerve X2 modules. Kraken X60 motors are in the BOM. The drive base holds four SPARK MAX controllers (per CAD).
ENDGAME A Deep Hang subassembly (525-5000) is in the top level. A plate frame with cutouts sits low on the front face. The drive base has left and right cage guides (per CAD).	**AUTONOMOUS** Unconfirmed
VISION The CAD has a LimeLight Mount and a center camera mount with a two-piece camera case. The BOM names no camera model (per CAD).	**PUBLIC CAD / DESIGN** Main robot CAD (Onshape)

Onshape CAD: Main robot CAD (Onshape) · Main robot CAD (Onshape)

Profile	663 Power Sharks Thresher USA-MA	Local EPA 49 (#689) 20-19-2

Coral-only scorer; single-stage elevator with a pivoting arm; based on the Rust Hounds Ri3D

SCORING (CORAL / ALGAE) Two compliant wheels at the tip of a pivoting arm. The arm pivots on a plate at the top of the elevator (per CAD).	**INTAKE** Angled chute at the rear takes coral from the coral station. It slopes down to a cradle at the base of the elevator (per CAD).
ELEVATOR / ARM Elevator built from T-slotted aluminum extrusion with HTD belts, driven by REV MAXPlanetary gearboxes. A CTRE mag encoder housing is on the elevator. The arm pivots at the top of the moving stage (per CAD).	**DRIVETRAIN** Swerve drive with 4 SDS MK4i modules (simplified models). Kraken X60 motors are in the BOM (per CAD).
ENDGAME Unconfirmed	**AUTONOMOUS** Unconfirmed
VISION One Limelight 4 on a printed bracket at the front of the frame (per CAD).	**PUBLIC CAD / DESIGN** Onshape CAD

Onshape CAD: Onshape CAD · Onshape CAD

Profile	8410 Oyster River Overdrive USA-NH	Local EPA 48 (#726) 19-21-1

Carriage coral holder and algae arm; two-stage elevator; pivot arm and winch cage climber; REV MAXSwerve

SCORING (CORAL / ALGAE) Scoring uses the intake assembly on the elevator carriage. It holds a coral between inner and outer polycarbonate plates. An algae arm with a wheel at its end is part of the same assembly (per CAD).	**INTAKE** Intake assembly on the elevator carriage, with a coral model in it. A NEO 550 with a REV UltraPlanetary is in the assembly. No ground intake is visible (per CAD).
ELEVATOR / ARM Elevator with a base, a first stage, a second stage and a carriage. A gearbox with two NEO motors sits at the base of the elevator. The Limelight mounts at the top of the elevator (per CAD).	**DRIVETRAIN** Swerve drive with four REV MAXSwerve 3in modules. NEO and NEO 550 motors with SPARK MAX controllers are in the BOM. Square frame of 2x1 MAXTube (per CAD).
ENDGAME Cage climber at one end of the frame. A pivoting arm is driven by a REV UltraPlanetary. A winch (Nautilus Winch) uses a NEO with a MAXPlanetary. The CAD shows a field cage model held in the climber (per CAD).	**AUTONOMOUS** Unconfirmed
VISION One Limelight 3 on a mount at the top of the elevator. The CAD draws its view cone (per CAD).	**PUBLIC CAD / DESIGN** Onshape CAD

Onshape CAD: Onshape CAD · Onshape CAD

Profile	4192 Jaguar Robotics Iris USA-TX	Local EPA 47 (#769) 14-36-1

Coral end effector on chain-driven elevator; flex-wheel intake; compliant-wheel grabber; barb-finger arm; SDS MK4 swerve

SCORING (CORAL / ALGAE) A box-shaped housing on top of the elevator holds one coral at an angle. A separate grabber subassembly (GR) has a 4 in compliant wheel, two 2 in compliant wheels and a REV Touch Sensor. In the CAD the grabber floats outside the frame and is not mounted (per CAD).	**INTAKE** The intake subassembly (IN) uses eight 2 in flex wheels on belt-driven shafts and a SWYFT Ranger distance sensor. Angled plates on the top housing form a V-shaped opening (per CAD).
ELEVATOR / ARM Chain-driven elevator on 1x1 MAXTube and 2x1 tube uprights. The elevator subassembly has two #25 chains and two REV MAXPlanetary gearboxes. NEO Vortex motors are in the BOM (per CAD).	**DRIVETRAIN** Swerve with four SDS MK4 modules. The module parts are Falcon 500 configurations (per CAD).
ENDGAME A pivot arm at the frame edge carries barb fingers and barb bodies. It is driven by #25 chain from a NEO Vortex through a MAXPlanetary. Its position matches a cage climber, but the CAD does not name it (per CAD).	**AUTONOMOUS** Unconfirmed
VISION The BOM names one Limelight 3 (per CAD).	**PUBLIC CAD / DESIGN** Onshape CAD

Onshape CAD: Onshape CAD · Onshape CAD · Impact material (Google Drive) · Impact material thread (CD) · Scouting reports thread (CD)

Profile	2470 Team BJORG USA-MN	Local EPA 45 (#841) 17-18

Roller end effector on arm, coral station chute, tilted elevator, hang mechanism, MK4i swerve

SCORING (CORAL / ALGAE) Roller end effector at the outer end of an arm. The CAD shows a coral held between its rollers (per CAD).	**INTAKE** A polycarbonate chute on the side opposite the end effector slopes toward the elevator. A 'Coral Intake' sub-assembly with coral guides and beam break sensors is in the CAD (per CAD).
ELEVATOR / ARM Elevator tilted from vertical. An 'Arm' sub-assembly on the elevator carries the end effector (per CAD).	**DRIVETRAIN** Swerve drive with four SDS MK4i modules (per CAD).
ENDGAME A 'Hang' sub-assembly is in the CAD (per CAD).	**AUTONOMOUS** Unconfirmed
VISION Left and right Limelight mounts are in the CAD. The Limelight model is not named (per CAD).	**PUBLIC CAD / DESIGN** CAD (Onshape)

Onshape CAD: CAD (Onshape) · CAD (Onshape)

Profile	4561 TerrorBytes USA-NC	Local EPA 45 (#858) 34-13-1

Roller end effector on a wrist; pivoting elevator; climber; SDS MK4i swerve

SCORING (CORAL / ALGAE) A wrist at the top of the elevator carries the end effector. The end effector has a roller of black wheels across its front (per CAD).	**INTAKE** The top level has no separate intake subassembly. The roller on the end effector is the only pickup hardware visible in the CAD (per CAD).
ELEVATOR / ARM Elevator on a tilted mast with a carriage. A Pivot subassembly at the base tilts the mast. The pivot has four REV MAXPlanetary gearboxes, 60T and 66T gears, #35 sprockets and a REV Through Bore Encoder (per CAD).	**DRIVETRAIN** Swerve with four SDS MK4i modules. The module BOM has both Kraken X60 and Falcon 500 parts (per CAD).
ENDGAME A Climber V2 subassembly is in the top level. Forked plates point up at the rear of the frame (per CAD).	**AUTONOMOUS** Unconfirmed
VISION The BOM names two Limelight 3 cameras (per CAD).	**PUBLIC CAD / DESIGN** Competition robot CAD (Onshape)

Onshape CAD: Competition robot CAD (Onshape) · Competition robot CAD (Onshape)

Profile	9418 Pastabots USA-TX	Local EPA 43 (#960) 27-21

Differential wrist

SCORING (CORAL / ALGAE) Unconfirmed	**INTAKE** Unconfirmed
ELEVATOR / ARM Unconfirmed	**DRIVETRAIN** Swerve drive with four REV MAXSwerve 3in modules. NEO Vortex motors with SPARK Flex controllers and NEO 550 motors are in the BOM. Frame of 1x1 MAXTube with belly pans (per CAD).
ENDGAME Cage climber: a pivoting climb arm with left and right cage hug parts and a cage settler. A 1.5 in winch spool on a shaft is driven through a REV MAXPlanetary. The CAD shows the robot hanging from a field cage model (per CAD).	**AUTONOMOUS** Unconfirmed
VISION One Arducam on a mount at the frame edge, with its view cone drawn in the CAD. The drivetrain also has a second alignment stream camera plate and an OrangePi 5 case (per CAD).	**PUBLIC CAD / DESIGN** Onshape CAD

Onshape CAD: Onshape CAD · Onshape CAD · Code (GitHub)

Profile	1740 Cyber Colonels USA-CT	Local EPA 42 (#988) 12-17-1

January plan: coral-only, RustHOUNDS Ri3D-style pivoting dunk arm on an elevator; passive ramp intake; WCP Swerve X2

SCORING (CORAL / ALGAE) Plan as of 2025-01-12: passive end effector on a pivoting arm that 'dunks' coral onto the reef, after the RustHOUNDS Ri3D concept. The team wanted to look at letting the coral staging shelf also eject coral onto L1, and considered a separate algae removal arm on the fixed elevator stage.	**INTAKE** Planned as of 2025-01-12: passive ramp intake at the coral station. 'Just chuck it in' human player loading was a kickoff need. Ground pickup was listed as nice to have.
ELEVATOR / ARM Elevator with a pivoting arm. The team tested dunk behavior on a lumber, cart and 3D printed test rig, trimming a PVC arm to compare lengths.	**DRIVETRAIN** WCP Swerve X2 modules with Kraken motors. First built as a 30 in x 30 in chassis with cross rails for the elevator; the team expected it might be cut down by 2 in.
ENDGAME Shallow cage climb was a need and deep climb a want at kickoff. By 2025-03-18 the team was redesigning its climber. A mentor post shows a prototype: 3D printed plates with flexures and stealth wheels that pull the cage bar in under motor torque. With motor braking or a ratchet, the plate stiffness holds the bar like a latch. The part is intended to screw on in place of an Everybot harpoon hook and be winched in. An earlier cutting-board version lifted the robot, then failed at a thin section left by a CNC router setup error.	**AUTONOMOUS** Kickoff targets: an auto that leaves and scores L1, and one that scores L1 and attempts L4. Autonomous scoring and loading alignment was a need.
VISION Orange Pi and cameras bought for PhotonVision testing; on 2025-01-10 students were mounting them on the 2024 robot for reef and loading station alignment work. The software lead chose AdvantageKit to review and replay logs because full-scale testing time was short.	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- Derive the cycle target from match time: about 105 s over 8 coral gives the cycle time.
- Limit scope to protect testing time: a 2024 add-on cost testing time and reliability. The team dropped algae scoring because it expected many algae robots.
- Prototype motion cheaply, on a test rig, before CAD.
- Reinforce printed test fixtures: reef branches with 3/4 in steel conduit inside the PVC upright were stiff enough to use; PVC alone was too flexible.
- Check router toolpaths on flexure parts before cutting.

Onshape CAD: Onshape CAD · Onshape CAD · Build thread (CD) · Code (GitHub) · Team YouTube channel

Profile	7525 Pioneers USA-TN	Local EPA 42 (#1007) 21-15

Angled roller coral mechanism on the carriage; station funnel and passthrough; two-stage elevator; MK4i swerve

SCORING (CORAL / ALGAE) Coral mechanism on the elevator carriage: an angled, belt-driven roller path with 2 in flex wheels and 3 in compliant wheels between polycarbonate plates (per CAD).	**INTAKE** Polycarbonate funnel at the rear takes coral from the coral station. A Passthrough assembly with a Kraken X60 and belts carries coral from the funnel toward the coral mechanism (per CAD).
ELEVATOR / ARM Elevator with a base, Stage 1, Stage 2 and a carriage (per CAD).	**DRIVETRAIN** Swerve drive with 4 SDS MK4i modules configured with Kraken X60 and Falcon 500 motors (per CAD).
ENDGAME No endgame mechanism in the CAD (per CAD).	**AUTONOMOUS** Unconfirmed
VISION Unconfirmed	**PUBLIC CAD / DESIGN** Competition robot CAD (Onshape)

Onshape CAD: Competition robot CAD (Onshape) · Competition robot CAD (Onshape)

■ Study pick

614 Night Hawks Stand Mixer

USA-VA

Local EPA 41 (#1010)

19-24-1

2-in-1 ground coral intake (L1 hold or pass-through) feeding a 'Canal' to the end effector

SCORING (CORAL / ALGAE) The end effector receives coral from the Canal. It detects a held coral when its motor shows a current spike and the LaserCAN no longer sees the coral.	**INTAKE** Ground coral intake with two modes. A 0.85 in OD, 0.65 in ID PVC pipe stops the coral, so the driver can score it on L1 from the intake. A button spins the rollers faster; the PVC flexes and the coral passes through to the Canal. The Canal also takes coral from the Coral Station when the human player drops it in.
ELEVATOR / ARM The Canal carries coral from the intake to the end effector; a LaserCAN on the belly panel trips as the coral passes. A non-team reply describes a single-stage elevator; the team did not confirm it.	**DRIVETRAIN** Swerve drive with 4 Thrifty Swerve modules with printed encoder protectors. NEO Vortex motors with SPARK Flex controllers are in the BOM. A navX-MXP is on the drivebase (per CAD).
ENDGAME Unconfirmed	**AUTONOMOUS** Unconfirmed
VISION Coral sensing uses a LaserCAN and motor current. One Limelight 3G camera is on a Limelight mount on the elevator assembly (per CAD).	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- Combine signals for state detection, as the end effector does.

Onshape CAD: Onshape CAD · CAD and binder release thread (CD) · Onshape CAD · CAD and tech binder (team website)

Profile

114 Eaglestrike Theseus

USA-CA

Local EPA 38 (#1154)

14-12

Roller end effector on a pivot arm; wide front pivoting ground intake; elevator; SDS MK4i swerve

SCORING (CORAL / ALGAE) Roller end effector at the lower tip of a trussed pivot arm. It holds two blue wheels. A belt runs along the arm to the end effector (per CAD).	**INTAKE** Wide ground intake at the front, outside the frame perimeter. It pivots on side plates. It holds several shafts of green compliant wheels (per CAD).
ELEVATOR / ARM Elevator at the rear of the frame. The arm pivots at the top of the elevator carriage. The BOM holds a custom elevator gearbox (ElevatorGearbox) and Kraken X60 motors (per CAD).	**DRIVETRAIN** Swerve with 4 SDS MK4i modules (simplified BOM model). Kraken X60 motors are in the BOM. Square frame with a belly pan (per CAD).
ENDGAME Unconfirmed	**AUTONOMOUS** Unconfirmed
VISION Unconfirmed	**PUBLIC CAD / DESIGN** Onshape CAD

Onshape CAD: Onshape CAD · Onshape CAD · Reveal thread (CD) · Reveal video

Profile	246 Lobstah Bots Beluga USA-MA	Local EPA 38 (#1146) 23-19

Roller end effector, coral station ramp and funnel, two-stage elevator, MAXSwerve

SCORING (CORAL / ALGAE) Roller end effector ('Combined End Effector') with compliant wheels, a coral hood and a NEO motor. It mounts at an angle at the top of the elevator (per CAD).	**INTAKE** A sheet-metal ramp with funnel walls ('5000 Ramp') sits on the side opposite the end effector and slopes toward the elevator. A 'Coral Ground Assembly' is also in the CAD (per CAD).
ELEVATOR / ARM Elevator with a base and two stages ('Stage 1', 'Stage 2'). It has a constant-force spring, a magnetic limit switch and a hard stop (per CAD).	**DRIVETRAIN** Swerve drive with four REV MAXSwerve modules (per CAD).
ENDGAME No endgame mechanism in the CAD (per CAD).	**AUTONOMOUS** Unconfirmed
VISION Left and right camera mounts are on the drive base. The BOM does not name a camera (per CAD).	**PUBLIC CAD / DESIGN** 'Beluga' full robot CAD (Onshape)

Onshape CAD: 'Beluga' full robot CAD (Onshape) · 'Beluga' full robot CAD (Onshape)

Profile	4488 Shockwave Riptide USA-OR	Local EPA 38 (#1145) 17-11

Belted roller end effector on a wrist; three-stage telescoping pivot arm; separate climber; WCP Swerve X swerve

SCORING (CORAL / ALGAE) A wrist at the tip of the arm carries the end effector (M05-KrakenRedesign). It has belt-driven rollers between two pairs of plates (per CAD).	**INTAKE** The CAD shows no separate intake. The end effector on the arm is the only game piece mechanism in the CAD (per CAD).
ELEVATOR / ARM Pivoting arm with three telescoping stages (FirstStage, SecondStage, ThirdStage). The stages are belt driven with HTD5 pulleys and idlers. A gear train in the chassis drives the pivot. A gas spring anchor is in the BOM. Ratchet plates are on the arm (per CAD).	**DRIVETRAIN** Swerve with four WCP Swerve X (Flipped) modules. Kraken X60 motors and CTRE CANcoders are in the BOM (per CAD).
ENDGAME The CAD has a separate Climber Assembly. The chassis has a pawl with a rack and pinion moved by a JF-0826B solenoid, next to the pivot gear train (per CAD).	**AUTONOMOUS** Unconfirmed
VISION Two Orange Pi coprocessor cases sit in the chassis. Camera handle parts mount at the swerve module corners. The BOM names no camera model (per CAD).	**PUBLIC CAD / DESIGN** 'Riptide' CAD (Onshape)

Onshape CAD: 'Riptide' CAD (Onshape) · CAD and code release (CD) · 'Riptide' CAD (Onshape) · Code (GitHub)

Profile	7312 T3 Nessie USA-TX	Local EPA 35 (#1349) 24-18

Belted coral/algae end effector; elbow and wrist pivots; 3-stage GreyT cascade elevator; cage climber; swerve

SCORING (CORAL / ALGAE) End effector of compliance wheels linked by belts that holds both coral and algae. The first version was too large, so the team revisited a design similar to Spectrum's intake and turned it 90 degrees. In testing it took coral from the source in both orientations and held algae when shaken. It mounts on a MAX spline shaft at the wrist pivot.	**INTAKE** Coral comes from the source into the end effector; the early prototype also picked algae from the ground and the reef. A slap-down ground coral intake concept was dropped for complexity, coral jam risk and poor fit with autonomous tasks.
ELEVATOR / ARM Three-stage GreyT Cascading Elevator from WestCoast. An elbow pivot on the carriage turns the arm on a MAX spline shaft through 2:1 sprockets, belt-driven by a REV MAX 90-degree gearbox, with an absolute encoder. A wrist pivot uses a 90-degree gearbox at 2:1.	**DRIVETRAIN** Swerve. The programming team coded a test swerve base and reported it ready to go on the competition robot.
ENDGAME Cage climber inspired by the RustHOUNDS Ri3D climber: a pivot with a metal pole, turned by a 90-degree gearbox at 200:1. The pole enters the cage, rotates the cage and keeps turning until the robot is off the ground. The team's priority list ranked the shallow cage above the deep cage.	**AUTONOMOUS** Unconfirmed
VISION Unconfirmed	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- Write down why a concept is dropped, as the team did for its slap-down intake with a telescoping arm.
- Reorient before redesigning: the turned Spectrum-like design fixed that design's coral scoring and arm mounting problems.
- Rank scoring tasks first: the team's priority list put L2-L4 and algae removal above L1, processor, deep cage and net.

Onshape CAD: Onshape CAD · Onshape CAD · Reveal video 'Nessie'

Profile	2079 4H ALARM Robotics USA-MA	Local EPA 29 (#1774) 9-19-1

Top-down roller end effector on a wrist; rear coral funnel; 2-stage cascade elevator; deep cage climber; 28x28 swerve

SCORING (CORAL / ALGAE) Carriage with a 'goose neck' plate and a wrist, the design the team was working on in Week 3 after a swing-through arm found no workable fixed angle in CAD. Changed after the V1 build (post of 2025-02-22): the V1 end effector had trouble intaking coral, removed algae slowly and took longer to score L4. The team remodeled the end effector as V2 with a top-down roller arrangement. The team states V2 removes algae more easily and gives better grip and coral centering in most scenarios.	**INTAKE** Coral from the human player station; in Week 3 the team leaned toward the view that ground coral pickup might not be worth the added weight. V2 (2025-02-22) added a passive funnel at the back of the robot for human player coral drops and for intaking under defense. Algae ground intake on a pivot, as of 2025-02-03: two side plates (0.22 in polycarbonate or 0.125 in aluminum) with a roller, and a hex standoff at the bottom in place of a second roller.
ELEVATOR / ARM 2-stage cascade elevator, chosen over a telescopic arm because telescopic arms had not worked for the team in past years.	**DRIVETRAIN** 28 x 28 in swerve base, sized for stability when extended to score L4. The team added 1x1 standoffs to lower the base plate from about 1.2 in to about 0.2 in off the floor, after 4481 reported robots lifting on algae. This also lowered the COG.
ENDGAME Deep cage climber with a low hinge. The arm pivots at the bottom, is pulled down by a string and lifted by a spring. The cage clamp moved from one pivot to two pivots to reduce the force needed to slide onto the cage. The 1x1 tube arm weighs 1.28 lbs.	**AUTONOMOUS** Unconfirmed
VISION Planned in Week 3: PhotonVision on 4 Arducams, one per side, for full-field localization, with Limelights for game-piece tracking.	**PUBLIC CAD / DESIGN** CAD (Onshape)

LESSONS FOR STUDENTS

- Sort needs from wants first: swerve, all four reef levels and a climb were needs; ground coral, deep cage and a wrist were wants.
- Model the whole robot against the reef and the station in CAD before committing to an arm.
- Track weight per part: the 1x1 tube climber arm is about 5 lbs less than the 2x1 version.
- Test bumper materials on a repeatable rig: a cage hit a 30 lb box; EVA foam and polyethylene held up better, and a combination of both held up better still.
- Build V1 early and judge it on the field tasks.

Onshape CAD: CAD (Onshape) · CAD (Onshape) · Build thread (CD) · Code (GitHub) · Climber prototype run (video) · Bumper material test (video)

Profile	7691 TSA All Stars USA-TX	Local EPA 25 (#2124) 18-24-1

Arm end effector on an elevator; pivoting ground coral intake; side algae grabber; deep climber (later removed); swerve

SCORING (CORAL / ALGAE) An arm on the elevator sets the coral angle for each reef level. The end effector and its backup broke in the third match at Houston. A rebuilt end effector used a stronger 3D printing filament and also failed.	**INTAKE** Over-the-bumper ground coral intake on a pivot, called the 'dustpan', which hands coral to the elevator. A separate attachment on the side picks up algae and carries it to the processor. The team states the intake and handoff did not work as designed. At Space City the intake broke and the team played two matches as defense; coral and algae falling into the robot cost the team multiple matches there.
ELEVATOR / ARM Elevator, the team's first. The team states the elevator was not braced enough. At Houston they planned 1x1 MAXTube bracing with 3D printed gussets as a quick fix.	**DRIVETRAIN** Swerve: the week 4 post describes base code with vision and swerve subsystems. A swerve motor broke at the offseason TRI event.
ENDGAME A deep cage climb mechanism at the rear, with a design guided by 118's Everybot. Before the District Championship the team worked on the code and the climb, but states it did not work. The team later removed the climber and the baseplate because the robot was overweight.	**AUTONOMOUS** Unconfirmed
VISION The coding team worked on AprilTags for the first time; earlier seasons relied mostly on driver sight and a camera when it worked.	**PUBLIC CAD / DESIGN** Onshape CAD

LESSONS FOR STUDENTS

- Design the connections, not only the parts: the team states its subsystem CAD was sound but the integration, wiring and handoff were not.
- Brace a first elevator in CAD, not as a quick fix at the event.
- Back up CAD: the team reports its Onshape file was destroyed during the Houston event, which forced a re-CAD in the pit.
- Close openings where game pieces can fall in, and secure the battery: unplugged batteries cost matches at the District Championship.
- The season review led to new rules: the CAD subteam now requires a year of robotics experience to join, and the team plans to build only from CAD checked by an audit system.

Onshape CAD: Onshape CAD · Onshape CAD · Onshape document linked in the build thread · Build thread (CD) · 2025-2026 build thread with the season review (CD)

Profile	3481 Bronc Botz Justice USA-TX	Local EPA 23 (#2295) 13-26

Coral outtake on a chain-driven elevator; over-the-bumper coral ground intake; SDS MK4 swerve

SCORING (CORAL / ALGAE) A coral outtake assembly rides on the elevator carriage (per CAD).	**INTAKE** Over-the-bumper ground intake (25W4000 OTB) at the front. A NEO Vortex with a SPARK Flex drives rollers of 4 in and 2 in compliant wheels through HTD 5 mm pulleys. Angled plates guide coral into it (per CAD).
ELEVATOR / ARM Elevator driven by #25 chain from a MAXPlanetary 2-stage gearbox. Diagonal braces tie the top of the elevator to the frame (per CAD).	**DRIVETRAIN** Swerve with 4 SDS MK4 modules, motors on top. The module parts carry Falcon-spline pinions. Square frame with a bellypan (per CAD).
ENDGAME Unconfirmed	**AUTONOMOUS** Unconfirmed
VISION A Limelight 3G is in the BOM (per CAD).	**PUBLIC CAD / DESIGN** Onshape CAD

Onshape CAD: Onshape CAD · Onshape CAD

Profile	847 PHRED USA-OR	Local EPA 22 (#2423) 10-17

Elevator with an elevator-mounted intake; pneumatics; build thread reports swerve code work

SCORING (CORAL / ALGAE) Coral is held between two side plates on the elevator carriage, with a motor-driven wheel roller above it. No separate algae mechanism is visible (per CAD).	**INTAKE** The intake mounts on the elevator carriage and is the same mechanism that holds the coral. Two horizontal wheels, each with a motor above it, sit low at the front of the frame (per CAD).
ELEVATOR / ARM Elevator with two fixed uprights joined by a cross tube at the top, and a carriage that carries the intake. VersaPlanetary gearboxes are in the BOM (per CAD).	**DRIVETRAIN** Swerve drive with four SDS MK4i modules. The drivetrain assembly holds eight NEO motors, with SPARK MAX controllers and CANcoders. Square frame (per CAD).
ENDGAME A climber assembly (New Climber Assembly) is in the CAD at the end of the frame opposite the intake, inside a sheet-panel enclosure. Its mechanism is not visible in the rendered views. A pneumatic cylinder and a Viair 90C compressor are in the BOM (per CAD).	**AUTONOMOUS** Unconfirmed
VISION Unconfirmed	**PUBLIC CAD / DESIGN** Top Level Robot CAD (Onshape)

Onshape CAD: Top Level Robot CAD (Onshape) · Top Level Robot CAD (Onshape) · Team GitHub

Profile	1595 The Dragons King Ghidorah USA-WA	Local EPA 22 (#2469) 12-22

Boat-hook lift chosen for a low CG; small 21x21x24 in frame

SCORING (CORAL / ALGAE) Coral outtake on a carbon fiber tube carriage at the top of the lift. A REV UltraPlanetary rotates the outtake through a belt. The carriage also holds a subassembly named 'Barge' (per CAD).	**INTAKE** Algae assembly at the front: a long roller of compliant wheels on a four-bar linkage, driven through a custom gear and belt gearbox. A 'Coral Intake v2' part and a separate intake rotation gearbox are also in the BOM (per CAD).
ELEVATOR / ARM Boat-hook pole at the center of the robot lifts the carriage. Carbon fiber tubes form an A-frame on the carriage (per CAD).	**DRIVETRAIN** Swerve drive with four SDS MK4 modules with Falcon 500 motors (per CAD).
ENDGAME The CAD has a climber subassembly with a tube and a barb fitting (per CAD).	**AUTONOMOUS** Unconfirmed
VISION Limelight camera on a mount with a protector plate. The BOM does not name the Limelight model (per CAD).	**PUBLIC CAD / DESIGN** Onshape CAD

Onshape CAD: Onshape CAD · Onshape CAD · CAD release thread (CD) · Design overview (Onshape) · Behind the Bumpers video

Profile	2577 Pingry Robotics USA-NJ	Local EPA 20 (#2631) 14-13

Roller end effector on pivot arm, coral funnel ramp, elevator, WCP Swerve X

SCORING (CORAL / ALGAE) Roller end effector ('Shnoot') driven by a Kraken X60 through GT2 belts. It sits on a pivot arm at the top of the elevator (per CAD).	**INTAKE** A funnel ramp ('V3 Ramp') on the rear of the elevator frame guides coral from the station. A CANrange sensor is in the CAD (per CAD).
ELEVATOR / ARM Elevator with a base, a first stage and a carriage, built on WCP CC2025 mast parts. The elevator assembly uses #35 chain sprockets (per CAD).	**DRIVETRAIN** Swerve drive with four WCP Swerve X modules (per CAD).
ENDGAME No endgame mechanism in the CAD (per CAD).	**AUTONOMOUS** Unconfirmed
VISION Two Limelight 3G cameras are in the BOM. Their mount positions are not confirmed (per CAD).	**PUBLIC CAD / DESIGN** Competition robot CAD (Onshape)

Onshape CAD: Competition robot CAD (Onshape) · Competition robot CAD (Onshape)

■ Study pick

1806 S.W.A.T. Atom

USA-MO

Local EPA 10 (#3554)

9-16

Rebuilt mid-season toward a 2056-style coral/algae claw on an arm; custom welded elevator; swerve

SCORING (CORAL / ALGAE) Week 2 design: a 3-DOF coral claw with an intake motor, an open/close motor, and rotation from inside to outside the robot. The first prototype used 8 in compliant wheels with no grip on coral. 3D printed gears broke in version 4; in Week 5 the team redesigned both claws without printed gears. Changed after Central Missouri: the plan became one claw for algae and coral on an arm, inspired by 2056. The team assembled a '2056 style claw' by 2025-03-13, but the rebuild was not finished for Greater Kansas City. The retrospective says the arm pivot was too floppy and had too much backlash for fast or precise motion.	**INTAKE** The Week 2 concept had a ground coral intake on the right side and a ground algae intake at the front, with coral station loading kept. The concept changed in Week 3; the team lists slightly narrower ground intakes as a con. Changed after Central Missouri: a floor coral intake inspired by 1690 and 118, plus a coral righting mechanism tested on 2025-03-12. At Greater Kansas City the intake chain bound; the team says the double sprockets did not seem to have enough spacing. The team removed the intake and used a feeder station funnel.
ELEVATOR / ARM The Week 2 concept put the elevator at the back of the robot. Elevator based on the team's 2018/2019 design: 2x1x1/8 in C-channel stitch welded to 1.5 x 1/8 in flat bar, with delrin/acetal rollers on shoulder bolts. In Week 5 the team moved to side rigging with 4 spools and cascade rigging. The elevator calculation linked in the thread uses 2 Kraken X60 at a 5.333 reduction. The rebuild plan kept this elevator with fewer stages, because the arm reaches higher. At Greater Kansas City, 3/16 Dyneema could not lift the elevator; team 1802 lent 1/16 steel aircraft cable, and the V-groove bearings held it. Cable tension from the rigging angles stopped the elevator from going down much below its starting height.	**DRIVETRAIN** 28 x 28 in frame. Swerve with YAGSL configuration and 'snap angles' heading presets at 60 deg steps for the reef. The practice bot tested 3D printed 95A TPU wheels. On the competition robot the 3D printed wheels were slicks by the 2nd match of defense at Central Missouri.
ENDGAME The Week 2 plan was a cage-shaped hole in the belly pan and a claw on one elevator stage. By Week 3 the team had a prototype climber claw that uses the elevator to lift. The climber hook was in CAD by Week 5.	**AUTONOMOUS** In Week 5 the team tested paths in AdvantageKit simulation for a 4-coral auto, all from the ground, ending with an algae run to the processor. The team calls these paths 'probably wishful thinking'. The retrospective says controls students had almost no time with the robot.
VISION Vision PC. Its Ethernet port burned out 2 days before Greater Kansas City; the team advises turning off PoE on the radio when it is not used.	**PUBLIC CAD / DESIGN** 'Atom' CAD (Onshape)

LESSONS FOR STUDENTS

- Check rotation direction before printing parts: the first claw prototype had its wheels spinning in opposite directions.
- Test printed parts under load early: printed claw gears broke under drill testing.
- Simulation needs the current configuration: the robot did not move in YAGSL simulation until the team entered this year's gear ratios.
- Size the elevator cable to the load.
- Read the pros and cons the thread lists for the Week 3 concept change. The retrospective says to count DOFs to judge complexity.

Onshape CAD: 'Atom' CAD (Onshape) · 'Atom' CAD (Onshape) · Code (GitHub) · Build thread (CD) · Week 5 update video · Intake testing video (Instagram)

Sources: the Spectrum 3847 CAD Collection, team CAD, binder and code releases, Chief Delphi release and reveal threads, and match data from The Blue Alliance. EPA is Local EPA (approx), computed independently. It is not official Statbotics data. "Unconfirmed" means the public material does not state the detail. Text marked (per CAD) was read from the team's Onshape CAD (parts list and rendered views) where no write-up states the detail.