


The **luahyperbolic** LaTeX package

Damien Mégy

Version: 2026/8/31



LaTeX code for above tiling: `\hyperbolicTiling{2}{4}{5}[scale=5,color=teal,depth=24]`

Luahyperbolic is still in an early development phase. Changes and bug fixes are happening frequently, check the [changelog](#). This is version 2026/8/31. At the time this PDF was compiled, the last version on CTAN was version 2026-03-16. The latest version of this package is available at: github.com/dmegy/luahyperbolic.

Contents


1	Introduction	2	3.2	Endpoints, midpoint, interpolate	11
1.1	What you can do with this package	2	3.3	Intersections	12
1.2	What this package cannot do for you	2	3.4	Reflections and projections	14
1.3	Efficiency	2	3.5	Exponential map	15
1.4	How to load the package	3	3.6	Automorphisms (direct isometries)	15
1.5	Dependencies	3	3.7	Orbits under automorphisms	17
1.6	Exporting the pictures	3	3.8	Triangle geometry (CAUTION)	18
1.7	(Advanced users) Build from source	3	4	Tilings	21
2	Drawing and labeling elements	4	4.1	Draw Tilings	21
2.1	Draw and label points	4	4.2	Fill tilings	22
2.2	Draw/label/mark segments/lines/rays	4	4.3	Tilings without any Lua code	23
2.3	Circles, semicircles, arcs	8	5	Overview of the lua libraries	24
2.4	Horocycles and hypercycles	10	5.1	complex.lua	24
2.5	Printing custom strings to TikZ	10	5.2	luahyperbolic	24
2.6	Modifying default styles	11	6	Changelog	25
3	Defining points	11	7	Known bugs	25
3.1	Random points with uniform density	11	8	Index	25

1 Introduction

1.1 What you can do with this package


1. Draw hyperbolic geometry pictures, high precision (PDF output).
2. Use an easy syntax. At least, easier than with $\text{\LaTeX}$ macros and bloody PGF.
3. Export generated pictures to external tikz files if you want.
4. Read the source code and learn hyperbolic geometry.
5. Compile **without** installing python packages or lua packages etc.
6. Compile **without** "shell-escape" mode.
7. Compile everything in a single pass. No (Leeloo Dallas) multipass. Want to illustrate Euclid's fifth postulate? Do it right there in your TeX file without having to include external files:

```
\begin{luacode*}
hyper.tikzBegin("scale=2")
local P = complex(0.5,-0.2)
local A = complex.exp_i(math.pi/20)
for k=1,10 do
    hyper.drawLine(P, A^k, "teal")
end
hyper.labelPoint(P, "$P$", "left=.2cm")
local style = "very thick, dashed, red"
hyper.drawLine(complex.J,-complex.I,style)
hyper.tikzEnd()
\end{luacode*}
```



8. Draw Tilings in one line, without any Lua code:

```
\hyperbolicTiling{3}{4}{7}[scale=1.4]
\hyperbolicTiling{4}{4}{inf}[scale=1.4,
    ↪ color=violet, backgroundcolor=pink
    ↪ !20, depth=6]
```



1.2 What this package cannot do for you

1. Really intensive computations, millions of geodesics etc. Source code is not optimized to keep maximum readability. All computations involve automorphisms. See other remarks below.
2. Coffee.

1.3 Efficiency

For heavy computations, please use a ~~Python~~ C library. Nevertheless, this library is still reasonably efficient and usable:

- The first tiling illustration of this documentation (hyperbolic 2-4-5 tiling with 2361 geodesics) just compiled in 2.6 seconds on a 2020 Intel MacBook Air laptop. (Other users report 1.48 second on a MacBook Air M1, and .99 second on a Mac Studio M4 Max.)
- This entire documentation including all pictures compiles in approx. 20 seconds on the same 2020 Intel MacBook Air (17 seconds on a Mac Studio M4 Max), the majority of the time spent on the tilings. The package is suitable for producing lecture notes in hyperbolic geometry, which was the reason for all of this. For an entire book with dozens of pictures, you may need to externalize some of the pictures.

- Tests show that the bottleneck is TikZ, not Lua. In a future version, some future maintainer may add other frontends to the library, including drawing directly to the PDF with PDF primitives which are several orders of magnitude faster than TikZ.

1.4 How to load the package

Local install

Simply put the `luahyperbolic.sty` file in your working directory and add the following line to your `.tex` preamble:

```
\usepackage{luahyperbolic}
```

The single file `luahyperbolic.sty` contains everything needed, including the necessary library for complex numbers. It can be sent to colleagues by email, etc.

It will declare two Lua globals: `complex` and `hyper`, and define a `hyperbolicTiling` command for convenience.

If the `.sty` file is not in the same directory as your `.tex` file, you can write `\usepackage{../luahyperbolic}`.

1.5 Dependencies

The package `luahyperbolic` requires the following packages:

- `tikz`
- `luacode`

It loads them if they are not loaded already.

The LaTeX files must be compiled with the **lualatex** engine.

1.6 Exporting the pictures

1.6.1 When finishing a picture

Simply add a filename to the closing `hyper.tikzEnd()` instruction, as below:

```
hyper.tikzEnd("myfile.tikz")
```

This will save the current picture (including `\begin{tikzpicture}[options]` and `\end{tikzpicture}`).

1.6.2 In the middle of the tikzpicture

It is also possible to export the current picture at any point with `hyper.tikzExport(optional-filename)`. If no filename is provided, the package will name it `hyper_picture_N` with `N` the picture counter. `Luahyperbolic` keeps count of how many pictures have been produced in the document. This allows exporting images in loops, or drawing several steps of the same picture.

1.7 (Advanced users) Build from source

The `luahyperbolic.sty` is pre-generated from a template `.sty` file and four `.lua` modules :

1. `complex.lua`
2. `luahyperbolic-core.lua`
3. `luahyperbolic-tikz.lua`
4. `luahyperbolic-tilings.lua`

These files are in the `lua/` subdirectory of the package repo.


To build the `luahyperbolic.sty` from `.lua` source files, execute `lua build.lua` in the `lua` subdirectory of the package. This will build and update (replace) the existing `.sty` file.

2 Drawing and labeling elements

2.1 Draw and label points

2.1.1 Draw and label points


```
\begin{luacode*}
local A = complex(0.3,0.2)
local B = 2*A
local I, J = complex.I, complex.J
local C, D, E = I*A, I*B, J*B
hyper.tikzBegin()
hyper.drawPoint(0,"white", draw=red)
hyper.drawPoints(A, B, C, "teal")
hyper.drawPoints(D, E)
hyper.labelPoint(A,"$A$", "below right, blue")
hyper.labelPoints(B,"$B$", C, "$C$")
hyper.labelPoint(D,"$D$", "left=.4cm, red")
hyper.tikzEnd()
\end{luacode*}
```



2.2 Draw/label/mark segments/lines/rays


2.2.1 Segments lines and rays (through two points)

```
\begin{luacode*}
local A = -complex.I/2
local B = (1+complex.I)/2
local C = complex(-0.7,0.4)
local D = complex(-0.7,-0.3)
hyper.tikzBegin()
hyper.drawLine(A, B, "red")
hyper.drawSegment(B,C,"dashed, ForestGreen")
hyper.drawRay(C,D,"double,double distance=1pt"
    ↪ )
hyper.drawLine(D,-D, "green!50!black")
hyper.drawLine(A, 1, "gray, line width=2pt")
hyper.drawLine(1, complex.I, "teal")
hyper.drawPoints(A, B, C, D)
hyper.labelPoints(A, "$A$", B, "$B$", C, "$C$"
    ↪ , D, "$D$")
hyper.tikzEnd()
\end{luacode*}
```



2.2.2 Triangles and polygons

```
\begin{luacode*}
local A = complex(.9,.2)
local B = complex(.5,.7)
local C = complex(0,.9)
hyper.tikzBegin()
hyper.drawTriangle(A, B, C)
hyper.drawTriangle(-A, -B, -C, "red")
hyper.drawPolygon(-.9, -.7, complex(-.7,.4),
    ↪ complex(-.9,.3), "blue")
local points={}
for k=1,5 do
    table.insert(points, complex.polar(.4,k*2*
        ↪ math.pi/5))
end
hyper.drawPolygonFromTable(points,"teal")
hyper.tikzEnd()
\end{luacode*}
```



2.2.3 Triangles with prescribed angles


```
\begin{luacode*}
local function myTriangle(a, b, c, color)
    hyper.tikzBegin("scale=1.4")
    local A, B, C = hyper.triangleWithAngles(a,
        ↪ b, c)
    hyper.drawTriangle(A, B, C, color)
    hyper.tikzEnd()
end

local PI = math.pi

myTriangle(PI/2, PI/6, PI/10, "red")
myTriangle(2*PI/5, PI/4, PI/5, "red!50!blue")
tex.print("\\par")


myTriangle(2*PI/3, PI/8, PI/20, "blue")
myTriangle(PI/3, PI/4, 0, "blue!50!green")
tex.print("\\par")

myTriangle(PI/3, 0, 0, "ForestGreen")
myTriangle(0, 0, 0, "green!50!red")
\end{luacode*}
```




2.2.4 Label and mark segments

```
\begin{luacode*}
local A = -complex.I/2
local B = (1+complex.I)/2
local C = complex(-0.7,0.4)
local D = complex(-0.7,-0.3)
hyper.tikzBegin()
hyper.drawPolygon(A, B, C, D, "teal")
hyper.markSegment(A,B,"|")
local marking = "\\textcolor{red}{||}"
hyper.markSegment(B,C,marking)
hyper.labelSegment(C,D,"$3$", "fill=white,
    ↪ draw=blue")
hyper.labelSegment(D, A,"$\\alpha$", "below")
hyper.labelPoint(A, "$A$", "below")
hyper.tikzEnd()
\end{luacode*}
```




2.2.5 Regular polygons

```
\begin{luacode*}
local O1 = complex(.5,.2)
local A1 = complex(.7,.3)
local O2 = complex(-0.1,0)
local A2 = complex(-.4,.3)
local O3 = complex(0,.7)
local A3 = complex(0,.9)
hyper.tikzBegin()
hyper.drawRegularPolygon(O1, A1, 3)
hyper.drawRegularPolygon(O2, A2, 5, "blue")
hyper.drawRegularPolygon(O3, A3, 8, "green!50!
    ↪ black")
hyper.drawPoints(O1,O2,O3)
hyper.tikzEnd()
\end{luacode*}
```




2.2.6 Polygonal lines

```
\begin{luacode*}
hyper.tikzBegin()
-- drawPolyline :
hyper.drawPolyline(0, 1, complex.I, -1, "red")
-- drawPolylineFromTable :
local points={}
local N=30
for k=1, N do
    table.insert(points, complex.polar(k/N, k*
        ↪ math.pi/3))
end
hyper.drawPolylineFromTable(points,"teal")
hyper.tikzEnd()
\end{luacode*}
```




2.2.7 Lines and rays (point and tangent vector)

```
\begin{luacode*}
local A = complex(-0.2,-0.5)
local B = complex(-0.5,0.5)
local C = complex(0,0.2)
local v = complex(1,0)
hyper.tikzBegin()
myVec = ">=latex, red"
myLine = "dashed, gray"
hyper.drawLineFromVector(A, v, myLine)
hyper.drawRayFromVector(B, v, myLine)
hyper.drawRayFromVector(C, v, myLine)
hyper.drawVector(A,v,myVec)
hyper.drawVector(B,v,myVec)
hyper.drawVector(C,v,myVec)
hyper.drawPoints(A, B, C)
hyper.tikzEnd()
\end{luacode*}
```




2.2.8 Perpendicular bisector

```
\begin{luacode*}
local A = complex(-0.2,-0.5)
local B = complex(-0.7,0.3)
hyper.tikzBegin()
hyper.drawPerpendicularBisector(A,B,"red")
hyper.drawSegment(A, B, "teal")
hyper.drawPoints(A,B)
hyper.labelPoints(A,"$A$", B, "$B$", "above
    ↪ right")
hyper.tikzEnd()
\end{luacode*}
```



2.2.9 Angle bisector

```
\begin{luacode*}
local A = complex(-0.2,-0.6)
local O = complex(0.3,0.3)
local B = complex(-0.7,0.3)
hyper.tikzBegin()
hyper.drawAngleBisector(A,O,B,"red")
hyper.drawPolyline(A,O,B, "teal")
hyper.drawPoints(A,O,B)
hyper.labelPoints(A, "$A$", O, "$O$", B, "$B$"
    ↪ )
hyper.tikzEnd()
\end{luacode*}
```




2.3 Circles, semicircles, arcs

2.3.1 Center and radius: drawCircle and fillCircle


```
\begin{luacode*}
local A = complex(0,0)
local B = complex(-0.5,-0.4)
local C = complex(0.8,0.1)
local D = .8*complex.I
local E = complex.polar(.6,math.rad(130))

hyper.tikzBegin()
hyper.drawCircle(A,1) -- default : black
hyper.drawCircle(B,1,"dashed, blue")
hyper.drawCircle(C,1,"thick, red, fill=red!20"
  ↪ )
hyper.fillCircle(D, 1) -- default : gray
hyper.fillCircle(E, 1,"ForestGreen!20")
hyper.tikzEnd()
\end{luacode*}
```




2.3.2 Circle through point

```
\begin{luacode*}
local O = complex(0.3,0.2)
local P = complex(0.7,-0.4)
local Q = complex(-0.1,0.4)
hyper.tikzBegin()
hyper.drawCircleThrough(O, P, "dotted, red")
-- or draw by hand :
hyper.drawCircle(O, hyper.distance(O,Q), "blue"
  ↪ )
hyper.drawPoints(O, P, Q)
hyper.labelPoints(O, "$O$", P, "$P$", Q, "$Q$"
  ↪ )
hyper.tikzEnd()
\end{luacode*}
```




2.3.3 Semicircles

```
\begin{luacode*}
local O = complex(0,0)
local A = complex(-0.3,0)
local P = complex(0.5,0.2)
local B = complex(0.7,-0.4)
hyper.tikzBegin()
hyper.drawSemicircle(O, A, "blue")
hyper.drawSemicircle(P, B, "red")
hyper.labelPoints(O, "$O$", A, "$A$", P, "$P$"
  ↪ , B, "$B$")
hyper.drawLine(P,B, "gray, dashed")
hyper.drawPoints(O, A, P, B)
hyper.tikzEnd()
\end{luacode*}
```




2.3.4 Arc (center and endpoints)

```
\begin{luacode*}
local O = complex(0,0)
local A = complex(0.5,0)
local B = complex.polar(0.5,math.pi/3)
hyper.tikzBegin()
hyper.drawArc(O, A, B, "very thick, red")
hyper.drawArc(O, B, A, "dashed")
hyper.drawPoints(O,A,B)
hyper.tikzEnd()
\end{luacode*}
```




2.3.5 Angles

```
\begin{luacode*}
local A = complex(-.5,-.3)
local B = complex(0.5,0)
local C = complex(0.2,.7)
hyper.tikzBegin()
hyper.drawLines(A, B, B, C, C, A, "teal")
hyper.drawAngle(B, A, C, "red, very thick")
hyper.drawAngle(A, C, B, "thick, double,
    ↪ double distance=2pt, blue")
hyper.drawAngle(A, B, C, "very thick, ->,
    ↪ green!50!black")
hyper.drawPoints(A, B, C)
hyper.labelPoints(A, "$A$", C, "$C$")
hyper.labelPoint(N, "$B$", "above right")
-- poor man's labelAngle:
hyper.labelPoint(A, "$\\alpha$", "above=.6cm,
    ↪ right=.7cm")
hyper.tikzEnd()
\end{luacode*}
```



2.3.6 Tangent (line) at point


```
\begin{luacode*}
local O = complex(0.3,0.2)
local P = complex(-0.1,0)
local phi = hyper.rotation(O,math.pi/4)
local Q = phi(P)
local R = phi(Q)
hyper.tikzBegin()
hyper.drawCircleThrough(O, P, "teal")
hyper.drawTangentAt(O,P,"red")
hyper.drawTangentAt(O,Q,"red")
hyper.drawTangentAt(O,R,"red")
hyper.drawPoints(O, P, Q, R)
hyper.tikzEnd()
\end{luacode*}
```



2.4 Horocycles and hypercycles


2.4.1 Horocycles

```
\begin{luacode*}
local theta=math.pi/3
local idealPoint = complex.exp_i(theta)
local N = 10
hyper.tikzBegin()
for k=1,N-1 do
    local point = idealPoint * (2*k/N-1)
    hyper.drawHorocycle(idealPoint,point,"red")
    -- and an orthogonal geodesic :
    local endPoint = complex.exp_i(theta+2*k*
        ↪ math.pi/N)
    hyper.drawLine(idealPoint,endPoint,"gray")
end
hyper.tikzEnd()
\end{luacode*}
```



2.4.2 Hypercycles


```
\begin{luacode*}
hyper.tikzBegin()
local A = 1
local B = complex.J
hyper.drawLine(A,B,"very thick, teal")
local N = 10
for k=1,N-1 do
    local P = (2*k/N-1)*(-B^2)
    hyper.drawHypercycleThrough(P, A, B, "red")
end
hyper.tikzEnd()
\end{luacode*}
```



2.5 Printing custom strings to TikZ

In case you want to insert custom TikZ instructions into the TikZ picture, the library provides a `tikzPrintf()` function, which is essentially `tex.print` composed with `string.format()`, but also saves the printed string to the TikZ buffer.

```
\begin{luacode*}
local A = complex.ONE
local B = complex.I
local C = (-A-B)/2
hyper.tikzBegin()
hyper.tikzPrintf(
    "\\draw[%s] (%f,%f) -- (%f,%f) ;",
    "red, thick, dashed", A.re, A.im, B.re, B.im
)
hyper.tikzPrintf(
    "\\draw[%s] (%f,%f) rectangle (%f,%f) ;",
    "blue, thick", C.re, C.im, 0.8, 0.7
)
hyper.tikzEnd()
\end{luacode*}
```



The package doesn't expose Euclidean drawing functions. Users should write TikZ directly in the picture as above with `tikzPrintf`, or use some other library, for example the amazing library `tkz-euclide`.

2.6 Modifying default styles

The drawing default styles are defined in Lua constants that the user can modify. Keys and default values include:


```
hyper.LABEL_STYLE = "above_left"
hyper.DRAW_POINT_RADIUS = 0.02
hyper.DRAW_POINT_STYLE = "white,draw=black"
hyper.BOUNDARY_CIRCLE_STYLE = "very_thick,black"
```

For a complete list, see the source file `luahyperbolic-tikz.lua`

3 Defining points

3.1 Random points with uniform density


```
\begin{luacode*}
local rMin, rMax = .3, .8
hyper.tikzBegin()
for k=1,100 do
    local M = hyper.randomPoint(rMin,rMax)
    hyper.drawPoint(M)
end
hyper.tikzPrintf("\\draw[dashed] (0,0) circle
    &rightarrow; (%s) ;", rMin)
hyper.tikzPrintf("\\draw[dashed] (0,0) circle
    &rightarrow; (%s) ;", rMax)
hyper.tikzEnd()
\end{luacode*}
```



3.2 Endpoints, midpoint, interpolate


3.2.1 Endpoints

```
\begin{luacode*}
local A = complex(.4,.5)
local B = complex(-.5,0)
local AA, BB = hyper.endpoints(A,B)
hyper.tikzBegin()
hyper.drawSegment(A,B, "very thick, teal")
hyper.drawSegments(AA,A, B, BB, "dashed, red")
hyper.labelPoints(A, "$A$", B, "$B$")
hyper.labelPoint(AA, "$A'$", "red, below")
hyper.labelPoint(BB, "$B'$", "red, below right
    &rightarrow; ")
hyper.drawPoints(A, B)
hyper.drawPoints(AA,BB,"white, draw=red")
hyper.tikzEnd()
\end{luacode*}
```




3.2.2 Midpoint

```
\begin{luacode*}
local A = complex(0.4,0.6)
local B = complex(-0.8,-0.3)
local M = hyper.midpoint(A,B)
hyper.tikzBegin()
hyper.drawSegment(A,B, "very thick, teal")
hyper.drawPoints(A, B, M)
hyper.labelPoints(A, "$A$", B, "$B$")
hyper.labelPoint(M, "$M$", "below right, red")
local marking = "\\textcolor{red}{||}"
hyper.markSegment(A,M,marking)
hyper.markSegment(M,B,marking)
hyper.tikzEnd()
\\end{luacode*}
```



3.2.3 Interpolate and barycenter


```
\begin{luacode*}
local A = complex(0.3,0.8)
local B = complex(-0.6,-0.3)
local P1 = hyper.interpolate(A, B, 1/3)
local P2 = hyper.interpolate(A, B, 2/3)
hyper.tikzBegin()
hyper.drawSegment(A,B, "thick, teal")
hyper.labelPoints(A, "$A$", B, "$B$")
hyper.markSegments(A, P1, P1, P2, P2, B, "||")
hyper.drawPoints(A, B, P1, P2)
hyper.tikzEnd()
\\end{luacode*}
```



3.3 Intersections


3.3.1 Line-Line (LL) intersection

```
\begin{luacode*}
local A = complex(0.4,0.3)
local B = complex(-0.4,-0.7)
local C = complex(0,0.7)
local D = complex(0.8,-0.4)
local P = hyper.interLL(A, B, C, D)
hyper.tikzBegin()
hyper.drawLines(A, B, C, D, "thick, teal")
hyper.drawPoints(A, B, C, D, "thick, teal")
hyper.drawPoint(P, "white, draw=red")
hyper.labelPoint(A, "$A$", "above")
hyper.labelPoint(B, "$B$")
hyper.labelPoint(C, "$C$", "left")
hyper.labelPoint(D, "$D$", "above")
hyper.labelPoint(P, "$P$", "left=.1cm, red")
hyper.tikzEnd()
\\end{luacode*}
```




3.3.2 Line-circle (LC) intersection

```
\begin{luacode*}
local A = complex(0.5,0.4)
local B = complex(-0.3,-0.7)
local O = complex(-0.4,0.2)
local radius = 1.5
local P, Q = hyper.interLC(A, B, O, radius)
hyper.tikzBegin()
hyper.drawLine(A, B, "teal")
hyper.drawCircle(O, radius, "teal")
hyper.drawSegments(O, P, O, Q, "red, dashed")
hyper.drawPoints(A, B, O, "teal")
hyper.drawPoints(P, Q, "white, draw=red")
hyper.labelPoints(A, "$A$", B, "$B$", O, "$O$")
    ↪ )
hyper.labelPoints(P, "$P$", Q, "$Q$", "red,
    ↪ below right")
local mark = "\\textcolor{red}{||}"
hyper.markSegments(O, P, O, Q, mark)
hyper.tikzEnd()
\end{luacode*}
```



3.3.3 Circle-circle (CC) intersection


```
\begin{luacode*}
local A = complex(-0.5,-.3)
local B = complex(0.3,0)
local r = hyper.distance(A, B)
local P, Q = hyper.interCC(A, r, B, r)
hyper.tikzBegin()
hyper.drawCircle(A, r, "teal")
hyper.drawCircle(B, r, "teal")
hyper.drawPolygon(A, B, P, "dashed, red")
hyper.drawPoints(P, Q, "white, draw=red")
hyper.drawPoints(A, B, "teal")
hyper.labelPoints(A, "$A$", B, "$B$", "below,
    ↪ teal")
hyper.labelPoints(P, "$P$", "above left, red")
hyper.labelPoint(Q, "$Q$", "red, below")
local mark = "\\textcolor{red}{||}"
hyper.markSegments(A, B, B, P, P, A, mark)
hyper.tikzEnd()
\end{luacode*}
```



3.4 Reflections and projections


3.4.1 Reflection across a geodesic line

```
\begin{luacode*}
local A = complex(0.8,0.2)
local B = complex(-0.3,0.5)
local M = complex(0.3,-0.6)
local Mp = (hyper.reflection(A,B))(M)
hyper.tikzBegin()
hyper.drawLine(A, B, "thick, teal")
hyper.drawPoints(A, B, M)
hyper.drawPoint(Mp, "red")
hyper.drawSegment(M, Mp, "dashed, red")
hyper.labelPoint(Mp, "$M'$", "left, red")
local P = hyper.interLL(A, B, M, Mp)
local mark = "\\textcolor{red}{||}"
hyper.labelPoints(A, "$A$", B, "$B$", M, "$M$"
    ↪ , "below")
hyper.markSegments(M, P, P, Mp, mark)
hyper.drawRightAngle(M, P, A, "red")
hyper.tikzEnd()
\end{luacode*}
```



3.4.2 Projection onto a geodesic line


```
\begin{luacode*}
local A = complex(0.8,0.2)
local B = complex(-0.3,0.5)
local M = complex(0.3,-0.6)
local P = (hyper.projection(A,B))(M)
hyper.tikzBegin()
hyper.drawLine(A, B, "thick, teal")
hyper.drawPoints(A, B, M)
hyper.drawPoint(P, "white, draw=red")
hyper.drawSegment(M, P, "dashed, red")
hyper.labelPoint(P, "$P$", "above, red")
hyper.labelPoints(A, "$A$", B, "$B$", M, "$M$"
    ↪ , "below")
hyper.drawRightAngle(M, P, A, "red")
hyper.tikzEnd()
\end{luacode*}
```



3.5 Exponential map

3.5.1 Image of a vector by exponential map at a point


```
\begin{luacode*}
local P = complex(-.2,-.3)
local vect = complex.exp_i(math.pi/4)
hyper.tikzBegin()
hyper.drawRayFromVector(P, vect, "gray")
for k=1,5 do
    local A = hyper.expMap(P)(k*vect)
    hyper.drawPoint(A, "white, draw=red")
end
hyper.drawPoint(P)
hyper.labelPoint(P,"$P$")
hyper.drawVector(P,vect, "red")
hyper.tikzEnd()
\end{luacode*}
```



3.6 Automorphisms (direct isometries)


3.6.1 (Elliptic) Rotation by 60°

```
\begin{luacode*}
local O = complex(0.3,0.3)
local r = hyper.rotation(O,math.pi/3)
local points = {O, -.8, complex.J/2, -complex.
    ↪ I/2, complex(-.5,-.3), complex(.7,.3)}
hyper.tikzBegin()
for _,P in ipairs(points) do
    local rP = r(P)
    hyper.drawCircleThrough(O,P, "gray!10")
    hyper.drawArc(O,P,rP,"->, red, thick")
    hyper.drawPolyline(P,O,rP, "red!10")
    hyper.drawPoint(P)
end
hyper.drawPoint(O,"black")
hyper.tikzEnd()
\end{luacode*}
```




3.6.2 Symmetry around a point (rotation by 180°)

```
\begin{luacode*}
local O = complex(0.2,0.2)
local s = hyper.symmetry(O)
local points={complex(-.8,.1), complex(.6,0),
    ↪ complex(0,-.5)}
hyper.tikzBegin()
for k, P in ipairs(points) do
    hyper.drawCircleThrough(O, P, "gray!10")
    local sP = s(P)
    hyper.drawSegment(P,sP, "red, dashed")
    hyper.drawPoints(P,sP)
    hyper.labelPoint(P, "$P_{".. k ..}$")
    hyper.labelPoint(sP, "$\\sigma(P_{".. k ..}"
    ↪ })$")
end
hyper.drawPoint(O)
hyper.tikzEnd()
\end{luacode*}
```



3.6.3 Hyperbolic automorphism


```
\begin{luacode*}
local A = complex(0.4,0.3)
local phi = hyper.automorphism(A,0)
local N=6
hyper.tikzBegin()
style1 = "dotted, red!50"
style2 = "thick, red"
for k=1,N do
    local P = complex.polar(k/N, k*math.pi/N)
    local Q = phi(P)
    hyper.drawLine(O,P,style1)
    hyper.drawLine(-A,Q,style2)
    if k < N then
        hyper.drawCircleThrough(O,P, style1)
        hyper.drawCircleThrough(-A,Q,style2)
    end
end
hyper.tikzEnd()
\end{luacode*}
```



3.7 Orbits under automorphisms


3.7.1 Orbit under elliptic automorphism (rotation)

```
\begin{luacode*}
local nbIterations = 10
local O = complex(0.1,0.2)
local points = {0, -.8, complex.J/2, -complex.
    ↪ I/2, complex(-.5,-.3), complex(.7,.3)}
local rot = hyper.rotation(0,math.pi/30) --
    ↪ angle in radians
hyper.tikzBegin()
hyper.drawPoint(0,"red")
for _,P in ipairs(points) do
    hyper.drawCircleThrough(O,P,"draw opacity
        ↪ =0.2")
    hyper.drawPointOrbit(P, rot, nbIterations)
end
hyper.tikzEnd()
\end{luacode*}
```




3.7.2 Orbit under hyperbolic automorphism

```
\begin{luacode*}
local points = {0, -.8, complex.J/2, -complex.
    ↪ I/2, complex(-.5,-.3), complex(.7,.3)}
local nbIterations = 10
local A = complex(0.05,0.05)
local phi = hyper.automorphism(A,0)
local X, Y = hyper.endpoints(A,0)
hyper.tikzBegin()
hyper.drawLine(A,0,"red!50")
for _,P in ipairs(points) do
    hyper.drawHypercycleThrough(P,X,Y,"gray")
    hyper.drawPointOrbit(P, phi, nbIterations)
end
hyper.drawPoint(A,"red")
hyper.labelPoint(A,"$A$", "above left, red")
hyper.drawPointOrbit(A, phi, nbIterations, "
    ↪ red")
hyper.tikzEnd()
\end{luacode*}
```



3.7.3 Orbit under parabolic automorphism


```
\begin{luacode*}
local nbIterations = 10
local limit = complex.exp_i(math.pi/3) -- on
    ↪ circle
local phi = hyper.parabolic(limit,math.pi/30)
local points={
    complex(0,0), complex(0,.7),
    complex(.4,.4), complex(.3,.7),
    complex(-.8,.4), complex(-.4,0),
    complex(.4,-.45)}
hyper.tikzBegin()
for _,P in ipairs(points) do
    hyper.drawPointOrbit(P, phi, nbIterations)
    hyper.drawHorocycle(limit, P, "red, draw
        ↪ opacity=.3")
end
hyper.tikzEnd()
\end{luacode*}
```



3.8 Triangle geometry (CAUTION)


3.8.1 Centroid (intersection of medians)

```
\begin{luacode*}
hyper.tikzBegin()
local A = complex(0.1,0.8)
local B = complex(-0.7,-0.3)
local C = complex(0.6,-0.2)
local AA = hyper.midpoint(B,C)
local BB = hyper.midpoint(C,A)
local CC = hyper.midpoint(A,B)
local G = hyper.triangleCentroid(A,B,C)
hyper.drawTriangle(A,B,C)
hyper.drawSegments(A, AA, B, BB, C, CC, "teal"
    ↪ )
hyper.drawPoints(AA,BB,CC)
hyper.drawPoint(G,"white, draw=teal")
-- CAUTION :
local wrong = hyper.interpolate(A,AA,2/3)
hyper.drawPoint(wrong, "red")
hyper.tikzEnd()
\end{luacode*}
```




3.8.2 Incenter and incircle

```
\begin{luacode*}
hyper.tikzBegin()
local A = complex(0.1,0.8)
local B = complex(-0.7,-0.3)
local C = complex(0.6,-0.2)
local I = hyper.triangleIncenter(A,B,C)
hyper.drawTriangle(A,B,C,"teal")
hyper.drawPoint(I,"white",draw=red)
hyper.labelPoint(I,"$I$", "below left")
hyper.drawIncircle(A,B,C,"red")
-- show intersection :
local mystyle = "dashed, red!50"
hyper.drawAngleBisector(A,B,C,mystyle)
hyper.drawAngleBisector(B,C,A,mystyle)
hyper.drawAngleBisector(C,A,B,mystyle)
hyper.tikzEnd()
\end{luacode*}
```



3.8.3 Circumcenter and circumcircle (CAUTION: does not always exist)

```
\begin{luacode*}
local A = complex(0.1,0.8)
local B = complex(-0.6,-0.5)
local C = complex(0.6,-0.2)
local O = hyper.triangleCircumcenter(A,B,C)
local BC = hyper.midpoint(B,C)
local CA = hyper.midpoint(C,A)
local AB = hyper.midpoint(A,B)
hyper.tikzBegin()
local mystyle = "dashed, red!50"
hyper.drawTriangle(A,B,C,"teal")
hyper.drawPerpendicularBisector(A,B,mystyle)
hyper.drawPerpendicularBisector(B,C,mystyle)
hyper.drawPerpendicularBisector(C,A,mystyle)
hyper.drawCircumcircle(A,B,C,"red")
hyper.labelPoint(O,"$O$", "below left")
hyper.drawRightAngle(O,CA,C,"red",1/8)
hyper.drawRightAngle(O,BC,B,"red",1/8)
hyper.drawPoints(O,A,B,C,AB,BC,CA)
hyper.labelPoints(A,"$A$", B,"$B$", C,"$C$"
    <math>\rightarrow</math>,"above")
hyper.tikzEnd()
\end{luacode*}
```




3.8.4 Orthocenter (CAUTION: does not always exist)

```

\begin{luacode*}
local A = complex(0.1,0.8)
local B = complex(-0.7,-0.4)
local C = complex(0.6,-0.2)
local H = hyper.triangleOrthocenter(A,B,C)
local AA = hyper.projection(B,C)(A)
local BB = hyper.projection(C,A)(B)
local CC = hyper.projection(A,B)(C)

hyper.tikzBegin()
local mystyle = "dashed, red!50"
local style2 = "very thick, red"
hyper.drawTriangle(A,B,C,"teal")
hyper.drawPerpendicularThrough(A,B,C,mystyle)
hyper.drawPerpendicularThrough(B,C,A,mystyle)
hyper.drawPerpendicularThrough(C,A,B,mystyle)
hyper.drawRightAngle(A,AA,B,style2,1/15)
hyper.drawRightAngle(B,BB,C,style2,1/8)
hyper.drawRightAngle(C,CC,A,style2,1/12)
hyper.labelPoints(A, "$A$", B, "$B$", C, "$C$"
    ↪ )
hyper.drawPoints(AA,BB,CC,H,"above")
hyper.tikzEnd()
\end{luacode*}

```




4 Tilings

4.1 Draw Tilings


4.1.1 Triangle tiling (almost) by hand

```
\begin{luacode*}
local PI = math.pi
local A, B, C = hyper.triangleWithAngles(PI/2,
    ↪ PI/4, PI/5)
local geodesics = {
    {hyper.endpoints(A,B)},
    {hyper.endpoints(B,C)},
    {hyper.endpoints(C,A)}
}
geodesics = hyper.propagateGeodesics(geodesics
    ↪ , 12) -- depth = 12
hyper.tikzBegin()
hyper.drawLinesFromTable(geodesics, "green!50!
    ↪ black, draw opacity=.5")
hyper.drawTriangle(A,B,C,"red, very thick")
hyper.tikzEnd()
\end{luacode*}
```




4.1.2 Triangle tiling with less code

```
\begin{luacode*}
local PI = math.pi
local DEPTH = 12
local A, B, C = hyper.triangleWithAngles(PI/2,
    ↪ PI/3, 0)
hyper.tikzBegin()
hyper.drawTilingFromTriangle(A, B, C, DEPTH, "
    ↪ teal, draw opacity=.5")
hyper.drawTriangle(A,B,C,"red, very thick")
hyper.tikzEnd()
\end{luacode*}
```



4.1.3 Triangle tiling with even less code


```
\begin{luacode*}
local PI = math.pi
hyper.tikzBegin()
hyper.drawTilingFromAngles(PI/3, PI/5, PI/7, 12)
hyper.tikzEnd()
\end{luacode*}
```



4.2 Fill tilings


4.2.1 The 3–4–5 triangle tiling

```
\begin{luacode*}
local PI = math.pi
local DEPTH = 10
local A, B, C = hyper.triangleWithAngles(PI/3,
    ↪ PI/4, PI/5)
hyper.tikzBegin()
hyper.fillTilingFromTriangle(A, B, C, DEPTH)
-- default color is black
hyper.drawPolygon(A, B, C, "thick, red")
hyper.tikzEnd()
\end{luacode*}
```




4.2.2 Same 3–4–5 tiling centered on point B

```
\begin{luacode*}
local PI = math.pi
local DEPTH = 10
local A, B, C = hyper.triangleWithAngles(PI/3,
    ↪ PI/4, PI/5)
local phi = hyper.automorphism(B)
A, B, C = phi(A), phi(B), phi(C) -- put B in
    ↪ the center
hyper.tikzBegin()
hyper.fillTilingFromTriangle(A, B, C, DEPTH, "
    ↪ fill opacity=.2, teal!80!black, draw=
    ↪ black")
hyper.drawPolygon(A, B, C, "thick, red")
hyper.tikzEnd()
\end{luacode*}
```



4.2.3 Same 3–4–5 tiling centered on point C

```
\begin{luacode*}
local PI = math.pi
local DEPTH = 10
local A, B, C = hyper.triangleWithAngles(PI/3,
    ↪ PI/4, PI/5)
local phi = hyper.automorphism(C)
A, B, C = phi(A), phi(B), phi(C) -- put C in
    ↪ the center
hyper.tikzBegin()
hyper.tikzPrintf("\\fill[orange!30] (0,0)
    ↪ circle (1);")
hyper.fillTilingFromTriangle(A, B, C, DEPTH, "
    ↪ teal")
hyper.drawPolygon(A, B, C, "thick, red")
hyper.tikzEnd()
\end{luacode*}
```



4.3 Tilings without any Lua code

The package provides a TeX macro for users who want to completely avoid Lua.



The syntax is `\hyperbolicTiling{p}{q}{r}[options]` with p, q, r positive integers or `inf` satisfying $\frac{1}{p} + \frac{1}{q} + \frac{1}{r} < 1$. The associated hyperbolic triangle has angles $\frac{\pi}{p}$, $\frac{\pi}{q}$, and $\frac{\pi}{r}$.

The above tilings were obtained with the following commands:

```
\hyperbolicTiling{3}{4}{5}[scale=4]
\hyperbolicTiling{3}{3}{4}[scale=4,depth=12]
\hyperbolicTiling{2}{3}{7}[scale=2.5, color=teal, depth=16]
\hyperbolicTiling{2}{5}{9}[scale=2.5, color=gray]
\hyperbolicTiling{4}{4}{4}[scale=2.5, depth=6, color=purple,backgroundcolor=pink!30]
\hyperbolicTiling{2}{5}{inf}[scale=2, depth=6, color=brown]
\hyperbolicTiling{2}{inf}{inf}[scale=2, depth=6, color=olive]
\hyperbolicTiling{3}{inf}{inf}[scale=2, depth=6, color=orange]
\hyperbolicTiling{inf}{inf}{inf}[scale=2, depth=5, color=violet]
```

Default values are : `scale=3, depth=8, color=black, backgroundcolor=white`.

5 Overview of the lua libraries

The Lua files are in the `lua/` subdirectory of the repo.

To build the `luahyperbolic.sty` from the Lua source files, run `lua build.lua` on the `lua/` directory. (Lua must be installed.)

The Lua source files are not needed to compile a LaTeX document using `luahyperbolic`, only the `.sty` file is necessary.

5.1 `complex.lua`

Functions

<code>__add</code>	<code>__unm</code>	<code>det</code>	<code>isColinear</code>	<code>isReal</code>	<code>rotate90</code>
<code>__div</code>	<code>abs</code>	<code>distinct</code>	<code>isComplex</code>	<code>isUnit</code>	<code>scal</code>
<code>__eq</code>	<code>abs2</code>	<code>dot</code>	<code>isImag</code>	<code>log</code>	<code>toPolar</code>
<code>__mul</code>	<code>arg</code>	<code>exp</code>	<code>isInteger</code>	<code>new</code>	<code>unit</code>
<code>__pow</code>	<code>clone</code>	<code>exp_i</code>	<code>isNear</code>	<code>nonzero</code>	
<code>__sub</code>	<code>coerce</code>	<code>invert</code>	<code>isNearInteger</code>	<code>polar</code>	
<code>__tostring</code>	<code>conj</code>	<code>isClose</code>	<code>isNot</code>	<code>rotate</code>	

Constants (numbers and complex numbers)

`EPS`, `EPS_INV`, `I`, `J`, `ONE`, `ZERO`, `__index`,

5.2 `luahyperbolic`

The `luahyperbolic` library consists of three submodules : `luahyperbolic-core`, `luahyperbolic-tikz` and `luahyperbolic-tilings`. These three submodules are flattened in a single **hyper** global module. (The submodules are still available in three tables `hyper.core`, `hyper.tikz` and `hyper.tilings` if necessary.)

Functions beginning with underscore are available in the module but should not be needed for normal use. Don't use them, they could become private in the future and not be available to users anymore.

Functions

<code>__assert</code>	<code>drawAngle</code>	<code>drawSegment</code>
<code>__assert_in_closed_disk</code>	<code>drawAngleBisector</code>	<code>drawSegments</code>
<code>__assert_in_disk</code>	<code>drawArc</code>	<code>drawSemicircle</code>
<code>__circle_to_euclidean</code>	<code>drawCircle</code>	<code>drawTangentAt</code>
<code>__coerce_assert_in_closed_disk</code>	<code>drawCircleThrough</code>	<code>drawTilingFromAngles</code>
<code>__coerce_assert_in_disk</code>	<code>drawCircumcircle</code>	<code>drawTilingFromTriangle</code>
<code>__ensure_order</code>	<code>drawHorocycle</code>	<code>drawTriangle</code>
<code>__error</code>	<code>drawHypercycleThrough</code>	<code>drawVector</code>
<code>__geodesic_data</code>	<code>drawIncircle</code>	<code>endpoints</code>
<code>__in_closed_disk</code>	<code>drawLine</code>	<code>endpointsAngleBisector</code>
<code>__in_disk</code>	<code>drawLineFromVector</code>	<code>endpointsPerpendicularBisector</code>
<code>__in_half_plane</code>	<code>drawLines</code>	<code>expMap</code>
<code>__metric_factor</code>	<code>drawLinesFromTable</code>	<code>fillCircle</code>
<code>__midpoint_to_origin</code>	<code>drawPerpendicularBisector</code>	<code>fillTilingFromAngles</code>
<code>__on_circle</code>	<code>drawPerpendicularThrough</code>	<code>fillTilingFromTriangle</code>
<code>__on_line</code>	<code>drawPoint</code>	<code>interCC</code>
<code>__on_segment</code>	<code>drawPointOrbit</code>	<code>interLC</code>
<code>__radial_half</code>	<code>drawPoints</code>	<code>interLL</code>
<code>__radial_scale</code>	<code>drawPolygon</code>	<code>interpolate</code>
<code>__warning</code>	<code>drawPolygonFromTable</code>	<code>labelPoint</code>
<code>angle</code>	<code>drawPolyline</code>	<code>labelPoints</code>
<code>automorphism</code>	<code>drawPolylineFromTable</code>	<code>labelSegment</code>
<code>automorphismFromPairs</code>	<code>drawRay</code>	<code>markSegment</code>
<code>automorphismSending</code>	<code>drawRayFromPoints</code>	<code>markSegments</code>
<code>barycenter2</code>	<code>drawRayFromVector</code>	<code>midpoint</code>
<code>distance</code>	<code>drawRegularPolygon</code>	<code>mobiusTransformation</code>
<code>distanceToLine</code>	<code>drawRightAngle</code>	<code>parabolic</code>

pointOrbit	tangentVector	tikz_shape_euclidean_segment
projection	tikzBegin	tikz_shape_segment
propagateGeodesics	tikzClearBuffer	triangleCentroid
randomPoint	tikzDefineNodes	triangleCircumcenter
reflection	tikzEnd	triangleIncenter
rotation	tikzExport	triangleOrthocenter
rotationFromPair	tikzGetFirstLines	triangleWithAngles
symmetry	tikzPrintf	
symmetryAroundMidpoint	tikz_shape_closed_line	

Constants

Numbers: DRAW_ANGLE_DIST, DRAW_POINT_RADIUS, EPS, QUANTIZATION_SCALE, tikzNbPicturesExported,

Strings: ANGLE_STYLE, BOUNDARY_CIRCLE_STYLE, CIRCLE_STYLE, DRAW_POINT_STYLE, GEODESIC_STYLE, HOROCYCLE_STYLE, HYPERCYCLE_STYLE, LABEL_STYLE, MARKING_SIZE, MARKING_STYLE, TIKZ_BEGIN_DISK, module, tikzpictureOptions,

Tables: core, options, tikz, tikzBuffer, tilings,

6 Changelog

- 2026-04-12: added function `fillCircle(center, radius, options)`
- 2026-03-23: `expMap` now takes only one argument, a point, and returns a function. New syntax is `newPoint = hyper.expMap(Point)(vector)`
- 2026-03-16: first version uploaded to CTAN

7 Known bugs

1. Cannot use the TeX macro `\hyperbolicTiling` inside a `begin{center}` environment. Boxes and `\centering` don't work well either.
2. This documentation sometimes errors during compilation with error `pgf : dimension too large` but a second compilation always succeeds.

8 Index

Index of functions used in this documentation

automorphism, 16

complex

- exp_i, 2

drawAngle, 9

drawAngleBisector, 7

drawArc, 9

drawCircle, 8

drawCircleThrough, 8

drawCircumcircle, 19

drawHorocycle, 10

drawHypercycleThrough, 10

drawIncircle, 19

drawLine, 4

drawLineFromVector, 7

drawLinesFromTable, 21

drawPerpendicularBisector, 7

drawPerpendicularThrough, 20

drawPoint, 4

drawPointOrbit, 17

drawPoints, 4

drawPolygon, 5

drawPolygonFromTable, 5

drawPolyline, 6

drawPolylineFromTable, 6

drawRay, 4

drawRayFromVector, 7

drawRegularPolygon, 6

drawRightAngle, 14

drawSegment, 4

drawSemicircle, 8

drawTangentAt, 9

drawTilingFromAngles, 21

drawTilingFromTriangle, 21

drawTriangle, 5

drawVector, 7

endpoints, 11

expMap, 15

fillCircle, 8

fillTilingFromTriangle, 22

interCC, 13

interLC, 13

interLL, 12

interpolate, 12

labelPoint, 4

labelPoints, 4

labelSegment, 6

markSegment, 6

midpoint, 12

parabolic, 18

projection, 14

propagateGeodesics, 21

randomPoint, 11

reflection, 14

rotation, 15

symmetry, 16

tikzBegin, 2

tikzEnd, 2

tikzExport, 3

tikzPrintf, 10

triangleCentroid, 18

triangleCircumcenter, 19

triangleIncenter, 19

triangleOrthocenter, 20

triangleWithAngles, 5