Package luahyperbolic

Damien Mégy

March 2, 2026



Contents

1 Introduction **2**
- 1.1 What you can do with this package . . . 2
- 1.2 What this package cannot do for you . . 2
- 1.3 Efficiency 2
- 1.4 How to load the package 2
- 1.5 How to customize the package 3
- 1.6 Environment hyperbolicdisk 3
  - 1.6.1 Exporting the pictures 3

2 Drawing and labeling elements **4**
- 2.1 Points 4
- 2.2 Geodesic segments, lines and rays 4
- 2.3 Circles, semicircles, arcs 7
- 2.4 Horocycles 9

3 Defining points **9**
- 3.1 Random points 9
- 3.2 Midpoint, interpolate, barycenter 10
- 3.3 Intersections 10
- 3.4 Reflections and projections 11
- 3.5 Automorphisms (direct isometries) . . . 12
- 3.6 Orbits under automorphisms 14
- 3.7 Triangle geometry (CAUTION) 15

4 Tilings **17**
- 4.1 Source code of first picture 17
- 4.2 More images just for fun 18

5 Overview of the lua libraries **18**
- 5.1 complex.lua 18
- 5.2 luahyperbolic-tikz.lua and hyperbolic-core 19

1 Introduction

1.1 What you can do with this package

1. Draw hyperbolic geometry pictures, high precision (pdf output).
2. Use an easy syntax. At least, easier than with LaTeXmacros and bloody pgf.
3. Export generated pictures to external tikz files if you want.
4. Read the source code and learn hyperbolic geometry.
5. Compile **without** installing python packages or lua packages etc.
6. Compile **without** "shell-escape" mode.
7. Compile everything in a single pass. No (Leeloo Dallas) multipass. Want to illustrate Euclid's fifth postulate ? Do it right there in your tex file without having to include external files :

Euclid's 5th Postulate

```
\begin{luacode*}
hyper.tikzBegin("scale=2.5")
local P = complex(0.5,-0.2)
local A = complex.exp_i(math.pi/10)
for k=1,5 do
  hyper.drawLine(P, A^k, "teal")
end
hyper.labelPoint(P, "$P$", "left=.2cm")
local style = "very thick, dashed, red"
hyper.drawLine(complex.J,-complex.I,style)
hyper.tikzEnd("euclid5thPostulate.tikz")
\end{luacode*}
```



1.2 What this package cannot do for you

1. Really intensive computations, millions of geodesics etc. Source code is not optimized to keep maximum readability. All computations involve automorphisms. See other remarks below.
2. Coffee

1.3 Efficiency

For heavy computations, please use a ~~Python~~ C library. Nevertheless, this library is still reasonably efficient and usable:

- The first tiling illustration of this documentation (hyperbolic 2-4-5 tiling with 2361 geodesics) compiled in 4.55 seconds on a 2020 intel macbook air laptop.
- This entire documentation including all pictures compiles in approx. 15 seconds on the same machine, the majority of the time weing spent on the tilings. The package is suitable for producing lecture notes in hyperbolic geometry, which was the reason for all of this. For an entire book with dozens of pictures, you may need to externalize some of the pictures.
- Tests show that the bottleneck is TikZ, not Lua. In a future version, some future maintainer may add other fontends to the library, including drawing directly to the pdf with pdf primitives wich are several orders of magnitude faster than tikz.

1.4 How to load the package

Local install

Simply put the `luahyperbolic.sty` file in your working directory and add the following line to your tex preamble :

```
\usepackage{luahyperbolic}
```

The file `luahyperbolic.sty` **contains everything needed**, including the necessary library for complex numbers. It can be sent to colleagues by email etc.

It will declare two lua globals : `complex` and `hyper`, and define a `hyperbolicdisk` environment for convenience.

If the sty file is not in the same directory as your tex file, you can write `\usepackage{../luahyperbolic}`

CTAN

Not available yet.

1.5 How to customize the package

The `luahyperbolic.sty` is generated from three lua modules : `complex.lua`, `luahyperbolic-core.lua` and `luahyperbolic-tikz.lua`. These files are in the `lua/` subdirectory of the package repo.

To build the `luahyperbolic.sty` from lua source files, execute `lua build.lua` in the root directory of the package. This will backup the old sty file to the `backup/` directory, then buid and replace the existing sty file.

1.6 Environment hyperbolicdisk

The package provides the latex environment `\begin{hyperbolicdisk} ... \end{hyperbolicdisk}` which is defined as follows:

```
\newenvironment{hyperbolicdisk}[1][scale=3]{%
  \begin{tikzpicture}[#1]
    \draw[very thick] (0,0) circle (1);
    \clip (0,0) circle (1);
}{%
  \end{tikzpicture}
}
```

In this documentation, we prefer to use the lua functions `hyper.tikzBegin(options)` and `hyper.tikzEnd(export_file)` that enable export functionalities, see below.

1.6.1 Exporting the pictures

Simply add a filename to the closing `hyper.tikzEnd()` instruction, as below:

```
hyper.tikzEnd("myfile.tikz")
```

This will save the current picture (including `\begin{tikzpicture}[options]` and `\end{tikzpicture}`).

It is also possible to export the current picture at any point with `hyper.tikzExport(optional-filename)`. If no filename is provided, the package will name it `hyper_picture_N` with `N` the picture counter. Luahyperbolic keeps count of how many pictures have been produced in the document. This allows exporting images in loops, or drawing several steps of the same picture.

2 Drawing and labeling elements

2.1 Points

Draw and label points

```
\begin{luacode*}
local O = 0
local A = complex(0.3,0.2)
local B = 2*A
local C = (1-complex.I)/2
local D = B*complex.I
local E = complex.exp_i(-5*math.pi/6)/2
hyper.tikzBegin()
hyper.drawPoint(O,"white, draw=red")
hyper.drawPoints(A, B, C, "teal")
hyper.drawPoints(D, E)
hyper.labelPoint(A,"$A$", "below right, blue")
hyper.labelPoints(B,"$B$", C, "$C$")
hyper.labelPoint(D,"$D$","below=.4cm, red")
hyper.tikzEnd()
\end{luacode*}
```



2.2 Geodesic segments, lines and rays

Segments lines and rays (through two points)

```
\begin{luacode*}
hyper.tikzBegin()
local A = -complex.I/2
local B = (1+complex.I)/2
local C = complex(-0.7,0.4)
local D = complex(-0.7,-0.3)
hyper.drawLine(A, B, "red")
hyper.drawSegment(B,C,"dashed, ForestGreen")
hyper.drawRay(C,D,"double,double distance=2pt")
hyper.drawLine(D,-D, "green!50!black")
hyper.drawLine(A, 1, "gray, line width=2pt")
hyper.drawLine(1, complex.I, "teal")
hyper.drawPoints(A, B, C, D)
hyper.labelPoints(A, "$A$", B, "$B$", C, "$C$",
    ↪ D, "$D$")
hyper.tikzEnd()
\end{luacode*}
```



Triangles and polygons

```
\begin{luacode*}
hyper.tikzBegin()
hyper.drawTriangle(
  complex(.9,.2),
  complex(.5,.7),
  complex(.7,-.2), "red")
local points={}
for k=1,5 do
  table.insert(points, complex.polar(.5,k*2*
      ↪ math.pi/5))
end
hyper.drawPolygonFromTable(points,"teal")
hyper.tikzEnd()
\end{luacode*}
```



Regular polygons

```
\begin{luacode*}
hyper.tikzBegin()
local O1 = complex(.5,.2)
local A1 = complex(.7,.3)
local O2 = complex(-0.1,0)
local A2 = complex(-.4,.3)
local O3 = complex(0,.7)
local A3 = complex(0,.9)
hyper.drawRegularPolygon(O1, A1, 3, "red")
hyper.drawRegularPolygon(O2, A2, 5, "blue")
hyper.drawRegularPolygon(O3, A3, 8, "green!50!
    ↪ black")
hyper.drawPoints(O1,O2,O3)
hyper.tikzEnd()
\end{luacode*}
```



Polygonal lines

```
\begin{luacode*}
hyper.tikzBegin()
hyper.drawPolyline(0, 1, complex.I, -1, "red")
local points={}
for k=1, 15 do
  table.insert(points, complex.polar(k/15, k))
end
hyper.drawPolylineFromTable(points,"teal")
hyper.tikzEnd()
\end{luacode*}
```



Lines and rays (point and tangent vector)

```
\begin{luacode*}
hyper.tikzBegin()
local A = complex(-0.2,-0.5)
local B = complex(-0.5,0.5)
local C = complex(0,0.2)
local v =  complex(1,0)
hyper.drawLineFromVector(A, v, "->, red")
hyper.drawRayFromVector(B, v, "->, blue")
hyper.drawRayFromVector(C, v, "->, Green")
hyper.drawPoints(A, B,C)
hyper.drawTangentVector(A,v,"red")
hyper.drawTangentVector(B,v,"blue")
hyper.drawTangentVector(C,v,"Green")
hyper.tikzEnd()
\end{luacode*}
```



Perpendicular bisector

```
\begin{luacode*}
hyper.tikzBegin()
local A = complex(-0.2,-0.5)
local B = complex(-0.7,0.3)
hyper.drawPerpendicularBisector(A,B,"red")
hyper.drawPoints(A,B)
hyper.drawSegment(A, B, "teal")
hyper.labelPoints(A,"$A$", B, "$B$", "above
    ↪ right")
hyper.tikzEnd()
\end{luacode*}
```



Angle bisector

```
\begin{luacode*}
hyper.tikzBegin()
local A = complex(-0.2,-0.6)
local O = complex(0.3,0.3)
local B = complex(-0.7,0.3)
hyper.drawAngleBisector(A,O,B,"red")
hyper.drawPoints(A,O,B)
hyper.drawPolyline(A,O,B, "teal")
hyper.labelPoints(A, "$A$", O, "$O$", B, "$B$")
hyper.tikzEnd()
\end{luacode*}
```



2.3 Circles, semicircles, arcs

Center and radius

```
\begin{luacode*}
hyper.tikzBegin()
local points = {
  complex(0,0),
  complex(-0.5,-0.4),
  complex(0.8,0.1),
  complex(0,0.9)
}
for _,point in ipairs(points) do
  hyper.drawCircle(point,1,"teal")
  hyper.drawPoint(point)
end
-- NOTE : all circles have same radius=1 !
hyper.tikzEnd()
\end{luacode*}
```



Circle through point

```
\begin{luacode*}
hyper.tikzBegin()
local O = complex(0.3,0.2)
local P = complex(0.7,-0.4)
local Q = complex(-0.1,0.4)
hyper.drawCircleThrough(O, P, "dotted, red")
-- or by hand :
hyper.drawCircle(O, hyper.distance(O,Q), "blue"
    ↪ )
hyper.drawPoints(O, P, Q)
hyper.labelPoints(O, "$O$", P, "$P$", Q, "$Q$")
hyper.tikzEnd()
\end{luacode*}
```



Semicircles

```
\begin{luacode*}
hyper.tikzBegin()
local O = complex(0,0)
local A = complex(-0.3,0)
local P = complex(0.5,0.2)
local B = complex(0.7,-0.4)
hyper.drawSemicircle(O, A, "blue")
hyper.drawSemicircle(P, B, "red")
hyper.drawPoints(O, A, P, B)
hyper.labelPoints(O, "$O$", A, "$A$", P, "$P$",
    ↪  B, "$B$")
hyper.drawLine(P,B, "gray, dashed")
hyper.tikzEnd()
\end{luacode*}
```



Arc (center and endpoints)

```
\begin{luacode*}
hyper.tikzBegin()
local O = complex(0,0)
local A = complex(0.5,0)
local B = complex.polar(0.5,math.pi/3)
hyper.drawArc(O,A,B, "red")
hyper.drawPoints(O,A,B)
hyper.tikzEnd()
\end{luacode*}
```



Angles

```
\begin{luacode*}
hyper.tikzBegin()
local A = complex(-.5,-.3)
local B = complex(0.5,0)
local C = complex(0.2,.7)
hyper.drawLines(A, B, B, C, C, A, "teal")
hyper.drawAngle(B, A, C, "red, very thick")
hyper.drawAngle(A, C, B, "thick, double, double
    ↪  distance=2pt, blue")
hyper.drawAngle(A, B, C, "very thick, ->, green
    ↪ !50!black")
hyper.drawPoints(A, B, C)
hyper.labelPoints(A, "$A$", C, "$C$")
hyper.labelPoint(N, "$B$", "above right")
-- poor man's labelAngle:
hyper.labelPoint(A,"$\\alpha$", "above=.6cm,
    ↪ right=.7cm")
hyper.tikzEnd()
\end{luacode*}
```



Tangent at point

```
\begin{luacode*}
hyper.tikzBegin()
local O = complex(0.3,0.2)
local P = complex(0.1,-0.4)
local Q = hyper.rotation(O,math.pi/3)(P)
hyper.drawCircleThrough(O, P)
hyper.drawPoints(O, P, Q)
hyper.drawTangentAt(O,P,"red")
hyper.drawTangentAt(O,Q,"teal")
hyper.tikzEnd()
\end{luacode*}
```



2.4 Horocycles

Horocycles

```
\begin{luacode*}
hyper.tikzBegin()
local theta=math.pi/3
local idealPoint = complex.exp_i(theta)
local N = 10
for k=1,N-1 do
  local point = idealPoint * (2*k/N-1)
  hyper.drawHorocycle(idealPoint,point,"red")
  -- and an orthogonal geodesic :
  local endPoint = complex.exp_i(theta+2*k*math
      ↪ .pi/N)
  hyper.drawLine(idealPoint,endPoint,"gray")
end
hyper.tikzEnd()
\end{luacode*}
```



3 Defining points

3.1 Random points

Random points with uniform density

```
\begin{luacode*}
local rMin, rMax = .3, .8
hyper.tikzBegin()
for k=1,100 do
  local M = hyper.randomPoint(rMin,rMax)
  hyper.drawPoint(M)
end
hyper.tikzPrintf("\\draw[dashed] (0,0) circle
    ↪ (%s) ;", rMin)
hyper.tikzPrintf("\\draw[dashed] (0,0) circle
    ↪ (%s) ;", rMax)
hyper.tikzEnd()
\end{luacode*}
```



3.2 Midpoint, interpolate, barycenter

Midpoint

```
\begin{luacode*}
hyper.tikzBegin()
local A = complex(0.4,0.4)
local B = complex(-0.8,-0.3)
local M = hyper.midpoint(A,B)
hyper.drawSegment(A,B, "teal")
hyper.drawPoints(A,B,M)
hyper.labelPoints(A, "$A$", B, "$B$", M, "$M$")
hyper.tikzEnd()
\end{luacode*}
```



Interpolate and barycenter

```
\begin{luacode*}
hyper.tikzBegin()
local A = complex(0.3,0.8)
local B = complex(-0.7,-0.4)
hyper.drawSegment(A,B, "teal")
for k=0,10 do
  local M = hyper.interpolate(A, B, k/10)
  hyper.drawPoint(M)
  if k % 2 == 0 then
    hyper.labelPoint(M, "$M_{" .. k .. "}$", "
        ↪ below right")
  end
end
hyper.tikzEnd()
\end{luacode*}
```



3.3 Intersections

Line-Line (LL) intersection

```
\begin{luacode*}
hyper.tikzBegin()
local A = complex(0.4,0.3)
local B = complex(-0.4,-0.7)
local C = complex(0,0.7)
local D = complex(0.8,-0.2)
local P = hyper.interLL(A, B, C, D)
hyper.drawLines(A, B, C, D, "teal")
hyper.drawPoints(A, B, C, D,"teal")
hyper.drawPoint(P,"red")
hyper.labelPoint(A, "$A$", "above")
hyper.labelPoint(B, "$B$")
hyper.labelPoint(C, "$C$", "left")
hyper.labelPoint(D, "$D$", "above")
hyper.labelPoint(P, "$P$", "left=.1cm, red")
hyper.tikzEnd()
\end{luacode*}
```



Line-circle (LC) intersection

```
\begin{luacode*}
hyper.tikzBegin()
local A = complex(0.5,0.4)
local B = complex(-0.3,-0.7)
local O = complex(-0.2,0.1)
local radius = 1
local P, Q = hyper.interLC(A, B, O, radius)
hyper.drawLine(A, B, "teal")
hyper.drawCircle(O,radius, "teal")
hyper.drawPoints(A, B, O, "teal")
hyper.drawPoints(P, Q, "red")
hyper.labelPoints(A, "$A$", B, "$B$", O, "$O$")
hyper.labelPoints(P, "$P$", Q, "$Q$", "red,
    ↪ below right")
hyper.tikzEnd()
\end{luacode*}
```



Circle-circle (CC) intersection

```
\begin{luacode*}
hyper.tikzBegin()
local O1 = complex(-0.6,-.3)
local O2 = complex(0.5,0)
local r1, r2 = 1, 2
local P, Q = hyper.interCC(O1, r1, O2, r2)
hyper.drawCircle(O1,r1, "teal")
hyper.drawCircle(O2,r2, "teal")
hyper.drawPoints(P, Q, "red")
hyper.drawPoints(O1, O2, "teal")
hyper.labelPoints(O1, "$O_1$", O2, "$O_2$", "
    ↪ left, teal")
hyper.labelPoints(P, "$P$", "above left, red")
hyper.labelPoint(Q, "$Q$", "red, below")
hyper.tikzEnd()
\end{luacode*}
```



3.4 Reflections and projections

Reflection across a geodesic line

```
\begin{luacode*}
hyper.tikzBegin()
local A = complex(0.8,0.2)
local B = complex(-0.3,0.5)
local M = complex(0.3,-0.6)
local Mp = (hyper.reflection(A,B))(M)
hyper.drawLine(A, B, "teal")
hyper.drawPoints(A, B, M)
hyper.drawPoint(Mp,"red")
hyper.drawSegment(M,Mp,"dashed,red")
hyper.labelPoint(Mp,"$M'$", "left, red")
hyper.labelPoints(A, "$A$", B, "$B$", M, "$M$",
    ↪  "below")
hyper.tikzEnd()
\end{luacode*}
```



Projection onto a geodesic line

```
\begin{luacode*}
hyper.tikzBegin()
local A = complex(0.8,0.2)
local B = complex(-0.3,0.5)
local M = complex(0.3,-0.6)
local P = (hyper.projection(A,B))(M)
hyper.drawLine(A, B, "teal")
hyper.drawPoints(A, B, M)
hyper.drawPoint(P,"red")
hyper.drawSegment(M,P,"dashed,red")
hyper.labelPoint(P,"$P$", "above, red")
hyper.labelPoints(A, "$A$", B, "$B$", M, "$M$",
    ↪  "below")
hyper.tikzEnd()
\end{luacode*}
```



3.5 Automorphisms (direct isometries)

(Elliptic) rotation around a point (regular octogon)

```
\begin{luacode*}
hyper.tikzBegin()
local O = complex(0.3,0.2)
local M = complex(0.5,-0.4)
hyper.drawPoints(O)
for k=1,8 do
  local P = (hyper.rotation(O,2*math.pi/8))(M)
  hyper.drawSegment(M, P, "red")
  hyper.drawSegment(O,M, "dashed,red")
  M = P
end
hyper.drawCircle(O,hyper.distance(O,M),"thin,
    ↪ gray")
hyper.tikzEnd()
\end{luacode*}
```



Symmetry around a point (rotation by 180°)

```
\begin{luacode*}
hyper.tikzBegin()
local O = complex(0.2,0.2)
local s = hyper.symmetry(O)
hyper.drawPoints(O)
local points={complex(-.8,.1), complex(.6,0),
    ↪ complex(0,-.5)}
for k, P in ipairs(points) do
  hyper.drawCircleThrough(O, P, "gray!10")
  local sP = s(P)
  hyper.drawPoints(P,sP)
  hyper.drawSegment(P,sP, "red, dashed")
  hyper.labelPoint(P, "$P_{".. k .."}$")
  hyper.labelPoint(sP, "$\\sigma(P_{".. k ..."})
      ↪ $")
end
hyper.tikzEnd()
\end{luacode*}
```



Rotation by 60°

```
\begin{luacode*}
hyper.tikzBegin()
local O = complex(0.1,0.1)
local r = hyper.rotation(O,math.pi/3)
hyper.drawPoints(O)
for k=1,5 do
  local P = hyper.randomPoint(0.3,0.9)
  local rP = r(P)
  hyper.drawCircleThrough(O,P, "gray!10")
  hyper.drawArc(O,P,rP,"->, red")
  hyper.drawPolyline(P,O,rP, "red!10")
  hyper.drawPoint(P)
end
hyper.tikzEnd()
\end{luacode*}
```



Hyperbolic automorphims

```
\begin{luacode*}
hyper.tikzBegin()
local A = complex(0.4,0.3)
local phi = hyper.automorphism(A,0)
local N=6
style1 = "dotted, red!50"
style2 =  "thick, red"
for k=1,N do
  local P = complex.polar(k/N, k*math.pi/N)
  local Q = phi(P)
  hyper.drawLine(0,P,style1)
  hyper.drawLine(-A,Q,style2)
  if k < N then
    hyper.drawCircleThrough(0,P, style1)
    hyper.drawCircleThrough(-A,Q,style2)
  end
end
hyper.tikzEnd()
\end{luacode*}
```



3.6 Orbits under automorphisms

Orbit under elliptic automorphism (rotation)

```
\begin{luacode*}
hyper.tikzBegin()
local nbPoints = 7
local nbIterations = 5
local O = complex(0.1,0.2)
local rot = hyper.rotation(O,math.pi/20) --
    ↪ angle in radians
hyper.drawPoint(O,"red")
for k=1,nbPoints do
  local P = hyper.randomPoint(0,.9)
  hyper.drawCircleThrough(O,P,"draw opacity=0.2
      ↪ ")
  hyper.drawPointOrbit(P, rot, nbIterations)
end
hyper.tikzEnd()
\end{luacode*}
```



Orbit under hyperbolic automorphism

```
\begin{luacode*}
hyper.tikzBegin()
local nbPoints = 10
local nbIterations = 5
local A = complex(0.1,0.1)
local phi = hyper.automorphism(A,0)
for k=1,nbPoints do
  local P = hyper.randomPoint(0,.9)
  hyper.drawPointOrbit(P, phi, nbIterations)
end
hyper.drawPoint(A,"red")
hyper.labelPoint(A,"$A$", "above left, red")
hyper.drawPointOrbit(A, phi, nbIterations, "red
    ↪ ")
hyper.tikzEnd()
\end{luacode*}
```



Orbit under parabolic automorphism

```
\begin{luacode*}
hyper.tikzBegin()
local nbIterations = 7
limit = complex.exp_i(math.pi/3) -- on circle
local phi = hyper.parabolic(limit,math.pi/20)
local points={
  complex(0,0), complex(0,.7),
  complex(.4,.4), complex(.3,.7),
  complex(-.8,.4), complex(-.4,0),
  complex(.4,-.45)}
for _,P in ipairs(points) do
  hyper.drawPointOrbit(P, phi, nbIterations)
  hyper.drawHorocycle(limit, P, "red, draw
      ↪ opacity=.3")
end
hyper.tikzEnd()
\end{luacode*}
```



3.7 Triangle geometry (CAUTION)

Centroid (intersection of medians)

```
\begin{luacode*}
hyper.tikzBegin()
local A = complex(0.1,0.8)
local B = complex(-0.7,-0.3)
local C = complex(0.6,-0.2)
local AA = hyper.midpoint(B,C)
local BB = hyper.midpoint(C,A)
local CC = hyper.midpoint(A,B)
local G = hyper.triangleCentroid(A,B,C)
hyper.drawTriangle(A,B,C)
hyper.drawSegments(A, AA, B, BB, C, CC, "teal")
hyper.drawPoints(AA,BB,CC)
hyper.drawPoint(G,"white, draw=teal")
-- CAUTION :
local wrong = hyper.interpolate(A,AA,2/3)
hyper.drawPoint(wrong, "red")
hyper.tikzEnd()
\end{luacode*}
```



Incenter and incircle

```
\begin{luacode*}
hyper.tikzBegin()
local A = complex(0.1,0.8)
local B = complex(-0.7,-0.3)
local C = complex(0.6,-0.2)
local I = hyper.triangleIncenter(A,B,C)
hyper.drawTriangle(A,B,C,"teal")
hyper.drawPoint(I,"white, draw=red")
hyper.labelPoint(I,"$I$", "below left")
hyper.drawIncircle(A,B,C,"red")
-- show intersection :
local mystyle = "dashed, red!50"
hyper.drawAngleBisector(A,B, C, mystyle)
hyper.drawAngleBisector(B,C,A, mystyle)
hyper.drawAngleBisector(C,A,B, mystyle)
hyper.tikzEnd()
\end{luacode*}
```



Circumcenter and circumcircle (CAUTION : does not always exist)

```
\begin{luacode*}
hyper.tikzBegin()
local A = complex(0.1,0.8)
local B = complex(-0.6,-0.5)
local C = complex(0.6,-0.2)
hyper.drawTriangle(A,B,C,"teal")
local mystyle = "dashed, red!50"
hyper.drawPerpendicularBisector(A, B, mystyle)
hyper.drawPerpendicularBisector(B, C, mystyle)
hyper.drawPerpendicularBisector(C, A, mystyle)
local O = hyper.triangleCircumcenter(A,B,C)
hyper.drawCircumcircle(A,B,C,"red")
hyper.labelPoint(O,"$O$", "below left")
local BC = hyper.midpoint(B,C)
local CA = hyper.midpoint(C,A)
local AB = hyper.midpoint(A,B)
hyper.drawRightAngle(O, CA, C,"red",1/8)
hyper.drawRightAngle(O,BC,B,"red",1/8)
hyper.drawPoints(O,A,B,C,AB,BC,CA)
hyper.labelPoints(A, "$A$", B, "$B$", C, "$C$",
    ↪ "above")
hyper.tikzEnd()
\end{luacode*}
```



Orthocenter (CAUTION : does not always exist)

```
\begin{luacode*}
hyper.tikzBegin()
local A = complex(0.1,0.8)
local B = complex(-0.7,-0.4)
local C = complex(0.6,-0.2)
hyper.drawTriangle(A,B,C,"teal")
local mystyle = "dashed, red!50"
hyper.drawPerpendicularThrough(A,B,C,mystyle)
hyper.drawPerpendicularThrough(B,C,A,mystyle)
hyper.drawPerpendicularThrough(C,A,B,mystyle)
local AA = hyper.projection(B,C)(A)
local BB = hyper.projection(C,A)(B)
local CC = hyper.projection(A,B)(C)
local style2 = "very thick, red"
hyper.drawRightAngle(A,AA,B,style2,1/15)
hyper.drawRightAngle(B,BB,C,style2,1/8)
hyper.drawRightAngle(C,CC,A,style2,1/12)
hyper.labelPoints(A, "$A$", B, "$B$", C, "$C$")
local H = hyper.triangleOrthocenter(A,B,C)
hyper.drawPoints(AA,BB,CC,H,"above")
hyper.tikzEnd()
\end{luacode*}
```



4 Tilings

The two following tilings are drawn with `TILING_DEPTH=12`

Triangle tiling

```
\begin{luacode*}
hyper.tikzBegin()
local A, B, C = hyper.fundamentalRightTriangle
    ↪ (4,5)
local geodesics = {
{hyper.endpoints(A,B)},
  {hyper.endpoints(B,C)},
  {hyper.endpoints(C,A)}}
geodesics = hyper.propagateGeodesics(geodesics,
    ↪  TILING_DEPTH)
hyper.drawLinesFromTable(geodesics, "green!50!
    ↪ black, draw opacity=.5")
hyper.drawTriangle(A,B,C,"red, very thick")
hyper.tikzEnd()
\end{luacode*}
```



Triangle tiling with one angle zero

```
\begin{luacode*}
hyper.tikzBegin()
local A, B, C = hyper.fundamentalIdealTriangle
    ↪ (3,2)
local geodesics = {
  {hyper.endpoints(A,B)},
  {hyper.endpoints(B,C)},
  {hyper.endpoints(C,A)}
}
geodesics = hyper.propagateGeodesics(geodesics,
    ↪  TILING_DEPTH)
hyper.drawLinesFromTable(geodesics, "teal, draw
    ↪  opacity=.5")
hyper.drawTriangle(A,B,C,"red, very thick")
hyper.tikzEnd()
\end{luacode*}
```



4.1 Source code of first picture

```
\begin{luacode*}
local A, B, C = hyper.fundamentalRightTriangle(4,5)
local phi = hyper.automorphism(C,0)
A,B,C = phi(A), phi(B), phi(C) -- center on pentagon
local geodesics = {
  {hyper.endpoints(A,B)},
  {hyper.endpoints(B,C)},
  {hyper.endpoints(C,A)}
}
geodesics = hyper.propagateGeodesics(geodesics, 24)
local shapes={}
for k,pair in ipairs(geodesics) do
  table.insert(shapes,hyper.shape_closed_line(pair[1], pair[2]))
end
shapes_string = table.concat(shapes, " ")
hyper.tikzBegin("scale=6")
hyper.tikzPrintf("\\fill[even odd rule] (0,0) circle (1) %s ;",shapes_string)
hyper.drawRegularPolygon(complex.ZERO, B,5,  "line width=.15cm, cyan")
```

```
hyper.tikzEnd()
\end{luacode*}
```

4.2 More images just for fun



5 Overview of the lua libraries

The Lua files are in the `lua/` subdirectory of the repo.

To build the `luahyperbolic.sty` from the lua source files, run `lua build.lua` on the root directory. (Lua must be installed)

The Lua source files are not needed to compile a latex document using luahyperbolic, only the sty file is necessary.

5.1 complex.lua

Functions

___add	___mul	___tostring	abs2	coerce	distinct
___div	___pow	___unm	arg	conj	dot
___eq	___sub	abs	clone	det	exp

exp_i	isColinear	isNear	isUnit	polar	toPolar
invert	isComplex	isNearInteger	log	rotate	unit
isClose	isImag	isNot	new	rotate90	
isClosePair	isInteger	isReal	nonzero	scal	

Constants (numbers and complex numbers)

EPS, EPS_INV, I, J, ONE, ZERO, ___index,

5.2 luahyperbolic-tikz.lua and hyperbolic-core

Functions

_assert	drawLineFromVector	labelPoint
_assert_in_closed_disk	drawLines	labelPoints
_assert_in_disk	drawLinesFromTable	metric_factor
_coerce_assert_in_closed_disk	drawPerpendicularBisector	midpoint
_coerce_assert_in_disk	drawPerpendicularThrough	midpointToOrigin
_ensure_order	drawPoint	mobiusTransformation
_error	drawPointOrbit	parabolic
_in_closed_disk	drawPoints	parabolic_fix1
_in_disk	drawPolySeg	projection
_in_half_plane	drawPolySegFromTable	propagateGeodesics
_on_circle	drawPolygon	radial_half
_on_geodesic	drawPolygonFromTable	radial_scale
_warning	drawPolyline	randomPoint
acosh	drawPolylineFromTable	reflection
angle	drawRay	rotation
asinh	drawRayFromPoints	rotationFromPair
atanh	drawRayFromVector	shape_closed_line
automorphism	drawRegularPolygon	shape_euclidean_segment
automorphismFromPairs	drawRightAngle	shape_segment
automorphismSending	drawSegment	sinh
barycenter2	drawSegments	symmetry
circle_to_euclidean	drawSemicircle	symmetryAroundMidpoint
cosh	drawTangentAt	tangentVector
distance	drawTangentVector	tikzBegin
distance_to_geodesic	drawTriangle	tikzClearBuffer
distance_to_origin	endpoints	tikzEnd
drawAngle	endpoints_angle_bisector	tikzExport
drawAngleBisector	endpoints_perpendicular_bisector	tikzGetFirstLines
drawArc	exp_map	tikzPrintf
drawCircle	exp_map_at_origin	tikz_define_nodes
drawCircleRadius	fundamentalIdealTriangle	triangleCentroid
drawCircleThrough	fundamentalRightTriangle	triangleCircumcenter
drawCircumcircle	geodesic_data	triangleIncenter
drawHorocycle	interCC	triangleOrthocenter
drawIncircle	interLC	
drawLabeledPoint	interLL	
drawLine	interpolate	

Constants

Numbers : DRAW_EPS, DRAW_EPS_INV, DRAW_POINT_RADIUS, EPS, SCALE, tikzNbPicturesExported,

Strings : TIKZ_BEGIN_DISK, module, tikzOptions,

Tables : tikzBuffer,