

Cps 706 Final Project

A simple content distribution network.

Group #30 Members

- Frank Vumbaca
- Mitchell Mohorovich
- Yan Jedrasik

Usage

Compiling

- To compile the project, simply run `javac -d PROJECT_ROOT *.java` on the src directory, where `PROJECT_ROOT` can be an explicit, or relative path to the project root folder. This is so that the correct configuration assets are available at runtime.

Running

The application contains multiple sub-commands for each component of the project. After compiling, you can run each sub-application as follows:

- `java Main client LOCAL_DNS_IP`

Where `LOCAL_DNS_IP` is the IP address of the local DNS server

- `java Main dns config_dns.txt`

Where `config_dns.txt` is a file describing the initial DNS records for the server

- `java Main web [index.txt[F1.mp4[...]]]`

Where the passed in files make up the available content (index.txt is used for all requests to `/`)

NOTE: Default port configurations are loaded from `config.txt`. All outgoing requests are sent to the default ports.

To Run The demo, Run These Commands

- *machine 1 (hercdn.ca)*
 - `java Main web F1.mp4 F2.mp4 F3.mp4 F4.mp4 F5.mp4`
 - `java Main dns herdns.txt`
- *machine 2 (hiscdn.ca)*
 - `java Main web index.txt`
 - `java Main dns hisdns.txt`
- *machine 3 (local DNS)*
 - `java Main dns localdns.txt`
- *machine 4 (client)*
 - `java Main client LOCAL_DNS_IP`

where `LOCAL_DNS_IP` is the IP of the local DNS machine

Configuration Files

Pre-configured files for the demo:

- `config.txt` ***must be consistent across all connected instances - this defines the protocol ports**

```
1 | web 40295
2 | dns 40296
```

- `localdns.txt`

```
1 | hiscinema.com A 141.117.232.30
2 | www.hiscinema.com CNAME hiscinema.com
3 | hercdn.ca A 141.117.232.29
4 | www.hercdn.ca CNAME hercdn.ca
5 | hiscinema.com NS 141.117.232.30
6 | hercdn.ca NS 141.117.232.29
```

- `hisdns.txt`

```
1 | video.hercdn.ca V hercdn.ca
```

- `herdns.txt`

```
1 | video.hercdn.ca V hercdn.ca
```