

Crear una instancia de flujo de trabajo

Prerrequisitos

1. Ejecución de Zeebe Broker con punto final `localhost:26500` (predeterminado)
2. Ejecute el [ejemplo Implementar un flujo de trabajo](#)

WorkflowInstanceCreator.java

[Fuente en github](#)



```
/*
 * Copyright Camunda Services GmbH and/or licensed to Camunda Services GmbH
 * under
 * one or more contributor license agreements. See the NOTICE file distributed
 * with this work for additional information regarding copyright ownership.
 * Licensed under the Zeebe Community License 1.0. You may not use this file
 * except in compliance with the Zeebe Community License 1.0.
 */
package io.zeebe.example.workflow;

import io.zeebe.client.ZeebeClient;
import io.zeebe.client.ZeebeClientBuilder;
import io.zeebe.client.api.response.WorkflowInstanceEvent;

public class WorkflowInstanceCreator {

    public static void main(final String[] args) {
        final String broker = "127.0.0.1:26500";

        final String bpmnProcessId = "demoProcess";

        final ZeebeClientBuilder builder =
ZeebeClient.newClientBuilder().brokerContactPoint(broker).usePlaintext();

        try (ZeebeClient client = builder.build()) {

            System.out.println("Creating workflow instance");

            final WorkflowInstanceEvent workflowInstanceEvent =
                client
                    .newCreateInstanceCommand()
                    .bpmnProcessId(bpmnProcessId)
                    .latestVersion()
                    .send()
                    .join();

            System.out.println(
                "Workflow instance created with key: " +
workflowInstanceEvent.getWorkflowInstanceKey());
        }
    }
}
```