

bookmark-gt

Bookmark manager for Emacs

Daniel M. German

August 13, 2026

Contents

1	Install	2
2	Getting started	3
2.1	Master switch: <code>bookmark-gt-mode</code>	3
2.2	Opt-in modes	3
2.2.1	<code>bookmark-gt-auto-update-mode</code>	3
2.2.2	<code>bookmark-gt-default-tags-mode</code>	3
2.2.3	<code>bookmark-gt-browsel-tabs-mode</code>	4
3	User interface	4
3.1	The <code>*Bookmarks-gt List*</code> buffer	4
3.1.1	Columns	4
3.1.2	Keys	5
3.2	Jump reader: <code>bookmark-gt-jump</code>	5
3.2.1	Elisp signatures	6
3.3	Non-file bookmark types	7
3.3.1	URL bookmarks — <code>bookmark-gt-set-url</code>	7
3.3.2	Dired bookmarks — <code>bookmark-gt-handler-dired-jump</code>	7
3.3.3	Function bookmarks — <code>bookmark-gt-set-function</code>	7
3.3.4	Sequence bookmarks — <code>bookmark-gt-set-sequence</code>	8
3.3.5	File-type handlers — override the file-jump path per pattern	8
3.3.6	View bookmarks — save the list buffer’s current view	8
4	Setting bookmarks	8
4.1	Tag reader	8
4.2	Same-name policy	9
4.3	Relocate: change a bookmark’s target	9
5	In-file behaviors	10
5.1	In-buffer cycling	10
5.2	Per-bookmark highlighting	10
5.3	Region bookmarks	11

6	Trackers	11
6.1	Visit tracker	11
6.2	File-rename tracker	12
7	Extension API	12
7.1	Handler registry	12
7.2	Group registry	13
7.3	Extension points	13
8	Compatibility	14
8.1	Data compat with bookmark+	14
8.2	Migrating from bookmark+	14
9	Reference	15
9.1	Selected customization	15
10	Acknowledgements	15
11	License	16

A bookmark manager for Emacs, that replaces the the built-in `bookmark.el` inspired by `bookmark+`.

It supports most of `bookmark+`'s features: tags, non-file bookmark types, temporary bookmarks, bookmark highlighting, and others.

`bookmark-gt` is integrated with `consult`, `marginalia`, and `orderless`.

Bookmark files created with `bookmark-gt` can be read by the built-in `bookmark` package and by `bookmark+`. `bookmark-gt` can also read files created by either of those.

1 Install

Using `use-package` with a local directory

```
(use-package bookmark-gt
  :straight nil
  :load-path "~/emacs.d/modules/bookmark-gt"
  :bind (("C-x r m" . bookmark-gt-set)      ; supersede built-in bookmark-set
         ("C-x r l" . bookmark-gt-list)    ; supersede bookmark-bmenu-list
         ("C-x r b" . bookmark-gt-jump)    ; fuzzy jump reader
         ("C-x r u" . bookmark-gt-set-url)) ; new: bookmark a URL
  :config
  (bookmark-gt-mode 1))
```

Requires Emacs 30.1+. Soft-deps (loaded when present, package works without them):

- `marginalia` — bookmark completion annotator (`tags · type · path`).
- `consult` — jump reader UI (falls back to plain `completing-read`).
- `orderless` — enables the `,@type / ;tag` narrowing particles.
- `browse1` — required only for the browser-tabs feature. See below

2 Getting started

2.1 Master switch: `bookmark-gt-mode`

Global minor mode. When enabled, it installs:

- the interactive tag reader into `bookmark-gt-set`;
- the marginalia annotator into the `bookmark` completion category;
- the temp-bookmark filter on `bookmark-save` (temp records excluded from disk);
- the file-rename tracker on `rename-file` (see below).

Turning it off removes all of the above.

2.2 Opt-in modes

Three independent global minor modes, off by default. Enable each only if you use the feature.

2.2.1 `bookmark-gt-auto-update-mode`

Bookmarks carrying the `auto-update` alist property get their position refreshed to the visiting buffer's current point on every idle tick. Useful for e-readers, long-form documents, `pdf-tools` page tracking.

Triggers: an idle timer (`bookmark-gt-auto-update-interval`, default 60 s) plus `kill-buffer-hook` and `window-state-change-hook`. Also registered into the ephemeral refresh hook, so `g` in the list buffer or opening the jump reader triggers an immediate refresh.

Toggle the property on the row at point with `~` in the list buffer, or `M-x bookmark-gt-auto-update-toggle NAME`.

2.2.2 `bookmark-gt-default-tags-mode`

Seeds the tag reader on `bookmark-gt-set` with context-appropriate tags. Configured via a small DSL:

```
(setq bookmark-gt-default-tags "work")           ; single tag
(setq bookmark-gt-default-tags '("work" "urgent")) ; list
(setq bookmark-gt-default-tags                    ; function
  (lambda (record)
    (cond ((string-prefix-p "/proj/" (bookmark-gt-filename-of record))
           '("project"))
          ((eq (bookmark-gt-handler-type record) 'url)
           '("web"))
          (t nil))))
```

Errors in the function form are demoted to a warning; nothing is applied without user confirmation. The user always sees the defaults as prefill in the tag reader and can edit or clear them.

2.2.3 bookmark-gt-browsel-tabs-mode

Exposes the browser's open tabs as bookmarks (temporary — not saved to disk). Requires `browsel` to be installed and connected.

Refresh is on-demand, not on a timer:

- immediate refresh on mode enable;
- before every `bookmark-gt-jump` read;
- before opening the list buffer;
- on `g` (revert) in the list buffer;
- M-x `bookmark-gt-browsel-tabs-refresh` for a manual refresh.

Turning the mode off clears our tab records and unregisters the refresher. Records owned by other browsel-related packages (`browsel-tab-manager-bookmark-jump` etc.) are left alone.

The refresh loop suppresses per-tab hook execution and auto-save inside the batch — with 100+ tabs the whole refresh takes ~50 ms total (30 ms fetch + 20 ms store).

Customizable:

- `bookmark-gt-browsel-tabs-browsers` — list of browser clients to query, nil = all connected.
- `bookmark-gt-browsel-tabs-filter` — nil / regexp / predicate applied per tab before storing.

3 User interface

3.1 The *Bookmarks-gt List* buffer

M-x `bookmark-gt-list` opens the buffer. It is a `tabulated-list-mode` derivative — click a column header to sort, press `S` for column-at-point sort, and `s` (specific to `bookmark-gt`) to cycle the sort column through the marker and data columns.

3.1.1 Columns

Col	Header	Meaning
0	*	Selection: * if marked with <code>m</code> , <code>D</code> if flagged for deletion with <code>d</code> , blank else
1	~	Auto-update: ~ if the record carries the <code>auto-update</code> prop, blank else
2	t	Temp: <code>t</code> if the record carries <code>bmkp-temp</code> , blank else
3	Name	Truncated at <code>bookmark-gt-list-name-width</code> (default 32) with an ellipsis
4	Type	From the handler registry — File, URL, EWW, Dired, Info, Org, PDF, BrowserTab, Function, S
5	Group	Aggregate category — Web, File, Doc, Code, Media, Other
6	Tags	,-joined, truncated at <code>bookmark-gt-list-tags-width</code> (default 24)
7	Loc	<code>filename</code> , or the URL if non-file

The Name of a bookmark whose file no longer exists on disk renders with a strikethrough (`bookmark-gt-face-missing-file`). Remote (Tramp) paths are not probed — the existence check is local only.

3.1.2 Keys

Key	Action
RET	Jump
o	Jump in another window
C-o	Same as o
v	Preview in another window (leaves point in the list)
m	Mark row (numeric prefix: mark N rows down)
d	Flag row for deletion
x	Delete every flagged row (prompts for confirmation)
u	Unmark row
U	Unmark every row
~	Toggle auto-update on row
T	Toggle temp on row
H	Toggle display of temporary bookmarks in this buffer
r	Rename bookmark
R	Relocate (change filename or URL)
t e	Edit tags (editable comma-separated list; add and remove in one prompt)
t a	Add tags (sequential reader with completion; empty RET / M-RET ends)
t r	Remove tags (sequential reader; completion restricted to the row's tags)
a	Edit annotation
/	Filter (choose by-type / by-tag / by-name-regexp / unfilter)
s	Cycle sort column
g	Revert (refresh ephemeral sources first)
C-x C-s	Save the bookmark file ('bookmark-save')
i	Inspect record (pretty-print alist in a popup)
q	Quit

Selection marks are stored in a buffer-local hash keyed by record cons identity — they survive sort, revert, and after-hook re-renders.

3.2 Jump reader: bookmark-gt-jump

Uses `consult--read` when `consult` is loaded, falls back to `completing-read` otherwise. Both accept two narrowing particles when `orderless` is loaded:

- `,@TYPE` — narrow to bookmarks of TYPE (`url`, `eww`, `file`, `dired`, `info`, `org`, `pdf`, `browser-tab`, `magit`, `help`, `image`, `epub`, or any registered/derived type).
- `;TAG` — narrow to bookmarks carrying TAG.

Mid-read tag filter:

- `M-t` — add a tag filter and restart the read. Active filters are shown as labels in the prompt.
- `M-d` — pop the most recent tag filter.
- `M-D` — clear every active tag filter.

3.2.1 Emacs signatures

All three entry points take keyword arguments only:

```
(cl-defun bookmark-gt-jump
  (&key bookmark display-function bookmarks-list bookmarks-filter
    sort-by preselect))
```

```
(cl-defun bookmark-gt-jump-other-window
  (&key bookmark bookmarks-list bookmarks-filter sort-by preselect))
```

```
(cl-defun bookmark-gt-jump-tagged
  (&key tag bookmark bookmarks-list bookmarks-filter sort-by preselect))
```

- `:BOOKMARK` — bookmark name or record. When nil, prompt.
- `:DISPLAY-FUNCTION` — a function of one argument (a buffer); passed to ‘bookmark-jump’ as its display func.
- `:BOOKMARKS-LIST` — alist to use as the candidate pool. Defaults to ‘bookmark-alist’. Ignored when `:BOOKMARK` is supplied.
- `:BOOKMARKS-FILTER` — predicate on a record; a candidate is kept when the predicate returns non-nil. Ignored when `:BOOKMARK` is supplied.
- `:SORT-BY` — mru (by last-visited desc), visits (by visits desc), or nil (preserve pool order). Defaults to `bookmark-gt-jump-default-sort` (mru by default).
- `:PRESELECT` — positive integer. When set (and vertico is loaded), the reader positions the cursor on the N-th candidate via a one-shot minibuffer-setup hook. Useful for a "jump back to previous" workflow: with MRU sort and `:preselect 1`, RET selects the second-most-recent record.
- `:TAG` (required for `-tagged`) — string seeding the reader’s active tag filter.

Candidate row layout is customizable via `bookmark-gt-jump-candidate-format-function` (default: `bookmark-gt-jump-candidate-default`). A custom function receives the record and must return a propertized string with the `bookmark-gt-name`, `consult--type`, and (optional) `bookmark-gt-particles` text properties — see the default function’s docstring for the contract.

Examples:

```
;; Jump directly to a known bookmark
(bookmark-gt-jump :bookmark "my-bookmark")

;; Jump with a custom display function (other-frame etc.)
(bookmark-gt-jump :display-function #'switch-to-buffer-other-frame)

;; Prompt but only among file bookmarks
(bookmark-gt-jump :bookmarks-filter #'bookmark-gt-handler-file-p)

;; Prompt among a custom subset alist
```

```
(bookmark-gt-jump :bookmarks-list my-project-bookmarks)

;; Prompt among project files tagged "urgent"
(bookmark-gt-jump-tagged :tag "urgent"
                        :bookmarks-filter #'bookmark-gt-handler-file-p)
```

3.3 Non-file bookmark types

3.3.1 URL bookmarks — bookmark-gt-set-url

Interactive:

```
M-x bookmark-gt-set-url RET
URL: https://example.org RET
Bookmark name: Example RET
```

Elisp:

```
(bookmark-gt-set-url "https://example.org" "Example" '("web" "reference"))
```

The URL bookmark's handler (`bookmark-gt-handler-url-jump`) opens the URL via `browse-url`. It also throws `bookmark-gt-skip-post-handler` so the built-in post-handler flow does not pop up an annotation buffer moving focus from the browser back to Emacs.

3.3.2 Dired bookmarks — bookmark-gt-handler-dired-jump

The built-in `dired.el` does not provide a bookmark handler. `bookmark-gt` provides one that calls (`dired FILENAME`). Records migrated from `bookmark+` (`bmkp-jump-dired`) are still recognized as Dired type via the registry alias; you can migrate them off `bookmark+` by setting their `handler` property to `bookmark-gt-handler-dired-jump`.

3.3.3 Function bookmarks — bookmark-gt-set-function

A function bookmark stores a callable (a symbol or lambda) under the `function` alist key. Jumping invokes the callable.

Interactive:

```
M-x bookmark-gt-set-function RET
Function bookmark name: rebuild-project RET
Function to call on jump: my-project-rebuild RET
```

Elisp:

```
(bookmark-gt-set-function "rebuild" #'my-project-rebuild)
(bookmark-gt-set-function "flip-theme"
                        (lambda () (my-toggle-theme)))
```

3.3.4 Sequence bookmarks — bookmark-gt-set-sequence

A sequence bookmark stores a list of bookmark names under the `sequence` alist key. Jumping visits each in order via `bookmark-jump`.

Interactive: prompts for the sequence name, then reads existing bookmark names one at a time until you enter empty input.

Elisp:

```
(bookmark-gt-set-sequence "morning-workspace"
                          '("inbox" "todo.org" "calendar"))
```

3.3.5 File-type handlers — override the file-jump path per pattern

`bookmark-gt-file-type-handlers` is an alist mapping a filename regexp to a bookmark handler function. When jumping a file bookmark whose `filename` matches, the mapped function is called with the bookmark record instead of the built-in `find-file` path. The function's contract is the same as any 'bookmark.el' handler: one argument, the record.

Typical use: open certain file types with an external program instead of an Emacs buffer.

```
(defun my-mac-open (bookmark)
  "Open BOOKMARK's file with macOS's 'open' command."
  (call-process "open" nil 0 nil
    (bookmark-prop-get bookmark 'filename)))

(setq bookmark-gt-file-type-handlers
  '(("\\.pdf\\'" . my-mac-open)
    ("\\.\\(mp4\\|mkv\\)\\'" . my-mac-open)))
```

If the handler opens an external target and does not want the built-in post-jump popup, it should end with `(bookmark-gt-skip-post-handler 'file-type)`.

Entries are tried in list order; the first matching regexp wins. The advice on `bookmark-default-handler` is installed by `bookmark-gt-mode` and removed when the mode turns off.

3.3.6 View bookmarks — save the list buffer's current view

A view bookmark captures the presentation state of the `*Bookmarks-gt List*` buffer — active filters, sort key, and the show-temp toggle — under the `filters`, `sort-key`, and `show-temp` alist keys. Jumping opens the list buffer (if needed), restores the state, and redraws.

To save: open the list, set the filters/sort/show-temp you want, then M-x `bookmark-gt-set`. The list mode installs its own `bookmark-make-record-function`, so the standard `set` command captures a view record automatically — no dedicated command is needed. Marks and point are intentionally not saved; they are per-session, not part of the view.

Elisp: construct the record via `bookmark-gt-set-non-file` with handler `bookmark-gt-handler-view-jump` and the three props; see `bookmark-gt-list--make-record` for the shape.

4 Setting bookmarks

4.1 Tag reader

`bookmark-gt-tags-read` prompts for tags one at a time. Each prompt is a plain `completing-read` against every tag that currently appears in `bookmark-alist`, ordered most-recently-used first (based

on `bookmark-gt-tags-history`; completion history is the MRU signal).

Terminators:

- Empty RET — finish, return the accumulated list.
- M-RET — submit the current input (if non-empty), then finish.

Any non-empty RET accepts the current tag and prompts for another. The running accumulator is shown in the prompt as `~Tags [foo,bar]` (M-RET or empty RET to finish): `~`.

The reader is invoked by `bookmark-gt-set` when `bookmark-gt-prompt-for-tags-flag` is non-nil (default) and seeds itself with any tags provided by `bookmark-gt-default-tags-mode` or another `bookmark-gt-set-tag-reader-hook` contributor.

4.2 Same-name policy

Setting a bookmark whose name is already in use is not an error. The name the new record ends up stored under is determined by these rules, in order:

1. **Prefix-argument override.** When M-x `bookmark-gt-set` is called with a prefix argument (NO-OVERWRITE non-nil from Lisp), a <N> suffix is always appended. Same semantics as built-in `bookmark-set` with C-u.
2. **Update in place.** If `bookmark-gt-same-name-overwrite` is non-nil (the default) and the existing record has the same handler AND the same filename as the new one, the existing record is replaced in place. This is the "update this bookmark's location" case: re-setting `todo` inside `todo.org` when `todo` already points to `todo.org` moves the existing record's position to point.
3. **Shared name across records.** If `bookmark-gt-allow-duplicate-names` is non-nil (the default), the new record is stored under the literal name even when another record already uses it — two bookmarks in different files (or with different handlers) can share the same name. Example: a `todo` bookmark in each of several project files.
4. **Fallback.** With both flags off, any collision that isn't handled by rule 2 receives a <N> suffix.

Caveat on rule 3. Emacs's `bookmark-jump NAME` and `bookmark-get-bookmark NAME` return the first alist match. When two records share a name, only one is reachable that way; the others still appear in `bookmark-gt-list` and `bookmark-gt-jump` (both iterate the alist directly and distinguish records by the Location column). Set `bookmark-gt-allow-duplicate-names` to nil if name-based lookup matters more to you than shared names.

4.3 Relocate: change a bookmark's target

M-x `bookmark-gt-relocate NAME` changes where an existing bookmark points, dispatching on the record's shape:

- File records (a `filename` key) prompt via `read-file-name`; default is the current filename so a rename is a matter of editing. `position` is left unchanged — the common trigger is a file rename, and the offset is still valid.
- URL records (a `url` key: URL bookmarks, browser-tab bookmarks) prompt for the new URL via `read-string`.

- Records with neither key raise a `user-error`.

In the list buffer, `R` relocates the row's record. The after-hook fires so the list, highlight overlays, and any other observer refresh automatically.

For a genuinely new position within a different file, jump to the target, place point, and re-invoke `bookmark-gt-set` with the same name — the same-name-overwrite policy (above) updates `position` in place.

5 In-file behaviors

5.1 In-buffer cycling

Two autoloaded commands iterate over the bookmarks whose file matches the current buffer's file, sorted by position:

- `M-x bookmark-gt-cycle-next` — jump to the next bookmark position after point.
- `M-x bookmark-gt-cycle-prev` — jump to the previous one.

Both wrap around at the ends of the sequence. Print the bookmark's name via `message` so the destination bookmark is identified. No overlay dependency — cycling uses record data directly, so it works whether or not `bookmark-gt-highlight-enable` is on.

Records without a numeric `position` (e.g. Dired records) are skipped; bookmarks pointing at other files are ignored.

Convenient bindings (in your init):

```
(global-set-key (kbd "C-c n") #'bookmark-gt-cycle-next)
(global-set-key (kbd "C-c p") #'bookmark-gt-cycle-prev)
```

5.2 Per-bookmark highlighting

When `bookmark-gt-mode` is on, every file-visiting buffer gets an overlay per bookmark that points at that file. Overlays use `bookmark-gt-face-highlight` (inherits `hl-line` by default) and span:

- The bookmark's line, for point bookmarks.
- The whole region (from `position` line-start to `end-position` line-end), for region bookmarks.

Hovering shows the bookmark name via `help-echo`.

Triggers:

- `find-file-hook` creates overlays as files are opened.
- `bookmark-gt-set-after-hook` refreshes overlays after any mutation. Targeted single-file refresh when the mutation affects a specific record; full refresh only when a batch operation runs the hook with the `nil` sentinel.
- `bookmark-after-jump-hook` records the point after the jump in a buffer-local hash so records that carry no numeric `position` (e.g. org-heading bookmarks, whose target is resolved by `org-bookmark-heading-jump` at jump time) still get an overlay after the user visits them. The recorded position is consulted by `bookmark-gt-highlight--effective-position` as a fallback when `position` is absent.

Customization:

- `bookmark-gt-highlight-enable` (default `t`) — opt out. Set to `nil` to suppress highlighting even while the mode is on.
- `bookmark-gt-face-highlight` — face for the overlay. Rebind to a subtler / stronger color as you prefer.

Overlays are process-scoped display state; they are removed when the buffer is killed, and are cleared entirely when `bookmark-gt-mode` turns off. Nothing is written to disk. The post-jump position hash is likewise buffer-local and transient.

5.3 Region bookmarks

When `bookmark-gt-mode` is on and the region is active on M-x `bookmark-gt-set`, the record captures both anchors plus context strings so the region can be re-selected on jump:

- `position` = (`region-beginning`)
- `end-position` = (`region-end`)
- `front-context-region-string` = N characters preceding `end-position` (for re-anchoring)
- `rear-context-region-string` = N characters following `end-position`
- `front-context-string` / `rear-context-string` = the built-in standard re-anchor strings around the start

Alist-key names match `bookmark+` so records round-trip losslessly. The built-in `bookmark.el` ignores the extra keys and jumps to `position` only.

On jump, a hook on `bookmark-after-jump-hook` pushes the mark at `end-position` (adjusted by the delta between the record's raw `position` and the actual point after built-in re-anchoring) and activates it — the region reappears highlighted.

Customization:

- `bookmark-gt-use-region` (default `t`) — opt out of capture and restore. Records that already carry region info keep it; this flag only gates the set/restore paths.
- `bookmark-gt-region-context-size` (default 40) — chars of context captured around `end-position`.

6 Trackers

6.1 Visit tracker

When `bookmark-gt-mode` is on, an entry on `bookmark-after-jump-hook` increments each jumped bookmark's `visits` property by one and refreshes its `last-visited` prop to the current time. URL and browser-tab handlers throw `bookmark-gt-skip-post-handler` (which bypasses the hook), so they call `bookmark-gt-record-visit` at the end of their handler body — same effect.

Enables `:sort-by 'mru` and `:sort-by 'visits` in the jump reader for every bookmark type without user action.

Visit tracking does NOT bump `bookmark-alist-modification-count`, so a jump does not trigger an auto-save. Changes persist to disk at the next explicit `bookmark-save` (or on Emacs exit).

6.2 File-rename tracker

When `bookmark-gt-mode` is on, an `:around` on `rename-file` rewrites any bookmark whose `filename` matches the source path to the destination. Intercepts Dired renames (`R`) as well, since Dired uses `rename-file` internally.

Two guards:

- `bookmark-gt-track-renames` — user opt-out, default `t`. Set to `nil` to disable tracking entirely; the flag is read at call time so changes take effect immediately.
- `backup-file-name-p` on the destination — always skipped. Emacs's default save mode renames `ORIG` → `ORIG~` before writing new content; without this guard the bookmark would follow the rename and end up pointing at your backup file. (Bookmark+'s tracker has this bug; ours does not.)

Directory renames update only bookmarks whose `filename` equals the directory exactly. Children are NOT rewritten.

7 Extension API

7.1 Handler registry

`bookmark-gt-handler-alist` is a flat alist keyed by handler symbol. Each entry:

```
(HANDLER . (:type TYPE-SYMBOL :name STRING :group GROUP-SYMBOL
            :face FACE :narrow-char CHAR :doc STRING))
```

Multiple handler symbols may share the same `:type` (URL has three handler-symbol aliases, browser-tab has three, etc.). Entries are included for: file, URL, EWW, Dired, Info, Org, PDF, browser-tab, Magit, Help, Image, EPUB (nov.el).

Register a new handler (or an alias for an existing type):

```
(bookmark-gt-handler-register
 'my-custom-jump my-legacy-jump-handler)
(list :type 'custom :name "Custom" :group 'other
      :face 'bookmark-gt-face-file :narrow-char ?c
      :doc "My custom bookmark type."
      :preview #'my-preview-fn)) ; optional
```

The optional `:preview` key overrides what `bookmark-gt-list-preview` (bound to `TAB` in the list buffer) does for that handler. Called with the record; runs inside `save-selected-window` so it can pop up a preview buffer without moving point away from the list. When absent, preview falls back to `bookmark-jump-other-window` on the record's own jump handler — the current default. Useful for e.g. rendering a URL in an EWW buffer as preview while `RET` still opens the external browser.

Unknown handler symbols are auto-classified via a fallback that strips common suffixes (`-bookmark-jump-handler`, `-bookmark-jump`, `-jump-handler`, `--handle-bookmark`) and title-cases the leading segment. So `foo-bookmark-jump` shows up as type "Foo" without any registration. Its group defaults to `other`.

Type predicates: `bookmark-gt-handler-file-p`, `-url-p`, `-eww-p`, `-dired-p`, `-info-p`, `-org-p`, `-pdf-p`, `-browser-tab-p`. Each does `(eq (bookmark-gt-handler-type record) 'TYPE)`.

7.2 Group registry

Groups aggregate multiple types so users can filter or narrow by an aggregate category (e.g. "web" covers URL + EWW + browser-tab) rather than one type at a time.

Groups are DERIVED from the handler registry at classification time — they are not stored on the record, never written to disk.

Six built-in groups are provided:

Symbol	Name	Narrow char	Types
web	Web	w	url, eww, browser-tab
file	File	f	file, dired
doc	Doc	d	info, org, pdf, help, epub
code	Code	c	magit
media	Media	m	image
other	Other	o	catch-all for unregistered handlers

`bookmark-gt-group-alist` is the registry (group symbol → `:name/:narrow-char/:doc` plist). Register a new group:

```
(bookmark-gt-group-register
 'science '(:name "Sci" :narrow-char ?s
            :doc "Science / research bookmarks."))
```

The list buffer shows a **Group** column (after **Type**). The consult jump reader narrows by group — pressing **w** SPC shows every web bookmark regardless of type. Per-type filtering remains available via the `,@TYPE` orderless particle. Filter in the list via `/` → **by-group**.

Accessor: `(bookmark-gt-handler-group RECORD)` returns the group symbol (or **other** when the handler is unregistered).

7.3 Extension points

Every non-trivial mechanism has a documented extension point.

- `bookmark-gt-set-name-reader-hook` — refine the bookmark name before the interactive prompt. (`default-name` context) → string (first non-nil wins).
- `bookmark-gt-set-tag-reader-hook` — chained: each hook gets (`record seed-tags`) and returns new seed-tags. This is where `bookmark-gt-default-tags-mode` and the interactive tag reader register themselves.
- `bookmark-gt-set-after-hook` — runs on every mutation. The list buffer refreshes here; other observers can as well.
- `bookmark-gt-ephemeral-refresh-hook` — runs before jump, list open, and list revert. Ephemeral sources (`bookmark-gt-browsel-tabs-mode`, `bookmark-gt-auto-update-mode`) register into it.
- `bookmark-gt-filter-alist` — filter registry for the list buffer's `/` command.
- `bookmark-gt-sort-alist` — sort registry (includes name and type entries).

8 Compatibility

8.1 Data compat with bookmark+

By design, bookmark-gt reads and writes alist entries under the same keys bookmark+ uses so files round-trip both ways:

Key	Meaning
tags	List of tag strings
bmkp-temp	Temp-record marker
auto-update	Auto-tracking flag
visits	Visit count
last-visited	Last visit timestamp
created	Record creation timestamp
last-modified	Record last-mutation timestamp

Two shape differences we accommodate on read:

- Bookmark+ writes the placeholder string " - no file -" into `filename` for non-file records. `bookmark-gt-filename-of` treats it as nil. Bookmark-gt records omit `filename` entirely for non-file records.
- Bookmark+ URL records store the URL under `location`. Bookmark-gt writes it under `url`. Both are read by `bookmark-gt-url-of`.

8.2 Migrating from bookmark+

Records saved by bookmark+ carry handler symbols (`bmkp-jump-dired`, `bmkp-jump-url-browse`, `bmkp-jump-url-browse-other-window`, `bmkp-gt-browse-tabs-jump`) that are unbound when bookmark+ is not loaded. bookmark-gt registers these symbols as classification aliases so the list buffer's Type column and the jump reader's narrow menu work regardless — but jumping still calls `(funcall <symbol> record)` and fails when the function is not defined.

Fix once with `bookmark-gt-migrate`:

```
;; One-time; not autoloaded - load explicitly.
(require 'bookmark-gt-migrate)
;; Preview mutates 'bookmark-alist' in memory only.
(bookmark-gt-migrate-from-bookmark-plus)
;; Inspect via 'M-x bookmark-gt-list' - verify the migrated
;; rows show the expected Type and jump correctly - then commit:
(bookmark-save)
```

What the migration does per record:

- Rewrites the `handler` symbol to the bookmark-gt equivalent.
- For URL records, copies `location` to `url` (bookmark-gt's convention) and drops `location`.
- Strips bookmark+ bookkeeping props that have no bookmark-gt meaning: `bmkp-gt-load-index`, `buffer-name`, `dired-directory`, `dired-marked`, `dired-subdirs`, `dired-hidden-dirs`, `dired-switches`, `front-context-region-string`, `rear-context-region-string`, empty annotation, empty tags.

- Preserves `filename`, `position`, `front-context-string`, `rear-context-string`, `visits`, `last-visited`, `created`, `last-modified`.

Records already in `bookmark-gt` form (or plain file bookmarks with a `nil` handler) are left untouched. Keep a copy of the bookmark file before running.

9 Reference

9.1 Selected customization

Variable	Default	What it does
<code>bookmark-gt-list-name-width</code>	32	Character width of the Name column in <code>*Bookmarks-gt List*</code> .
<code>bookmark-gt-list-type-width</code>	12	Character width of the Type column.
<code>bookmark-gt-list-tags-width</code>	24	Character width of the Tags column.
<code>bookmark-gt-list-buffer-name</code>	<code>"*Bookmarks-gt List*"</code>	Name of the buffer opened by <code>M-x bookmark-gt-list</code> .
<code>bookmark-gt-list-selection-mark</code>	<code>?*</code>	Character shown in the mark column for the selected record.
<code>bookmark-gt-list-deletion-mark</code>	<code>?D</code>	Character shown in the mark column for the deleted record.
<code>bookmark-gt-list-default-show-temp</code>	<code>t</code>	Whether new list buffers show temporary records.
—	—	(View bookmarks: no defcustom; save via <code>bookmark-gt-save</code> .)
<code>bookmark-gt-jump-name-max-width</code>	40	Character width at which the jump reader wraps.
<code>bookmark-gt-jump-default-sort</code>	<code>'mru</code>	Sort order used by <code>bookmark-gt-jump</code> when no <code>bookmark-gt-jump-sort</code> is set.
<code>bookmark-gt-auto-update-interval</code>	60	Seconds of idle time between ticks of <code>bookmark-gt-auto-update</code> .
<code>bookmark-gt-track-renames</code>	<code>t</code>	When non- <code>nil</code> , <code>rename-file</code> rewrites any bookmark file.
<code>bookmark-gt-default-tags</code>	<code>nil</code>	Under <code>bookmark-gt-default-tags-mode</code> , the tags to show.
<code>bookmark-gt-prompt-for-tags-flag</code>	<code>t</code>	Whether the tag reader prompts on bookmark selection.
<code>bookmark-gt-same-name-overwrite</code>	<code>t</code>	When a new bookmark's name matches an existing one, whether to overwrite.
<code>bookmark-gt-allow-duplicate-names</code>	<code>t</code>	Allow two records to share the same literal name.
<code>bookmark-gt-highlight-enable</code>	<code>t</code>	Per-bookmark line overlays in file-visiting mode.
<code>bookmark-gt-file-type-handlers</code>	<code>nil</code>	Alist mapping filename regexp to a handler.
<code>bookmark-gt-browsel-tabs-browsers</code>	<code>nil</code>	List of browsel browser client names to query.
<code>bookmark-gt-browsel-tabs-filter</code>	<code>nil</code>	Filter applied to each fetched tab before it is displayed.

10 Acknowledgements

`bookmark-gt` owes a substantial debt to Drew Adams and his `bookmark+` package, both in design and in code. Nearly every feature `bookmark-gt` provides — tags, non-file bookmark types (URL, EWW, region bookmarks), temporary bookmarks, visit tracking, per-bookmark highlighting, tag-driven filtering, the file-rename tracker — was first introduced in `bookmark+`.

Concretely reused:

- **Handler bodies.** The URL bookmark handler (`bookmark-gt-handler-url-jump`) and the Dired handler (`bookmark-gt-handler-dired-jump`) were copied from `bookmark+`'s corresponding handlers (`bmkp-jump-url-browse` and `bmkp-jump-dired`) and lightly adapted — same jump semantics, same record-shape expectations, minor changes to fit `bookmark-gt`'s registry and its `bookmark-gt-skip-post-handler` throw convention.
- **Record schema.** The on-disk alist keys — `tags`, `bmkp-temp`, `auto-update`, `visits`, `last-visited`, `location` (URL alias), `front-context-region-string` / `rear-context-region-string` (re-

gion bookmarks), and the " - no file -" filename placeholder for non-file records — are all adopted from bookmark+'s format verbatim so bookmark files round-trip in either direction without data loss.

`bookmark-gt` is a rewrite with different architectural choices (no advice on other packages, a single registry per axis, tabulated-list-mode instead of custom rendering), not a fork. But the user-visible features, the design ideas, and the handler code included in this package all originate from Drew's work.

11 License

GPL-3.0-or-later. See `LICENSE`.