

Parameter estimation of partial differential equations via neural networks

Alexander Glushko, Dmitry I. Kabanov

23 June 2019

We are interested in applying neural networks to the problem of parameter estimation of partial differential equations from given observations. Precisely, we are given data $\{D_i\} = \{t_i, x_i, u_i\}, i = 1, \dots, N$ that are observed from the solution of partial differential equation of the form:

$$u_t + \mathcal{N}(u) = 0, \quad (1)$$

where $u = u(t, x)$ is the solution of the equation, subscript t denotes differentiation with respect to time, $\mathcal{N}(u; \lambda)$ is a nonlinear algebraic-differential operator, λ is a vector of parameters. The goal is to estimate λ from the observations $\{D_i\}$ via simultaneous training of neural networks $u(x, t)$ and

$$f(t, x; \lambda) = u_t + \mathcal{N}(u) \quad (2)$$

via training procedure defined by minimizing the mean square error (MSE)

$$\text{MSE} = \text{MSE}_u + \text{MSE}_f, \quad (3)$$

where

$$\text{MSE}_u = \frac{1}{N} \sum_{i=1}^N [u(t_i, x_i) - u_i]^2, \quad \text{MSE}_f = \frac{1}{N} \sum_{i=1}^N [f(t_i, x_i)]^2. \quad (4)$$

As a concrete example, we consider linear heat equation

$$u_t - \lambda u_{xx} - g(t, x) = 0 \quad (5)$$

with one scalar sought-for parameter λ and given source function $g(t, x)$.

As a more difficult example, we consider viscous Burgers' equation

$$u_t + \lambda_1 u u_x - \lambda_2 u_{xx} = 0, \quad x \in [-1; 1], t \in [0, 1] \quad (6)$$

with sought-for parameter $\lambda = (\lambda_1, \lambda_2)^T$. This equation is nonlinear and serves as a prototype of the governing equations of fluid dynamics. It is known that the solutions of this equation may develop sharp gradients in finite time even for smooth initial condition.