
OPTALG Documentation

Release 1.1.1

Tomas Tinoco De Rubira

February 11, 2017

CONTENTS

1	Getting Started	3
1.1	Download	3
1.2	Installation	3
1.3	Example	3
2	Optimization Solvers	5
2.1	NR	5
2.2	IQP	5
2.3	LCCP	7
2.4	AugL	7
2.5	Ipopt	7
3	API Reference	9
3.1	Linear Solvers	9
3.2	Optimization Problems	10
3.3	Optimization Solvers	11
4	Indices and tables	15
	Python Module Index	17
	Python Module Index	19
	Index	21

Welcome! This is the documentation for OPTALG, last updated February 11, 2017.

What is OPTALG?

OPTALG is a Python package that provides algorithms, wrappers, and tools for solving large and sparse optimization problems.

License

OPTALG is released under the BSD 2-clause license.

Contact

- [Tomas Tinoco De Rubira](#)

Documentation Contents

GETTING STARTED

This section describes how to get started with OPTALG. In particular, it covers required packages, installation, and provides a quick example showing how to use this package.

- **Numpy** ($\geq 1.8.2$)
- **Scipy** ($\geq 0.13.3$)
- **Dill** ($\geq 0.2.5$)
- **MUMPS** ($= 4.10$) (optional)
- **IPOPT** ($\geq 3.12.6$) (optional)

1.1 Download

The latest version of OPTALG can be downloaded from <https://github.com/ttinoco/OPTALG>.

1.2 Installation

The OPTALG Python module can be installed using:

```
> sudo -E python setup.py install
```

from the root directory of the package. If **MUMPS** is not available, then the option `--no_mumps` should be added to the above command. If **IPOPT** is not available, then the option `--no_ipopt` should be added to the above command. Otherwise, you need to define an environment variable `IPOPT` such that the directories `IPOPT/lib` and `IPOPT/include/coin` contain the libraries and header files, respectively, needed by **IPOPT**.

To test, first execute the command:

```
> python setup.py build_ext --inplace
```

with `--no_mumps` or `--no_ipopt` if necessary, and then `nosetests -s -v`.

1.3 Example

As a quick example of how to use OPTALG, consider the task of solving a quadratic program. This can be done as follows:

>>> coming soon

OPTIMIZATION SOLVERS

In OPTALG, optimization solvers are objects of type `OptSolver`, and optimization problems are objects of type `OptProblem`, which represents general problems of the form

$$\begin{aligned} &\text{minimize} && \varphi(x) \\ &\text{subject to} && Ax = b && : \lambda \\ & && f(x) = 0. && : \nu \\ & && l \leq x \leq u. && : \pi, \mu \end{aligned}$$

Before solving a `problem` with a specific solver, the solver parameters can be configured using the method `set_parameters()`. Then, the `solve()` method can be invoked with the `problem` to be solved as its argument. The status, optimal primal variables, and optimal dual variables can be extracted using the class methods `get_status()`, `get_primal_variables()`, and `get_dual_variables()`, respectively.

2.1 NR

This solver, which corresponds to the class `OptSolverNR`, solves problems of the form

$$\begin{aligned} &\text{find} && x \\ &\text{subject to} && Ax = b \\ & && f(x) = 0. \end{aligned}$$

using the Newton-Raphson algorithm. It requires the number of variables to be equal to the number of constraints.

2.2 IQP

This solver, which corresponds to the class `OptSolverIQP`, solves convex quadratic problems of the form

$$\begin{aligned} &\text{minimize} && \frac{1}{2}x^T Hx + g^T x \\ &\text{subject to} && Ax = b && : \lambda \\ & && l \leq x \leq u. && : \pi, \mu \end{aligned}$$

using an interior point method. Quadratic problems solved with this solver must be instances of the class `QuadProblem`, which is a subclass of `OptProblem`. The following example shows how to solve the quadratic

problem

$$\begin{array}{ll}\text{minimize} & 3x_1 - 6x_2 + 5x_1^2 - 2x_1x_2 + 5x_2^2 \\ \text{subject to} & x_1 + x_2 = 1 \\ & 0.2 \leq x_1 \leq 0.8 \\ & 0.2 \leq x_2 \leq 0.8\end{array}$$

using `OptSolverIQP`:

```
>>> import numpy as np
>>> from optalg.opt_solver import OptSolverIQP, QuadProblem

>>> g = np.array([3., -6.])
>>> H = np.array([[10., -2],
...              [-2., 10]])

>>> A = np.array([[1., 1.]])
>>> b = np.array([1.])

>>> u = np.array([0.8, 0.8])
>>> l = np.array([0.2, 0.2])

>>> problem = QuadProblem(H, g, A, b, l, u)

>>> solver = OptSolverIQP()

>>> solver.set_parameters({'quiet': True,
...                       'tol': 1e-6})

>>> solver.solve(problem)

>>> print solver.get_status()
solved
```

Then, the optimal primal and dual variables can be extracted, and feasibility and optimality can be checked as follows:

```
>>> x = solver.get_primal_variables()
>>> lam, nu, mu, pi = solver.get_dual_variables()

>>> print x
[ 0.20  0.80 ]

>>> print x[0] + x[1]
1.00

>>> print l <= x
[ True  True ]

>>> print x <= u
[ True  True ]

>>> print pi
[ 9.00e-01  1.80e-06 ]

>>> print mu
[ 1.80e-06  9.00e-01 ]

>>> print np.linalg.norm(g+np.dot(H, x)-np.dot(A.T, lam)+mu-pi)
1.25e-15
```

```
>>> print np.dot(mu, u-x)
2.16e-06

>>> print np.dot(pi, x-l)
2.16e-06
```

2.3 LCCP

This solver, which corresponds to the class `OptSolverLCCP`, solves convex linearly-constrained problems of the form

$$\begin{array}{ll} \text{minimize} & \varphi(x) \\ \text{subject to} & Ax = b \quad : \lambda \\ & l \leq x \leq u. \quad : \pi, \mu \end{array}$$

using an interior point method.

2.4 AugL

This solver, which corresponds to the class `OptSolverAugL`, solves optimization problems of the form

$$\begin{array}{ll} \text{minimize} & \varphi(x) \\ \text{subject to} & Ax = b \quad : \lambda \\ & f(x) = 0. \quad : \nu \end{array}$$

using an Augmented Lagrangian algorithm. It requires the objective function to be strongly convex.

2.5 Ipopt

This is a Python wrapper of the interior-point solver `IPOPT`. It corresponds to the class `OptSolverIpopt`, and solves optimization problems of the form

$$\begin{array}{ll} \text{minimize} & \varphi(x) \\ \text{subject to} & Ax = b \quad : \lambda \\ & f(x) = 0. \quad : \nu \\ & l \leq x \leq u. \quad : \pi, \mu \end{array}$$

API REFERENCE

3.1 Linear Solvers

`optalg.lin_solver.new_linsolver` (*name*, *prop*)

Creates a linear solver.

Parameters *name* : string

prop : string

Returns *solver* : `LinSolver`

class `optalg.lin_solver.lin_solver.LinSolver` (*prop*=*'unsymmetric'*)

Linear solver class.

Parameters *prop* : {`symmetric`, `unsymmetric`}

analyze (*A*)

Analyzes structure of *A*.

Parameters *A* : matrix

analyzed = `None`

Flag that specifies whether the matrix has been analyzed.

factorize (*A*)

Factorizes *A*.

Parameters *A* : matrix

factorize_and_solve (*A*, *b*)

Factorizes *A* and solves $Ax=b$.

Returns *x* : vector

is_analyzed ()

Determine whether the matrix has been analyzed.

Returns *flags* : {`True`, `False`}

prop = `None`

Linear system property {`'symmetric'`, `'unsymmetric'`}.

solve (*b*)

Solves system $Ax=b$.

Parameters *b*: vector :

Returns *x* : vector

class `optalg.lin_solver.mumps.LinSolverMUMPS` (*prop='unsymmetric'*)
Linear solver based on MUMPS.

class `optalg.lin_solver.superlu.LinSolverSUPERLU` (*prop='unsymmetric'*)
Linear solver based on SuperLU.

3.2 Optimization Problems

class `optalg.opt_solver.problem.OptProblem`
Class for representing general optimization problems.

A = None
Matrix for linear equality constraints

H_combined = None
Linear combination of Hessians of nonlinear constraints

Hphi = None
Objective function Hessian (lower triangular)

J = None
Jacobian of nonlinear constraints

b = None
Right-hand side for linear equality constraints

combine_H (*coeff, ensure_psd=False*)
Forms and saves a linear combination of the individual constraint Hessians.

Parameters *coeff* : vector

ensure_psd : {True, "False"}

eval (*x*)
Evaluates the objective value and constraints at the give point.

Parameters *x* : vector

f = None
Nonlinear equality constraint function

get_num_linear_equality_constraints ()
Gets number of linear equality constraints.

Returns *num* : int

get_num_nonlinear_equality_constraints ()
Gets number of nonlinear equality constraints.

Returns *num* : int

get_num_primal_variables ()
Gets number of primal variables.

Returns *num* : int

gphi = None
Objective function gradient

l = None
Lower limits

lam = None
Lagrange multipliers for linear equality constraints

mu = None
Lagrange multipliers for upper limits

nu = None
Lagrange multipliers for nonlinear equality constraints

phi = None
Objective function value

pi = None
Lagrange multipliers for lower limits

show ()
Displays information about the problem.

u = None
Upper limits

x = None
Initial point

class optalg.opt_solver.problem_quad.**QuadProblem** (*H, g, A, b, l, u, x=None, lam=None, mu=None, pi=None*)

Quadratic program class.

Parameters **H** : symmetric matrix

g : vector

A : matrix

l : vector

u : vector

x : vector

3.3 Optimization Solvers

class optalg.opt_solver.opt_solver.**OptSolver**
Optimization solver class.

add_callback (*c*)
Adds callback function to solver.

Parameters **c** : Function

add_termination (*t*)
Adds termination condition to solver.

Parameters **t** : Function

callbacks = None
List of callback functions.

fdata = None
Function data container.

get_dual_variables ()
Gets dual variables.

Returns lam : vector

nu : vector

mu : vector

pi : vector

get_error_msg()
Gets solver error message.

Returns message : string

get_iterations()
Gets number of iterations.

Returns iters : int

get_primal_variables()
Gets primal variables.

Returns variables : ndarray

get_results()
Gets results.

Returns results : dictionary

get_status()
Gets solver status.

Returns status : string

info_printer = None
Information printer (function).

is_status_solved()
Determines whether the solver solved the given problem.

Returns flag : {True, False}

line_search(*x, p, F, GradF, func, smax=inf*)
Finds steplength along search direction *p* that satisfies the strong Wolfe conditions.

Parameters *x* : current point (ndarray)

p : search direction (ndarray)

F : function value at *x* (float)

GradF : gradient of function at *x* (ndarray)

func : function of *x* that returns function object with attributes *F* and *GradF* (function)

smax : maximum allowed steplength (float)

Returns s : steplength that satisfies the Wolfe conditions (float).

parameters = None
Parameters dictionary.

reset()
Resets solver data.

set_error_msg(msg)
Sets solver error message.

Parameters msg : string

set_info_printer (*printer*)
Sets function for printing algorithm progress.

Parameters **printer** : Function.

set_parameters (*parameters*)
Sets solver parameters.

Parameters **parameters** : dict

set_status (*status*)
Sets solver status.

Parameters **status** : string

solve (*problem*)
Solves optimization problem.

Parameters **problem** : OptProblem

terminations = None
List of termination conditions.

class optalg.opt_solver.nr.**OptSolverNR**
Newton-Raphson algorithm.

class optalg.opt_solver.iqp.**OptSolverIQP**
Interior-point quadratic program solver.

class optalg.opt_solver.lccp.**OptSolverLCCP**
Interior-point solver for linearly-constrained convex programs.

class optalg.opt_solver.augl.**OptSolverAugL**
Augmented Lagrangian algorithm.

class optalg.opt_solver.ipopt.**OptSolverIpopt**
Interior point nonlinear optimization algorithm.

INDICES AND TABLES

- *genindex*
- *modindex*
- *search*

O

`optalg`, 1

O

`optalg`, 1

A

A (optalg.opt_solver.problem.OptProblem attribute), 10
 add_callback() (optalg.opt_solver.opt_solver.OptSolver method), 11
 add_termination() (optalg.opt_solver.opt_solver.OptSolver method), 11
 analyze() (optalg.lin_solver.lin_solver.LinSolver method), 9
 analyzed (optalg.lin_solver.lin_solver.LinSolver attribute), 9

B

b (optalg.opt_solver.problem.OptProblem attribute), 10

C

callbacks (optalg.opt_solver.opt_solver.OptSolver attribute), 11
 combine_H() (optalg.opt_solver.problem.OptProblem method), 10

E

eval() (optalg.opt_solver.problem.OptProblem method), 10

F

f (optalg.opt_solver.problem.OptProblem attribute), 10
 factorize() (optalg.lin_solver.lin_solver.LinSolver method), 9
 factorize_and_solve() (optalg.lin_solver.lin_solver.LinSolver method), 9
 fdata (optalg.opt_solver.opt_solver.OptSolver attribute), 11

G

get_dual_variables() (optalg.opt_solver.opt_solver.OptSolver method), 11
 get_error_msg() (optalg.opt_solver.opt_solver.OptSolver method), 12
 get_iterations() (optalg.opt_solver.opt_solver.OptSolver method), 12

get_num_linear_equality_constraints() (optalg.opt_solver.problem.OptProblem method), 10
 get_num_nonlinear_equality_constraints() (optalg.opt_solver.problem.OptProblem method), 10
 get_num_primal_variables() (optalg.opt_solver.problem.OptProblem method), 10
 get_primal_variables() (optalg.opt_solver.opt_solver.OptSolver method), 12
 get_results() (optalg.opt_solver.opt_solver.OptSolver method), 12
 get_status() (optalg.opt_solver.opt_solver.OptSolver method), 12
 gphi (optalg.opt_solver.problem.OptProblem attribute), 10

H

H_combined (optalg.opt_solver.problem.OptProblem attribute), 10
 Hphi (optalg.opt_solver.problem.OptProblem attribute), 10

I

info_printer (optalg.opt_solver.opt_solver.OptSolver attribute), 12
 is_analyzed() (optalg.lin_solver.lin_solver.LinSolver method), 9
 is_status_solved() (optalg.opt_solver.opt_solver.OptSolver method), 12

J

J (optalg.opt_solver.problem.OptProblem attribute), 10

L

l (optalg.opt_solver.problem.OptProblem attribute), 10
 lam (optalg.opt_solver.problem.OptProblem attribute), 10
 line_search() (optalg.opt_solver.opt_solver.OptSolver method), 12
 LinSolver (class in optalg.lin_solver.lin_solver), 9

LinSolverMUMPS (class in `optalg.lin_solver.mumps`), 9
LinSolverSUPERLU (class in `optalg.lin_solver.superlu`),
10

M

`mu` (`optalg.opt_solver.problem.OptProblem` attribute), 11

N

`new_linsolver()` (in module `optalg.lin_solver`), 9
`nu` (`optalg.opt_solver.problem.OptProblem` attribute), 11

O

`optalg` (module), 1
`OptProblem` (class in `optalg.opt_solver.problem`), 10
`OptSolver` (class in `optalg.opt_solver.opt_solver`), 11
`OptSolverAugL` (class in `optalg.opt_solver.augl`), 13
`OptSolverIpopt` (class in `optalg.opt_solver.ipopt`), 13
`OptSolverIQP` (class in `optalg.opt_solver.iqp`), 13
`OptSolverLCCP` (class in `optalg.opt_solver.lccp`), 13
`OptSolverNR` (class in `optalg.opt_solver.nr`), 13

P

`parameters` (`optalg.opt_solver.opt_solver.OptSolver` attribute), 12
`phi` (`optalg.opt_solver.problem.OptProblem` attribute), 11
`pi` (`optalg.opt_solver.problem.OptProblem` attribute), 11
`prop` (`optalg.lin_solver.lin_solver.LinSolver` attribute), 9

Q

`QuadProblem` (class in `optalg.opt_solver.problem_quad`),
11

R

`reset()` (`optalg.opt_solver.opt_solver.OptSolver` method),
12

S

`set_error_msg()` (`optalg.opt_solver.opt_solver.OptSolver` method), 12
`set_info_printer()` (`optalg.opt_solver.opt_solver.OptSolver` method), 12
`set_parameters()` (`optalg.opt_solver.opt_solver.OptSolver` method), 13
`set_status()` (`optalg.opt_solver.opt_solver.OptSolver` method), 13
`show()` (`optalg.opt_solver.problem.OptProblem` method),
11
`solve()` (`optalg.lin_solver.lin_solver.LinSolver` method), 9
`solve()` (`optalg.opt_solver.opt_solver.OptSolver` method),
13

T

`terminations` (`optalg.opt_solver.opt_solver.OptSolver` attribute), 13

U

`u` (`optalg.opt_solver.problem.OptProblem` attribute), 11

X

`x` (`optalg.opt_solver.problem.OptProblem` attribute), 11