

PASO 1:

```
dmme@debian: ~  
Copyright (c) 2000, 2018, Oracle, MariaDB Corporation AB and others.  
Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.  
MariaDB [(none)]> CREATE DATABASE vulnerable_db;  
Query OK, 1 row affected (0.007 sec)  
  
MariaDB [(none)]> USE vulnerable_db  
Database changed  
MariaDB [vulnerable_db]> CREATE TABLE usuarios (  
    -> id INT AUTO_INCREMENT PRIMARY KEY, nombre_usuario VARCHAR(50),  
    -> contrasena VARCHAR(50) );  
Query OK, 0 rows affected (0.026 sec)  
  
MariaDB [vulnerable_db]> INSERT INTO usuarios (nombre_usuario, contrasena) VALUES ('admin', '1234');  
Query OK, 1 row affected (0.005 sec)  
  
MariaDB [vulnerable_db]> INSERT INTO usuarios (nombre_usuario, contrasena) VALUES ('user', 'passwd');  
Query OK, 1 row affected (0.004 sec)
```

PASO 2:

```
root@debian:~# cd /var/www/html/  
root@debian:/var/www/html# touch login.php  
root@debian:/var/www/html# nano login.php  
root@debian:/var/www/html#
```

```
GNU nano 8.4 login.php
<?php
$conn = new mysqli('localhost', 'root', 'vulnerable_db');
if ($conn->connect_error) {
    die("Connection failed: ". $conn->connect_error);
}
if ($_SERVER['REQUEST_METHOD'] == 'POST') {

    $usuario = $_POST['usuario'];
    $contrasena = $_POST['contrasena'];

    $sql = "SELECT * FROM usuarios WHERE nombre_usuario='$usuario' AND contrasena="
    $result = $conn->query($sql);

    if ($result->num_rows > 0) {
        echo "Login exitoso";
    } else {
        echo "Credenciales invalidas";
    }
}
?>

<form method="POST" action="login.php">
    Usuario: <input type="text" name="usuario"><br>
    Contraseña: <input type="password" name="contraseña"><br>
    <input type="submit" value="Ingresar">
</form>
```

PASO 3:



