





Sector 3 Sector 2 Sector 1

20W Stealth (Indoor or Outdoor)









Sector 3


Sector 2





Option 2 – Lancaster
Outdoor 20W Stealth


Outdoor 20W Stealth No-L18


BB6630 4G/5G (VF)














BB6630 4G (VF)



Indoor or Outdoor:

20W Low 20W Low L18 20W Low UNLR 20W Low Non-RRU 20W BB to 20W Low ULNR







Items 80-85 - RPM 777 700/00130 (RXA I/O – RXB I/O)






BB6630 4G (VF)








Sector 3


Sector 2



























Signal connections for GU900 12W/20W (3-sector)

Items 80-85 - RPM 777 700/00130 (RXA I/O - RXB I/O)

Sector 3

Sector 2




Signal connections for GU900 12W (2-sector)


Items 80-83 - RPM 777 700/00130 (RXA I/O – RXB I/O)








Signal connections for 5G 8x8 (TEF)






Signal connections for 5G M-MiMO (TEF)











Signal connections for 5G 8x8 (MoRAN)

Sector 3


Sector 2



Signal connections for 5G M-MiMO (MoRAN)



Transmission connections For MoRAN




CABLE INSTRUCTIONS

10G Optic (TN B-TN A): RPM 253 3512/2000

Ethernet cable (TN C-TN D): RPM 777 341/01400

IDLE cable (IDL A-IDL A) & (IDL B-IDL B): RPM 777 417/00800



Signal connections for GU900 20W (3-sector) Low/Stealth/Small UL


Items 80-85 - RPM 777 700/00130 (RXA I/O – RXB I/O)








Telefonica Beacon3 SIU connectivity



In some configs, DUW U9 is connected via optical (GE3 on SIU and TN-B on DUW)



Internal power cabling

Pos.	Connections	Qty.	Product No.	
1	PCU AC 06 - PSU AC in 6, 7	2	Included in PCU AC	
2	PCU AC 06 outlet - PSU AC in 4, 5	2	RPM 777 270/01000	
3	PCU AC 06 - PSU AC in 1, 2, 3	3	Included in PCU AC	
4	AC heater — SCU (Heater A - see Figure 6)	1	Included in AC heater	
5	AC heater — PCU AC 06: AC out	1		
6	PCF 01 03 - BFU	2	RPM 777 171/01300	
	(Temperature sensor cable)			
7	PCF 01 03 - BFU	2	RPM 777 299/01300 ⁽¹⁾	
			RPM 777 343/01200 ⁽²⁾	
8	BFU — Battery string	2		
	(Temperature sensor cable)		RPM 777 346/01000	
9	BFU — Battery string	2	RPM 777 161 /01000	
	(Battery cable)			


- (1) Valid for only BFU 01 01.
- (2) Valid for BFU 01 01, BFU 01 02 and BFU 01 03.

Notes:

RBS 6102 with PCU AC 06 and seven PSUs doesn't support AC heater. The AC port on the PSU AC, previously used for the AC heater, can be used to power the 7th PSU.

Leave the AC heater disconnected on site for now and this needs to be replaced with a DC heater for future upgrades as per availability in stock.

The BFU-2 will not be connected to the internal battery as part of the upgrade therefore the cables are not included in BoM.



Pos. Connections SHU 02 01 Qty. Product No. 1 First SHU 02 01: A1 – SCU: EC-bus A 1 RPM 777 01/00400 2 Second SHU 02 01: A1 – SCU EC-bus B 1 RPM 777 01/01000 3 Power 6306: EC Ext – SCU EC-bus E 1 RPM 777 562/L

SHU Cabling & Port Configuration

SHU 1

Port A	Used by	Port B	Used by
A1	SCU (EC A)	B1	DU-1/ Baseband-1
A2	PDU-1	B2	PDU-2
A3	PSU-1	B3	PSU-2
A4	PSU-3	B4	PSU-4/PDU-6
A5	DU-2/ Baseband-2	B5	BFU-1
A6	DU-3/ Baseband-3	B6	PSU-5/PDU-7
A7	DU-4/ Baseband-4	B7	PDU-3/PSU-7
A8	PDU-4/PSU-8	B8	-

SHU 2

Port A	Used by	Port B	Used by
A1	SCU (EC B)	B1	-
A2	DU-5/ Baseband-5	B2	PSU-6
A3	DU-6/ Baseband-6	B3	PDU-5
A4	-	B4	PSU-4/PDU-6
A5	BFU-2	B5	PDU-8
A6	-	B6	PSU-5/PDU-7
A7	-	B7	PDU-3/PSU-7
A8	PDU-4/PSU-8	B8	-