

Upgrading and uninstalling

Replacing an existing installation, and taking SD off the machine.

This page continues Installing SD Core.

Upgrading

Installing a new release over an existing one updates your database.

REPLACED	KEPT, AND NOT TOUCHED
the catalogue and compiled programs	your accounts and their passwords
the BASIC source	the private catalogue
the messages and include records	which Windows users are linked to which SD accounts
the VOC templates and library routines	the commands each account may run
the SDSYS BP programs	your print queue and held reports
terminfo, the licence, the contributor list	everything under your own accounts, and sd.conf

Anything SD created while it was running — your VOC included — is left exactly as it is.

The dictionaries are brought up to date for you. Upgrading reapplies the dictionary definitions the release ships: it adds and updates the entries SD ships and leaves alone any you added. If that step cannot run, the installer says so at the end rather than finishing quietly, and upgrade-dicts.log in C:\ProgramData\SD says what happened.

Every account's VOC is brought up to date for you. The installer runs update.accounts all, which walks every registered account, so a command this release adds can be typed in accounts that already existed. This did not happen before W1.0-0: an upgrade replaced the shipped files and no existing account — including the system account — ever gained a new verb.

To refresh one account by hand afterwards, update.accounts in that account updates it and offers the rest.

Two limits are worth knowing before you rely on it.

SD only ever adds records to a VOC, never removes them. An account created before a verb was withdrawn keeps it. `update.accounts` cannot be relied on to take something away.

A record you have customised can be held back on purpose. Put `[locked]` in field 1 after the type code and the upgrade leaves that record alone, naming it in a message so you know what was withheld — and therefore which corrections this release made that you have not taken. Verbs are the exception: a locked verb is updated anyway, and you are told which. The administrator documentation covers it under *Accounts and security*.

Uninstalling

It is the standard Windows uninstall — Settings ► Apps, or `unins000.exe`.

The default does not touch your accounts, the database or the configuration. Inno removes only what it installed and only removes a directory if it is empty, so everything the running system created is invisible to it.

Removing the data is a separate, opt-in prompt that defaults to keeping it, and says exactly what it destroys and where. **A silent uninstall never deletes the database**, whatever the prompt would have offered.

The uninstaller does not remove OpenSSH. It may predate SD or be in use by something else. It does restore `sshd_config`, keeping the original as `sshd_config.before-sd` — but it deliberately does **not** widen the firewall rule back, because restoring it would mean opening a port on the way out.