

SD TCL - Syntax

Every verb you can type, alphabetically, with its syntax and nothing else.

A lookup card, and nothing else. If you know which verb you want and have forgotten its arguments, it is here. If you want to know what it *does*, the subject documents are where that lives.

Italics mark something you supply, **bold** a word typed as it stands, braces an optional part, and a vertical bar separates alternatives. SD folds case, so any of this may be typed in either case.

This page is generated, and it is checked for completeness rather than proof-read for it. The roster is computed from SD's own VOC: the verb records in `newvoc` plus the ones an administrator account adds, which is **147** verbs, and `tools/mktc1syntax.py` refuses to write the page if any of them has no line. The shapes come from the subject documents, where each verb is described in full.

The tier column is the VOC, not an opinion. It is read from `TIER.OMIT.STANDARD` and `TIER.ADD.ADMINISTRATOR`, the same two lists the account-creation code uses, so it cannot drift from what an account actually gets. **A verb your account does not have is not refused — the name is simply not recognised.**

standard	82 verbs	every account has these
programmer	42 more	withheld from a standard account
administrator	23 more	and several need an elevated session as well

The verbs

	SYNTAX	TIER
<code>!</code>	<code>! command</code>	A
<code>abort</code>	<code>abort {message}</code>	
<code>alias</code>	<code>alias command target</code>	
<code>analyse.file</code>	<code>analyse.file {dict} file</code> <code>{statistics} {lptr}</code>	P

	SYNTAX	TIER
<code>analyze.file</code>	<code>analyze.file</code> — the same verb as <code>analyse.file</code>	P
<code>append.sd.path</code>	<code>append.sd.path</code> { <code>on</code> <code>off</code> }	
<code>autologout</code>	<code>autologout</code> { <i>minutes</i> }	
<code>basic</code>	<code>basic</code> { <i>file</i> } <i>record</i> { <i>record</i> ...}	P
<code>bell</code>	<code>bell on</code> <code>off</code>	
<code>break</code>	<code>break on</code> <code>off</code>	
<code>build.index</code>	<code>build.index</code> <i>file field ...</i> <code>all</code>	
<code>catalog</code>	<code>catalog</code> { <i>file</i> { <i>call.name</i> }} { <i>program</i> } { <code>local</code> }	<code>global</code>
<code>catalogue</code>	<code>catalogue</code> — the same verb as <code>catalog</code>	P
<code>cd</code>	<code>cd</code> { <code>dict</code> <code>data</code> } <i>file</i> { <i>i-type ...</i> } { <code>no.query</code> } { <code>no.page</code> } · <code>cd local</code> · <code>cd all</code>	
<code>clean.account</code>	<code>clean.account</code>	A
<code>clear.abort</code>	<code>clear.abort</code>	
<code>clear.data</code>	<code>clear.data</code>	
<code>clear.file</code>	<code>clear.file</code> { <code>data</code> <code>dict</code> } <i>file</i>	
<code>clear.input</code>	<code>clear.input</code>	
<code>clear.locks</code>	<code>clear.locks</code> { <i>n</i> }	A
<code>clear.prompts</code>	<code>clear.prompts</code>	
<code>clear.select</code>	<code>clear.select</code> { <i>list.no</i> }	
<code>clear.stack</code>	<code>clear.stack</code>	
<code>cleardata</code>	<code>cleardata</code> — the same verb as <code>clear.data</code>	

	SYNTAX	TIER
<code>clearinput</code>	<code>clearinput</code> — the same verb as <code>clear.input</code>	
<code>clearprompts</code>	<code>clearprompts</code> — the same verb as <code>clear.prompts</code>	
<code>clearselect</code>	<code>clearselect</code> — the same verb as <code>clear.select</code>	
<code>clr</code>	<code>clr</code>	
<code>cname</code>	<code>cname</code> <i>old.file</i> <code>to</code> <i>new.file</i>	P
<code>como</code>	<code>como on</code> { <i>record</i> } <code>off</code>	
<code>compile.dict</code>	<code>compile.dict</code> — the same verb as <code>cd</code>	P
<code>config</code>	<code>config</code> { <code>lptr</code> } <code>gpl</code>	
<code>configure.file</code>	<code>configure.file</code> { <code>dict</code> } <i>voc.name</i> { <i>parameters</i> } <code>default</code>	
<code>copy</code>	<code>copy from</code> { <code>dict</code> } <i>src</i> { <code>to</code> { <code>dict</code> } <i>tgt</i> } { <i>id</i> ...} { <code>(options)</code> }	P
<code>copy.list</code>	<code>copy.list</code> <i>list</i> { <code>,</code> <i>new</i> } { <code>from</code> <i>src</i> } { <code>to</code> <i>tgt</i> } { <i>options</i> }	
<code>copyp</code>	<code>copyp</code> { <code>dict</code> } <i>file id</i> ... { <code>(options)</code> }	P
<code>count</code>	<code>count</code> { <code>dict</code> } <i>file</i> { <i>selection</i> }	
<code>create.account</code>	<code>create.account user</code> <i>programmer</i> < <code>ssh</code> <i>name</i> { <code>administrator</code> }	
<code>create.file</code>	<code>create.file</code> { <code>dict</code> } <i>voc.name</i> { <code>directory</code> } { <i>parameters</i> }	P

	SYNTAX	TIER
<code>create.index</code>	<code>create.index</code> <i>file field ...</i> { <code>no.nulls</code> } { <code>pathname</code> <i>path</i> }	P
<code>cs</code>	<code>cs</code> — the same verb as <code>clr</code>	
<code>ct</code>	<code>ct</code> { <code>dict</code> } <i>file {id ...</i>	* { (options) }
<code>date</code>	<code>date</code>	<code>internal</code>
<code>date.format</code>	<code>date.format on</code>	<code>off</code>
<code>debug</code>	<code>debug</code>	P
<code>delete</code>	<code>delete</code> { <code>dict</code> } <i>file {id ...}</i> { <code>no.query</code> }	P
<code>delete.account</code>	<code>delete.account</code> <i>account</i>	A
<code>delete.catalog</code>	<code>delete.catalog</code> <i>name ...</i> { <code>global</code>	<code>local</code> }
<code>delete.catalogue</code>	<code>delete.catalogue</code> — the same verb as <code>delete.catalog</code>	P
<code>delete.common</code>	<code>delete.common</code> <i>name</i>	P
<code>delete.file</code>	<code>delete.file</code> { <code>dict</code>	<code>data</code> } <i>voc.name</i> { <code>force</code> } { <code>no.query</code> }
<code>delete.index</code>	<code>delete.index</code> <i>file field ...</i>	<code>all</code>
<code>delete.list</code>	<code>delete.list</code> <i>list</i>	
<code>display</code>	<code>display</code> <i>text</i>	
<code>dump</code>	<code>dump</code> { <code>dict</code> } <i>file {id ...</i>	* { (options) }
<code>echo</code>	<code>echo on</code>	<code>off</code>
<code>ed</code>	<code>ed</code> { <code>dict</code> } <i>file {id ...}</i>	P
<code>edit</code>	<code>edit</code> { <code>dict</code> } <i>file record</i>	P

	SYNTAX	TIER
<code>form.list</code>	<code>form.list</code> { <code>dict</code> } <i>file</i> <i>{list.no}</i>	
<code>format</code>	<code>format</code> { <i>file</i> } { <i>record</i> } { <code>case</code> }	
<code>fstat</code>	<code>fstat</code> <i>file</i> <code>on</code>	<code>off</code>
<code>generate</code>	<code>generate</code> { <code>dict</code> } <i>file</i> <i>record ...</i>	P
<code>get.list</code>	<code>get.list</code> <i>list</i> { <code>to</code> } <i>list.no</i>	
<code>get.stack</code>	<code>get.stack</code> { <i>name</i> }	
<code>go</code>	<code>go</code> <i>label</i>	
<code>grant</code>	<code>grant</code> <i>account</i> <code>to</code> <i>user</i>	A
<code>hsm</code>	<code>hsm on</code>	<code>off</code>
<code>hush</code>	<code>hush on</code>	<code>off</code>
<code>if</code>	<code>if</code> <i>condition command</i>	
<code>list</code>	<code>list</code> { <code>dict</code> } <i>file</i> <i>{selection} {fields} {options}</i>	
<code>list.common</code>	<code>list.common</code> { <code>all</code> }	
<code>list.diff</code>	<code>list.diff</code> <i>list.1</i> { <i>list.2</i> <i>{tgt}</i> } { <code>count.sup</code> }	
<code>list.files</code>	<code>list.files</code>	
<code>list.grants</code>	<code>list.grants</code> <i>account</i>	A
<code>list.index</code>	<code>list.index</code> <i>file</i> { <i>field ...</i> }	P
<code>list.inter</code>	<code>list.inter</code> <i>list.1</i> { <i>list.2</i> <i>{tgt}</i> } { <code>count.sup</code> }	
<code>list.item</code>	<code>list.item</code> { <code>dict</code> } <i>file</i> <i>{selection}</i>	

	SYNTAX	TIER
<code>list.label</code>	<code>list.label</code> { <code>dict</code> } <i>file</i> { <i>selection</i> } { <i>fields</i> }	
<code>list.locks</code>	<code>list.locks</code>	A
<code>list.readu</code>	<code>list.readu</code> { <i>user.no</i> } { <code>detail</code> } { <code>wait</code> } { <code>no.page</code> } { <code>lptr</code> } { <i>n</i> }	A
<code>list.union</code>	<code>list.union</code> <i>list.1</i> { <i>list.2</i> { <i>tgt</i> } } { <code>count.sup</code> }	
<code>list.vars</code>	<code>list.vars</code> { <i>pattern</i> }	
<code>listu</code>	<code>listu</code> { <code>no.page</code> } { <code>lptr</code> } { <i>n</i> }	A
<code>lock</code>	<code>lock</code> <i>n</i> { <code>no.wait</code> }	A
<code>logmsg</code>	<code>logmsg</code> <i>text</i>	
<code>logout</code>	<code>logout</code>	<i>n</i> ...
<code>logto</code>	<code>logto</code> <i>account</i>	
<code>make.index</code>	<code>make.index</code> <i>file field ...</i> { <code>no.nulls</code> } { <code>pathname</code> } <i>path</i> }	P
<code>map</code>	<code>map</code> { <code>all</code> } { <code>lptr</code> } { <i>n</i> } { <code>file</code> } { <i>name</i> }	P
<code>merge.list</code>	<code>merge.list</code> <i>list.no rel.op</i> <i>list.no</i> { <code>to</code> } <i>list.no</i> { <code>count.sup</code> }	
<code>message</code>	<code>message</code> <i>user.no</i> { <code>immediate</code> } { <i>text</i> }	
<code>micro</code>	<code>micro</code> { <code>dict</code> } <i>file record</i>	P
<code>modify.account</code>	<code>modify.account</code> <i>account</i> <code>programmer</code> <code>standard</code>	
<code>modify.password</code>	<code>modify.password</code> { <i>account</i> }	A

	SYNTAX	TIER
nselect	nselect <i>file</i> { <i>list.no</i> }	
off	off	
option	option <i>name</i> { on off }	
pause	pause { <i>seconds</i> }	
pdebug	pdebug { <i>command</i> }	P
pdump	pdump <i>n</i>	P
phantom	phantom <i>command</i>	P
printer	printer { <i>unit</i> } query at <i>name</i>	
pstat	pstat { user <i>n</i> } { level <i>n</i> } { no.page } { lptr { <i>n</i> }}	P
pterm	pterm display lptr	
qselect	qselect { dict } <i>file</i> { <i>id ...</i> * } { (options) }	
quit	quit — the same verb as off	
reformat	reformat { dict } <i>file</i> { <i>selection</i> } { <i>fields</i> }	P
release	release <i>file id ...</i> · release filelock <i>file</i>	
remote.api	remote.api { on local }	
remote.ssh	remote.ssh { on off }	
rename	rename — the same verb as as cname	P
report.src	report.src on off	
report.style	report.style { <i>name</i> off }	
revoke	revoke <i>account</i> from <i>user</i>	A

	SYNTAX	TIER
<code>run</code>	<code>run</code> <i>{file} record</i> <i>{arguments}</i>	P
<code>save.list</code>	<code>save.list</code> <i>list</i> <code>{ from</code> <i>list.no}</i>	
<code>save.stack</code>	<code>save.stack</code> <i>{name}</i>	
<code>search</code>	<code>search</code> <code>{ dict }</code> <i>file</i> <i>{selection}</i>	
<code>select</code>	<code>select</code> <code>{ dict }</code> <i>file</i> <i>{selection} {list.no}</i>	
<code>set</code>	<code>set</code> <i>name value</i>	
<code>set.date</code>	<code>set.date</code> <i>date</i>	A
<code>set.exit.status</code>	<code>set.exit.status</code> <i>n</i>	
<code>set.file</code>	<code>set.file</code> <i>account file</i> <i>pointer</i>	
<code>set.trigger</code>	<code>set.trigger</code> <i>file name</i> <i>{modes}</i>	P
<code>setptr</code>	<code>setptr</code> <i>unit</i>	<code>default</code> <code>,</code> <i>width</i> <code>,</code> <i>depth</i> <code>,</code> <i>top</i> <code>,</code> <i>bottom</i> <code>,</code> <i>mode</i> <code>{ , options}</code> <code>·</code> <code>setptr display</code> <code>·</code> <code>setptr unit</code> <code>,</code> <code>display</code>
<code>sh</code>	<code>sh</code> <i>command</i>	A
<code>show</code>	<code>show</code> <code>{ dict }</code> <i>file</i> <i>{selection}</i>	
<code>sleep</code>	<code>sleep</code> <i>n</i>	<i>hh</i> <code>:</code> <i>mm</i> <code>{ : ss}</code>
<code>sort</code>	<code>sort</code> <code>{ dict }</code> <i>file</i> <i>{selection} {fields} {options}</i>	
<code>sort.item</code>	<code>sort.item</code> <code>{ dict }</code> <i>file</i> <i>{selection}</i>	
<code>sort.label</code>	<code>sort.label</code> <code>{ dict }</code> <i>file</i> <i>{selection} {fields}</i>	
<code>sp.close</code>	<code>sp.close</code>	

	SYNTAX	TIER
sp.open	sp.open	
sp.view	sp.view	
spool	spool file id ... {lines n m} {lnum} {lptr n}	
sreformat	sreformat {dict} file {selection} {fields}	P
sselect	sselect {dict} file {selection} {list.no}	
ssh.server	ssh.server {install remove }	
status	status	
stop	stop	
sum	sum {dict} file {selection} field	
term	term	width{[, lines} {type}
time	time	internal
unlock	unlock file n {user n} id ...	all
update.accounts	update.accounts {all}	A
who	who	
who.am.i	who.am.i	

Blank in the tier column means every account has it; **P** is a programmer verb and **A** an administrator one.