

МИНИСТЕРСТВО ОБРАЗОВАНИЯ И НАУКИ РОССИЙСКОЙ
ФЕДЕРАЦИИ МОСКОВСКИЙ АВИАЦИОННЫЙ ИНСТИТУТ
(НАЦИОНАЛЬНЫЙ ИССЛЕДОВАТЕЛЬСКИЙ УНИВЕРСИТЕТ)

ЛАБОРАТОРНАЯ РАБОТА №5 по курсу объектно-ориентированное программирование I семестр, 2021/22 уч. год

Студент Прохоров Данила Михайлович, группа М80-208Б-20
Преподаватель Дорохов Евгений Павлович

Цель работы

Целью лабораторной работы является:

Закрепление навыков работы с классами.

Знакомство с умными указателями.

Задание

Необходимо спроектировать и запрограммировать на языке C++ класс-контейнер первого уровня, содержащий **одну** фигуру класса фигуры, согласно вариантам задания. Классы должны удовлетворять следующим правилам:

Требования к классу фигуры аналогичны требованиям из лабораторной работы 1.

Требования к классу контейнера аналогичны требованиям из лабораторной работы 2.

Класс-контейнер должен содержать объекты используя `std::shared_ptr<...>`.

Классы должны быть расположены в отдельных файлах: отдельно заголовки (.h), отдельно описание методов (.cpp).

Нельзя использовать:

Стандартные контейнеры `std`.

Шаблоны (template).

Объекты «по-значению»

Программа должна позволять:

Вводить произвольное количество фигур и добавлять их в контейнер.

Распечатывать содержимое контейнера.

Удалять фигуры из контейнера.

Вариант 21:

А) Структура данных – N-арное дерево.

Б) Фигура – Прямоугольник.

Дневник отладки

Во время выполнения лабораторной работы неисправностей возникало много, в основном все они были связаны с «введением» умных указателей. Но всё удалось отладить.

Недочёты

Недочётов не было обнаружено.

Выводы

Лабораторная работа №5 позволила мне понять концепцию умного указателя `shared_ptr` и попрактиковаться в их использовании. Также пришлось менять архитектуру программы, так как прошлая лабораторная не смогла «взаимодействовать» с умными указателями.

Исходный код

figure.h

```
#ifndef FIGURE_H
#define FIGURE_H
#include "point.h"

class Figure
{
public:
    //virtual void Print(std::ostream& os) = 0;
    virtual double Square() = 0;
    virtual ~Figure() {};
    virtual size_t VertexesNumber() = 0;
};

#endif
```

main.cpp

```
#include <iostream>
```

```

#include <sstream>
#include "tnarytree.h"
int main()
{
    double S = 0.;
    std::string string;
    TNaryTree t1(3);
    //std::cout << t1;
    t1.Update(Rectangle(std::cin), "cbc");
    t1.Update(Rectangle(std::cin), "");
    t1.Update(Rectangle(std::cin));
    t1.Update(Rectangle(std::cin), "c");
    t1.Update(Rectangle(std::cin), "cb");
    std::cout << t1.getItem("cb");
    std::cout << t1.getItem("cbb");
    t1.Update(Rectangle(std::cin), "cc");
    t1.Update(Rectangle(std::cin), "cbb");
    std::cout << t1;
    t1.Update(Rectangle(std::cin), "cbbb");
    if ((S = t1.Area()) == -1)
    {
        std::cout << "There is no such element in tree" << std::endl;
    }
    else
    {
        std::cout << "Area of subtree is " << S << std::endl;
    }
    if ((S = t1.Area("cbbccbc")) == -1)
    {
        std::cout << "There is no such element in tree" << std::endl;
    }
    else
    {
        std::cout << "Area of subtree is " << S << std::endl;
    }
    t1.Update(Rectangle(std::cin), "cbc");
    std::cout << t1;
    t1.Update(Rectangle(std::cin), "ccb");
    t1.Update(Rectangle(std::cin), "ccbb");
    t1.Update(Rectangle(std::cin), "cbcb");
    t1.Update(Rectangle(std::cin), "cbcb");
    std::cout << t1;
    if ((S = t1.Area("c")) == -1)
    {
        std::cout << "There is no such element in tree" << std::endl;
    }
    else
    {
        std::cout << "Area of subtree is " << S << std::endl;
    }
    t1.Update(Rectangle(std::cin), "cbbbc");
    std::cout << t1;
    t1.Update(Rectangle(std::cin), "cbbc");
    t1.Update(Rectangle(std::cin), "cbb");
    std::cout << t1;
    t1.Update(Rectangle(std::cin), "cbbc");
    t1.Update(Rectangle(std::cin), "cbbcbb");
    t1.Update(Rectangle(std::cin), "ccbc");
    t1.Update(Rectangle(std::cin), "cbbc");
}

```

```

t1.Update(Rectangle(std::cin), "cbbd");
t1.Update(Rectangle(std::cin), "cbbcbbc");
t1.Update(Rectangle(std::cin), "cbbcbbcbb");
std::cout << t1.getItem("cbbcbbcbb");
std::cout << t1.getItem("cbbbbbcbbcbbcbbc");
std::cout << t1;
TNaryTree t3(t1);

t3.Update(Rectangle(std::cin));
t3.Update(Rectangle(std::cin), "cbbcbbcbb");
t3.Update(Rectangle(std::cin), "cbbc");

std::cout << t1 << t3;

/*t1.Clear("ccc");
t1.Clear("b");
t1.Clear("cbbcbb");*/
std::cout << t1;
t1.RemoveSubTree("cb");
std::cout << t1;
t1.RemoveSubTree("cbb");
std::cout << t1;
t1.RemoveSubTree("cb");
std::cout << t1;
t1.RemoveSubTree("cbbcbb");
std::cout << t1;
t1.RemoveSubTree("ccb");
std::cout << t1;
t1.RemoveSubTree();
std::cout << t1 << t3;
TNaryTree t2(7);
t2.Update(Rectangle(std::cin));
t2.Update(Rectangle(std::cin), "c");
t2.Update(Rectangle(std::cin), "cb");
std::cout << t2;
t2.RemoveSubTree();
system("pause");
return 0;
}

```

rectangle.cpp

```

#include "rectangle.h"

Rectangle::Rectangle() : a(0.0, 0.0), b(0.0, 0.0), c(0.0, 0.0), d(0.0, 0.0), len1(0),
len2(0), square(0.0)
{
};

Rectangle::Rectangle(std::istream& is)
{
    is >> a >> b >> c >> d;
    len1 = dist(a, b);
    len2 = dist(b, c);
    square = len1 * len2;
}

```

```

Rectangle& Rectangle::operator= (Rectangle rectangle)
{
    a = rectangle.a;
    b = rectangle.b;
    c = rectangle.c;
    d = rectangle.d;
    len1 = dist(a, b);
    len2 = dist(b, c);
    square = len1 * len2;
    return rectangle;
};

bool Rectangle::operator== (Rectangle rectangle)
{
    if ((a == rectangle.a) && (b == rectangle.b) && (c == rectangle.c) && (d ==
rectangle.d))
    {
        return true;
    }
    return false;
};

void Rectangle::Print(std::ostream& os)
{
    os << "Rectangle: " << a << " " << b << " " << c << " " << d << std::endl;
}

std::istream& operator >>(std::istream& is, Rectangle& rectangle)
{
    is >> rectangle.a >> rectangle.b >> rectangle.c >> rectangle.d;
    return is;
};

std::ostream& operator <<(std::ostream& os, Rectangle rectangle)
{
    os << rectangle.a << " " << rectangle.b << " " << rectangle.c << " " << rectangle.d
<< "\n";
    return os;
};

size_t Rectangle::VertexesNumber()
{
    return 4;
}

double Rectangle::Square()
{
    return square;
}

Rectangle::~~Rectangle()
{
}

```

rectangle.h

```

#ifndef RECTANGLE_H

```

```

#define RECTANGLE_H
#include "figure.h"

class Rectangle : public Figure
{
public:
    Rectangle();
    Rectangle(std::istream& is);
    /*void copy(Rectangle rectangle);
    bool is_equal(Rectangle rectangle);*/
    void Print(std::ostream& os);
    double Square();
    friend std::istream& operator >>(std::istream& is, Rectangle& rectangle);
    friend std::ostream& operator <<(std::ostream& os, Rectangle rectangle);
    Rectangle& operator= (Rectangle rectangle);
    bool operator== (Rectangle rectangle);
    size_t VertexesNumber();
    virtual ~Rectangle();

private:
    Point a, b, c, d;
    double len1, len2;
    double square;
};

#endif

```

point.h

```

#ifndef POINT_H
#define POINT_H
#include <iostream>
#include <cmath>
#include <cstdlib>
#include <algorithm>
class Point
{
public:
    Point();
    Point(std::istream& is);
    Point(double x, double y);
    double length(Point& p1, Point& p2);
    friend std::istream& operator>>(std::istream& is, Point& p);
    friend std::ostream& operator<<(std::ostream& os, Point& p);
    bool operator== (Point point);
    friend double dist(Point& p1, Point& p2);

private:
    double x_, y_;
};

#endif

```

point.cpp

```
#include "point.h"

Point::Point() : x_(0.0), y_(0.0) {}

Point::Point(double x, double y) : x_(x), y_(y) {}

Point::Point(std::istream& is)
{
    is >> x_ >> y_;
}

double dist(Point& p1, Point& p2)
{
    double dx = (p1.x_ - p2.x_);
    double dy = (p1.y_ - p2.y_);
    return std::sqrt(dx * dx + dy * dy);
}

std::istream& operator >> (std::istream& is, Point& p)
{
    is >> p.x_ >> p.y_;
    return is;
}

std::ostream& operator << (std::ostream& os, Point& p)
{
    os << "(" << p.x_ << ", " << p.y_ << ")";
    return os;
}

bool Point::operator == (Point point)
{
    return (x_ == point.x_) && (y_ == point.y_);
}
```

tnarytree.cpp

```
#include "tnarytree.h"

TNaryTree::TNaryTree()
{
    this->N = 2;
    root = std::make_shared<Node>(Node(Rectangle(), 0, nullptr, nullptr));
}

TNaryTree::TNaryTree(int N)
{
    this->N = N;
    root = std::make_shared<Node>(Node(Rectangle(), 0, nullptr, nullptr));
}

TNaryTree::TNaryTree(TNaryTree& other)
{
}
```



```

    N = other.N;
    if (other.Empty())
    {
        root = nullptr;
        return;
    }
    root = std::make_shared<Node>(Node(other.root->rectangle, 0, nullptr, nullptr));
    BuildTree(root, other.root);
}

void TNaryTree::BuildTree(std::shared_ptr<Node>& current_node, std::shared_ptr<Node>
other_node)
{
    if (!other_node->child)
    {
        return;
    }
    current_node->child = std::make_shared<Node>(Node(other_node->child->rectangle,
other_node->child->remainder, current_node, nullptr));
    std::shared_ptr<Node>copy = current_node->child, other_copy = other_node->child;
    while (other_copy)
    {
        BuildTree(copy, other_copy);
        if (other_copy->right_brother)
        {
            copy->right_brother = std::make_shared<Node>(Node(other_copy-
>right_brother->rectangle, other_copy->right_brother->remainder, current_node, copy));
        }
        else
        {
            copy->right_brother = nullptr;
        }
        copy = copy->right_brother;
        other_copy = other_copy->right_brother;
    }
}

TNaryTree::Node::Node(Rectangle rectangle, int remainder, std::shared_ptr<Node> parent,
std::shared_ptr<Node> left_brother)
{
    this->rectangle = rectangle;
    this->remainder = remainder;
    this->parent = parent;
    this->child = child;
    this->left_brother = left_brother;
    this->right_brother = right_brother;
}

TNaryTree::Node::~~Node() {}

bool TNaryTree::Empty()
{
    if (root)
    {
        return false;
    }
    return true;
}

```

```

void TNaryTree::Node::abn()
{
}

Rectangle TNaryTree::getItem(std::string&& tree_path)
{
    try
    {
        if (!tree_path.length())
        {
            if (Empty())
            {
                throw std::invalid_argument("There's no root\n");
            }
            else
            {
                return root->rectangle;
            }
        }
        std::shared_ptr<Node> current_node = root;
        while (tree_path.length())
        {
            switch (tree_path[0])
            {
                case 'b':
                {
                    if (!current_node)
                    {
                        throw std::invalid_argument("There's no such
element in tree\n");
                    }
                    current_node = current_node->right_brother;
                    break;
                }
                case 'c':
                {
                    if (!current_node)
                    {
                        throw std::invalid_argument("There's no such
element in tree\n");
                    }
                    current_node = current_node->child;
                    break;
                }
                default:
                {
                    throw std::invalid_argument("String must contain only
'b' or 'c' characters\n");
                }
            }
            tree_path.erase(tree_path.begin());
        }
        if (!current_node)
        {
            throw std::invalid_argument("There's no such element in tree\n");
        }
        return current_node->rectangle;
    }
}

```

```

        catch (std::invalid_argument& error)
        {
            std::cout << error.what();
            return Rectangle();
        }
        catch (std::out_of_range& error)
        {
            std::cout << error.what();
            return Rectangle();
        }
    }

void TNaryTree::Update(Rectangle&& rectangle, std::string&& tree_path)
{
    try
    {
        if (!tree_path.length())
        {
            if (Empty())
            {
                root = std::make_shared<Node>(Node(rectangle, 0, nullptr,
nullptr));
            }
            else
            {
                root->rectangle = rectangle;
            }
            return;
        }
        std::shared_ptr<Node> current_node = root;
        while (tree_path.length() > 1)
        {
            switch (tree_path[0])
            {
                case 'b':
                {
                    if (!current_node)
                    {
                        throw std::invalid_argument("There's no such
element in tree\n");
                    }
                    current_node = current_node->right_brother;
                    break;
                }
                case 'c':
                {
                    if (!current_node)
                    {
                        throw std::invalid_argument("There's no such
element in tree\n");
                    }
                    current_node = current_node->child;
                    break;
                }
                default:
                {
                    throw std::invalid_argument("String must contain only
'b' or 'c' characters\n");
                }
            }
        }
    }
}

```

```

    }
    tree_path.erase(tree_path.begin());
}
switch (tree_path[0])
{
    case 'b':
    {
        if ((!current_node) || (!current_node->remainder))
        {
            throw std::out_of_range("Node already has " +
std::to_string(N) + " sons, so it's impossible to add another one\n");
        }
        if (!current_node->right_brother)
        {
            current_node->right_brother =
std::make_shared<Node>(Node(rectangle, current_node->remainder - 1, current_node->parent,
current_node));
        }
        else
        {
            current_node->rectangle = rectangle;
        }
        break;
    }
    case 'c':
    {
        if (!current_node)
        {
            throw std::invalid_argument("There's no such element in
tree\n");
        }
        if (!current_node->child)
        {
            current_node->child =
std::make_shared<Node>(Node(rectangle, N - 1, current_node, nullptr));
        }
        else
        {
            current_node->child->rectangle = rectangle;
        }
        break;
    }
    default:
    {
        throw std::invalid_argument("String must contain only 'b' or
'c' characters\n");
    }
}
tree_path.erase(tree_path.begin());
}
catch (std::invalid_argument& error)
{
    std::cout << error.what();
    return;
}
catch (std::out_of_range& error)
{
    std::cout << error.what();
    return;
}

```

```

    }
}

void TNaryTree::DeleteSons(std::shared_ptr<Node>& node)
{
    std::shared_ptr<Node> copy = node->child, previous = copy;
    while (copy)
    {
        if (copy->child)
        {
            DeleteSons(copy);
        }
        previous = copy;
        copy = copy->right_brother;
    }
    while (previous)
    {
        previous->right_brother = nullptr;
        previous = previous->left_brother;
    }
    node->child = nullptr;
    //previous->parent->child = nullptr;
}

void TNaryTree::RemoveSubTree(std::string&& tree_path)
{
    try
    {
        if (!tree_path.length())
        {
            if (Empty())
            {
                throw std::invalid_argument("The root is empty\n");
            }
            else
            {
                DeleteSons(root);
                root = nullptr;
                return;
            }
        }
        std::shared_ptr<Node> current_node = root;
        while (tree_path.length())
        {
            switch (tree_path[0])
            {
                case 'b':
                {
                    if (!current_node)
                    {
                        throw std::invalid_argument("There's no such
element in tree\n");
                    }
                    current_node = current_node->right_brother;
                    break;
                }
                case 'c':
                {
                    if (!current_node)

```

```

        {
            throw std::invalid_argument("There's no such
element in tree\n");
        }
        current_node = current_node->child;
        break;
    }
    default:
    {
        throw std::invalid_argument("String must contain only
'b' or 'c' characters\n");
    }
    tree_path.erase(tree_path.begin());
}
if (!current_node)
{
    throw std::invalid_argument("There's no such element in tree\n");
}
DeleteSons(current_node);
std::shared_ptr<Node> clone = current_node->right_brother;
if (current_node->left_brother)
{
    if (current_node->right_brother)
    {
        current_node->right_brother->left_brother = current_node-
>left_brother;
    }
    current_node->left_brother->right_brother = current_node-
>right_brother;
}
else
{
    current_node->parent->child = current_node->right_brother;
}
current_node = nullptr;
while (clone)
{
    ++(clone->remainder);
    clone = clone->right_brother;
}
}
catch (std::invalid_argument& error)
{
    std::cout << error.what();
    return;
}
catch (std::out_of_range& error)
{
    std::cout << error.what();
    return;
}
}

double TNaryTree::AreaOfSubtree(std::shared_ptr<Node> node)
{
    double S = node->rectangle.Square();
    std::shared_ptr<Node> current_node = node->child;
    while (current_node)

```

```

    {
        S += AreaOfSubtree(current_node);
        current_node = current_node->right_brother;
    }
    return S;
}

double TNaryTree::Area(std::string&& tree_path)
{
    try
    {
        if (Empty())
        {
            throw std::invalid_argument("The root is empty\n");
        }
        if (!tree_path.length())
        {
            return AreaOfSubtree(root);
        }
        std::shared_ptr<Node> current_node = root;
        while (tree_path.length())
        {
            switch (tree_path[0])
            {
                case 'b':
                {
                    if (!current_node)
                    {
                        throw std::invalid_argument("There is no such
element in tree\n");
                    }
                    current_node = current_node->right_brother;
                    tree_path.erase(tree_path.begin());
                    break;
                }
                case 'c':
                {
                    if (!current_node)
                    {
                        throw std::invalid_argument("There is no such
element in tree\n");
                    }
                    current_node = current_node->child;
                    tree_path.erase(tree_path.begin());
                    break;
                }
                default:
                {
                    throw std::invalid_argument("String must contain only
'b' or 'c' characters\n");
                }
            }
            tree_path.erase(tree_path.begin());
        }
        if (!current_node)
        {
            throw std::invalid_argument("There's no such element in tree\n");
        }
        return AreaOfSubtree(current_node);
    }
}

```

```

    }
    catch (std::invalid_argument& error)
    {
        std::cout << error.what();
        return -1.;
    }
    catch (std::out_of_range& error)
    {
        std::cout << error.what();
        return -1.;
    }
}

void PrintNode(std::ostream& os, std::shared_ptr<TNaryTree::Node> node)
{
    os << node->rectangle.Square();
    if (!node->child)
    {
        return;
    }
    std::shared_ptr<TNaryTree::Node> current_node = node->child;
    os << " : [";
    while (current_node)
    {
        PrintNode(os, current_node);
        if (current_node->right_brother)
        {
            os << ", ";
        }
        current_node = current_node->right_brother;
    }
    os << " ]";
}

std::ostream& operator<<(std::ostream& os, TNaryTree& tree)
{
    try
    {
        if (tree.Empty())
        {
            throw std::invalid_argument("The root is empty");
        }
        PrintNode(os, tree.root);
    }
    catch (std::invalid_argument& error)
    {
        os << error.what();
    }
    os << "\n";
    return os;
};

TNaryTree::~TNaryTree()
{
    if (!Empty())
    {
        DeleteSons(root);
        root = nullptr;
    }
}

```



```
}
```

tnarytree.h

```
#ifndef TNARYTREE_H
#define TNARYTREE_H
#include "rectangle.h"
#include <exception>
#include <string>

class TNaryTree
{
private:
    struct Node
    {
        TNaryTree::Node(Rectangle rectangle, int remainder, std::shared_ptr<Node>
parent, std::shared_ptr<Node> left_brother);
        int remainder;
        Rectangle rectangle;
        std::shared_ptr<Node> parent;
        std::shared_ptr<Node> child;
        std::shared_ptr<Node> left_brother;
        std::shared_ptr<Node> right_brother;
        void abn();
        ~Node();
    };
    std::shared_ptr<Node> root;
    int N;
public:
    TNaryTree();
    TNaryTree(int);
    TNaryTree(TNaryTree&);
    void BuildTree(std::shared_ptr<Node>&, std::shared_ptr<Node>);
    void Update(Rectangle&&, std::string&& = "");
    void RemoveSubTree(std::string&& = "");
    void DeleteSons(std::shared_ptr<Node>&);
    Rectangle getItem(std::string&& = "");
    bool Empty();
    double Area(std::string && = "");
    double AreaOfSubtree(std::shared_ptr<Node>);
    friend std::ostream& operator<<(std::ostream&, TNaryTree&);
    friend void PrintNode(std::ostream&, std::shared_ptr<TNaryTree::Node>);
    virtual ~TNaryTree();
};
#endif
```