



验报告

TEST REPORT

中心编号(No.): 201706AW170

样品名称:

内墙耐水腻子

Sample Name

委托单位: 保定佬工匠建筑装饰材料制造有限公司

Client

检验类别:

委托检验

Test Type

(国家)建筑材料工业技术监督研究中心

建筑材料工业于混砂浆产品质量监督检验测试中心 China Building Material Industry Genter for Quality Supervision and Test of Dry-mixed Mortar







(国家)建筑材料工业技术监督研究中心

建筑材料工业干混砂浆产品质量监督检验测试中心

China Building Material Industry Center for Quality Supervision and Test of Dry-mixed Mortar

检

TEST REPORT

中心编号(No.): 201706AW170

第1页共2页

			The same of the sa	
样品名称		检验类别	***************************************	
委托单位	保定佬工匠建筑装饰材料制造有限公司	商品标		
生产单位	保定佬工匠建筑装饰材料制造有限公司	等级		
生产日期		样品编号		
来样日期	2017年06月08日	规格型号		
样品数量	20kg	样品状态		
检验依据	JG/T298-2010《建筑室内闸赋子》			
检验项目	4. 初期干燥抗裂性(3h) - 25. 粘结强度 - 2-2-2-2-2-2-2-2-2-2-2-2-2-2-2-2-2-2-			
检验结论	*经检验,送检样品的初期干燥抗裂性(3h)。粘结强度的检验结果 符合标准 JG/T(298-2010 中耐水型(N)的技术指标要求。*			
	は 	2017年06	The state of the	

批准:

制、苏亮

检验单位地址。北京市朝阳区管崖中国建材院内北楼 电话。110-51164723 建筑材料工业技术监督研究中心

邮编: 100024

(国家)建筑材料工业技术监督研究中心

建筑材料工业干混砂浆产品质量监督检验测试中心

China Building Material Industry Center for Quality Supervision and Test of Dry-mixed Mortar

检验报告

TEST REPORT

中心编号(No.): 201706AW170

第2页共2页

序号	检验项目	标准要求 [研水型(N)]	检验结果	单项结论
	初期干燥抗裂性(3h)	15 mg		
料结强度,		>0.50	20.73 EA	
超	MPa	>0.30	0.34	

备注: (1) 配比: 粉: 水=1.0: 0.40:

(2) pH 值=10.2。

说。可明

Notice

- 1、本报告无由心"检验测试章"和骑缝章无效。
 - This test report is invalid without the seal.
- 2、本报告无广编制、审核、批准"一签字无效。

This test report is invalid without the signatures of the related persons.

- 3、本报告涂改、部分复印无效。
 - This test report is invalid if erased, altered or copied partially.
- 4、对本报告若有异议,应于收到报告之目起中五个工作目内向本中心提出,逾期恕不受理。
 - Any doubt should inform us within 15 workdays after receiving the test report.
- 5. 委托检验样品和委托信息由委托太提供,中心不对真实性负责,委托检验结果仅对来样负责。

The commissioned testing samples and commission information are provided by the applicant. The results shown in the test report refer only to the sample(s) tested unless otherwise stated. Identifying authenticity of the supplied samples and information is out of our responsibility.

- 6、本报告的法律责任由建筑材料工业技术监督研究中心承担。
 The legal responsibility of this test report is charged with Technical Supervision and Research Center of the Building Materials Industry.
- 7. 本报告采用防伤纸张,复印后应带有网络底纹。 This test report is printed on anti-counterfeiting paper. Its copy should have grid shading.

本中心联系方式:

地址(Address): 北京市朝阳区管庄东里一号北楼

No.1 Guanzhuang Dongli, Chaoyang District, Beijing 100024, P.R. China.

邮编(Post Code):100024

电话(Tel):(1010)(51164723)51164718

传真(Fax):(010)51164724

报告真伪查询(Tel):(010) 51164716

网排 (Web): http://www.dmtc.org.en/

电子邮箱(E-mail): dmtc2007@163.com

