



验报

TEST REPORT

中心编号(No.): 201511AW160

				The second secon	
	At-				The Control of the Control
-			11.47		A COMM
		The second second	PARTY.		
					-
ALC: NO PERSON NAMED IN COLUMN TWO IS NOT THE PERSON NAMED IN COLUMN TWO IS			The second second		A Part I
		The second second	J-1-1		
		The Total			DIF
The state of the s	the same of the same of	DOWN THE RESERVE			
		1		1 1 1	The Part of the
		1			J. J. ohl
	- 100		-		
	The state of the s		The state of the s		A Company of the Comp

样品名称: 蒸压灰砂砖 Sample Name

委托单位: 北京华荣合盛建材有限公司

Client

检验类别: 委托检验

Test Type

(国家)建筑材料工业技术监督研究中心

建筑材料工业干混砂浆产品质量监督检验测试中心 China Building Material Industry Center for Quality Supervision and Test of Dry-mixed Mortar





(国家)。建筑材料工业技术监督研究中心

建筑材料工业干混砂浆产品质量监督检验测试中心

China Building Material Industry Center for Quality Supervision and Test of Dry-mixed Mortar

检验报告

TEST REPORT

中心编号(No.): 201511AW160

第1页共2页

压灰砂砖 中华市中	检验类别	HILMITAUTA		
42745745	四型大刀	委托检验 1000000000000000000000000000000000000		
心京华荣合盛建材有限公司	商标			
5京华荣合盛建材有限公司	等。级	MU20级		
	样品编号			
015年11月17日	规格型号	240mm×115mm×45mm		
	样品状态	块状,外观完好		
B 11945-1999《蒸压灰砂砖》				
10 TABLE TO THE TOTAL THE				
	求。* 发日期: 2015	符合标准 GB 11945-1999 年 12 月 08 日 金验测试章)		
备注:(此处空台)				

(国家) 建筑材料工业技术监督研究中心

建筑材料工业干混砂浆产品质量监督检验测试中心

China Building Material Industry Center for Quality Supervision and Test of Dry-mixed Mortar

检验报告

TEST REPORT

中心编号(No.): 201511AW160

第2页共2页

序号	检验项目	标准要求 (MU20强度级别)		检验结果		单项结论
認	抗压强度/MPa	平均值	单块值	平均值	单块值	認認
認		≥20.0	≥16.0	22.0	20.0	

(以下空白)

备注: (此处空白)