

# APS OAuth Scopes Reference

Complete guide to OAuth scopes and permissions

## Contents

<b>1</b>	<b>APS OAuth Scopes Reference</b>	<b>2</b>
<b>2</b>	<b>Quick Reference</b>	<b>2</b>
<b>3</b>	<b>Data Management Scopes</b>	<b>3</b>
<b>4</b>	<b>Core Data Operations</b>	<b>3</b>
<b>5</b>	<b>data:read*</b>	<b>3</b>
<b>6</b>	<b>data:write*</b>	<b>3</b>
<b>7</b>	<b>data:create*</b>	<b>4</b>
<b>8</b>	<b>Object Storage Service (OSS) Scopes</b>	<b>4</b>
<b>9</b>	<b>Bucket Management</b>	<b>4</b>
<b>10</b>	<b>bucket:read*</b>	<b>4</b>
<b>11</b>	<b>bucket:create*</b>	<b>5</b>
<b>12</b>	<b>bucket:delete*</b>	<b>5</b>
<b>13</b>	<b>Model Derivative &amp; Viewer Scopes</b>	<b>5</b>
<b>14</b>	<b>viewables:read*</b>	<b>5</b>
<b>15</b>	<b>Design Automation Scopes</b>	<b>6</b>
<b>16</b>	<b>code:all*</b>	<b>6</b>
<b>17</b>	<b>Account &amp; Construction Cloud Scopes</b>	<b>6</b>
<b>18</b>	<b>BIM360/ACC Account Management</b>	<b>6</b>
<b>19</b>	<b>account:read*</b>	<b>6</b>
<b>20</b>	<b>account:write*</b>	<b>7</b>
<b>21</b>	<b>Common Scope Combinations</b>	<b>7</b>
<b>22</b>	<b>Basic File Operations</b>	<b>7</b>
<b>23</b>	<b>3D Model Workflow</b>	<b>7</b>
<b>24</b>	<b>Design Automation</b>	<b>7</b>
<b>25</b>	<b>BIM360/ACC Administration</b>	<b>7</b>
<b>26</b>	<b>Maximum Permissions (Development/Testing)</b>	<b>8</b>

<b>27 Scope Troubleshooting</b>	<b>8</b>
<b>28 Checking Current Scopes</b>	<b>8</b>
<b>29 Common Scope Issues</b>	<b>8</b>
<b>30 Error: “Insufficient privileges to access this resource”</b>	<b>8</b>
<b>31 Error: “Access denied to BIM360 project”</b>	<b>8</b>
<b>32 Error: “Cannot create bucket”</b>	<b>8</b>
<b>33 2-Legged vs 3-Legged Authentication</b>	<b>9</b>
<b>34 2-Legged OAuth (Server-to-Server)</b>	<b>9</b>
<b>35 3-Legged OAuth (User Authorization)</b>	<b>9</b>
<b>36 Scope Differences</b>	<b>9</b>
<b>37 Best Practices</b>	<b>9</b>
<b>38 1. Principle of Least Privilege</b>	<b>9</b>
<b>39 2. Scope Validation</b>	<b>9</b>
<b>40 3. Environment-Specific Scopes</b>	<b>10</b>
<b>41 4. Regular Scope Auditing</b>	<b>10</b>
<b>42 Advanced Scope Management</b>	<b>10</b>
<b>43 Dynamic Scope Requests</b>	<b>10</b>
<b>44 Scope Monitoring</b>	<b>10</b>
<b>45 Migration from Forge</b>	<b>10</b>
<b>46 Legacy Forge Scopes</b>	<b>10</b>
<b>47 Getting Help</b>	<b>11</b>
<b>48 Scope-Related Issues</b>	<b>11</b>
<b>49 Debugging Commands</b>	<b>11</b>

## 1 APS OAuth Scopes Reference

- Complete guide to Autodesk Platform Services OAuth scopes and when to use them\*\*
- 

## 2 Quick Reference

Scope	Purpose	APIs Enabled	Example Use Case
<code>data:read</code>	Read files, folders, projects	Data Management GET operations	Download files, list projects
<code>data:write</code>	Modify files and metadata	Data Management PUT/PATCH operations	Update file metadata, rename files
<code>data:create</code>	Create new resources	Data Management POST operations	Upload files, create folders
<code>bucket:read</code>	List and access buckets	OSS read operations	List available storage buckets

Scope	Purpose	APIs Enabled	Example Use Case
bucket:create	Create new buckets	OSS bucket creation	Setup new storage containers
bucket:delete	Remove buckets	OSS bucket deletion	Clean up unused storage
viewables:read	Access translated models	Model Derivative, Viewer SDK	Display 3D models in browser
code:all	Design Automation access	All Design Automation operations	Automate CAD operations
account:read	BIM360/ACC account info	Account Admin API reads	List account details
account:write	Modify BIM360/ACC settings	Account Admin API writes	Manage account settings

- 

### 3 Data Management Scopes

## 4 Core Data Operations

### 5 data:read'

- What it enables:\*\*
- Download files from projects and folders
- List project contents and folder hierarchy
- Read file metadata and version history
- Access item thumbnails and previews
- API Endpoints:\*\*

```
GET /data/v1/projects/{project_id}
GET /data/v1/projects/{project_id}/folders/{folder_id}/contents
GET /data/v1/projects/{project_id}/items/{item_id}/versions
GET /data/v1/projects/{project_id}/downloads
```

- RAPS Usage:\*\*

```
# Login with read-only access
raps auth login --scopes data:read

# List projects (requires data:read)
raps dm projects

# Download file (requires data:read)
raps dm download <item_id> ./local-file.dwg
```

### 6 data:write'

- What it enables:\*\*
- Update file metadata and custom attributes
- Modify folder properties
- Update version descriptions
- Change file relationships and references
- API Endpoints:\*\*

```
PATCH /data/v1/projects/{project_id}/items/{item_id}
PATCH /data/v1/projects/{project_id}/folders/{folder_id}
PATCH /data/v1/projects/{project_id}/versions/{version_id}
```

- RAPS Usage:\*\*

```

# Login with write permissions
raps auth login --scopes data:read,data:write

# Update file metadata
raps dm update-item <item_id> --name "Updated Model.rvt"

```

## 7 data:create<sup>‘</sup>

- What it enables:\*\*
- Upload new files to projects
- Create new folders and project structure
- Create new versions of existing items
- Establish file relationships
- API Endpoints:\*\*

```

POST /data/v1/projects/{project_id}/storage
POST /data/v1/projects/{project_id}/folders
POST /data/v1/projects/{project_id}/items
POST /data/v1/projects/{project_id}/versions

```

- RAPS Usage:\*\*

```

# Login with full data permissions
raps auth login --scopes data:read,data:write,data:create

# Upload new file
raps dm upload model.rvt --project <project_id> --folder <folder_id>

# Create new folder
raps dm create-folder "CAD Models" --parent <folder_id>

```

•

## 8 Object Storage Service (OSS) Scopes

## 9 Bucket Management

## 10 bucket:read<sup>‘</sup>

- What it enables:\*\*
- List available buckets
- Read bucket details and settings
- Access bucket contents (object listing)
- Download objects from buckets
- API Endpoints:\*\*

```

GET /oss/v2/buckets
GET /oss/v2/buckets/{bucketKey}/details
GET /oss/v2/buckets/{bucketKey}/objects
GET /oss/v2/buckets/{bucketKey}/objects/{objectName}

```

- RAPS Usage:\*\*

```

# Login with bucket read access
raps auth login --scopes bucket:read

```

```

# List all accessible buckets
raps bucket list

```

```

# List objects in bucket
raps oss list mybucket

```

## 11 bucket:create<sup>‘</sup>

- What it enables:\*\*
- Create new storage buckets
- Set bucket policies and retention
- Configure bucket permissions
- API Endpoints:\*\*

```
POST /oss/v2/buckets
```

- RAPS Usage:\*\*

```
# Login with bucket creation rights
raps auth login --scopes bucket:read,bucket:create
```

```
# Create new bucket
raps bucket create my-new-bucket --region us-west
```

## 12 bucket:delete<sup>‘</sup>

- What it enables:\*\*
- Delete empty buckets
- Remove bucket policies
- Clean up unused storage containers
- API Endpoints:\*\*

```
DELETE /oss/v2/buckets/{bucketKey}
```

- RAPS Usage:\*\*

```
# Login with full bucket permissions
raps auth login --scopes bucket:read,bucket:create,bucket:delete
```

```
# Delete unused bucket
raps bucket delete old-bucket --confirm
```

•

## 13 Model Derivative & Viewer Scopes

## 14 viewables:read<sup>‘</sup>

- What it enables:\*\*
- Access translated model derivatives (SVF/SVF2)
- Download viewable geometry and metadata
- Initialize Forge Viewer with models
- Extract model properties and metadata
- API Endpoints:\*\*

```
GET /modelderivative/v2/designdata/{urn}/manifest
GET /modelderivative/v2/designdata/{urn}/metadata/{guid}
GET /modelderivative/v2/designdata/{urn}/metadata/{guid}/properties
```

- RAPS Usage:\*\*

```
# Login for model viewing
raps auth login --scopes data:read,viewables:read
```

```
# Start translation for viewing
raps translate <urn> --formats svf2
```

```
# View model in browser
raps view <urn>
```

•

## 15 Design Automation Scopes

### 16 code:all‘

- What it enables:\*\*
- Create and manage Activities
- Upload and manage AppBundle
- Submit and monitor WorkItems
- Access all Design Automation engines (AutoCAD, Revit, Inventor, 3ds Max)
- API Endpoints:\*\*

```
GET /da/us-east/v3/engines  
POST /da/us-east/v3/appbundles  
POST /da/us-east/v3/activities  
POST /da/us-east/v3/workitems
```

- RAPS Usage:\*\*

```
# Login for Design Automation  
raps auth login --scopes code:all  
  
# List available engines  
raps da engines  
  
# Create activity  
raps da create-activity MyActivity --engine Autodesk.AutoCAD+24  
  
# Submit workitem  
raps da submit-workitem MyActivity --input input.dwg --output output.pdf
```

•

## 17 Account & Construction Cloud Scopes

### 18 BIM360/ACC Account Management

### 19 account:read‘

- What it enables:\*\*
- List account information and users
- Read project settings and permissions
- Access account-level reporting data
- View company and project structure
- API Endpoints:\*\*

```
GET /hq/v1/accounts  
GET /hq/v1/accounts/{account_id}/projects  
GET /hq/v1/accounts/{account_id}/users
```

- RAPS Usage:\*\*

```
# Login for account reading  
raps auth login --scopes account:read
```

```
# List accessible accounts  
raps acc accounts  
  
# List projects in account  
raps acc projects --account <account_id>
```

## 20 account:write\*

- What it enables:\*\*
- Modify account settings and permissions
- Create and configure projects
- Manage user access and roles
- Update company information
- API Endpoints:\*\*

```
POST /hq/v1/accounts/{account_id}/projects
PATCH /hq/v1/accounts/{account_id}/projects/{project_id}
POST /hq/v1/accounts/{account_id}/users
    • RAPS Usage:**  

# Login for account management
raps auth login --scopes account:read,account:write  

# Create new project
raps acc create-project "New Building Project" --account <account_id>  

# Add user to project
raps acc add-user user@company.com --project <project_id> --role admin
```

•

## 21 Common Scope Combinations

## 22 Basic File Operations

```
# Read-only access to files and projects
raps auth login --scopes data:read  

# Full file management (most common)
raps auth login --scopes data:read,data:write,data:create
```

## 23 3D Model Workflow

```
# Upload, translate, and view models
raps auth login --scopes data:read,data:write,data:create,viewables:read  

# Include bucket access for direct storage
raps auth login --scopes data:read,data:write,data:create,bucket:read,bucket:create,viewables:read
```

## 24 Design Automation

```
# Full Design Automation access
raps auth login --scopes code:all,data:read,data:write,data:create,bucket:read,bucket:create  

# DA with BIM360 integration
raps auth login --scopes code:all,data:read,data:write,data:create,account:read
```

## 25 BIM360/ACC Administration

```
# Read-only account access
raps auth login --scopes account:read,data:read
```

```
# Full account management
raps auth login --scopes account:read,account:write,data:read,data:write,data:create
```

## 26 Maximum Permissions (Development/Testing)

```
# All available scopes (use carefully)
```

```
raps auth login --scopes data:read,data:write,data:create,bucket:read,bucket:create,bucket:delete,viewab
```

•

## 27 Scope Troubleshooting

### 28 Checking Current Scopes

```
# View current authentication details
raps auth status
```

```
# Show detailed scope information
raps auth status --scopes
```

```
# Test specific scope permissions
raps auth test-scope data:read
```

## 29 Common Scope Issues

### 30 Error: “Insufficient privileges to access this resource”

- Cause:\*\* Missing required scope for the operation
- Solution:\*\*

```
# Check what scopes you have
raps auth status --scopes
```

```
# Re-authenticate with additional scopes
raps auth login --scopes data:read,data:write,data:create
```

### 31 Error: “Access denied to BIM360 project”

- Cause:\*\* User not added to project or missing account scope
- Solution:\*\*

```
# Login with account scope
raps auth login --scopes account:read,data:read
```

```
# Verify project access
raps acc projects
```

### 32 Error: “Cannot create bucket”

- Cause:\*\* Missing bucket:create scope
- Solution:\*\*

```
# Add bucket creation scope
raps auth login --scopes bucket:read,bucket:create
```

```
# Verify bucket permissions
raps auth test-scope bucket:create
```

- 

### 33 2-Legged vs 3-Legged Authentication

#### 34 2-Legged OAuth (Server-to-Server)

- When to use:\*\* Background processing, server applications, automation
- Available scopes:\*\* Limited subset, no user context
- RAPS command:\*\*

```
raps auth login --2legged --scopes data:read,bucket:read,code:all
```

#### 35 3-Legged OAuth (User Authorization)

- When to use:\*\* User-facing applications, accessing user's BIM360/ACC projects
- Available scopes:\*\* Full set, user context preserved
- RAPS command:\*\*

```
raps auth login --3legged --scopes data:read,data:write,account:read
```

#### 36 Scope Differences

Scope	2-Legged	3-Legged	Notes
data:read	Limited	Full	2-legged can't access user's BIM360/ACC
data:write	Limited	Full	2-legged can't modify user's projects
bucket:*	Full	Full	Both have same OSS access
code:all	Full	Full	Design Automation works with both
account:*	None	Full	Account management requires 3-legged

- 

### 37 Best Practices

#### 38 1. Principle of Least Privilege

Request only the scopes your application actually needs:

# Good: Only what's needed for file download  
raps auth login --scopes data:read

# Avoid: Requesting unnecessary permissions  
raps auth login --scopes data:read,data:write,data:create,bucket:delete,account:write

#### 39 2. Scope Validation

Always verify your scopes match your intended operations:

# Test specific functionality  
raps auth test-scope data:write  
raps auth test-scope bucket:create

## 40 3. Environment-Specific Scopes

Use different scopes for different environments:

```
# Development: Full access for testing
raps auth login --profile dev --scopes data:read,data:write,data:create,viewables:read,code:all

# Production: Minimal required scopes
raps auth login --profile prod --scopes data:read,viewables:read
```

## 41 4. Regular Scope Auditing

Periodically review and update your scope requirements:

```
# Review current permissions
raps auth status --scopes --verbose

# Check actual API usage
raps logs --scope-usage --last 30d
```

•

## 42 Advanced Scope Management

### 43 Dynamic Scope Requests

For applications with varying requirements:

```
# Base authentication
raps auth login --scopes data:read,bucket:read

# Request additional scopes when needed
raps auth extend-scopes --add data:write,data:create

# Remove unnecessary scopes
raps auth reduce-scopes --remove bucket:delete
```

## 44 Scope Monitoring

Track scope usage for optimization:

```
# Enable scope usage tracking
raps config set auth.track-scope-usage true

# Generate scope usage report
raps auth scope-report --period 30d
```

•

## 45 Migration from Forge

### 46 Legacy Forge Scopes

If migrating from Forge APIs, map old scopes to new ones:

Forge Scope	APS Equivalent	Notes
data:read	data:read	No change
data:write	data:write	No change
data:create	data:create	No change
bucket:read	bucket:read	No change

Forge Scope	APS Equivalent	Notes
bucket:create	bucket:create	No change
bucket:delete	bucket:delete	No change
viewables:read	viewables:read	No change
code:all	code:all	No change

- Migration command.\*\*

```
# Most Forge scopes work unchanged in APS
raps auth migrate-from-forge --verify-scopes
```

- 

## 47 Getting Help

## 48 Scope-Related Issues

1. Check APS Authentication Guide
2. Test with APS Postman Collection
3. Ask in RAPS Discord

## 49 Debugging Commands

```
# Comprehensive auth diagnosis
raps auth diagnose

# Test specific scope combination
raps auth test-scopes --scopes data:read,bucket:create --endpoint /oss/v2/buckets

# Generate auth report for support
raps auth support-report --sanitize
```

- \*\* Pro Tip:\*\* Use `raps auth status` regularly to verify your current scopes match your intended operations. RAPS will warn you if you're attempting operations without proper permissions.
- *Last verified: January 2026 against APS Authentication API v2 and RAPS v4.2.1*
- OAuth scopes may evolve. Check the official documentation for the latest information.\*