

6.009: Fundamentals of Programming

Week 9 Lecture: More Fun with Functions

11 April 2022

6.009 Labs 8-9

In labs 8-9, we're implementing an interpreter for a dialect of LISP.

Lab 8: basics of evaluation (including function calls)

Lab 9: conditionals, lists, and other nice things

LISP

```
def fib(n):  
    if n <= 1:  
        return n  
    return fib(n-1) + fib(n-2)
```

```
fib(20)
```

```
(:= (fib n)  
    (if (<= n 1)  
        n  
        (+ (fib (- n 1)) (fib (- n 2))))))
```

```
(fib 20)
```

Why Bother Writing Interpreters?

- It is *just so cool!!!*
- It can help you understand the semantics of languages you already know (and contrast differing semantics).
- There is something powerful about the idea that an interpreter (CPython, for example) is *just another program*.

Why LISP?

- LISP is weird/cool :)
 - *"A language that doesn't affect the way you think about programming, is not worth knowing"* -Alan Perlis
- MIT and LISP have a long history
 - invented here in 1958 (McCarthy)
 - one widely-used dialect (Scheme) implemented here as well, used in 6.001 from ~1980-2007
- LISP generally has very minimal syntax, so we can spend less time thinking about tokenizing/parsing, and more time thinking about rules for evaluation.

Functions

A key feature of our little LISP (and of Python) is the ability to define *functions* to abstract away the details of a particular computation.

Two Pieces: Function **Definition** and Function **Application**

Example:

```
def foo(x):  
    return x+7
```

```
foo(3)
```

```
(:= (foo x) (+ x 7))
```

```
(foo 3)
```

Another Example

```
def deriv(f, dx):  
    return lambda x: (f(x+dx) - f(x-dx)) / (2 * dx)
```

Another Example: in LISP

```
(:= (deriv f dx)
     (function (x) (/ (- (f (+ x dx)) (f (- x dx)))
                       (* 2 dx)))))
```

```
(:= (nth-deriv f n dx)
     (if (=? n 0)
         f
         (deriv (nth-deriv f (- n 1) dx) dx)
     )
)
```


Functions are Awesome!

Functions are really powerful; we can implement many other language features using them.

For example, our LISP does not have looping keywords like `for` or `while`. Does this mean that we can't write code that involves loops?