



# Object-Oriented Programming: Polymorphism

## OBJECTIVES

In this chapter you will learn:

- What polymorphism is, how it makes programming more convenient, and how it makes systems more extensible and maintainable.
- To declare and use `virtual` functions to effect polymorphism.
- The distinction between abstract and concrete classes.
- To declare pure `virtual` functions to create abstract classes.
- How to use run-time type information (RTTI) with downcasting, `dynamic_cast`, `typeid` and `type_info`.
- How C++ implements `virtual` functions and dynamic binding “under the hood.”
- How to use `virtual` destructors to ensure that all appropriate destructors run on an object.



## Assignment Checklist

---

Name: \_\_\_\_\_ Date: \_\_\_\_\_

Section: \_\_\_\_\_

Exercises	Assigned: Circle assignments	Date Due
<b>Prelab Activities</b>		
Matching	YES NO	
Fill in the Blank	11, 12, 13, 14, 15, 16, 17	
Short Answer	18, 19, 20, 21	
Programming Output	22, 23	
Correct the Code	24, 25, 26, 27	
<b>Lab Exercises</b>		
Lab Exercise — Polymorphic Banking	YES NO	
Debugging	YES NO	
<b>Labs Provided by Instructor</b>		
1.		
2.		
3.		
<b>Postlab Activities</b>		
Coding Exercises	1, 2, 3, 4, 5	
Programming Challenges	1, 2	



## Prelab Activities

### Matching

Name: \_\_\_\_\_ Date: \_\_\_\_\_

Section: \_\_\_\_\_

After reading Chapter 13 of C++ *How to Program: Fifth Edition*, answer the given questions. These questions are intended to test and reinforce your understanding of key concepts and may be done either before the lab or during the lab.

For each term in the column on the left, write the corresponding letter for the description that best matches it from the column on the right.

Term	Description
___ 1. virtual function	a) Class that is defined, but never intended to be used by the programmer to create objects.
___ 2. virtual function table	b) Functions that contain an initializer of = 0.
___ 3. Override a virtual function	c) Allows objects of different classes related by inheritance to respond differently to the same message.
___ 4. Dynamic binding	d) Part of C++'s run-time type information.
___ 5. virtual base-class destructor	e) Process of replacing an inherited base-class member function with a derived-class one.
___ 6. Abstract base class	f) Programming in the general.
___ 7. Pure virtual function	g) An executing program uses this to select the proper function implementation each time a virtual function is called.
___ 8. Polymorphism	h) Occurs only off pointer or reference handles.
___ 9. Concrete class	i) Resolves the problem that arises when processing dynamically allocated objects in a class hierarchy, polymorphically.
___ 10. typeid	j) Class from which objects can be instantiated.



**Prelab Activities**

Name: \_\_\_\_\_

**Fill in the Blank**

Name: \_\_\_\_\_ Date: \_\_\_\_\_

Section: \_\_\_\_\_

Fill in the blank for each of the following statements:

11. \_\_\_\_\_ functions allow programs to be written to process objects of types that may not exist when the program is under development.
12. \_\_\_\_\_ is implemented via `virtual` functions.
13. Classes from which objects can be \_\_\_\_\_ are called concrete classes.
14. A class is made abstract by declaring one or more \_\_\_\_\_.
15. Resolving `virtual` function references at compile-time is known as \_\_\_\_\_.
16. Objects of a(n) \_\_\_\_\_ class cannot be instantiated in a program.
17. A class with 0 pointers in the *vtable* is a(n) \_\_\_\_\_ class.





**Prelab Activities**

Name: \_\_\_\_\_

**Short Answer**

Name: \_\_\_\_\_ Date: \_\_\_\_\_

Section: \_\_\_\_\_

In the space provided, answer each of the given questions. Your answers should be as concise as possible; aim for two or three sentences.

18. Discuss some of the problems that arise when using `switch` logic to process different objects. How do virtual functions and polymorphic programming eliminate the need for `switch` logic?

19. Briefly discuss what a *vtable* is and how it keeps track of virtual functions.

20. What problem arises when using polymorphism to process dynamically allocated objects of a class hierarchy? How is it resolved?

## Prelab Activities

Name: \_\_\_\_\_

### Short Answer

21. What are some of the program-design advantages of using polymorphism?

## Prelab Activities

Name: \_\_\_\_\_

### Programming Output

Name: \_\_\_\_\_ Date: \_\_\_\_\_

Section: \_\_\_\_\_

For each of the given program segments, read the code and write the output in the space provided below each program. [Note: Do not execute these programs on a computer.]

For *Programming Output Exercises 22 and 23*, use the class definitions in Fig. L 13.1.

```
1  #include <iostream>
2  using std::cout;
3  using std::endl;
4
5  #include <string>
6  using std::string;
7
8  // class Oyster definition
9  class Oyster
10 {
11 public:
12     // constructor
13     Oyster( string genusString )
14     {
15         genus = genusString;
16     } // end class Oyster constructor
17
18     // function getPhylum definition
19     string getPhylum() const
20     {
21         return "Mollusca";
22     } // end function getPhylum
23
24     // function getName definition
25     virtual string getName() const
26     {
27         return "Oyster class";
28     } // end function getName
29
30     // function getGenus definition
31     string getGenus() const
32     {
33         return genus;
34     } // end function getGenus
35
36     // print function
37     virtual void print() const = 0;
38 private:
39     string genus;
40 }; // end class Oyster
41
```

**Fig. L 13.1** | Oyster.cpp. (Part I of 2.)

**Prelab Activities**

Name: \_\_\_\_\_

**Programming Output**

```
42 // class VirginiaOyster definition
43 class VirginiaOyster : public Oyster
44 {
45 public:
46     // constructor calls base-class constructor
47     VirginiaOyster()
48         : Oyster( "Crassostrea" )
49     {
50         // empty
51     } // end class VirginiaOyster constructor
52
53     // function getName definition
54     virtual string getName() const
55     {
56         return "VirginiaOyster class";
57     } // end function getName
58
59     // print function
60     virtual void print() const
61     {
62         cout << "Phylum: " << getPhylum()
63             << "\tGenus: " << getGenus();
64     } // end print function
65 }; // end class VirginiaOyster
```

**Fig. L 13.1** | Oyster.cpp. (Part 2 of 2.)

22. What is output by the following program? Use class Oyster and VirginiaOyster (Fig. L 13.1).

```
1  #include <iostream>
2
3  using std::cout;
4  using std::endl;
5
6  #include "Oyster.cpp"
7
8  int main()
9  {
10     VirginiaOyster oyster;
11     Oyster *baseClassPtr;
12
13     baseClassPtr = &oyster;
14     baseClassPtr->print();
15
16     cout << endl;
17     return 0;
18 } // end main
```

*Your answer:*

**Prelab Activities**

Name: \_\_\_\_\_

**Programming Output**

23. What is output by the following program segment? Assume that the `Oyster` class member function `print` has been changed to that shown below.

```
1  // function print definition
2  virtual void print() const
3  {
4      cout << "Oysters belong to Phylum " << getPhylum() << endl;
5  } // end function print
```

```
1  #include <iostream>
2  using std::cout;
3  using std::endl;
4
5  #include "oyster.cpp"
6
7  int main()
8  {
9      VirginiaOyster *ptr;
10     VirginiaOyster oyster;
11     Oyster *oysterPtr;
12
13     oysterPtr = &oyster;
14     ptr = &oyster;
15
16     ptr -> print();
17     cout << endl;
18
19     oysterPtr -> print();
20     cout << endl << oysterPtr -> getPhylum();
21
22     cout << endl;
23     return 0;
24 } // end main
```

*Your answer:*



**Prelab Activities**

Name: \_\_\_\_\_

**Correct the Code**

Name: \_\_\_\_\_ Date: \_\_\_\_\_

Section: \_\_\_\_\_

For each of the given program segments, determine if there is an error in the code. If there is an error, specify whether it is a logic, syntax or compilation error, circle the error in the program, and write the corrected code in the space provided after each problem. If the code does not contain an error, write “no error.” [Note: It is possible that a program segment may contain multiple errors.]

24. The following code defines an abstract class named Base:

```
1 // class Base definition
2 class Base
3 {
4 public:
5     void print() const;
6 }; // end class Base
```

Your answer:

25. The following is a modified version of the definition of class VirginiaOyster from Fig. L 13.1. Assume member function print is defined in another file.

```
1 // class VirginiaOyster definition
2 class VirginiaOyster : public Oyster
3 {
4 public:
5     // constructor
6     virtual VirginiaOyster( string genusString )
7     {
8         genus = genusString;
9     } // end class VirginiaOyster constructor
10
```

**Prelab Activities**

Name: \_\_\_\_\_

**Correct the Code**

```
11 // constructor
12 VirginiaOyster( char *genusString )
13 {
14     genus = genusString;
15 } // end class VirginiaOyster constructor
16
17 // print function
18 void print() const;
19 }; // end class VirginiaOyster
```

*Your answer:*



## Prelab Activities

Name: \_\_\_\_\_

### Correct the Code

26. The following program defines two classes—BaseClass and DerivedClass—and instantiates an object of type BaseClass. [Note: Only the definitions for BaseClass and DerivedClass are shown; assume that another file is provided that contains the classes' implementations.]

```
1  // class BaseClass definition
2  class BaseClass
3  {
4  public:
5      BaseClass( int = 0, int = 0 );
6      virtual void display() = 0;
7  private:
8      int x;
9      int y;
10 }; // end class BaseClass
11
12 // class DerivedClass definition
13 class DerivedClass
14 {
15 public:
16     DerivedClass( int = 0, int = 0, int = 0 );
17     virtual void display();
18 private:
19     int z;
20 }; // end class BaseClass
21
22 int main()
23 {
24     BaseClass b( 5, 10 );
25     b.display();
26     return 0;
27 } // end main
```

Your answer:

## Prelab Activities

Name: \_\_\_\_\_

### Correct the Code

27. The following program segments define two classes: `Name` and `NameAndWeight`. `Name` should be an abstract base class and `NameAndWeight` should be a concrete derived class. Function `main` should declare an object of type `NameAndWeight` and print its name and weight. [*Note:* Only the definitions for `Name` and `NameAndWeight` are shown; assume files containing member function definitions have been provided elsewhere.]

```
1 // class Name definition
2 class Name
3 {
4 public:
5     Name( string );
6     virtual void printName() const = 0;
7 private:
8     string name;
9 }; // end class Name
10
11 // class NameAndWeight definition
12 class NameAndWeight : public Name
13 {
14 public:
15     NameAndWeight( string, int = 0 );
16     virtual void displayWeight() const;
17 private:
18     int weight;
19 }; // end class NameAndWeight
```

```
1 #include <iostream>
2 using std::cout;
3 using std::endl;
4
5 int main()
6 {
7     NameAndWeight object( "name", 100 );
8
9     cout << "name: " << object.printName() << endl;
10    cout << "weight: " << object.displayWeight() << endl;
11    return 0;
12 } // end main
```

*Your answer:*

## Lab Exercises

---

### Lab Exercise — Polymorphic Banking

Name: \_\_\_\_\_ Date: \_\_\_\_\_

Section: \_\_\_\_\_

This problem is intended to be solved in a closed-lab session with a teaching assistant or instructor present. The problem is divided into five parts:

1. Lab Objectives
2. Description of the Problem
3. Sample Output
4. Program Template (Fig. L 13.2–Fig. L 13.8)
5. Problem-Solving Tips

The program template represents a complete working C++ program, with one or more key lines of code replaced with comments. Read the problem description and examine the sample output; then study the template code. Using the problem-solving tips as a guide, replace the `/* */` comments with C++ code. Compile and execute the program. Compare your output with the sample output provided. The source code for the template is available at [www.deitel.com](http://www.deitel.com) and [www.prenhall.com/deitel](http://www.prenhall.com/deitel).

#### Lab Objectives

This lab was designed to reinforce programming concepts from Chapter 13 of *C++ How To Program: Fifth Edition*. In this lab, you will practice:

- Creating an `Account` base class that contains `virtual` functions and derived classes `SavingsAccount` and `CheckingAccount`.
- Defining `virtual` functions.
- Calling `virtual` functions.
- Downcasting with a pointer with the `dynamic_cast` operator.

#### Description of the Problem

Develop a polymorphic banking program using the `Account` hierarchy created in Exercise 12.10. Create a vector of `Account` pointers to `SavingsAccount` and `CheckingAccount` objects. For each `Account` in the vector, allow the user to specify an amount of money to withdraw from the `Account` using member function `debit` and an amount of money to deposit into the `Account` using member function `credit`. As you process each `Account`, determine its type. If an `Account` is a `SavingsAccount`, calculate the amount of interest owed to the `Account` using member function `calculateInterest`, then add the interest to the account balance using member function `credit`. After processing an `Account`, print the updated account balance obtained by invoking base class member function `getBalance`.

## Lab Exercises

Name: \_\_\_\_\_

## Lab Exercise — Polymorphic Banking

## Sample Output

```

Account 1 balance: $25.00
Enter an amount to withdraw from Account 1: 15.00
Enter an amount to deposit into Account 1: 10.50
Adding $0.61 interest to Account 1 (a SavingsAccount)
Updated Account 1 balance: $21.11

Account 2 balance: $80.00
Enter an amount to withdraw from Account 2: 90.00
Debit amount exceeded account balance.
Enter an amount to deposit into Account 2: 45.00
$1.00 transaction fee charged.
Updated Account 2 balance: $124.00

Account 3 balance: $200.00
Enter an amount to withdraw from Account 3: 75.50
Enter an amount to deposit into Account 3: 300.00
Adding $6.37 interest to Account 3 (a SavingsAccount)
Updated Account 3 balance: $430.87

Account 4 balance: $400.00
Enter an amount to withdraw from Account 4: 56.81
$0.50 transaction fee charged.
Enter an amount to deposit into Account 4: 37.83
$0.50 transaction fee charged.
Updated Account 4 balance: $380.02

```

## Template

```

1  // Lab 1: Account.h
2  // Definition of Account class.
3  #ifndef ACCOUNT_H
4  #define ACCOUNT_H
5
6  class Account
7  {
8  public:
9      Account( double ); // constructor initializes balance
10     /* Write a function prototype for virtual function credit */
11     /* Write a function prototype for virtual function debit */
12     void setBalance( double ); // sets the account balance
13     double getBalance(); // return the account balance
14 private:
15     double balance; // data member that stores the balance
16 }; // end class Account
17
18 #endif

```

Fig. L 13.2 | Account.h.

**Lab Exercises**

Name: \_\_\_\_\_

**Lab Exercise — Polymorphic Banking**

```
1 // Lab 1: Account.cpp
2 // Member-function definitions for class Account.
3 #include <iostream>
4 using std::cout;
5 using std::endl;
6
7 #include "Account.h" // include definition of class Account
8
9 // Account constructor initializes data member balance
10 Account::Account( double initialBalance )
11 {
12     // if initialBalance is greater than or equal to 0.0, set this value
13     // as the balance of the Account
14     if ( initialBalance >= 0.0 )
15         balance = initialBalance;
16     else // otherwise, output message and set balance to 0.0
17     {
18         cout << "Error: Initial balance cannot be negative." << endl;
19         balance = 0.0;
20     } // end if...else
21 } // end Account constructor
22
23 // credit (add) an amount to the account balance
24 void Account::credit( double amount )
25 {
26     balance = balance + amount; // add amount to balance
27 } // end function credit
28
29 // debit (subtract) an amount from the account balance
30 // return bool indicating whether money was debited
31 bool Account::debit( double amount )
32 {
33     if ( amount > balance ) // debit amount exceeds balance
34     {
35         cout << "Debit amount exceeded account balance." << endl;
36         return false;
37     } // end if
38     else // debit amount does not exceed balance
39     {
40         balance = balance - amount;
41         return true;
42     } // end else
43 } // end function debit
44
45 // set the account balance
46 void Account::setBalance( double newBalance )
47 {
48     balance = newBalance;
49 } // end function setBalance
50
51 // return the account balance
52 double Account::getBalance()
53 {
54     return balance;
55 } // end function getBalance
```

**Fig. L 13.3** | Account.cpp.

## Lab Exercises

Name: \_\_\_\_\_

## Lab Exercise — Polymorphic Banking

```

1 // Lab 1: SavingsAccount.h
2 // Definition of SavingsAccount class.
3 #ifndef SAVINGS_H
4 #define SAVINGS_H
5
6 #include "Account.h" // Account class definition
7
8 class SavingsAccount : public Account
9 {
10 public:
11     // constructor initializes balance and interest rate
12     SavingsAccount( double, double );
13
14     double calculateInterest(); // determine interest owed
15 private:
16     double interestRate; // interest rate (percentage) earned by account
17 }; // end class SavingsAccount
18
19 #endif

```

Fig. L 13.4 | SavingsAccount.h.

```

1 // Lab 1: SavingsAccount.cpp
2 // Member-function definitions for class SavingsAccount.
3 #include "SavingsAccount.h" // SavingsAccount class definition
4
5 // constructor initializes balance and interest rate
6 SavingsAccount::SavingsAccount( double initialBalance, double rate )
7     : Account( initialBalance ) // initialize base class
8 {
9     interestRate = ( rate < 0.0 ) ? 0.0 : rate; // set interestRate
10 } // end SavingsAccount constructor
11
12 // return the amount of interest earned
13 double SavingsAccount::calculateInterest()
14 {
15     return getBalance() * interestRate;
16 } // end function calculateInterest

```

Fig. L 13.5 | SavingsAccount.cpp.

```

1 // Lab 1: CheckingAccount.h
2 // Definition of CheckingAccount class.
3 #ifndef CHECKING_H
4 #define CHECKING_H
5
6 #include "Account.h" // Account class definition
7
8 class CheckingAccount : public Account
9 {
10 public:
11     // constructor initializes balance and transaction fee
12     CheckingAccount( double, double );
13

```

Fig. L 13.6 | CheckingAccount.h. (Part 1 of 2.)

## Lab Exercises

Name: \_\_\_\_\_

## Lab Exercise — Polymorphic Banking

```

14  /* Write a function prototype for virtual function credit,
15     which will redefine the inherited credit function */
16  /* Write a function prototype for virtual function debit,
17     which will redefine the inherited debit function */
18 private:
19     double transactionFee; // fee charged per transaction
20
21     // utility function to charge fee
22     void chargeFee();
23 }; // end class CheckingAccount
24
25 #endif

```

Fig. L 13.6 | CheckingAccount.h. (Part 2 of 2.)

```

1  // Lab 1: CheckingAccount.cpp
2  // Member-function definitions for class CheckingAccount.
3  #include <iostream>
4  using std::cout;
5  using std::endl;
6
7  #include "CheckingAccount.h" // CheckingAccount class definition
8
9  // constructor initializes balance and transaction fee
10 CheckingAccount::CheckingAccount( double initialBalance, double fee )
11     : Account( initialBalance ) // initialize base class
12 {
13     transactionFee = ( fee < 0.0 ) ? 0.0 : fee; // set transaction fee
14 } // end CheckingAccount constructor
15
16 // credit (add) an amount to the account balance and charge fee
17 void CheckingAccount::credit( double amount )
18 {
19     Account::credit( amount ); // always succeeds
20     chargeFee();
21 } // end function credit
22
23 // debit (subtract) an amount from the account balance and charge fee
24 bool CheckingAccount::debit( double amount )
25 {
26     bool success = Account::debit( amount ); // attempt to debit
27
28     if ( success ) // if money was debited, charge fee and return true
29     {
30         chargeFee();
31         return true;
32     } // end if
33     else // otherwise, do not charge fee and return false
34         return false;
35 } // end function debit
36
37 // subtract transaction fee
38 void CheckingAccount::chargeFee()
39 {
40     Account::setBalance( getBalance() - transactionFee );

```

Fig. L 13.7 | CheckingAccount.cpp. (Part 1 of 2.)

## Lab Exercises

Name: \_\_\_\_\_

## Lab Exercise — Polymorphic Banking

```

41     cout << "$" << transactionFee << " transaction fee charged." << endl;
42 } // end function chargeFee

```

Fig. L 13.7 | CheckingAccount.cpp. (Part 2 of 2.)

```

1  // Lab 1: polymorphicBanking.cpp
2  // Processing Accounts polymorphically.
3  #include <iostream>
4  using std::cout;
5  using std::cin;
6  using std::endl;
7
8  #include <iomanip>
9  using std::setprecision;
10 using std::fixed;
11
12 #include <vector>
13 using std::vector;
14
15 #include "Account.h" // Account class definition
16 #include "SavingsAccount.h" // SavingsAccount class definition
17 #include "CheckingAccount.h" // CheckingAccount class definition
18
19 int main()
20 {
21     // create vector accounts
22     /* Write declarations for a vector of four pointers
23        to Account objects, called accounts */
24
25     // initialize vector with Accounts
26     accounts[ 0 ] = new SavingsAccount( 25.0, .03 );
27     accounts[ 1 ] = new CheckingAccount( 80.0, 1.0 );
28     accounts[ 2 ] = new SavingsAccount( 200.0, .015 );
29     accounts[ 3 ] = new CheckingAccount( 400.0, .5 );
30
31     cout << fixed << setprecision( 2 );
32
33     // loop through vector, prompting user for debit and credit amounts
34     for ( size_t i = 0; i < accounts.size(); i++ )
35     {
36         cout << "Account " << i + 1 << " balance: $"
37             << /* Call the getBalance function through Account pointer i */;
38
39         double withdrawalAmount = 0.0;
40         cout << "\nEnter an amount to withdraw from Account " << i + 1
41             << ": ";
42         cin >> withdrawalAmount;
43         /* Call the debit function through Account pointer i */
44
45         double depositAmount = 0.0;
46         cout << "Enter an amount to deposit into Account " << i + 1
47             << ": ";
48         cin >> depositAmount;
49         /* Call the credit function through Account pointer i */
50

```

Fig. L 13.8 | polymorphicBanking.cpp. (Part 1 of 2.)



## Lab Exercises

Name: \_\_\_\_\_

## Lab Exercise — Polymorphic Banking

```

51     // downcast pointer
52     SavingsAccount *savingsAccountPtr =
53         /* Write a dynamic_cast operation to attempt to downcast
54            Account pointer i to a SavingsAccount pointer */
55
56     // if Account is a SavingsAccount, calculate and add interest
57     if ( /* Write a test to determine if savingsAccountPtr isn't 0 */ )
58     {
59         double interestEarned = /* Call member function calculateInterest
60                                through savingsAccountPtr */;
61         cout << "Adding $" << interestEarned << " interest to Account "
62              << i + 1 << " (a SavingsAccount)" << endl;
63         /* Use the credit function to credit interestEarned to
64            the SavingsAccount pointed to by savingsAccountPtr*/
65     } // end if
66
67     cout << "Updated Account " << i + 1 << " balance: $"
68          << /* Call the getBalance function through Account pointer i */
69          << "\n\n";
70 } // end for
71
72 return 0;
73 } // end main

```

Fig. L 13.8 | polymorphicBanking.cpp. (Part 2 of 2.)

## Problem-Solving Tips

1. To achieve polymorphism, declare the functions that should be called polymorphically as `virtual`. To indicate a `virtual` function within a class definition, add “`virtual`” before the function prototype. When the `virtual` functions are redefined in a derived class, those member function prototypes should also be preceded by the keyword `virtual` as a good programming practice.
2. To determine if a pointer to an `Account` object is actually pointing to a `SavingsAccount` object, downcast it to a `SavingsAccount *` using the `dynamic_cast` operator. If the pointer returned by this operation is not the null pointer (i.e., 0) then the object is a `SavingsAccount` object and that pointer can be used to access members unique to class `SavingsAccount`.
3. Remember that your compiler may require you to enable run-time type information (RTTI) for this particular project before this program will run correctly.



## Lab Exercises

Name: \_\_\_\_\_

### Debugging

Name: \_\_\_\_\_ Date: \_\_\_\_\_

Section: \_\_\_\_\_

The program (Fig. L 13.9–Fig. L 13.15) in this section does not run properly. Fix all the compilation errors so that the program will compile successfully. Once the program compiles, compare the output with the sample output, and eliminate any logic errors that may exist. The sample output demonstrates what the program's output should be once the program's code has been corrected.

### Sample Output

```
This animal is a lion
This animal's height and weight are as follows:
Height: 45      Weight: 300

Enter a new height (using standard units): 50
Enter a new weight (using standard units): 400
Here are the new height and weight values
50
400

This animal is a dog, its name is: Fido
This animal's height and weight are as follows:
Height: 60      Weight: 120

Enter a new height (using standard units): 50
Enter a new weight (using standard units): 116
Which units would you like to see the height in? (Enter 1 or 2)
    1. metric
    2. standard
2
Which units would you like to see the weight in? (Enter 1 or 2)
    1. metric
    2. standard
1
Here are the new height and weight values
50
52
```

## Lab Exercises

Name: \_\_\_\_\_

## Debugging

## Broken Code

```

1 // Debugging: Animal.h
2 #ifndef ANIMAL_H
3 #define ANIMAL_H
4
5 #include <string>
6 using std::string;
7
8 // Note: class Animal is an abstract class
9 // class Animal definition
10 class Animal
11 {
12 public:
13     Animal( int = 0, int = 0 );
14
15     void setHeight( int );
16     virtual int getHeight() const = 0;
17
18     void setWeight( int );
19     virtual int getWeight() const = 0;
20
21     virtual void print() const = 0;
22 private:
23     int height;
24     int weight;
25 }; // end class Animal
26
27 #endif // ANIMAL_H

```

Fig. L 13.9 | Contents of Animal.h.

```

1 // Debugging: Animal.cpp
2 #include <iostream>
3 using std::cout;
4 using std::endl;
5
6 #include "Animal.h"
7
8 // default constructor
9 Animal::Animal( int h, int w )
10 {
11     height = h;
12     weight = w;
13 } // end class Animal constructor
14
15 // function print definition
16 virtual void Animal::print() const
17 {
18     cout << "This animal's height and weight are as follows:\n"
19          << "Height: " << height << "\tWeight: " << weight
20          << endl << endl;
21 } // end function print
22

```

Fig. L 13.10 | Contents of animal.cpp. (Part 1 of 2.)

## Lab Exercises

Name: \_\_\_\_\_

### Debugging

```
23 // return height
24 int Animal::getHeight() const
25 {
26     return height;
27 } // end function getHeight
28
29 // return weight
30 int Animal::getWeight() const
31 {
32     return weight;
33 } // end function getWeight
34
35 // function setHeight definition
36 virtual void Animal::setHeight( int h )
37 {
38     height = h;
39 } // end function setHeight
40
41 // function setWeight definition
42 virtual void Animal::setWeight( int w )
43 {
44     weight = w;
45 } // end function setWeight
```

**Fig. L 13.10** | Contents of animal.cpp. (Part 2 of 2.)

```
1 // Debugging: Lion.h
2 #ifndef LION_H
3 #define LION_H
4
5 #include "Animal.h"
6
7 // class Lion definition
8 class Lion : public Animal
9 {
10 public:
11     Lion( int = 0, int = 0 );
12     virtual void print() const;
13 }; // end class Lion
14
15 #endif // LION_H
```

**Fig. L 13.11** | Contents of Lion.h.

```
1 // Debugging: Lion.cpp
2 #include <iostream>
3
4 using std::cout;
5 using std::endl;
6
7 #include "Lion.h"
8
```

**Fig. L 13.12** | Contents of Lion.cpp. (Part 1 of 2.)

## Lab Exercises

Name: \_\_\_\_\_

## Debugging

```

 9 // default constructor
10 Lion::Lion( int h, int w )
11     : Animal( h, w )
12 {
13     // empty
14 } // end class Lion constructor
15
16 // function print definition
17 void Lion::print() const
18 {
19     cout << "This animal is a lion\n";
20     Animal::print();
21 } // end function print

```

Fig. L 13.12 | Contents of Lion.cpp. (Part 2 of 2.)

```

 1 // Debugging: Dog.h
 2 #ifndef DOG_H
 3 #define DOG_H
 4
 5 #include "Animal.h"
 6
 7 // class Dog definition
 8 class Dog : public Animal
 9 {
10 public:
11     Dog( int = 0, int = 0, string = "Toto" );
12
13     virtual void print() const = 0;
14     virtual void getHeight() const = 0;
15     virtual void getWeight() const = 0;
16     string getName() const;
17     void setName( string );
18 private:
19     bool useMetric( string ) const;
20     string name;
21     int metricHeight;
22     int metricWeight;
23 }; // end class Dog
24
25 #endif // DOG_H

```

Fig. L 13.13 | Contents of Dog.h.

```

 1 // Debugging Dog.cpp
 2 #include <iostream>
 3
 4 using std::cout;
 5 using std::endl;
 6 using std::cin;
 7
 8 #include "Dog.h"
 9

```

Fig. L 13.14 | Contents of Dog.cpp. (Part 1 of 3.)

## Lab Exercises

Name: \_\_\_\_\_

## Debugging

```

10 // default constructor
11 Dog::Dog( int h, int w, string n )
12     : Animal( h, w )
13 {
14     setName( n );
15     metricHeight = h * 2.5;
16     metricWeight = w / 2.2;
17 } // end class Dog constructor
18
19 // return name
20 string Dog::getName() const
21 {
22     return name;
23 } // end function getName
24
25 // function setName definition
26 void Dog::setName( string n )
27 {
28     name = n;
29 } // end function setName
30
31 // function print definition
32 void Dog::print() const
33 {
34     cout << "This animal is a dog, its name is: "
35         << name << endl;
36     Animal::print();
37 } // end function print
38
39 // return height
40 int Dog::getHeight()
41 {
42     if ( useMetric( "height" ) )
43         return metricHeight;
44     else
45         return Animal::getHeight();
46 } // end function print
47
48 // return weight
49 int Dog::getWeight()
50 {
51     if ( useMetric( "weight" ) )
52         return metricWeight;
53     else
54         return Animal::getWeight();
55 } // end function getWeight
56
57 // function useMetric definition
58 bool Dog::useMetric( string type ) const
59 {
60     int choice = 0;
61
62     cout << "Which units would you like to see the "
63         << type << " in? (Enter 1 or 2)\n"
64         << "\t1. metric\n"
65         << "\t2. standard\n";

```

Fig. L 13.14 | Contents of Dog.cpp. (Part 2 of 3.)

## Lab Exercises

Name: \_\_\_\_\_

## Debugging

```

66
67     cin >> choice;
68
69     if ( choice == 1 )
70         return true;
71     else
72         return false;
73 } // end function useMetric

```

Fig. L 13.14 | Contents of Dog.cpp. (Part 3 of 3.)

```

1  // Debugging: Debugging.cpp
2  #include <iostream>
3  using std::cout;
4  using std::endl;
5  using std::cin;
6
7  #include "Animal.h"
8  #include "Lion.h"
9  #include "Dog.h"
10
11 void setHeightWeight( Animal ) const;
12
13 int main()
14 {
15     Dog dog1( 60, 120, "Fido" );
16     Lion lion1( 45, 300 );
17
18     setHeightWeight( lion1 );
19     setHeightWeight( dog1 );
20     return 0;
21 } // end main
22
23 // function setHeightWeight definition
24 void setHeightWeight( Animal )
25 {
26     int height;
27     int weight;
28
29     a->print();
30     cout << "Enter a new height (using standard units): ";
31     cin >> height;
32     a->setHeight( height );
33
34     cout << "Enter a new weight (using standard units): ";
35     cin >> weight;
36     a->setWeight( weight );
37
38     height = a->getHeight();
39     weight = a->getWeight();
40
41     cout << "Here are the new height and weight values:\n"
42         << height << endl
43         << weight << endl << endl;
44 } // end function setHeightWeight

```

Fig. L 13.15 | Contents of debugging.cpp.



## Postlab Activities

---

### Coding Exercises

Name: \_\_\_\_\_ Date: \_\_\_\_\_

Section: \_\_\_\_\_

These coding exercises reinforce the lessons learned in the lab and provide additional programming experience outside the classroom and laboratory environment. They serve as a review after you have completed the *Prelab Activities* and *Lab Exercises* successfully.

For each of the following problems, write a program or a program segment that performs the specified action:

1. Write the header file for an abstract base class named `Base`. Include a virtual destructor and a virtual print function.
2. Write the header file for the class `Derived` that inherits publicly from class `Base` that you defined in *Coding Exercise 1*. Class `Derived` has one integer as its private data member and should have a print member function.

## Postlab Activities

Name:

## Coding Exercises

3. Override class `Derived`'s `print` member function to print the value of the class's private data member.
4. Create a `Derived` object and assign its address to a `Base` pointer. Explain why this assignment is allowed by the compiler.
5. Assign the `Base` pointer from *Coding Exercise 4* to a `Derived` pointer, without using any cast operators. Explain why this assignment is not permitted by the compiler?

**Postlab Activities**

Name: \_\_\_\_\_

**Programming Challenges**

Name: \_\_\_\_\_ Date: \_\_\_\_\_

Section: \_\_\_\_\_

The *Programming Challenges* are more involved than the *Coding Exercises* and may require a significant amount of time to complete. Write a C++ program for each of the problems in this section. The answers to these problems are available at [www.deitel.com](http://www.deitel.com) and [www.prenhall.com/deitel](http://www.prenhall.com/deitel). Pseudocode, hints and/or sample outputs are provided to aid you in your programming.

1. Modify the payroll system of Fig. 13.13–Fig. 13.23 to include private data member `birthDate` in class `Employee`. Use class `Date` from Fig. 11.12–Fig. 11.13 to represent an employee's birthday. Assume that payroll is processed once per month. Create a vector of `Employee` references to store the various employee objects. In a loop, calculate the payroll for each `Employee` (polymorphically), and add a \$100.00 bonus to the person's payroll amount if the current month is the month in which the `Employee`'s birthday occurs.

**Hints:**

- Since all employees have a birthday, the only class that needs to be modified to add a `birthDate` is the base class `Employee`.
- Add an appropriate member function for manipulating the birthday data such as `getBirthDate`.
- Modify the `Employee` class's constructor to ensure that the `birthDate` is initialized.
- Use standard library functions of `ctime` to determine the current month based on the computer's system clock.

**Postlab Activities**

Name: \_\_\_\_\_

**Programming Challenges**

- Sample output:

```
Employees processed polymorphically via dynamic binding:

salaried employee: John Smith
birthday: June 15, 1944
social security number: 111-11-1111
weekly salary: 800.00
earned $800.00

hourly employee: Karen Price
birthday: December 29, 1960
social security number: 222-22-2222
hourly wage: 16.75; hours worked: 40.00
HAPPY BIRTHDAY!
earned $770.00

commission employee: Sue Jones
birthday: September 8, 1954
social security number: 333-33-3333
gross sales: 10000.00; commission rate: 0.06
earned $600.00

base-salaried commission employee: Bob Lewis
birthday: March 2, 1965
social security number: 444-44-4444
gross sales: 5000.00; commission rate: 0.04; base salary: 300.00
old base salary: $300.00
new base salary with 10% increase is: $330.00
earned $530.00

deleting object of class SalariedEmployee
deleting object of class HourlyEmployee
deleting object of class CommissionEmployee
deleting object of class BasePlusCommissionEmployee
```

2. Use the Package inheritance hierarchy created in Exercise 12.9 to create a program that displays the address information and calculates the shipping costs for several Packages. The program should contain a vector of Package pointers to objects of classes TwoDayPackage and OvernightPackage. Loop through the vector to process the Packages polymorphically. For each Package, invoke *get* functions to obtain the address information of the sender and the recipient, then print the two addresses as they would appear on mailing labels. Also, call each Package's *calculateCost* member function and print the result. Keep track of the total shipping cost for all Packages in the vector, and display this total when the loop terminates.

## Postlab Activities

Name: \_\_\_\_\_

### Programming Challenges

**Hint:**

- Sample output:

```
Package 1
Sender:
Lou Brown
1 Main St
Boston, MA 11111
Recipient:
Mary Smith
7 Elm St
New York, NY 22222
Cost: $4.25
Package 2
Sender:
Lisa Klein
5 Broadway
Somerville, MA 33333
Recipient:
Bob George
21 Pine Rd
Cambridge, MA 44444
Cost: $8.82
Package 3
Sender:
Ed Lewis
2 Oak St
Boston, MA 55555
Recipient:
Don Kelly
9 Main St
Denver, CO 66666
Cost: $11.64
Total shipping cost: $24.71
```

