



# UNIVERSITY of LIMERICK

O L L S C O I L L U I M N I G H

COLLEGE of INFORMATICS and ELECTRONICS  
Department of Computer Science and Information Systems

## End-of-Semester Exam

---

<b>Academic Year:</b>	2007/2008	<b>Semester:</b>	Autumn
<b>Module Title:</b>	Document Architectures	<b>Module Code:</b>	CS4146
<b>Exam Duration:</b>	2½ Hours	<b>Total Marks:</b>	75 (75% of the final grade)
<b>Lecturer:</b>	Dr. N. S. Nikolov		

---

### Instructions to Candidates:

Please write all answers in the answer booklet.  
State clearly any assumptions you make.

Choose to answer either Q2.1 or Q2.2. All other questions should be answered.

---

## QUESTIONS

---

### Q1. Multiple-choice and short-answer questions (15 marks)

(N.B. Each multiple-choice question has **exactly one** correct answer.)

#### Q1.1. Which of the following is a binary document format? (1 mark)

- a. RTF
- b. Postscript
- c. Microsoft Word Document
- d. XML
- e. None of the above

#### Q1.2. XHTML is an \_\_\_\_\_ application. (1 mark)

- a. XML
- b. SGML
- c. XSLT
- d. SMTP
- e. None of the above

#### Q1.3. Describe briefly how structure can be separated from presentation in HTML documents. (3 marks)

**Q1.4.** If used in a DTD, B\* refers to element B that occurs in an XML document (1 marks)

- a. exactly once
- b. once followed by the + character
- c. zero, one, or more times
- d. at least once
- e. None of the above

In the following three questions consider the XML file:

```
<?xml version="1.0" encoding="utf-8"?>
<Class>
  <Student>
    <Name>Michelle</Name>
    <Course>Computer Systems</Course>
  </Student>
  <Student>
    <Name>Norah</Name>
    <Course>Software Localisation</Course>
  </Student>
  <Student>
    <Name>Peter</Name>
    <Course>Software Engineering</Course>
  </Student>
</Class>
```

**Q1.5.** What will be selected by the following XPath expression? (1 mark)

**`/Class/Student[3]/*[2]`**

**Q1.6.** What will be selected by the following XPath expression? (1 mark)

**`/Class/Student[2]/*[2]/ancestor::*[2]`**

**Q1.7.** What will be selected by the following XPath expression? (1 mark)

**`/Class/Student[2]/ancestor::*[1]/child::*[2]`**

**Hint:** The first child element of an element has index 1.

**Q1.8.** What are the four requirements for an XML document to be well formed? (3 marks)  
Can an XML document be well formed but not valid? Why?

**Q1.9.** Compare briefly bitmaps vs. vector images. (3 marks)

## Q2. Document Type Definition and XML Schema

(20 marks)

Choose to answer either Q2.1 or Q2.2.

Consider the following two XML documents.

tvshow01.xml	tvshow02.xml
<pre>&lt;?xml version="1.0" encoding="UTF-8"?&gt;  &lt;tvshow year="1999" rating="PG" season="1"&gt;   &lt;title&gt;Futurama&lt;/title&gt;   &lt;genrelist&gt;     &lt;genre name="Animation"/&gt;     &lt;genre name="SciFi"/&gt;     &lt;genre name="Comedy"/&gt;   &lt;/genrelist&gt;   &lt;creator&gt;     &lt;firstname&gt;Matt&lt;/firstname&gt;     &lt;surname&gt;Groening&lt;/surname&gt;   &lt;/creator&gt;   &lt;cast&gt;     &lt;castmember role="Philip J. Fry"&gt;       &lt;firstname&gt;Billy&lt;/firstname&gt;       &lt;surname&gt;West&lt;/surname&gt;     &lt;/castmember&gt;     &lt;castmember role="Turanga Leela"&gt;       &lt;firstname&gt;Katey&lt;/firstname&gt;       &lt;surname&gt;Sagal&lt;/surname&gt;     &lt;/castmember&gt;   &lt;/cast&gt; &lt;/tvshow&gt;</pre>	<pre>&lt;?xml version="1.0" encoding="UTF-8"?&gt;  &lt;tvshow year="1999" rating="PG" season="1"&gt;   &lt;title&gt;Futurama&lt;/title&gt;   &lt;genrelist&gt;     &lt;genre name="Cartoon"/&gt;   &lt;/genrelist&gt;   &lt;creator&gt;     &lt;firstname&gt;Matt&lt;/firstname&gt;     &lt;surname&gt;Groening&lt;/surname&gt;   &lt;/creator&gt;   &lt;cast&gt;     &lt;castmember role="Philip J. Fry"&gt;       &lt;firstname&gt;Billy&lt;/firstname&gt;       &lt;surname&gt;West&lt;/surname&gt;     &lt;/castmember&gt;   &lt;/cast&gt; &lt;/tvshow&gt;</pre>

**Q2.1.** Write a DTD such that tvshow01.xml conforms to it (i.e. it is valid), and tvshow02.xml does NOT conform to it (i.e. it is invalid).

**Hint:** Use any of the DTD declarations:

```
<!ELEMENT name (type)>
<!ATTLIST element_name
  attribute_name type default_value
  attribute_name type default_value
  ...
>
```

**Q2.2.** Write an XML Schema such that tvshow01.xml conforms to it (i.e. it is valid), and tvshow02.xml does NOT conform to it (i.e. it is invalid).

**Hint:** Use the following general structure for the schema

```
<?xml version="1.0" encoding="UTF-8"?>
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <!-- definition of simple types --> ...
  <!-- definition of complex types --> ...
  <xs:element name="root_element" type="root_element_type"/>
</xs:schema>
```

Q3. Consider the following XML document.

(20 marks)

```
library.xml
<?xml version="1.0" encoding="UTF-8"?>

<library>
  <section id="1" subject="Computer Science">
    <book language="English" copies="30">
      <title>C++ Primer</title>
      <author>
        <firstname>John</firstname>
        <surname>Murphy</surname>
      </author>
      <author>
        <firstname>Dan</firstname>
        <surname>North</surname>
      </author>
    </book>
    <book language="English" copies="40">
      <title>Problem Solving with Java</title>
      <author>
        <firstname>Nell</firstname>
        <surname>Dale</surname>
      </author>
    </book>
  </section>
  <section id="2" subject="Chemistry"/>
</library>
```

Let

```
xmlDoc = new ActiveXObject('Microsoft.XMLDOM');
xmlDoc.load('books.xml');
```

- a. (5 marks) Draw the XML DOM tree for **library.xml**. For each node, specify its name, type and value.
- b. (5 marks) What are the values of the variables **a**, **b**, and **c** after executing the following fragment of JavaScript code.

```
doc = xmlDoc.documentElement; //root
a = doc.firstChild.childNodes.item(0).firstChild.nodeValue;
b = doc.firstChild.childNodes.item(0).firstChild.firstChild.nodeValue;
c = doc.lastChild.getAttribute("subject");
```

- c. (5 marks) Write a JavaScript statement that assigns the contents of the last **surname** element (i.e., the string **"Dale"**) to a variable called **sname**.
- d. (5 marks) Write a JavaScript statement that assigns the value of the attribute **copies** of the first **book** element (i.e., **"30"**) to a variable called **ncopies**.


**Q4.** Consider the following XML document.

**(20 marks)**

**class.xml**

```
<?xml version="1.0" encoding="UTF-8"?>
<Class>
  <Students>
    <Student id="03453345">
      <Name>Michelle</Name>
      <Grade module="CS8182" value="3"/>
      <Grade module="CS8358" value="3"/>
      <Grade module="CS8234" value="1"/>
      <Grade module="CS8742" value="4.5"/>
    </Student>
    <Student id="03329032">
      <Name>Norah</Name>
      <Grade module="CS8182" value="8"/>
      <Grade module="CS8358" value="6.25"/>
      <Grade module="CS8234" value="5"/>
      <Grade module="CS8742" value="4"/>
    </Student>
    <Student id="03353453">
      <Name>Peter</Name>
      <Grade module="CS8182" value="1"/>
      <Grade module="CS8358" value="2"/>
      <Grade module="CS8234" value="2"/>
      <Grade module="CS8742" value="2"/>
    </Student>
  </Students>
</Class>
```

**a. (5 marks)** Write an XSLT stylesheet that transforms **class.xml** into an HTML document which contains only the names of the students. That is, when loaded in a browser the HTML document should look like:



**b. (15 marks)** Write an XSLT stylesheet that transforms **class.xml** into an XML document which contains only the students whose second grade is greater than or equal to 3, and has the following format:

```
<?xml version="1.0" encoding="utf-8"?>
<Class>
  <Student name="Michelle">
    <Grades>3, 2, 1, 4.5</Grades>
  </Student>
  <Student name="Norah">
    <Grades>8, 6.25, 5, 4</Grades>
  </Student>
</Class>
```

**Hint:** Use the expression `<xsl:if test="Grade[2] /@value >= 3">` to check the value of the second grade.

**End of Exam**