

A decorative graphic on the right side of the page. It features three blue circles of different sizes, each composed of concentric rings of varying shades of blue. Two thin blue lines intersect at a point between the top two circles, extending towards the top-left and bottom-right corners of the page. A third thin blue line extends from the bottom-right corner towards the bottom-right circle.

# CS4313

## Deliverable 4

All Database tables  
Description of all functionality  
All HTML Pages  
All PHP scripts  
List of copied material and sources

**David O Neill 0813001**  
**James McHugh 0052833**  
**Keiran Duggan 0866504**

**19/4/2010**

## Table of Contents


Database.....	4
Tables.....	4
Auction items.....	4
SQL.....	5
Auction pictures.....	6
SQL.....	6
Auction categories.....	7
SQL.....	7
Auction sub categories .....	7
SQL.....	7
Messages .....	8
SQL.....	8
Auction Bids.....	9
SQL.....	9
Item watching.....	10
SQL.....	10
Auction feedback.....	11
SQL.....	11
Addresses .....	12
SQL.....	12
OU users .....	13
SQL.....	13
OU groups.....	14
SQL.....	14
Countries .....	14
SQL.....	14
Locale.....	15
SQL.....	15
Referential Integrity Constraints .....	16
SQL.....	16
Overview.....	17
Relations Overview.....	17

Design & Implementation .....	18
Requirements .....	18
Major Processes .....	18
User Registration .....	18
Update registration .....	19
Login .....	19
Logout.....	19
Submit Auction .....	20
Browse Auctions .....	20
View auction .....	21
Bidding .....	21
Searching .....	21
Feedback.....	22
Watch item .....	22
Administrator .....	22
Delete User .....	22
Ban User .....	22
Update auction .....	22
Delete auction .....	22
Non Functional Requirements.....	23
Model – View - Controller .....	23
Sample controller .....	23
Sample Template .....	24
View Constructor .....	24
View Includes.....	24
View Processing.....	25
View Process Directive .....	26
View Output.....	26
Localisation .....	27
Security .....	28
Prototype UML Class Diagram.....	29
Copied materials.....	30

# Database

## Tables


### Auction items



## SQL

```
CREATE TABLE auction_items (  
  auction_id int(11) NOT NULL AUTO_INCREMENT,  
  price int(11) NOT NULL,  
  postage int(11) NOT NULL,  
  bidding_endtime timestamp NOT NULL DEFAULT '0000-00-00 00:00:00',  
  country_from int(11) NOT NULL,  
  sellerid int(11) NOT NULL,  
  `condition` int(1) NOT NULL,  
  bid_history int(11) NOT NULL,  
  starting_bid int(11) NOT NULL,  
  reserve int(11) NOT NULL,  
  item_header_description varchar(255) NOT NULL,  
  item_full_description blob NOT NULL,  
  cat_id int(11) NOT NULL,  
  subcat_id int(11) NOT NULL,  
  `status` int(1) NOT NULL,  
  PRIMARY KEY (auction_id),  
  KEY country_from (country_from),  
  KEY sellerid (sellerid),  
  KEY cat_id (cat_id),  
  KEY subcat_id (subcat_id)  
) ENGINE=InnoDB DEFAULT CHARSET=latin1;
```


## Auction pictures



## SQL

```
CREATE TABLE IF NOT EXISTS `auction_pictures` (  
  `pic_id` int(11) NOT NULL AUTO_INCREMENT,  
  `auction_id` int(11) NOT NULL,  
  `pic_url` varchar(255) NOT NULL,  
  PRIMARY KEY (`pic_id`),  
  KEY `auction_id` (`auction_id`)  
) ENGINE=InnoDB DEFAULT CHARSET=latin1 AUTO_INCREMENT=9;
```


### Auction categories

auction_categories		
	<b>cat_id</b>	int
	<b>name</b>	varchar(255)

### SQL

```
CREATE TABLE auction_categories (  
  cat_id int(11) NOT NULL AUTO_INCREMENT,  
  `name` varchar(255) NOT NULL,  
  PRIMARY KEY (cat_id)  
) ENGINE=InnoDB DEFAULT CHARSET=latin1;
```


### Auction sub categories



### SQL

```
CREATE TABLE auction_sub_categories (  
  subcat_id int(11) NOT NULL AUTO_INCREMENT,  
  `name` varchar(255) NOT NULL,  
  cat_id int(11) NOT NULL,  
  PRIMARY KEY (subcat_id),  
  KEY cat_id (cat_id)  
) ENGINE=InnoDB DEFAULT CHARSET=latin1;
```

## Messages




## SQL

```
CREATE TABLE messages (  
  msg_id int(11) NOT NULL AUTO_INCREMENT,  
  from_id int(11) NOT NULL,  
  to_id int(11) NOT NULL,  
  title varchar(255) NOT NULL,  
  body blob NOT NULL,  
  receipt int(1) NOT NULL,  
  `status` int(1) NOT NULL,  
  PRIMARY KEY (msg_id),  
  KEY from_id (from_id),  
  KEY to_id (to_id)  
) ENGINE=InnoDB DEFAULT CHARSET=latin1;
```



## Auction Bids




## SQL

```

CREATE TABLE auction_bids (
  id_bid int(11) NOT NULL AUTO_INCREMENT,
  user_id int(11) NOT NULL,
  amount int(11) NOT NULL,
  auction_id int(11) NOT NULL,
  `time` timestamp NOT NULL DEFAULT CURRENT_TIMESTAMP,
  PRIMARY KEY (id_bid),
  KEY auction_id (auction_id),
  KEY user_id (user_id)
) ENGINE=InnoDB DEFAULT CHARSET=latin1;
  
```


## Item watching



## SQL

```
CREATE TABLE item_watching (  
  watch_id int(11) NOT NULL AUTO_INCREMENT,  
  auction_id int(11) NOT NULL,  
  user_id int(11) NOT NULL,  
  PRIMARY KEY (watch_id),  
  KEY auction_id (auction_id),  
  KEY user_id (user_id)  
) ENGINE=InnoDB DEFAULT CHARSET=latin1;
```

## Auction feedback




## SQL

```

CREATE TABLE auction_feedback (
  feed_id int(11) NOT NULL AUTO_INCREMENT,
  auction_id int(11) NOT NULL,
  buyer_id int(11) NOT NULL,
  seller_id int(11) NOT NULL,
  rating_product int(1) NOT NULL,
  rating_promptness int(1) NOT NULL,
  rating_communication int(1) NOT NULL,
  rating_overall int(1) NOT NULL,
  rating_message mediumblob NOT NULL,
  PRIMARY KEY (feed_id),
  KEY auction_id (auction_id),
  KEY buyer_id (buyer_id),
  KEY seller_id (seller_id)
) ENGINE=InnoDB DEFAULT CHARSET=latin1;
  
```


## Addresses



## SQL

```
CREATE TABLE addresses (  
  id int(11) NOT NULL AUTO_INCREMENT,  
  user_id int(11) NOT NULL,  
  hnumber varchar(255) NOT NULL,  
  street varchar(255) NOT NULL,  
  county varchar(255) NOT NULL,  
  stateprovince varchar(40) NOT NULL,  
  country int(11) NOT NULL,  
  postcode varchar(10) NOT NULL,  
  PRIMARY KEY (id),  
  KEY user_id (user_id),  
  KEY country (country)  
) ENGINE=InnoDB DEFAULT CHARSET=latin1;
```


## OU users



## SQL

```
CREATE TABLE `ou_users` (  
  `userid` int(11) NOT NULL AUTO_INCREMENT,  
  `groupid` int(11) NOT NULL,  
  `username` varchar(70) NOT NULL,  
  `password` varchar(70) NOT NULL,  
  `alias` varchar(70) NOT NULL,  
  `fname` varchar(70) NOT NULL,  
  `lname` varchar(70) NOT NULL,  
  `dob` varchar(70) NOT NULL,  
  `country` int(11) NOT NULL,  
  `locale` int(11) NOT NULL,  
  `theme` varchar(50) NOT NULL,  
  `regdate` varchar(70) NOT NULL,  
  `lastaccess` varchar(70) NOT NULL,  
  `avatar` varchar(255) NOT NULL,  
  `email` varchar(255) NOT NULL,  
  PRIMARY KEY (`userid`),  
  KEY `groupid` (`groupid`),  
  KEY `country` (`country`),  
  KEY `locale` (`locale`)  
) ENGINE=InnoDB DEFAULT CHARSET=latin1 AUTO_INCREMENT=3 ;
```

## OU groups

ou_groups	
 <b>groupid</b>	int
<b>alias</b>	varchar(50)

## SQL

```
CREATE TABLE `ou_groups` (  
  `groupid` int(11) NOT NULL AUTO_INCREMENT,  
  `alias` varchar(50) NOT NULL,  
  PRIMARY KEY (`groupid`)  
) ENGINE=InnoDB DEFAULT CHARSET=latin1 AUTO_INCREMENT=7 ;
```


## Countries

countries	
<b>id</b>	int
<b>country</b>	varchar(255)

## SQL

```
CREATE TABLE `countries` (  
  `id` int(11) NOT NULL,  
  `country` varchar(255) NOT NULL,  
  KEY `id` (`id`)  
) ENGINE=InnoDB DEFAULT CHARSET=latin1;
```

## Locale

locale	
 <b>id</b>	int
<b>locale</b>	mediumblob
<b>language</b>	varchar(50)
<b>code</b>	varchar(10)
<b>available</b>	int

## SQL

```
CREATE TABLE `locale` (  
  `id` int(11) NOT NULL AUTO_INCREMENT,  
  `locale` varchar(50) NOT NULL,  
  `language` varchar(50) NOT NULL,  
  `code` varchar(10) NOT NULL,  
  `available` int(11) NOT NULL,  
  PRIMARY KEY (`id`)  
) ENGINE=InnoDB DEFAULT CHARSET=latin1 AUTO_INCREMENT=93 ;
```

## Referential Integrity Constraints


### SQL

```
ALTER TABLE `addresses`  
  ADD CONSTRAINT `addresses_ibfk_1` FOREIGN KEY (`user_id`) REFERENCES `ou_users` (`userid`),  
  ADD CONSTRAINT `addresses_ibfk_2` FOREIGN KEY (`country`) REFERENCES `countries` (`id`);  
  
ALTER TABLE `auction_bids`  
  ADD CONSTRAINT `auction_bids_ibfk_1` FOREIGN KEY (`user_id`) REFERENCES `ou_users` (`userid`),  
  ADD CONSTRAINT `auction_bids_ibfk_2` FOREIGN KEY (`auction_id`) REFERENCES `auction_items`  
  (`auction_id`);  
  
ALTER TABLE `auction_feedback`  
  ADD CONSTRAINT `auction_feedback_ibfk_1` FOREIGN KEY (`auction_id`) REFERENCES `auction_items`  
  (`auction_id`),  
  ADD CONSTRAINT `auction_feedback_ibfk_2` FOREIGN KEY (`buyer_id`) REFERENCES `ou_users` (`userid`),  
  ADD CONSTRAINT `auction_feedback_ibfk_3` FOREIGN KEY (`seller_id`) REFERENCES `ou_users` (`userid`);  
  
ALTER TABLE `auction_items`  
  ADD CONSTRAINT `auction_items_ibfk_1` FOREIGN KEY (`country_from`) REFERENCES `countries` (`id`),  
  ADD CONSTRAINT `auction_items_ibfk_2` FOREIGN KEY (`sellerid`) REFERENCES `ou_users` (`userid`),  
  ADD CONSTRAINT `auction_items_ibfk_3` FOREIGN KEY (`cat_id`) REFERENCES `auction_categories`  
  (`cat_id`),  
  ADD CONSTRAINT `auction_items_ibfk_4` FOREIGN KEY (`subcat_id`) REFERENCES  
  `auction_sub_categories` (`subcat_id`);  
  
ALTER TABLE `auction_pictures`  
  ADD CONSTRAINT `auction_pictures_ibfk_1` FOREIGN KEY (`auction_id`) REFERENCES `auction_items`  
  (`auction_id`);  
  
ALTER TABLE `auction_sub_categories`  
  ADD CONSTRAINT `auction_sub_categories_ibfk_1` FOREIGN KEY (`cat_id`) REFERENCES  
  `auction_categories` (`cat_id`);  
  
ALTER TABLE `item_watching`  
  ADD CONSTRAINT `item_watching_ibfk_1` FOREIGN KEY (`auction_id`) REFERENCES `auction_items`  
  (`auction_id`),  
  ADD CONSTRAINT `item_watching_ibfk_2` FOREIGN KEY (`user_id`) REFERENCES `ou_users` (`userid`);  
  
ALTER TABLE `messages`  
  ADD CONSTRAINT `messages_ibfk_1` FOREIGN KEY (`from_id`) REFERENCES `ou_users` (`userid`),  
  ADD CONSTRAINT `messages_ibfk_2` FOREIGN KEY (`to_id`) REFERENCES `ou_users` (`userid`);  
  
ALTER TABLE `ou_users`  
  ADD CONSTRAINT `ou_users_ibfk_1` FOREIGN KEY (`groupid`) REFERENCES `ou_groups` (`groupid`),  
  ADD CONSTRAINT `ou_users_ibfk_2` FOREIGN KEY (`country`) REFERENCES `countries` (`id`),  
  ADD CONSTRAINT `ou_users_ibfk_3` FOREIGN KEY (`locale`) REFERENCES `locale` (`id`);
```



## Overview

### Relations Overview



## Design & Implementation


### Requirements

#### Major Processes

##### *User Registration*

The PHP logic implements a series of validation checks to prevent the user from entering unwanted data. Email, username, minimum password length, addresses, DOB etc. are further checked with regular expressions to ensure coherent data. Any errors will be shown to the user by indicating which fields had incorrect data. Also the PHP logic has built in methods for taking AJAX requests, to check availability of username and email already in use prohibitions. Activation, although can be completed by email; is disabled as the server not have 'sendmail' enabled.

ALL html, CSS and JavaScript completed. JQuery and plugins are used for AJAX requests to the server on form elements to verify email, username are not already in use. Using JQuery, problems fields are identified immediately indicating to the user which fields have problem data. Dates are handled by JQuery plugin DATEPICKER to ensure valid dates. JQueryUI Modal windows give further indication to the user when problems occur to increase the visibility of system status and error prevention. (Nielsen's heuristics) Minor improvements to be made to CSS and avatar upload.



#### User account

Alias	<input type="text"/>	More than 5 characters please
Email	<input type="text"/>	Invalid e-mail address
Password	<input type="password"/>	More than 5 characters please
Retype Password	<input type="password"/>	

## Update registration

The PHP logic implements a series of validation checks to prevent the user from entering unwanted data. Any errors will be shown to the user by indicating which fields had incorrect data. Ajax and supported PHP logic upload allows the user to change the avatar, address, password and other details without refreshing the page.

ALL html, CSS and JavaScript completed. JQuery and plugins are used to show errors and prevent errors in user entered data. All updates are done using AJAX. Minor improvements to be made, (change email address) but cannot be implemented till sendmail is enabled.

athrú Focal Faire

---

Old Focal Faire	<input type="password"/>	✓
Nua Focal Faire	<input type="password"/>	
Retype Focal Faire	<input type="password"/>	

✓

## Login

The PHP logic implements a series of validation checks to prevent the user from entering unwanted data. Any errors will be shown to the user by indicating which fields had incorrect data. On login complete the users profile will decide which locale will be used on the following pages. If a user is banned they will be notified and prevented from logging in.

ALL html, CSS and JavaScript completed. JQuery and plugins are used to show error and prevent error in user entered data.

## Logout

The user's session is invalidated and the script returns the user to the main page.

## Submit Auction

The PHP logic implements a series of validation checks to prevent the user from entering unwanted data. Any errors will be shown to the user by indicating which fields had incorrect data. Prices, times etc are checked using regular expressions to check for coherent data. If there are any errors the page will be represented with notice errors next to the offending fields. PHP implemented to handle temporary storage of upload images until the process is complete.

ALL html, CSS and JavaScript completed. JQuery and plugins are used to show error and prevent error in user entered data. Ajax is used to upload images and is immediately presented on the auction item page. The user has the ability to remove a picture immediately if they wish to do so. Times and prices fields are validate by JQuery Date picker, time picker, price picker to prevent invalid data before submitting to the server.

## Browse Auctions

The sections are divided into categories and sub categories. PHP implements pagination and items per page. Auctions are shown only if the are newer than the current date. Listing can be viewed by category or by category and sub category. Sorting is also implemented, currently is allows for sorting by date, price, bids, postage and also by name. A series of validation checks prevents the user from sending mal formed GET queries which control the flow of these features. If malformed data is sent the script which go back to standard view.

```
if( $this->session->getKey( "sortby" ) == false || isset( $this->registry->__GET['sortby'] ) )
{
    if ( isset($this->registry->__GET['sortby']) )
    {
        if( $this->registry->__GET['sortby'] != "bidding_endtime" &&
            $this->registry->__GET['sortby'] != "bid_history" &&
            $this->registry->__GET['sortby'] != "price" &&
            $this->registry->__GET['sortby'] != "postage" )
        {
            $this->registry->__GET['sortby'] = "bidding_endtime";
        }
    }

    $this->session->setKey( "sortby" , isset( $this->registry->__GET['sortby'] ) ? $this->registry->__GET['sortby'] : "bidding_endtime" );
}
```

```
if( $this->session->getKey( "sortorder" ) == false || isset( $this->registry->__GET['sortorder'] ) )
{
    if ( isset($this->registry->__GET['sortorder']) )
    {
        if( $this->registry->__GET['sortorder'] != "ASC" && $this->registry->__GET['sortorder'] != "DESC")
        {
            $this->registry->__GET['sortorder'] = "ASC";
        }
    }

    $this->session->setKey( "sortorder" , isset( $this->registry->__GET['sortorder'] ) ? $this->registry->__GET['sortorder'] : "ASC" );
}
```

## *View auction*

The view auction page presents all auctions present and past. The output differs if the auction is complete and presents the winner on the page. The place bid option is removed. An auction is selected by providing the auctioned in a GET request. Validation checks take place to prevent malformed data from being sent in the GET request.

## *Bidding*

The bidding process implements a series of checks to prevent a user from bidding under the current bid. Firstly the user must be logged in, on the auction page the next bidding multiple will be presented, the user can bid higher but must be at least the bid presented in order to successfully bid. Once the bid is added the user can view his current bids on the 'my bids' section of the web page. He can see his / hers current bid and the current high bid.

```
if( $this->convert_datetime( $bidding_endtime ) <= time() )
{
    header('Location: viewauction.php?viewid='.$sauctionID);
    exit;
}
else
{
    if( $bid < $nextbid)
    {
        header('Location: viewauction.php?viewid='.$sauctionID.'&biderror=true&lastbid='.$bid);
        exit;
    }
    else
    {
        $now = date('Y.m.d H:i:s', time());
```

## *Searching*

The simple search is an auto suggests form on the main page. It allows the user to search by a name. The advanced search however allows the user to submit a series of predicates. The request and its predicates are sent to the server via AJAX. The PHP implements a query builder to query the SQL database and find the results the user is looking for. Finally the information is sent back to the browser and JavaScript is used to create a table which is then sort able using JavaScript.

## *Feedback*

After an auction is completed, the winning party has the opportunity to leave feedback on the item won. They access this through 'my bids' where a feedback button is available on the auctions they have won and where feedback has not already been left. The feedback page allows the user to leave feedback and levels of acceptance of promptness, communication, etc. Once feedback is left, the seller is able to view the feedback on the feedback page.

## *Watch item*

On the auction page a watch item button is available to allow users to add the item to their watching list. On the watching page the user can quickly view items they are watching and have the ability to remove the item from their watch list.

## *Administrator*

### *Delete User*

The administrator has the ability to remove a user. When removing the users the auctions for that user, pictures, feedback, messages, address is removed also because of the foreign key constraints existing in the database.

### *Ban User*

Banning users changes their group to group6. When the banned user attempts to login they are presented with error. Immediately their session is invalidated so as they cannot do anything with the account.

### *Update auction*

The administrator has the ability to change the Time and date of the auction end time and the ability to completely remove the auction if they wish to do so.

### *Delete auction*

The administrator first selects the user which is auctioning the item. Then a list of his or her items is shown and the administrator selects the auction to remove. On removing the pictures and feedback are also removed.

## Non Functional Requirements

### *Model – View - Controller*

#### Sample controller

The business logic is done in the controller instances before handing off to the view for output. Once the business logic is completed an array of Keys (replacements) and their values are constructed to tell the view which items are to be replaced within the output template html.

Three distinct types of values are present in the example below.

- A call back to the controller instance for a matched block that requires more processing.
- A replacement that requires a language translation
- A standard replacement.

This array is processed by the view, providing the name of the template to use in the View constructor.

```
1 <?php
2
3 require_once( dirname( __FILE__ ) . "/conf.php" );
4
5 class Sample extends Controller
6 {
7
8     public function __construct()
9     {
10         parent::__construct();
11         $this->index();
12     }
13
14
15     public function simpleCallback( $match )
16     {
17         $data = "";
18         // logic
19         // $data += $logic
20         // $output = $data;
21
22         return $output;
23     }
24
25
26     public function index()
27     {
28         // logic
29
30         $items = array (
31             "simpleCallback" => array ( "callback" , $this , "simpleCallback" ) , // simple callback
32             "title" => "%home%" , // output data for localization
33             "username" => $this->session->getCurrentUser() , // output the username
34         );
35
36         $this->view = new View( "Sample" );
37         $this->view->process ( $items );
38         $this->view->output ();
39     }
40 }
41
42 new Sample;
43
```

## Sample Template

```
1 @header@
2
3 <h1>{title}</h1>
4
5 %hello% {username}
6
7 <ul>
8 #callback#
9 <li>[replaceme]</li>
10 #/callback#
11 </ul>
12
13 @footer@
```

## View Constructor

```
47 public function __construct( $template = "index.html" )
48 {
49     parent::__construct();
50
51     $this->registry->__VIEW = $this;
52
53     if ( file_exists( __SITE_ROOT . "/views/" . $this->session->getTheme() . "/" . $template . ".tpl" ) )
54     {
55         $this->loadPlugins();
56         $this->page = join( "" , file( __SITE_ROOT . "/views/" . $this->session->getTheme() . "/" . $template . ".tpl" ) );
57         $this->applyIncludes();
58     }
59     else
60     {
61         $this->error = "views file $template not found.";
62     }
63 }
```

## View Includes

```
361 private function applyIncludes()
362 {
363     preg_match_all( "/\@[a-zA-Z0-9_\.\-]+\@/" , $this->page , $matches );
364
365     foreach( $matches as $match )
366     {
367         for ( $i = 0; $i < count( $match ); $i++ )
368         {
369             $include_name = substr( $match[$i] , 1 , strlen( $match[$i] ) - 2 );
370             $data = $this->loadFile( $include_name . ".tpl" );
371             $this->page = preg_replace( "@@" . $include_name . "@@" , $data , $this->page );
372         }
373     }
374
375     if( preg_match_all( "/\@[a-zA-Z0-9_\.\-]+\@/" , $this->page , $matches ) > 0 )
376     {
377         if( $this->rec_include < 2 )
378         {
379             $this->rec_include++;
380             $this->applyIncludes();
381         }
382     }
383 }
```

Includes are handled within the templates by matching the @INCLUDE\_THIS@ syntax. The file contents of file are then included in the final output. Levels of recursion are allowed, if the file included has further includes.



## View Processing

```
117 public function process( $tags = array() )
118 {
119     $global_directives = $this->registry->__COMMON->globalDirectives();
120
121     if( $global_directives )
122     {
123         $this->process( $tags ); // process tags first to allow override of global directives
124         $this->process( $global_directives );
125         return;
126     }
127
128     if ( sizeof( $tags ) > 0 )
129     {
130         foreach ( $tags as $tag => $data )
131         {
132             if( is_array( $data ) )
133             {
134                 $this->processDirective( $data[0], $data[1], $data[2] );
135                 unset( $tags[ $tag ] );
136                 $this->process( $tags );
137                 return;
138             }
139
140             if( file_exists( __SITE_ROOT . "/views/" . $this->session->getTheme() . "/" . $data ) && $data != "" )
141             {
142                 $data = $this->loadFile( $data );
143                 unset( $tags[ $tag ] );
144                 $this->page = preg_replace( "/" . $tag . "/" , $data , $this->page );
145                 $this->process( $tags );
146                 return;
147             }
148             else
149             {
150                 if( in_array( "{" . $tag . "}" , $this->hooks ) )
151                 {
152                     foreach( $this->plugin_hooks as $key => $hook )
153                     {
154                         if( $hook[1] == "{" . $tag . "}" )
155                         {
156                             $plugin_data = call_user_func_array( array( $hook[0] , $hook[2] ) , array( "{" . $tag . "}" , $data ) );
157                             $this->page = preg_replace( "/" . $tag . "/" , $plugin_data , $this->page );
158                         }
159                     }
160                     unset( $this->hooks[ "{" . $tag . "}" ] );
161                 }
162                 else
163                 {
164                     $this->page = preg_replace( "/" . $tag . "/" , $data , $this->page );
165                 }
166             }
167         }
168     }
169
170     if( preg_match_all( "/\\\[a-zA-Z0-9_\\.]+\\[\\]/" , $this->page , $matches ) > 0 )
171     {
172         if( $this->rec_replace < 2 )
173         {
174             $this->rec_replace++;
175             $this->process( $tags );
176         }
177         else
178         {
179             preg_replace("/\\\[a-zA-Z0-9_\\.]+\\[\\]/", "", $this->page); // cant find (so replace with nothing)
180         }
181     }
182 }
```

The first element in the replacement tags is an array which is identified as the processing directive. Line 132 identifies that a call back is required. The process directive method is called in the view and the values are handed off to this method. When the method is done processing the output is return and inputted in the html.

The second element is a replacement; line 164 handles this replacement by matching {title} in the view and replacing it with %home%. The third element is handled the same way.

## View Process Directive

```
197 private function processDirective( $match , $class , $callback )
198 {
199     $pattern = "/\#$match\#(.*)\#\/$match\#/s";
200     $num = preg_match( $pattern , $this->page , $matches );
201     if( $num > 0 )
202     {
203         $replacement = call_user_func_array( array( $class , $callback ) , array( $matches[1] ) );
204         $this->page = preg_replace( $pattern , $replacement , $this->page );
205     }
206 }
207
```

Using the call user function array method in PHP we call the controller instance method specified and pass the html matched (Sample view lines 8 -10) to this method for further processing.

## View Output

```
216 public function output()
217 {
218     $this->applyLocale();
219     echo $this->page;
220
221     if( isset ( $this->registry->__GET['debug'] ) || $this->session->getKey("debug") != false )
222     {
223         print "<center><div style='width:1000px;padding-left:30px;text-align:left'>";
224         $this->session->setKey("debug","true");
225         $this->db->dumpDebugLog();
226         $this->session->dumpDebugLog();
227         $this->registry->dumpDebugLog();
228         print "</div><div style='width:1000px;padding-left:30px;text-align:left' id='phpinfo'>";
229         ob_start () ;
230         phpinfo () ;
231         $pinfo = ob_get_contents () ;
232         preg_match ( '%<style type="text/css">(.*?)</style>.*?(<body>.*</body>)%s' , ob_get_clean(), $matches);
233         print $matches[2];
234         print "</div></center>";
235     }
236 }
```

Once the complete page is built the page is then printed to the output stream.

## Localisation

Localisation support was implemented using the Google translate service. Language packs were created using associative arrays. The key represented the text to replace and the value was the replacement text.

```
1 <?php
2
3 $locale = array(
4     "welcome" => "Bienvenue",
5     "Username" => "Nom d'utilisateur",
6     "Password" => "Mot de passe",
7     "password" => "Mot de passe",
8     "login" => "connexion",
9     "logout" => "logout",
10    "about" => "à propos de",
11    "news" => "nouvelles",
12    "translate" => "traduire",
13    ...
14 )
```

The last step in the view before output the html page is replacing all matching %welcome% using a regular expression replacement. The locality is determined by the users \$\_SESSION['locale'] and the correct language pack is included. Lines 320 - 327

In the case of %welcome% it would be replaced by "Bienvenue". Lines 338 – 341

```
316 private function applyLocale()
317 {
318     $pluginLocalesMerged = array();
319
320     $lang = $this->registry->__DB->query("select code from locale where id='".$this->session->getLanguage()."', 'one');
321
322     if($lang=="")
323     {
324         $lang = "en";
325     }
326
327     include( __SITE_ROOT . "/system/locale/" . $lang . ".php" );
328
329     foreach( $this->plugin_hooks as $key => $plugin )
330     {
331         if( ! in_array( get_class( $plugin[0] ) , $pluginLocalesMerged ) )
332         {
333             $pluginLocalesMerged[] = get_class( $plugin[0] );
334             $locale = array_merge( $locale , $plugin[0]->getLocale() );
335         }
336     }
337
338     foreach ( $locale as $word => $replacement )
339     {
340         $this->page = preg_replace( "/" . $word . "/" , $replacement , $this->page );
341     }
342 }
```

Depending on the locality is use the DOCTYPE for the html output was also replaced to confirm to the internet standards and ensure correct layout and reading orientation in the case of right to left languages.

## Security

First level of security is the un-setting the \$\_POST, \$\_GET and \$\_SERVER. These session datasets are stored in the registry class for later retrieval for use in the controllers. Each key pair in the datasets is stripped of slashes and then using 'mysql\_real\_escape\_string' is prepared for database usage.


As the inheritance graph indicates in the UML class diagram all of this processing is done before any of the controller logic, forcing the programmer to use the inbuilt protection overrides. Further checking is done in the Controller logic to ensure safe data.

```
private function escapeInputData ()
{
    foreach ( $_POST as $key => $val )
    {
        if ( is_array( $val ) )
        {
            foreach ( $val as $keya => $valb )
            {
                $this->__POST[ $key ][ $keya ] = mysql_real_escape_string ( stripslashes ( $valb ) );
            }
            unset ( $_POST[ $key ] );
        }
        else
        {
            $this->__POST[ $key ] = mysql_real_escape_string ( stripslashes ( $val ) );
            unset ( $_POST[ $key ] );
        }
    }

    foreach ( $_GET as $key => $val )
    {
        if ( is_array( $val ) )
        {
            foreach ( $val as $keya => $valb )
            {
                $this->__GET[ $key ][ $keya ] = mysql_real_escape_string ( stripslashes ( $valb ) );
            }
            unset ( $_GET[ $key ] );
        }
        else
        {
            $this->__GET[ $key ] = mysql_real_escape_string ( stripslashes ( $val ) );
            unset ( $_GET[ $key ] );
        }
    }

    foreach ( $_SERVER as $key => $val )
    {
        if ( is_array( $val ) )
        {
            foreach ( $val as $keya => $valb )
            {
                $this->__SERVER[ $key ][ $keya ] = mysql_real_escape_string ( stripslashes ( $valb ) );
            }
            unset( $_SERVER[ $key ] );
        }
        else
        {
            $this->__SERVER[ $key ] = mysql_real_escape_string ( stripslashes ( $val ) );
            unset ( $_SERVER[ $key ] );
        }
    }
}
```

# Prototype UML Class Diagram



## Copied materials

- **JQuery**
  - JavaScript Framework
    - <http://jquery.com/>
- **JQueryUI**
  - Tabs, Date picker, Dialog, effects
    - <http://jqueryui.com/>
- **JQuery Plugins**
  - Ajax Upload
    - <http://plugins.jquery.com/project/uploadify>
  - Cross Slide (images)
    - <http://plugins.jquery.com/project/easyslideshow>
  - Format currency
    - <http://plugins.jquery.com/project/currency>
  - Table Sorter
    - <http://plugins.jquery.com/project/tableSort>
  - Sizeable text area
    - <http://plugins.jquery.com/project/TextAreaResizer>
  - Time Picker
    - <http://plugins.jquery.com/project/timeEntry>
- **Fancy Box**
  - Image Preview
    - <http://fancybox.net/>
- **GTranslate**
  - Google Translate API Class
    - <http://code.google.com/p/gtranslate-api-php/>
- **Regular Expressions**
  - Email
    - <http://php.net/manual/en/function.preg-match.php>
  - Date
    - [http://dotnetslackers.com/Regex/re-16542\\_Regex\\_matches\\_a\\_date\\_in\\_dd\\_mm\\_yyyy\\_format.aspx](http://dotnetslackers.com/Regex/re-16542_Regex_matches_a_date_in_dd_mm_yyyy_format.aspx)
- **Reports Diagrams**
  - Db Visualizer (Entity relationships)
    - <http://www.dbvis.com/>
  - yEd Graph Editor (Flow Charts)
    - <http://www.yworks.com/>
  - Visual Paradigm For UML
    - <http://www.visual-paradigm.com/>
- **Theme**
  - Simple auction template
    - <http://www.freewebtemplates.com>