CS4125
SYSTEMS ANALYSIS
SPRING SEMESTER 2010-2011

J.J. Collins
Dept of CSIS
University of Limerick

Lecture P – W10L2

Introduction to Architecture

System Design: Architecture

- One of the major concerns in system design is architecture.

- According to Bass et al. “the software architecture of a program or computing system is the structure or structures of the system, which comprise software elements, the externally visible properties of those elements, and the relationships among them” (**Bass, L., P. Clements, and R. Kazman, *Software Architecture in Practice*. 2nd Edition. Addison Wesley. 2003.**)

Select Solutions Factory Example



Figure 8. Business Architecture.



Figure 10. Technical solutions architecture.

System Design: Subsystems

- Advantages of division of system into sub-systems:
  - Produces smaller units of development.
  - Maximises reuse at the component level.
  - Helps developers to cope with complexity.
  - Improves maintainability.
  - Improves portability.
- Each sub-system should have a clearly specified boundary and fully defined interfaces.
- Each sub-system provides services for other sub-systems, and two styles of communication make this possible: client server and peer to peer.
- Client server sub-systems better - less tightly coupled.
- Could also use component and deployment diagrams.

System Design: Layering & Partitioning

- Two approaches to division of software systems into sub-systems.
  - Layering: so called because different sub-systems represent different levels of abstraction.
  - Partitioning: each sub-system focuses on a different aspect of the functionality of the system as a whole.
- Pros and cons ???



Schematic of a layered architecture

System Design: Layering and Partitioning

- The OSI 7 layer model is an example of one of the best-known examples of a layered architecture.
- Buschmann et al. (1996) suggest that the following issues need to be addressed when applying a layered architecture:
  - Maintaining the stability of the interfaces of each layer.
  - The construction of other systems using the lower layers.
  - Variations in the appropriate level of granularity for sub-systems.
  - The further sub-division of complex layers.
  - Performance reductions due to a closed layered architecture.



Simple Layered Architecture

System Design: Layered Architecture

- Three layered architecture commonly used for business-oriented information systems.
- Eliminates tight coupling between user interfaces and data representation.
- A common four layered architecture separates the business logic into application logic and domain layers.
- Used when several applications may share one domain layer, or because complexity of business objects forces a separation into two layers.



Three Layered Architecture



Four Layered Architecture



Four layered architecture applied to part of the Agate management system

System Design: Layered Architecture

Buschmann et al. (1996):

1. Define criteria by which application will be grouped into layers i.e. level of abstraction from hardware.
   - Low levels primitives in lower layers, application concepts in higher layers.
2. Determine the number of layers.
3. Name the layers and assign functionality to them.
   - Top layers should focus on provision of services required by users.
   - Layer below that should focus on provision of services and infrastructure that support services in the top layer.
4. Specify the services for each layer.
   - Lower level layers should provide a limited set of primitive services that are used by a larger number of services in the higher layers.
5. Refine the layering by iterating through steps 1 to 4.
6. Specify interfaces for each layer.
7. Specify structure of each layer. May involve partitioning.
8. Specify communication between layers.
9. Reduce coupling between adjacent layers in a closed architecture – layers should be strongly encapsulated. Layers should only have knowledge of layer immediately below it.

System Design: MVC

- Many interactive systems use the Model-View-Controller (MVC) architectural pattern.
- Separates an application into three major types of components:
  - Models that comprise the main functionality.
  - Views that present the user interface.
  - Controllers that manage the update to views.
- Facilitates maintenance and portability.
- Common for the view to differ for each user.
- Implies that data and functionality available to each user should be tailored to needs. i.e. Agate case study, different perspectives of campaign manager and creative artist.
- An alternative architectural pattern for interactive systems is the Presentation-Abstraction-Control (PAC) pattern.

System Design: MVC

- Issues that should be addressed:
  - The same information should be capable of presentation in different formats in different windows.
  - Changes made within one view should be reflected immediately in all other views.
  - Changes in user interfaces should be easy to make.
  - Core functionality should be independent of the interface to enable multiple interface styles to co-exist.
- The MVC architecture solves the problems of updating by the separation of core functionality (model) from the interface through the use of a mechanism for propagating updates to other views.
- The interface is split into two elements: the output presentation (view) and the input controller.



Model–View–Controller (adapted from Hopkins and Horan, 1995

System Design: MVC Class Diagram



Responsibilities of MVC components, as applied to Agate

System Design: MVC - Behaviour



MVC component interaction (adapted from Buschmann et al., 1996)

System Design: MVC - Initialisation



System Design: MVC - Behaviour



System Design: Distributed Systems

- Distributed architectures usually supported by Distributed Database Management Systems (DBMS) and by middleware such as CORBA compliant object request brokers (ORBs).
- Figure 12 depicts a simplified version of the broker architecture for a distributed system (Buschmann et al., 1996).
- Broker decouples the client and server.



Simplified broker architecture



Broker architecture using Bridge components

System Design:



Broker architecture for local server (adapted from Buschmann et al., 1996)

System Design: Concurrency

- Different objects that are not actively executing at the same time may be implemented on same logical processor.
- Objects that operate concurrently must execute on different logical processors.
- Logical processors ultimately mapped to physical processors on deployment diagram.
- Examine use case descriptions.
- Examine state charts.
- Two types of concurrency:
  - Many to one: - multitasking.
  - Many to many: multi-processor environment - distributed system.
- On sequence diagrams, specify focus of control, and active objects.
- On a uni-processor hardware architecture, may use a scheduler sub-system to ensure that each thread of control operates within the constraints on its response time.

System Design: Concurrency



Scheduler handling concurrency

System Design: Processor Allocation

- The application should be divided into sub-systems.
- Processing requirements for each sub-system should be estimated.
- Access factors and location requirements should be specified.
- Concurrency requirements for the sub-systems should be identified.
- Each sub-system should be allocated to an appropriate hardware platform - PC, workstation, server, embedded micro-controller.
- Communications requirements should be identified.
- Communications infrastructure should be specified.

3. Reading

- Chapters 13 in Bennett et al. (Fourth Edition).

Have a look at:

- Sections 3 and 4 in Buschmann, F., Meunier, R., Rohnert, H., Sommerlad, P., and Stal, M. Pattern-Oriented Software Architecture: A System of Patterns. Wiley. 1996